2026 / 2027 CATALOGUE



MADE IN CRONENBERG
MADE IN GERMANY

TOOLS THAT ... inspire

STAHLWILLE®



Vera Bökenbrink
Managing Director

Udo Hehemann
Executive Board |
Head of Sales and Marketing

Powerful performance. Future-oriented.

STAHLWILLE is an impressive success story that unites tradition and innovation in a unique way. For over 160 years, as a medium-sized company, we have always had our customers' needs in mind and developed the best solutions of our time. This is how we have evolved from a tool manufacturer nestled in the mountains, to an international champion of innovation in the field of hand-held tools.

As a full-range tool supplier, we offer everything professional users need in almost every field of application and industry. From classic spanners to modern tool storage and transport solutions, from high-tech electronic torque tools for connected Industry 4.0 environments to testing and calibration technology that is state-of-the-art in every respect.

With our contemporary and forward-looking portfolio, we enable our customers to deliver outstanding work. Precise, fast and safe. In production, repair and maintenance. Every single day. All over the world.

We place high demands on ourselves: Our professional tools for trades and industry stand for quality that sets standards and impress with ergonomics and durability that leave nothing to be desired. This is possible because almost all of our value creation takes place "in-house": 95% production depth and a clear commitment to our German location leave no doubt that we will live up to what the "Made in Germany" quality seal promises.

Tools that inspire!

Yours
Vera Bökenbrink



Yours
Udo Hehemann




MADE IN CRONENBERG
MADE IN GERMANY



Always well informed – with the STAHLWILLE website.

The STAHLWILLE website offers comprehensive information on products and many additional resources, such as our whitepapers on torque technology or exclusive behind-the-scenes views of certain areas of application.

www.stahlwille.com



8 **Torque technology** 1

106 **Spanners** 2

140 **Socketry** 3

226 **IMPACT tools** 4

238 **Screwdrivers and bit tools** 5

278 **Factory and workshop equipment** 6

300 **Tool assortments** 7

388 **Pliers** 8

422 **Pullers** 9

432 **Special automotive tools** 10

460 **Miscellaneous tools** 11

490 **VDE tools** 12

MADE IN CRONENBERG. Made in Germany. Our commitment to our home location and uncompromising premium quality.



MADE IN CRONENBERG
MADE IN GERMANY

Made in Germany.

At STAHLWILLE, we develop and manufacture innovative premium-quality hand tools – Made in Germany. The products in our portfolio deliver outstanding performance and are designed for professional use and a long service life. And should something ever go wrong, we place particular emphasis on ensuring that our tools can be repaired – even many years after purchase.

At home all over the world.

Professional users in industry and the skilled trades around the world rely on the quality and performance of our tools and tool storage solutions. In countless projects across the globe, STAHLWILLE continues to demonstrate its expertise as a project partner and its reliability as a supplier.

STAHLWILLE GROUP

STAHLWILLE | VBW | ALARM

The STAHLWILLE Group

The STAHLWILLE Group brings together the STAHLWILLE, VBW and ALARM brands under one roof: three long-established and successful companies with a wealth of combined experience, united by their passion for high-quality tools and their strong focus on customer needs.

Our expertise.

We combine our unique heritage with state-of-the-art expertise. Thanks to our many years of experience, we understand the different demands our customers place on their tools – across a wide range of industries. This enables us to continuously develop our products and tailor them precisely to the needs of professional users. Over time, we have evolved from a traditional hand tool manufacturer into an innovative solutions provider.



Certified to multiple standards

We are certified in accordance with the ISO 14001:2015 environmental management standard, the ISO 9001:2015 quality management standard and the ISO 50001:2018 energy management standard. In addition, our production operations comply with the requirements of the European environmental management standard EMAS.

As part of our energy management system, we record and evaluate energy consumption, identify potential savings and implement measures to continuously improve energy efficiency.

PROGRESS STARTS WITH CONCRETE STEPS.

Responsible action is firmly embedded in STAHLWILLE's operational processes. We take social, ethical and environmental requirements into account in our policies and procedures and continuously develop them further. This includes defined requirements relating to working conditions, ethics and environmental management, as well as specific measures in the areas of energy, material use and production.

Our sustainability policy brings together the key principles for responsible and sustainable action. It provides a clear framework and translates our commitment into specific requirements for day-to-day operations.

Resources and the environment.

STAHLWILLE implements measures to reduce energy consumption. We record the resulting changes in CO_2 savings on the basis of defined calculation methods.

We are also working to reduce the use of plastic in our packaging. Wherever technically and functionally possible, we avoid plastic packaging and instead use paper-based materials such as solid board or recycled paper. Where plastic is required, we use materials with recycled content wherever these are available and technically suitable.

Certified management systems.

STAHLWILLE operates certified management systems in accordance with ISO 9001:2015 (quality management), ISO 50001:2018 (energy management) and ISO 14001:2015 (environmental management). Regular audits are carried out to verify compliance with the respective requirements of these standards.



Production in Germany.

A significant proportion of our production takes place at our sites in Germany. Our tools are designed for professional use and a long service life. As early as the product development stage, we take aspects such as repairability and the availability of spare parts into account. For many of our tools, we continue to provide spare parts and repair kits beyond the statutory periods.

Ethical conduct.

Our Code of Conduct provides guidance for our day-to-day actions and reflects the values and principles of the STAHLWILLE Group. It applies throughout the STAHLWILLE Group and also defines the framework for cooperation with our business partners.

The Code of Conduct sets out policies and requirements in areas including working conditions, ethics, and compliance, thereby creating a binding framework for the way we act and work together.

Technical development.

We continue to develop our products and production processes in line with the applicable environmental and safety requirements. One current example is the gradual transition from chromium VI to chromium III.


STAHLWILLE
MANOSKOP® 714/10
MADE IN CRONENBERG
MADE IN GERMANY

1 Torque technology



20 Torque screwdrivers, mechanical

22 Torque screwdrivers, electromechanical

26 Torque wrenches, mechanical

42 Torque wrenches, electronic, electromechanical

48 Accessories for torque tools

54 Torque tool sets

60 Insert tools

76 Torque multipliers

78 Spare part sets for ratchets and ratchet insert tools

80 Square drives

81 Calibration certificates

84 Test equipment and calibration systems

TORQUE TECHNOLOGY – We are your one-stop-shop for torque tools.

With increasing demands on the quality, safety and reproducibility of bolted joints, controlled bolt tightening is becoming increasingly important. STAHLWILLE is one of the world's leading torque specialists and has been developing "Made in Germany" torque solutions characterised by precision and durability for decades. Everything from a single source: In addition to torque and angle-controlled torque wrenches, our portfolio also includes torque testers and calibration systems that set standards time and time again.

Torque screwdrivers and torque wrenches.

The STAHLWILLE product range spans torque screwdrivers to mechanical, electromechanical or electronic torque/angle-controlled torque wrenches, to networkable torque tools with various interfaces.



Calibration technology.

As a world-renowned torque expert we offer a particularly broad portfolio of calibration systems. With the mechanical and motorised calibration systems from STAHLWILLE, torque tools are calibrated quickly and efficiently to established industry standards.



Testing technology.

In addition to their scheduled calibrations, torque tools should also be tested regularly for function and accuracy. This is the only way to ensure that the tools work exactly within the specification. With our SmartCheck, we offer an excellent solution for in-house testing, among other things.



TORQUE

DAPTIQ® TORQUE TECHNOLOGY – simply networked. Perfectly integrated.

Controlled bolt tightening is becoming increasingly important in production and maintenance. The same applies to the necessity to document bolted joints and bolting parameters. DAPTIQ® products offer the optimal solution: They can be integrated into existing leading systems without complex programming, or can be used with the GuideMaster software developed by STAHLWILLE. In both cases, they guarantee ease of use for the worker, shorter training times, increased process quality, and the reduction of time-consuming reworking or recalls.



MANOSKOP® 766 DAPTIQ® – short training time and high process reliability.

The electromechanical angle-controlled torque wrench MANOSKOP® 766 DAPTIQ® can exchange data bidirectionally and receive and execute instructions. The interface is implemented via cabled connection, radio (ISM), Bluetooth or WLAN. The familiar feeling of a mechanical click reduces operating errors and thus the error rate. Last but not least, automatic documentation of data is made possible in conjunction with the central systems.

https://stahlwille.com/en_gb/loesungen/daptiq/9f291d6d

DAPTIQ



In-house testing and calibration.

SmartCheck DAPTIQ® allows users to check their torque or angle-controlled torque wrenches in-house. This makes it possible to ensure that the tools operate reliably within the specified tolerance range before starting work. The SmartCheck DAPTIQ® offers an open interface for integration, such as in CAQ systems. This can be done either wirelessly via a Bluetooth module or via the USB interface.

With **perfectControl DAPTIQ®**, STAHLWILLE offers a calibration system that can calibrate torque wrenches and angle-controlled torque wrenches automatically, depending on the version. The user is guided through the entire test process by software. Electronic wrenches can be calibrated fully automatically for the most part. Once calibration is complete, the corresponding data is available to the higher-level Computer Aided Quality (CAQ) system for documentation.

INTELLIGENT TOOLS, SMART WORKFLOW – Software solutions from STAHLWILLE.

Be it the setup and parametrization of torque wrenches, digital tool management, test equipment monitoring or documentation of work processes: STAHLWILLE software enables work processes to be optimised completely intuitively and the highest quality standards to be complied with.



Comprehensive.

With the SensoMaster software, we are providing a centralised PC tool for reading out and configuring all electronic STAHLWILLE torque wrenches. The software detects the tool automatically and synchronises the bolted joints and sequences configured on the PC, as well as the work data and results that are stored on the tool.

Self-explanatory.

The software is self-explanatory thanks to its intuitive user interface with a clear tabular structure. It enables quick and easy programming of electronic torque wrenches and extensive evaluation, as part of a quality assurance strategy for example.

SensoMaster Live

SensoMaster Live enables the torque and angle of rotation to be displayed graphically on a PC in real time. Multiple tightenings can be displayed at the same time for comparison. The data can be saved in a CSV file and be imported again when required.

SOFTWARE



BluetoothMaster.

BluetoothMaster offers a quick, easy and intuitive pairing process. Using BluetoothMaster and the corresponding Bluetooth Low Energy Module, the torque wrenches MANOSKOP® 714 and MANOSKOP® 766 DAPTIQ® and the tester SmartCheck DAPTIQ® can be connected seamlessly to SensoMaster, GuideMaster and CheckMaster. Users can choose between three different modes of communication: TCP/IP, direct connection or Com-Port connection.

TorkMaster.

TorkMaster enables easy calibration of torque wrenches and screwdrivers in accordance with DIN EN ISO 6789, with little required on the part of the user. Loading curves and the measured values are graphically displayed, and calibration certificates are printed and/or saved as a PDF. A separate calibration history can be created for each tool.

In addition to the calibration, a tool-related machine capability test (MCT) is also possible.

CheckMaster.

With the help of the CheckMaster software, test data can be read out of the tester for documentation purposes, test certificates created and the basic settings of the SmartCheck tester changed easily.
A customer database can be created for this purpose and managed conveniently on the PC.



Discover the MySTAHLWILLE service portal.

In your own personal MySTAHLWILLE portal, you have access to software and firmware, 3D product data, and numerous other services.
service.stahlwille.com

TORQUE TECHNOLOGY PRODUCT OVERVIEW.

N

Torque screwdrivers

Category	Measuring range cN·m	Type		
Mechanical/Electromechanical	0 50 150 300 500 650 800 1.000	Electromechanical	Mechanical	Page
775	2 – 1.000 cN·m		○	21
760	15 – 600 cN·m		○	20
TORSIOTRONIC®	12 – 1.000 cN·m	○		22

Torque wrenches

Category	Measuring range N·m	Feedback type		Insert system		
Mechanical	0 50 150 300 500 650 800 1.000	Indicating	Clicking	Fixed	Interchangeable	Page
730 Quick	2 – 650 N·m		○		○	28–30
730/80	160 – 800 N·m		○		○	30
721 Quick	6 – 300 N·m		○	○		31
720Nf	160 – 800 N·m		○	○		32
721Nf	160 – 1.000 N·m		○	○		32
730N	4 – 1.000 N·m		○		○	33–35
730 Fix	10 – 1.000 N·m		○		○	35, 36
750NR	10 – 400 N·m		○	○		37
755	1.5 – 300 N·m		○	○*	○	27
71	160 – 800 N·m	○		○**	○	26
73Nm/15	2 – 15 N·m	○		○		27
730R VDE	4 – 50 N·m		○		○***	498
Electromechanical	0 50 150 300 500 650 800 1.000	Indicating	Clicking	Fixed	Interchangeable	Page
730D	10 – 1.000 N·m	○	○		○	43
714	1 – 1.000 N·m	○	○		○	46, 47
766 DAPTIQ®	1 – 1.000 N·m	○	○		○	12
Electronic	0 50 150 300 500 650 800 1.000	Indicating	Clicking	Fixed	Interchangeable	Page
713R	3 – 400 N·m	○			○	45
701	1 – 20 N·m	○		○		42

* only 755R/1 ** only 71aR/80 *** In case of repair



M

Testing and calibration technology

Category	Measuring range N·m	Type		
Testing devices	0 50 150 300 500 650 800 1.000 1.500	Electronic	Mechanical	Page
SmartCheck USB	1 – 1.500 N·m	○		85
SmartCheck Angle	0° – 720°	○		84
SmartCheck DAPTIQ®	1 – 1.500 N·m	○		13
7707 W	0.2 – 1.100 N·m	○		87
Test attachment for torque screwdrivers	0 50 150 300 500 650 800 1.000 1.500	Electronic	Mechanical	
7791-2	0.2 – 10 N·m		○	102
Mechanical calibration systems	0 50 150 300 500 650 800 1.000 3.000	Electronic	Mechanical	
7791 + 7791-1	1 – 1.000 N·m		○	99
7792 + 7792-1	1 – 3.000 N·m		○	100, 101
7790	0.2 – 10 N·m		○	102
Motorised calibration systems	0 50 150 300 500 650 800 1.000 1.500	Electronic	Mechanical	
perfectControl® 7794-1 + 7791-1	1 – 1.000 N·m		○	92, 93, 99
perfectControl® 7794-2 + 7791-1	1 – 1.000 N·m	○		94, 95, 99
perfectControl® 7794-3 + 7791-1	1 – 1.000 N·m	○		96/99

Category	Measuring range N·m												
Torque multipliers	0	50	150	300	500	650	800	1.000	1.500	5,000	8,000	12.000	Page
MULTIPOWER MP 100-1,500	1 – 1.500 N·m												76
MULTIPOWER MP 300	1 – 5.000 N·m**										– 8.000	– 12.000	76

** Catalogue items are available up to a maximum torque of 5.000 N·m. Variants with 8.000 N·m and 12.000 N·m are available on request..



Need more torque?
The STAHLWILLE MULTIPOWER torque multiplier enables up to 5,000 N·m to be achieved. More information on page 76.

STAHLWILLE TORQUE SCREWDRIVERS – Digital precision meets patented electromechanics.

The innovative TORSIOTRONIC® torque screwdrivers offers extensive possibilities for programming and comprehensive documentation of tightening data. This is because the development of the compact tool incorporated STAHLWILLE's many years of know-how in the field of digital torque technology as well as the patented electromechanical triggering technology, in which an audible and tangible 'click' signals when the target torque is reached. The perfect symbiosis of digital precision and proven mechanics has been awarded both the Red Dot Design Award and the German Design Award.

BRILLIANT



Finely tuned.

Particularly precise work thanks to the integrated ratchet with 80 teeth for a working angle of only 4.5° – for left and right tightening and in indicating or click mode.

Reliable.

A slipping mechanism prevents unintentional exceeding of the correct tightening torque and overtightening of the screw after the click.

High-contrast.

Clear display of all relevant information in a bright, energy efficient OLED colour display that can be read from almost any angle.

Can be documented.

The TORSIOTRONIC® stores up to 2,500 tightening results for reading and documenting on the PC at a later date via an integrated micro-USB interface.



MADE IN CRONENBERG
MADE IN GERMANY

TORSIOMAX 775.

The TORSIOMAX 775 with left-hand and right-hand tightening accepts all standard quarter-inch bits, form E 6.3, and prevents the screw from being overtightened with the help of a release coupling. The target torque can be set precisely and easily using a rotary micrometer scale.

TORSIOMETER 760.

Equipped with a flat torsion spring as a measuring element, the TORSIOMETER 760 indicates the torque currently applied to the screw. This protects against material damage and rework. The torque can be set variably – quickly and reliably.


TORQUE SCREWDRIVERS, MECHANICAL.

TORSIOMETER 760




Torque screwdrivers TORSIOMETER

- indicating type
- torsion leaf spring as measuring element
- for clockwise and counter-clockwise tightening
- with drag pointer
- with 1/4" internal hex drive (F 6.3 DIN 3126 / ISO1173)
- comparative scale in·lb
- inserts and connectors with external hex E 6.3 (1/4") DIN 3126 / ISO 1173 fit securely in the bit holder
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**



Product no.	Size	cN·m	in·lb	cN·m	mm	L mm	g
51040007	7.5	15-75	1.5-6.5	2.5	F 6.3	185	225
51040015	15	30-150	3-13	5	F 6.3	185	225
51040030	30	60-300	6-26	10	F 6.3	185	230
51040060	60	120-600	12-52	20	F 6.3	185	230



TORSIOMAX 775



775/3 775/12-30 775/100

Torque screwdrivers TORSIOMAX

- clicking type
- for controlled screw tightening in the cN·m and in·lb ranges
- for both single tightenings and for repetitive production tasks
- for clockwise and counter-clockwise tightening
- with 1/4" internal hex drive (F 6.3 DIN 3126 / ISO1173)
- adjustable setting via micrometer scale (rotating scale)
- disengaging clutch prevents overtightening of the fastener
- specially designed handle for safe transmission of torque
- insert tools: all bits with 1/4" hex E 6.3, such as PHILLIPS®, slotted, TORX®, hex, POZIDRIV® etc.
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 6%**




Product no.	Size	cN·m	in·lb	cN·m	in·lb	mm	L mm	g
51060003 [1]	3	2-30	-	0.2	-	F 6.3	105	55
51060012 [2]	12	20-120	-	1	-	F 6.3	157	180
51060030 [2]	30	40-300	-	1	-	F 6.3	160	205
51060050 [2]	50	100-500	-	2.5	-	F 6.3	205	420
51060100 [3]	100	400-1000	-	5	-	F 6.3	235	630
51460003 [1]	a/3	-	0.2-3	-	0.02	F 6.3	105	55
51460012 [2]	a/12	-	2-12	-	0.1	F 6.3	157	200
51460050 [2]	a/50	-	10-50	-	0.25	F 6.3	205	440

[1] with a swivelling handle end to improve tool control; and with a clamping screw for locking the torque value once set

[2] with additional locking mechanism to prevent unintentional adjustment of the set torque

[3] with screw-on handles to reduce effort required for high torques



TORQUE SCREWDRIVERS, ELECTROMECHANICAL.



Key features of torque screwdrivers
TORSIOTRONIC®

- electromechanical, indicating and clicking type
- for clockwise and counter-clockwise tightening
- visual, acoustic, and haptic dual-stop signals
- with 1/4" external square drive (6.3 DIN 3120/ISO 1174-1) and integrated ratchet function with 80 teeth, working angle of 4.5°, for holding 1/4" sockets
- after clicking, the slipping mechanism prevents unintended overshooting of the set tightening torque and overtightening of the screw is prevented
- bright and efficient OLED - colour display readable from virtually any angle
- optical evaluation of the tightening torque by traffic light colours on the display and side mounted LEDs
- supported languages: DE, EN, IT, FR, ES
- stores up to 2,500 joints and sequences for transfer to the PC via an integrated micro-USB interface
- tolerances for evaluation purposes can be set individually
- short training time thanks to virtually self-explanatory controls and an easy-to-understand menu structure
- 3 operating modes (Click, Track, Peak-Hold)
- bolted joints and sequence plans parameterizable
- with a 1/4" inner square at the end of the handle (6.3 DIN 3120/ ISO 1174-1) for accommodating a 1/4" T-handle
- units of measurement: cN·m, N·m, ft·lb, in·lb, in·oz
- included in delivery: software SensoMaster 4, USB cable, bit holder, T-handle (size 10)
- supplied with lithium battery 3.6 V, type 18650, packed according to UN 3481
- the GEN3 version can charge the battery in situ via the micro-USB cable if required
- with 2-component handle
- patented
- in a sturdy plastic box
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4 %**

TORSIOTRONIC®





Electromechanical torque screwdrivers

- long battery life with battery-saving standby mode
- the batteries are quick and easy to change.
- supplied with 3.6 V lithium battery, type 18650, packaged according to UN 3481

Product no.	cN·m	N·m	ft·lb	in·lb	in·oz	L mm	g
96510712	12-120	0.12-1.2	0.08-0.885	1.06-10.7	16.9-169.9	317	569
96510730	30-300	0.3-3	0.2-2.3	2.6-26.6	42-425	317	570
96510760	60-600	0.6-6	0.4-4.45	5.3-53.1	84.5-849.5	317	572
96510700	100-1000	1-10	0.7-7.3	8.8-88.5	141-1417	317	575
96511712 [1]	12-120	0.12-1.2	0.08-0.885	1.06-10.7	16.9-169.9	317	523
96511730 [1]	30-300	0.3-3	0.2-2.3	2.6-26.6	42-425	317	524
96511760 [1]	60-600	0.6-6	0.4-4.45	5.3-53.1	84.5-849.5	317	526
96511700 [1]	100-1000	1-10	0.7-7.3	8.8-88.5	141-1417	317	529

[1] version as 96510712-96510700, but without battery **(not hazardous goods)**

STAHLWILLE TORSIOTRONIC® –
The innovative torque screwdriver.





Precise.

Particularly precise work thanks to the integrated ratchet with 80 teeth for a working angle of just 4.5° – for left and right tightening and indicating or clicking mode.



Documentable.

The TORSIOTRONIC® stores up to 2,500 tightening results for reading and documenting on the PC at a later date via an integrated micro-USB interface.



Ready.

Long battery life with battery-saving standby mode. Always ready for use thanks to a quick and easy rechargeable battery.

MECHANICAL TORQUE WRENCHES – For more efficiency and safety.

Mechanical torque wrenches from STAHLWILLE impress with their easy operation, their technical features and the long-term stability of the measured values: Sophisticated controls ensure greater safety and speed when adjusting the target torque. A precise technology inside for precise triggering. Optimised ergonomics to prevent operator errors and fatigue. And a triggering mechanism with a bending beam, which eliminates the need to unwind the spring to '0' after use.

SIMPLE



Quick.

MANOSKOP® 730 Quick: Convenient and quick to adjust – thanks to particularly large thumbhole and non-slip adjustment slider.

Reliable.

The QuickRelease technology prevents unintentional removal of the insert tools and makes it possible to change tools quickly.

Simple.

Quick external adjustment without dismantling the torque wrench using 2 adjustment points.

Exceptional.

The mechanical torque wrenches from STAHLWILLE feature a low-wear clicking mechanism with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not under load unless the tool is being used, which means that it does not need to be reset to '0' after use.



Flexible.

Thanks to a wide measuring range spanning 4 – 650 N·m and interchangeable insert tools (9x12 mm, 14x18 mm, 22x28 mm), the MANOSKOP® 730 Quick range is particularly flexible.

Precise.

The design with opposing arrow shaped pointers allows quick and precise torque adjustment.

An overview of the mechanical torque wrenches can be found on page 16 and 17!

TORQUE WRENCHES, MECHANICAL.

Key features of torque wrenches
MANOSKOP® 71


- indicating type
- drag indicator dial gauge
- dual scale N·m/ft·lb
- scale made of special luminescent, bright yellow foil for clear readability even in poor visibility conditions
- measuring element as bending plate in the handle
- handle with integrated force compensator
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- readjustment does not require disassembly
- delivered in a textile bag
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4 %**

71/80



Torque wrench MANOSKOP®

- mount for interchangeable shell tools
- when combined with adaptor No. 7370/80, 14 x 18 mm insert tools can also be used (max. 650 N·m)
- with overload protection
- counter-clockwise tightening by turning the insert tools over




Product no.	N·m	ft·lb	N·m	ft·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50030080	160-800	120-600	10	10	24.5 x 28	1048	28	24	1050	95	2300

71aR/80



Torque wrench MANOSKOP®

- with permanently installed ratchet
- 36 teeth
- for controlled clockwise tightening
- dial gauge secured with an additional protective ring




Product no.	N·m	ft·lb	N·m	ft·lb	■ "	L mm	b mm	h mm	L_F mm	g
50450080	160-800	100-600	10	10	3/4	1152	70	30	1060	4900

73Nm/15



Friction gauge

— indicating type
— drag indicator dial gauge
— with built-in square for clockwise measurements
— no 'blinking cursor' during the measurement process
— weight reduction through use of aluminium inserts
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 4%**



Product no.	N·m	N·m	■ "	L mm	b mm	h mm	L_F mm	g
50240015	2-15	0.5	1/2	298.5	72	50	250	676

Key features of torque wrenches

MANOSKOP® 755 series


— clicking type with dual stop signal
— for work on assembly lines or for repetitive production tasks.
— no adjustment scale; therefore adjustment with test equipment is required, e.g. with the STAHLWILLE test devices No. 7707 W, SmartCheck or the perfectControl® calibration systems No. 7794, or calibration systems No. 7706. 7791)
— particularly lightweight design
— handle and shaft made of rectangular steel pipe
— clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measuring range limit of the torque wrench)
— can be supplied pre-set at defined torque value and with certification (additional charge applies)
— **accuracy ± 4 %**

755R/1



Torque wrench Series MANOSKOP®

— measurements are independent of the point of application of force
— for controlled clockwise tightening
— with permanently installed ratchet
— 22 teeth




Product no.	N·m	ft·lb	■ "	L mm	b mm	h mm	g
50100001	1.5-12.5	1.0-9.0	1/4	173.5	22	18	335

755



Torque wrenches Series MANOSKOP®

— with holder for interchangeable insert tools
— counter-clockwise tightening by turning the insert tools over



Product no.	Size	N·m	ft·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50010004	4	4-40	3-30	9 x 12	201	22	18	172	17.5	500
50010010	10	20-100	15-74	9 x 12	318	28	24	289	17.5	635
50010020	20	40-200	30-147	14 x 18	457	28	24	435	25	1045
50010030	30	60-300	40-220	14 x 18	609	28	24	587	25	1210

Key features of torque wrenches
Service MANOSKOP® 730 Quick


- clicking type with dual stop signal
- no reset to '0' required
- the measuring element is only under load during tightening
- with holder for interchangeable insert tools
- with QuickRelease safety lock (size 5-65)
- non-slip adjuster with thumb recess for quick torque adjustment
- fine, tapered pointers
- clicking mechanism insensitive to continuous loads and counter-loads (max. up to the measuring range limit of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- counter-clockwise tightening by turning the insert tools over
- easy adjustment without disassembly via 2 adjustment screws
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

730 Quick



Torque wrenches Service MANOSKOP® (N·m)

- N·m scale only




Product no.	Size	N·m	N·m	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50184001	2-1	2-10	0.25	9 x 12	179	27.5	23.6	157.2	17.5	315
50184002	2	4-20	0.5	9 x 12	179	27.5	23.6	157.2	17.5	315
50184004	4	8-40	1	9 x 12	223	27.5	23.6	200.8	17.5	395

730a Quick



Torque wrenches Service MANOSKOP® (in·lb)

- in·lb scale only



Product no.	Size	in·lb	in·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50584001	a/2-1	17.5-87.5	2.5	9 x 12	179	27.5	23.6	157.2	17.5	315
50584002	a/2	30-175	5	9 x 12	179	27.5	23.6	157.2	17.5	315
50584004	a/4	70-350	10	9 x 12	223	27.5	23.6	200.8	17.5	395


730 Quick



Torque wrenches Service MANOSKOP®

— dual scale N·m/ft·lb

— also available on request as a N·m only version without dual scale



Product no.	Size	N·m	ft·lb	N·m	ft·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50184005	5	6-50	5-36	2	1	9 x 12	315	28	23	288	17.5	780
50184010	10	20-100	15-72.5	2.5	2.5	9 x 12	370	28	23	343	17.5	936
50184012	12	25-130	20-95	2.5	2.5	14 x 18	410	28	23	390	25	1074
50184020	20	40-200	30-145	5	5	14 x 18	455	28	23	435	25	1310
50184030	30	60-300	50-220	10	10	14 x 18	520	28	23	500	25	1400
50184040	40	80-400	60-300	10	10	14 x 18	590	28	23	570	25	1540
50184065 [1] [2]	65	130-650	100-480	20	20	14 x 18	875	30.6	25.6	855	25	3192
50184565 [1] [2]	II/65	130-650	100-480	20	20	22 x 28	897	30.6	25.6	907	55	4104

[1] recommended ratchet insert tool No. 735/40HD


[2] supplied in textile bag

730a Quick



Torque wrenches Service MANOSKOP®

— dual scale N·m/in·lb



Product no.	Size	N·m	in·lb	N·m	in·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50584005	a/5	6-50	50-440	2	10	9 x 12	315	28	23	288	17.5	780
50584010	a/10	20-100	180-880	2.5	20	9 x 12	370	28	23	343	17.5	934
50584012	a/12	25-130	225-1150	2.5	25	14 x 18	410	28	23	390	25	1076
50584020	a/20	40-200	350-1750	5	50	14 x 18	455	28	23	435	25	1216


TOOLS THAT
... inspire

730R Quick



Torque wrenches Service MANOSKOP®

- dual scale N·m/ft·lb
- with holder for interchangeable insert tools
- with ratchet No. 735
- 60 teeth




Product no.	Size	N·m	ft·lb	N·m	■ "	mm	L mm	b_1 mm	b_2 mm	h mm	L_F mm	S_F mm	g
96501054	2-1	2-10	-	0.5	1/4	9 x 12	250	60	22	55	157.2	17.5	480
96504002	2	4-20	-	0.5	3/8	9 x 12	255	55	33	55	157.2	17.5	455
96504004	4	8-40	-	1	3/8	9 x 12	285	55	33	55	200.8	17.5	642
96504005	5	6-50	5-36	2	3/8	9 x 12	380	50	33	50	288	17.5	994
96504010	10	20-100	15-72.5	2.5	1/2	9 x 12	430	55	33	55	343	17.5	1190
96504012	12	25-130	20-95	2.5	1/2	14 x 18	475	52	43	52	390	25	1488
96504020	20	40-200	30-145	5	1/2	14 x 18	530	55	43	55	435	25	1626
96504030	30	60-300	50-220	10	1/2	14 x 18	590	50	43	50	500	25	1400
96504040	40	80-400	60-300	10	3/4	14 x 18	675	72	50	63	570	25	2694

730/80



Torque wrench Service MANOSKOP®

- dual scale N·m/ft·lb
- with holder for interchangeable shell tools
- when combined with adaptor No. 7370/80, 14 x 18 mm insert tools can also be used (max. 650 N·m)
- delivered in a textile bag



Product no.	N·m	ft·lb	N·m	ft·lb	■ mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50180080	160-800	120-600	20	20	24.5 x 28	970	46	43	990	95	4925



Key features of torque wrenches
Standard MANOSKOP® 721 Quick


- clicking type with dual stop signal
- no reset to '0' required
- the measuring element is only under load during tightening
- quick adjustment thanks to easy-to-operate clamping lever in handle
- non-slip adjuster with thumb recess for quick torque adjustment
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measuring range limit of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- only for controlled clockwise tightening
- easy adjustment without disassembly via 2 adjustment screws
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4 %**

721 Quick



Torque wrenches Standard MANOSKOP®

- dual scale N·m/ft·lb
- with permanently installed ratchet



Product no.	Size	N·m	ft·lb	N·m	ft·lb	■ "	L mm	b_1 mm	b_2 mm	h_1 mm	h_2 mm	L_F mm	Number of teeth	g
50204005	5	6-50	5-36	2	1	3/8	352	28	27.5	23	14.5	293	30	880
50204015	15	30-150	25-110	5	5	1/2	452	28	41	23	18	387	36	1282
50204020	20	40-200	30-145	5	5	1/2	483	28	41	23	18	418	36	1349
50204030 [1]	30	60-300	50-220	10	10	1/2	553	28	44	23	27.5	486	36	1646


[1] size 30 with push through square drive for counter-clockwise tightening (for replacement square drive see page 80)

721QR Quick



Torque wrenches Standard MANOSKOP®

- dual scale N·m/ft·lb
- with permanently installed QuickRelease ratchet
- 36 teeth



Product no.	Size	N·m	ft·lb	N·m	ft·lb	■ "	L mm	b_1 mm	b_2 mm	h_1 mm	h_2 mm	L_F mm	g
50204115	15	30-150	25-110	5	5	1/2	452.5	28	41	23	18	387	1268
50204120	20	40-200	30-145	5	5	1/2	482	28	41	23	18	416.5	1338


Key features of torque wrenches
Standard MANOSKOP® 720Nf/721Nf


- clicking type with dual stop signal
- dual scale N·m/ft·lb
- anti-clockwise tightening via push-through square drive
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- easy adjustment without disassembly via 2 adjustment screws
- delivered in a textile bag
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4 %**

720Nf/80



Torque wrench Standard MANOSKOP® with fixed square drive
- 3/4" external square drive
- with reversible square





Product no.	N·m	ft·lb	N·m	ft·lb	■ "	L mm	b mm	h mm	L_F mm	g
50190081	160-800	120-600	20	20	3/4	1034	45	42	938	5650


721Nf





721Nf/80

721Nf/100

Torque wrenches Standard MANOSKOP®
- 3/4" external square drive
- with permanently installed ratchet
- with reversible square
- 30 teeth







Product no.	Size	N·m	ft·lb	N·m	ft·lb	■ "	L mm	L_1	b_1 mm	b_2 mm	h mm	L_F mm	g
50200081	80	160-800	120-600	20	20	3/4	1050.5	-	46.5	76	42	938	6380
96502001	100	200-1000	150-725	25	25	3/4	820	1503.5	46.5	76	42	1365.5	7010

Key features of mechanical torque wrenches
Service MANOSKOP® 730N


- clicking type with dual stop signal
- no reset to '0' required
- the measuring element is only under load during tightening
- fast, precise adjustment with QuickSelect quick adjustment
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measuring range limit of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- easy adjustment without disassembly via 2 adjustment screws
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017

730N



Torque wrench Service MANOSKOP®

- dual scale N·m/in·lb
- with holder for interchangeable insert tools
- with QuickRelease safety lock
- counter-clockwise tightening by turning the insert tools over
- **accuracy ± 4**




Product no.	Size	N·m	in·lb	N·m	in·lb	fine scale	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50181102	2	4-20	40-180	1	10	0.2 N·m	9 x 12	275	28	23	226	17.5	737

730N



Torque wrenches Service MANOSKOP®

- dual scale N·m/ft·lb
- with holder for interchangeable insert tools
- with QuickRelease safety lock
- counter-clockwise tightening by turning the insert tools over
- supplied in a textile bag (from size 65)
- **accuracy ± 3%**



Product no.	Size	N·m	ft·lb	N·m	ft·lb	fine scale	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50181005	5	10-50	7-37	5	1	0.25 N·m	9 x 12	330	28	23	280.5	17.5	831
50181010	10	20-100	15-75	10	2.5	0.5 N·m	9 x 12	386	28	23	336	17.5	988
50181012	12	25-130	20-95	10	2.5	0.5 N·m	14 x 18	421	28	23	379	25	1128
50181020	20	40-200	30-150	10	5	1 N·m	14 x 18	467	28	23	424.5	25	1264
50181040	40	80-400	60-300	20	10	2 N·m	14 x 18	607	28	23	564.5	25	1655
50181065 *	65	130-650	100-480	50	20	2.5 N·m	14 x 18	890	30.6	25.6	848	25	3231
50181365	II/65	130-650	100-480	50	20	2.5 N·m	22 x 28	911	30.6	25.6	900	55	3504
50181080	80	160-800	120-600	100	25	5 N·m	22 x 28	1178	30.6	25.6	1167	55	4825
50181100	100	200-1000	150-750	100	25	5 N·m	22 x 28	1363	30.6	25.6	1352	55	5000


* recommended ratchet insert tool No. 735/40HD

730Na



Torque wrenches Service MANOSKOP®

- dual scale ft·lb/in·lb
- with holder for interchangeable insert tools
- with QuickRelease safety lock
- counter-clockwise tightening by turning the insert tools over
- **accuracy ± 3% (size a/2: 4%)**




Product no.	Size	ft·lb	in·lb	in·lb	ft·lb	fine scale	mm	L mm	b mm	h mm	L_F mm	S_F mm	g
50581102	a/2	3-15	40-180	10	0.5	2 in·lb	9 x 12	275	28	23	226	17.5	737
50581005	a/5	7-37	90-450	50	1	2.5 in·lb	9 x 12	330	28	23	280.5	17.5	831
50581010	a/10	15-75	180-900	100	2.5	5 in·lb	9 x 12	386	28	23	336	17.5	988
50581020	a/20	30-150	350-1800	100	5	10 in·lb	14 x 18	467	28	23	424.5	25	1264
50581040	a/40	60-300	800-3600	100	20	2 ft·lb	14 x 18	607	28	23	564.5	25	1655

730NR



Torque wrenches Service MANOSKOP®

- dual scale N·m/ft·lb
- with permanently installed fine-tooth ratchet
- 60 teeth
- in sturdy plastic box (size 65 in sheet steel box)
- **accuracy ± 4%**



Product no.	Size	N·m	ft·lb	N·m	ft·lb	fine scale	■ "	L mm	b_1 mm	b_2 mm	h_1 mm	h_2 mm	L_F mm	g	g with box
96503105	5 FK	10-50	7-37	5	1	0.25 N·m	3/8	364	28	33	23	24	280.5	973	1763
96503110	10 FK	20-100	15-75	10	2.5	0.5 N·m	1/2	420	28	33	23	24	336.5	1146	1934
96503120	20 FK	40-200	30-150	10	5	1 N·m	1/2	513.5	28	43	23	26	425	1583	2370
96502140	40 FK	80-400	60-300	20	10	2 N·m	3/4	657	28	50	23	31.5	564.5	2122	2657
96502265	65 FK-HD	130-650	100-480	50	20	2.5 N·m	3/4	944	30.6	58	25.6	36	848	3698	6188




730NR QR



Torque wrenches Service MANOSKOP®

— dual scale N·m/ft·lb
— with permanently installed QuickRelease ratchet
— with QuickRelease safety lock
— 30 teeth
— in a sturdy plastic box
— **accuracy ± 4%**



Product no.	Size	N·m	ft·lb	N·m	ft·lb	fine scale	■ "	L mm	b1 mm	b2 mm	h1 mm	h2 mm	LF mm	g	g with box
96502105	5QR FK	10-50	7-37	5	1	0.25 N·m	3/8	372.5	28	29	23	14.5	291	961	1386
96502110	10QR FK	20-100	15-75	10	2.5	0.5 N·m	1/2	428.5	28	29	23	14.5	346.5	1129	1554
96502120	20QR FK	40-200	30-150	10	5	1 N·m	1/2	526	28	41	23	18	438.5	1589	2014

Key features of mechanical torque wrenches
Service/Series MANOSKOP® 730 Fix


— clicking type with dual stop signal
— adjustment knob can be unscrewed and removed after setting the desired torque value - subsequent changing of the setting is thus prevented
— no reset to '0' required
— the measuring element is only under load during tightening
— with holder for interchangeable insert tools
— with QuickRelease safety lock
— fast, precise adjustment with QuickSelect quick adjustment
— counter-clockwise tightening by flipping the insert tools over
— clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measuring range limit of the torque wrench)
— optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
— easy adjustment without disassembly via 2 adjustment screws
— with 2-component handle
— in sturdy plastic box (sizes 80-100 in sheet steel box)
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 3%**

730 Fix



Torque wrenches Service/Series MANOSKOP®

— dual scale N·m/ft·lb
— for work on assembly lines or for repetitive production tasks



Product no.	Size	N·m	ft·lb	N·m	ft·lb	fine scale	mm	L mm	b mm	h mm	LF mm	SF mm	g	g with box
96503005	5	10-50	7-37	5	1	0.25 N·m	9 x 12	330	28	23	280.5	17.5	828	1632
96503010	10	20-100	15-75	10	2.5	0.5 N·m	9 x 12	386	28	23	336	17.5	986	1788
96503012	12	25-130	20-95	10	2.5	0.5 N·m	14 x 18	421	28	23	379	25	1124	1928
96503020	20	40-200	30-150	10	5	1 N·m	14 x 18	467	28	23	424.5	25	1266	1890
96503040	40	80-400	60-300	20	10	2 N·m	14 x 18	607	28	23	564.5	25	1666	2444
96503065 *	65	130-650	100-480	50	20	2.5 N·m	14 x 18	890	30.6	25.6	848	25	3242	6500
96503465	II/65	130-650	100-480	50	20	2.5 N·m	22 x 28	911	30.6	25.6	900	55	3490	7000
96503080	80	160-800	120-600	100	25	5 N·m	22 x 28	1178	30.6	25.6	1167	55	4794	10500
96503100	100	200-1000	150-750	100	25	5 N·m	22 x 28	1363	30.6	25.6	1352	55	5196	11000

* recommended ratchet insert tool No. 735/40HD

Torque technology



Triple safety

— adjustment knob can be unscrewed and removed after setting the desired torque value- subsequent changing of the setting is thus prevented

— the supplied TORX® Tamper Resistant locking screw also protects against tampering, as do the enclosed adhesive seals
— no adjustment possible without breaking the seal


730a Fix




Torque wrenches Service/Series MANOSKOP®

— dual scale ft·lb/in·lb

— for work on assembly lines or for repetitive production tasks





Product no.	Size	ft·lb	in·lb	in·lb	ft·lb	fine scale	mm	L mm	b mm	h mm	L_F mm	S_F mm	g	g with box
96583005	a/5	7-37	90-450	50	1	2.5 in·lb	9 x 12	330	28	23	280.5	17.5	832	1638
96583010	a/10	15-75	180-900	100	2.5	5 in·lb	9 x 12	386	28	23	336	17.5	988	1790
96583020	a/20	30-150	350-1800	100	5	10 in·lb	14 x 18	467	28	23	424.5	25	1066	2072
96583040	a/40	60-300	800-3600	100	20	2 ft·lb	14 x 18	607	28	23	564.5	25	1670	2614



BECAUSE YOU DON'T HAVE TIME FOR YOGA...




750NR

The torque wrench with relaxation factor.



Outstanding.

STAHLWILLE on it, STAHLWILLE in it: Quality "Made in Germany", robust and durable. Made of high-quality steel with a special matt finish!



Precise.

Thanks to the easily readable scale, integrated fine scale, and the clearly tangible haptic feedback of the precise mechanical triggering.



Balanced.

Beautiful design with new, ergonomically optimised handle – for low-fatigue work.



Relaxed.


Adjustment of the target torque via an easily accessible rotary knob at the end of the handle. With 10 N·m per revolution (Model 750NR/200), this torque wrench is the fastest in its class!

750NR



Torque wrenches

- dual scale N·m/ft·lb
- clicking type with dual stop signal
- with permanently installed, reversible fine-tooth ratchet
- 60 teeth
- resilient, long-lasting spring mechanism
- fast, precise adjustment with QuickSelect quick adjustment
- for controlled clockwise tightening
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- effortless and precise adjustment and fixing of the target torque using adjustment knob on the end of the handle
- ready for operation again immediately after release
- for maximum measuring accuracy and a long service life, it is recommended to reset the torque wrench to '0' after use
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**



Product no.	N·m	ft·lb	N·m	ft·lb	fine scale	"	L mm	b1 mm	b2 mm	h1 mm	h2 mm	LF mm	g
50021003	20-100	15-74	5	10	0.25 N·m	3/8	443	28	35	23	14	348	1150
50021004	40-200	30-150	10	20	0.5 N·m	1/2	526.7	28	43	23	16	464	1460
50021006	80-400	60-300	20	40	1 N·m	3/4	678.7	28	58	23	24	574.3	2550

ELECTRONIC TORQUE WRENCHES –
Extremely reliable, extremely precise.

No compromises – whether programming and parameterising bolted joints and entire bolting sequences, whether digital measurement and evaluation, or downloading bolted joint data for documentation. In terms of precision, handling and connectivity, STAHLWILLE's electronic torque wrenches are pioneering.

PRECISE



Documenting.

The SENSOTORK® 713R offers extensive documentation options. Up to 2,000 tightening operations are stored with a time stamp.

Connecting.

Parametrisation of the torque wrench or downloading the stored data. The USB interface makes this possible together with the optional SensoMaster software.

Multisensory.

The achieved torque is signalled visually, acoustically and haptically – by means of an LCD with multi-colour backlighting, warning tone and vibration.



Compact.

The SENSOTORK® 701 impresses with its slim and compact design and is specially designed for low torques in the range of 1–20 N·m. Ideal for tightening screws on modern materials such as plastic, magnesium or aluminium.

MADE IN CRONENBERG
MADE IN GERMANY

Precise.

With integrated fine-tooth ratchet with 80 teeth and QuickRelease safety lock, which allows quick tool changes whilst preventing unintentional loss of the attached tool.

Efficient.

The SENSOTORK® 701 offers direct adjustment of the target torque on the tool. The single-button control allows quick and easy setting of units and modes (track, peak hold, user mode including target with evaluation).

An overview of the electronic torque wrenches can be found on page 16 and 17!

ELECTROMECHANICAL TORQUE WRENCHES – Precise. Simple. Documented.

Parameterise bolted joints with absolute precision down to the decimal place, measure digitally, evaluate in real time and document for quality assurance? Electromechanical torque wrenches from STAHLWILLE are ideal for more demanding applications and also offer the sensory feedback usually only offered by mechanical torque wrenches.

LEADING



Documenting.

Our electromechanical torque wrenches are easy to configure and program with the SensoMaster software. This means that all data can be downloaded, stored and subjected to further analysis on the PC for better monitoring and optimisation of the work processes.

Intuitive.

High-resolution colour graphics display alongside indicator lights. Yellow light: Prewarning threshold reached. Green light: Measured value within the tolerance range. Red light: Measured value outside the tolerance range.

Connecting.

Simple documentation of the recorded measurements on the PC via the USB interface and via an optional Bluetooth Low Energy module.



Unique.

The best of both worlds: Electromechanical torque wrenches from STAHLWILLE combine the uncompromising precision of an electronic torque tool with the proven feeling of a real, mechanical click.



Time saving.

When using an insert tool with a different length, the user no longer has to recalculate and adjust the target torque. The user simply enters the new extension length. The torque wrench then performs the conversion automatically.

Diverse.

With the electromechanical torque wrench, you are equipped for every bolted joint: Users have four different measurement modes at their disposal with 'Torque', 'Angle of rotation', 'Torque with angle of rotation control' and 'Angle of rotation with torque control'.

An overview of the electromechanical torque wrenches can be found on page 16 and 17!


TORQUE WRENCHES, ELECTRONIC, ELECTROMECHANICAL.

701/2



Electronic torque wrenches SENSOTORK®

- idicating type
- with permanently installed fine-tooth ratchet
- 80 teeth allow for a working angle of just 4.5° - enabling you to work efficiently, even in the tightest spaces
- with QuickRelease safety lock
- very slim and compact design for small torques from 1-20 N·m
- measurement independent of the point of force application
- units of measurement: N·m, cN·m, ft·lb, in·lb
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- results can be documented (with SensoMaster), evaluation of bolted joint by coloured LEDs, buzzer, and vibration
- supplied with 3.6 V lithium-metal battery, type 14500, packaged according to UN3091, Class 9
- adjustable joint parameters
- with 2-component handle
- in a sturdy plastic box
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**



Product no.	cN·m	N·m	in·lb	ft·lb	■ "	L mm	b mm	h mm	L_F mm	g	g with box
96504502	100-2000	1-20	9-180	0.7-15	1/4	210	22.6	10	160	145	710
96504602 *	100-2000	1-20	9-180	0.7-15	1/4	210	22.6	10	160	132	700

* version as 96504502, but without battery **(not hazardous goods)**




Key features of torque wrenches
Service/Series MANOSKOP® 730D/730DR

- patented electromechanical system
- acoustic and visual clicking
- with holder for interchangeable insert tools
- with QuickRelease safety lock
- quick setup via a convenient keyboard
- extension length compensation function: automatic compensation of the tightening torque when a deviating extension length is entered
- overload protection by acoustic and optical warning signals
- accidental adjustment is not possible due to automatic key lock
- indicating mode even for counter-clockwise torques
- units of measurement: N·m, ft·lb, in·lb
- different tolerance limits adjustable depending on the type of bolted joint
- optical evaluation of the result by green and red display
- additional locking of the presets (function mode, target value, unit of measure, tolerances, extension length deviation) by PIN code
- stores up to 7,500 tightening results
- USB interface for data transfer
- automatic warning of the next calibration date
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- with 2-component handle
- supplied with 2 x 1.5 V AA batteries. NiMH batteries AA/LR6, 1.2 V, can be used
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 2%, ± 1 digit**

730D



Electromechanical torque wrenches Service/Series MANOSKOP®
- in sturdy plastic box (sizes 40-100 in steel box)





Product no.	Size	N·m	ft·lb	in·lb	Setting/Indicating display resolution N·m	ft·lb	in·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g	g with box
96501710	10	10-100	7.4-75	90-900	0.2/0.1	0.2/0.1	2/1.0	9 x 12	467	28	23	426.5	17.5	1085	1510
96501720	20	20-200	15-150	180-1800	0.5/0.1	0.5/0.1	5/1.0	14 x 18	548	28	23	515	25	1361	1896
96501740	40	40-400	30-300	360-3600	1.0/0.1	1.0/0.1	10/1.0	14 x 18	688	28	23	655	25	3300	5155
96501765 *	65	65-650	48-480	580-5800	1.0/0.1	1.0/0.1	10/1.0	14 x 18	870	30.6	25.6	837	25	3300	6000
96501965	II/65	65-650	48-480	580-5800	1.0/0.1	1.0/0.1	10/1.0	22 x 28	892	30.6	25.6	889	55	3224	7500
96502080	80	80-800	60-600	720-7200	1.0/1.0	1.0/1.0	10/1.0	22 x 28	1160	30.6	25.6	1157	55	4577	10500
96502100	100	100-1000	74-750	900-9000	1.0/1.0	1.0/1.0	10/1.0	22 x 28	1344	30.6	25.6	1341	55	4995	11000

* recommended ratchet insert tool No. 735/40HD

730DR




Electromechanical torque wrenches Service/Series MANOSKOP®
- includes reversible ratchet No. 735
- in sturdy plastic box (sizes 40-100 in steel box)

Product no.	Size	N·m	ft·lb	in·lb	Setting/Indicating display resolution N·m	ft·lb	in·lb	■ "	mm	L mm	b mm	h mm	Number of teeth	g	g with box
96501810	10	10-100	7.4-75	90-900	0.2/0.1	0.2/0.1	2/1.0	1/2	9 x 12	501	95	74	60	1232	1657
96501820	20	20-200	15-150	180-1800	0.5/0.1	0.5/0.1	5/1.0	1/2	14 x 18	595	95	74	60	1663	2198
96501840	40	40-400	30-300	360-3600	1.0/0.1	1.0/0.1	10/1.0	3/4	14 x 18	738	83	70	60	2232	4722
96501865	65	65-650	48-480	580-5800	1.0/0.1	1.0/0.1	10/1.0	3/4	14 x 18	975	85	70	60	3767	6530
96502065	II/65	65-650	48-480	580-5800	1.0/0.1	1.0/0.1	10/1.0	3/4	22 x 28	977	140	100	60	3994	9000
96501880	80	80-800	60-600	720-7200	1.0/0.1	1.0/0.1	10/1.0	3/4	22 x 28	1255	120	90	30	6492	12500
96501800	100	100-1000	74-750	900-9000	1.0/0.1	1.0/0.1	10/1.0	3/4	22 x 28	1439	120	100	30	6910	12500

FOR ABSOLUTE ACCURACY –
STAHLWILLE angle-controlled torque wrenches.

For high-accuracy applications – Category A bolted connections, for example – just checking the torque is not enough. As well as the torque, it is crucial to tighten to the correct tightening angle. The torque reading specifies how much force was applied to tighten a fastener. For many applications, this is perfectly good enough. However, in certain cases, an additional measure of accuracy is an essential requirement. The tightening force that is generated between the workpieces in a bolted joint has to be exactly adhered to: if the force is too great, there is a risk of breakage. If it is too low, on the other hand, the connection will not be firm enough and may lead to failure in the assembly under normal operation conditions.



Since the tension is dependent on the tightening torque and the angle, measuring equipment that can measure both quantities precisely is required. For applications of this kind, STAHLWILLE has exactly the solutions industry needs.



MANOSKOP® 714 | page 46


SENSOTORK® 713R | page 45

713R




Electronic angle-controlled torque wrenches SENSOTORK®

- simple and flexible operation thanks to menu guidance on the large display
- particularly broad measurement range (5-100 % of the nominal value)
- includes reversible ratchet No. 735
- with QuickRelease safety lock
- for clockwise and counter-clockwise tightening
- measurement independent of the point of force application
- convenient angle of rotation measurement with an extremely wide angle of rotation range
- units of measurement: N·m, ft·lb, in·lb
- prewarning threshold for visual, tactile and acoustic signals can be set
- multicoloured backlit LED display gives visual cue about the status of the process (traffic light principle)
- extension length compensation function: automatic compensation of the tightening torque when a deviating extension length is entered
- easy to maintain thanks to simple adjustment and automatic notification of the next calibration date
- multiple bolted joints can be combined into a menu-guided sequence
- tightening operations are saved with a date and time stamp
- individual identification designation possible
- password protection against unintentional adjustment and unauthorised access
- compliant with DKD-R 3-7, class 2
- with 2 calibration certificates (torque in accordance with DIN EN ISO 6789-2:2017/angle of rotation based on VDI/VDE 2648-2)
- in sturdy plastic box (size 40 in sturdy steel box)
- supplied with 2 x 1.5 V AA batteries. NiMH batteries AA/LR6, 1.2 V can also be used.
- fully automatic calibration (torque) with the perfectControl® calibration system No. 7794-2
- readjustment does not require disassembly
- torque and angle of rotation are visible at the same time
- **angle of rotation accuracy ± 1°, ± 1 digit to 100°, >100° at least 1%, ± 1 digit**
- **torque accuracy ± 1 %, ± 1 digit**



Product no.	Size	N·m	ft·lb	■ "	mm	L mm	b mm	h mm	L_F mm	S_F mm	Number of teeth	g	g with box
96501606	6	3-60	2.5-44	3/8	9 x 12	378	33	24	299	17.5	60	856	1500
96501620	20	10-200	7-148	1/2	14 x 18	608	43	26	524	25	60	1552	2430
96501640	40	20-400	15-296	3/4	14 x 18	838	50	31.5	750	25	60	2332	5555



Key features of angle-controlled torque wrenches

Service/Series MANOSKOP® 714/714R

- patented electromechanical system
- acoustic and visual clicking
- 4 measuring modes (torque, angle of rotation, torque with 'angle of rotation' monitoring variable, angle of rotation with 'torque' monitoring variable)
- high-resolution colour OLED display and side mounted signal lights
- 3 function modes: clicking, peak hold and track
- visual evaluation of the bolted joint: yellow light (pre-warning threshold reached), green light (within tolerance range), red light (outside tolerance range)
- freely configurable menu structure
- battery cap/battery pack with bayonet connection
- optional: Li-ion battery no. 7195-2 and charger no. 7160
- micro USB interface for data transmission
- optional Bluetooth Low Energy module (5.2)
- with QuickRelease safety lock
- interchangeable system for insert tools
- data storage for up to 2,500 tightening results, including date and time stamp
- up to 200 bolted joints in a maximum of 25 sequences can be programmed
- different tolerance limits adjustable depending on the type of bolted joint
- fast and precise setting via the keyboard
- password protected keypad lock
- acoustic and visual signals warn of torque wrench overload and forced clicking in clockwise tightening mode
- automatic indication of the next calibration date, user-configurable according to elapsed time and/or number of operations
- fully automatic calibration and adjustment with the perfectControl® calibration and adjustment systems No. 7794-2 (torque) or No. 7794-3 (torque and angle of rotation) for reducing error influencing factors or calibration system No. 7791
- units of measurement: N·m, ft·lb, in·lb
- extension length compensation function: automatic compensation of the tightening torque when a deviating extension length is entered
- ready for operation again immediately after release
- clockwise and counter-clockwise tightening - the insert tool must be turned over for counter-clockwise torque in 'clicking' function mode
- torque and angle of rotation displays visible simultaneously
- measurement regardless of the force application point (for sizes 1, 2 and 4)
- 3 certificates included (torque indicating/clicking in accordance with DIN EN ISO 6789-2:2017, angle of rotation based on VDI/VDE 2648-2)
- with 2-component handle
- supplied with USB cable, 4 batteries AAA/LR03, 1.5 V

714



714/2




714/80

product design award 2013

Electromechanical angle-controlled torque wrenches MANOSKOP®

- in sturdy plastic box (sizes 40-100 in steel box)
- registered design, patented
- **angle of rotation display resolution 0.1°**
- **angle of rotation accuracy ± 1°, ± 1 digit to 100°, >100° at least 1%, ± 1 digit**
- **torque display resolution ≤ 60 N·m: 0.01 N·m; > 60 N·m: 0.1 N·m; >400 N·m: 1 N·m**
- **torque accuracy ± 2%, ± 1 digit**



Product no.	Size	N·m	ft·lb	in·lb	mm	L mm	b mm	h mm	L_F mm	S_F mm	g	g with box
96500901	1	1-10	0.7-7.5	9-90	9 x 12	226	28	23	188	17.5	370	795
96500902	2	2-20	1.5-15	18-180	9 x 12	226	28	23	188	17.5	380	805
96500904	4	4-40	3-30	36-360	9 x 12	252	28	23	214	17.5	420	845
96500906	6	6-60	4.5-45	54-540	9 x 12	393	28	23	355	17.5	810	1235
96500910	10	10-100	7.4-75	90-900	9 x 12	466	28	23	428	17.5	1085	1655
96500920	20	20-200	15-150	180-1800	14 x 18	547	28	23	516	25	1361	1896
96500940	40	40-400	30-300	360-3600	14 x 18	687	28	23	656	25	1765	5155
96500965	65	65-650	48-480	580-5800	22 x 28	890	30.6	25.6	890	55	3222	7000
96500980	80	80-800	60-600	720-7200	22 x 28	1158	30.6	25.6	1158	55	4572	10400
96500100	100	100-1000	74-750	900-9000	22 x 28	1343	30.6	25.6	1343	55	4990	10500

714R



714R/2



714R/80

Electromechanical angle-controlled torque wrenches MANOSKOP®

- with ratchet insert tool
- in sturdy plastic box (sizes 40-100 in steel box)
- **angle of rotation display resolution 0.1°**
- **angle of rotation accuracy ± 1°, ± 1 digit to 100°, >100° at least 1%, ± 1 digit**
- **torque display resolution ≤ 60 N·m: 0.01 N·m; > 60 N·m: 0.1 N·m; >400 N·m: 1 N·m**
- **torque accuracy ± 2%, ± 1 digit**

Product no.	Size	N·m	ft·lb	in·lb	■ "	mm	L mm	b mm	h mm	Number of teeth	g	g with box
96501001	1	1-10	0.7-7.5	9-90	1/4	9 x 12	269	80	70	22	432	857
96501002	2	2-20	1.5-15	18-180	1/4	9 x 12	269	80	70	22	442	867
96501004	4	4-40	3-30	36-360	1/4	9 x 12	295	80	70	22	482	907
96501006	6	6-60	4.5-45	54-540	3/8	9 x 12	427	80	70	60	965	1390
96501010	10	10-100	7.4-75	90-900	1/2	9 x 12	500	80	70	60	1232	1657
96501020	20	20-200	15-150	180-1800	1/2	14 x 18	594	80	70	60	1663	2198
96501040	40	40-400	30-300	360-3600	3/4	14 x 18	737	95	68	60	2275	5665
96501065	65	65-650	48-480	580-5800	3/4	22 x 28	980	125	95	60	5137	9000
96501080	80	80-800	60-600	720-7200	3/4	22 x 28	1253	130	95	30	6487	12300
96501100	100	100-1000	73-735	885-8850	3/4	22 x 28	1438	130	100	30	6905	12500




7380N/7385N



Angle gauges

— for angle of rotation controlled screw tightening, with static read-off point
— reliable reading from any angle through 2 tapered scales
— with detachable magnet for attaching a $^{1}/_{2}$" square drive socket
— to be used in conjunction with a tightening tool, e.g. Service MANOSKOP® No. 730N
— the choice of angle gauge disc - with $^{1}/_{2}$" or $^{3}/_{4}$" square - depends on the size of the square drive of the tightening tool used



Product no.	Model	⊔⊔⊔	■ "	O "	L mm	b mm	h mm	g
54010001	7380N	2°	$^{1}/_{2}$	$^{1}/_{2}$	416	78	43	505
54010002	7385N	2°	$^{3}/_{4}$	$^{3}/_{4}$	416	78	76	720


ACCESSORIES FOR TORQUE TOOLS.

BLE-MODUL 714



Bluetooth Low Energy module 714

— module for connecting to torque wrenches
— wireless transmission of bolted joint data to the PC
— seamless integration with the STAHLWILLE SensoMaster 4 software
— establish and manage the connection using the free middleware 'BluetoothMaster'



Product no.	for model	L mm	b mm	h mm	g
52110220	714	68	38	58	60

Li-Ion AA 3,7V / 800mAh



Lithium-ion battery

— standard Li-ion battery, 800 mAh and 3.7 V
— hazardous goods: Lithium-ion battery according to UN 3481, Class 9

Product no.	for model	Voltage	g
59220007	701/2	3.7 V	24

7162



Charger Lithium 2

— versatile charger for AA and AAA battery types
— powered by micro USB cable
— LEDs show the operating and charging status
— contains: charger, USB cable

Product no.	for model	Input voltage	Output voltage	g
54100062	701, TORSIOTRONIC®	4.75-5.25 V	3.7 V	75

7195-2



Li-Ion battery for No. 714

— max. charging voltage 4.2 V
— capacity: 2.600 mAh
— hazardous goods: Lithium-ion battery according to UN 3481, Class 9

Product no.	for model	Voltage	g
54101195	714	4.2 V	74

7160



Charging dock for Li-Ion battery No. 7195-2

— incl. power adaptor
— input: 100-240 V AC
— output: 4.2 V DC
— charging time: 4 hours
— with interchangeable power outlet adaptors

Product no.	Output voltage	g
54100060	4.2 V	440

7761



Interface adaptor

— required for automatic calibration and adjustment of the electronic/electromechanical torque and angle-controlled torque wrenches with micro USB interface and with the calibration and adjustment systems perfectControl® No. 7794-2, 7794-3

Product no.		g
52110061		26

7761/3



Interface adaptor set

— required for automatic calibration and adjustment of the electronic/electromechanical torque and angle-controlled torque wrenches with micro USB interface and with the calibration and adjustment systems perfectControl® No. 7794-2, 7794-3

Contains 3-pieces:

1 interface adaptor **No. 7761**
1 jack-push/pull cable **No. 7752**
1 power supply unit with interchangeable power outlet adaptors **No. 7760**

Product no.	Content pcs.	g
96521161	3	255

7751



Jack cable

— with 3.5 mm jack plug at each end
— angled 90°

Product no.	for model	L m	g
52110051	7721, 7722, 7723, 7724, 7757-1, 7707 W	1.5	50

7751-1



Jack-push/pull cable

— connection between laboratory transducers No. 7728 and USB adaptor or display device.
— with jack plug angled at 90° and push/pull connector

Product no.	for model	L m	g
52110054	7728	1.5	38

7751-3



Jack-push/pull cable, short

— with jack plug angled at 90° and push/pull connector

Product no.	for model	L m	g
52110058	7728	0.25	18

7752



Jack cable
- connection between the transducer and the display device or USB adaptor
- with jack plugs, angled by 90° on one side

Product no.	for model	L m	g
52110052	7721.7722,7723.7724, 7757-1, 7707 W	2	35


7760



Power supply
- regulated switching power supply AC/DC power supply AC adaptor
- input: 110-240 V AC
- output: 9 V DC
- with interchangeable power outlet adaptors

Product no.	for model	Input voltage	g
52110056	7750	110-230 V	201

7732-2




SensoMaster software license
- recording of screw tightening with the MANOSKOP® 714, SENSOTORK® 713R (from firmware 4.X), SENSOTORK® 701 and TORSIOTRONIC®
- representation of torque over time, angle of rotation over time, torque over angle of rotation
- displays multiple curves at the same time
- export data for further processing
- single-user licence

Product no.	for model	g
96585235	714, 713R, SENSOTORK® 701, TORSIOTRONIC®	111

7763



USB power supply
- regulated switching power supply AC/DC power supply AC adaptor
- input voltage 100-240 V, 50-60 Hz
- max. input current 0.3 A
- max. output power 10 watts
- output voltage: 5-5.2 V
- efficiency: USA DOE Level VI / Ecodesign Directive 2009/125/EC, (EU) 2019/1782
- protection against water penetration when used indoors



Product no.	for model	Input voltage	Output voltage	g
52110063	SmartCheck; 7162	100-240 V	5-5.2 V	108

7757-1



USB adaptor
- USB Type-A adaptor to Ø 3.5 mm jack socket

Product no.		g
52111057		10

TorkMaster
Simple, professional calibration.

— adjustment of torque wrenches and torque screwdrivers, calibration according to recognised standards and the creation of declarations of conformity and calibration certificates in accordance with DIN EN ISO 6789, the STAHLWILLE TorkMaster software enables all of this
— with maximum safety and minimum effort for the user.
— all data is automatically stored securely, and the calibration is fully documented
— the optional CAQ interface enables connection to your primary CAQ system, which thus has access to all test data at all times

7759-4



USB adaptor, jack cable and TorkMaster software
Connection between perfectControl® or the transducer (No. 7721-7724) and the PC. For adjustment and calibration of torque wrenches and torque screwdrivers. For creating calibration certificates according to DIN EN ISO 6789. These can be printed or saved as a PDF file.
— 'as found' and 'as left' calibrations can be documented
— graphical display of loading curves
— user management
— 17 languages
— test resource manager
System requirements: PC, Microsoft Windows operating system, USB port

Product no.	L m	⚖ g
96583629	1.5	65

7759-6



USB adaptor, jack-push/pull cable and TorkMaster software
Connection between perfectControl® or the laboratory transducer (No. 7728) and the PC. For adjustment and calibration of torque wrenches and torque screwdrivers. For creating calibration certificates according to DIN EN ISO 6789. These can be printed or saved as a PDF file.
— 'as found' and 'as left' calibrations can be documented
— graphical display of loading curves
— user management
— 17 languages
— test resource manager
System requirements: PC, Microsoft Windows operating system, USB port

Product no.	L m	⚖ g
96583631	1.5	72

7759-5



USB adaptor, jack cable and SensoMaster 4 software
— SensoMaster 4 software for electronic and electromechanical STAHLWILLE torque wrenches
— intuitive user interface with a clear tabular structure
— quick and easy programming of electronic and electromechanical torque wrenches
— enables extensive evaluations, such as those used in quality assurance
— read out saved wrench data and saved bolted joints: screw connection identification number, tool serial number, date, and time of tightening, set point torque or set point angle of rotation, target torque, tightening torque or angle of rotation reached, tolerances, bolted joint evaluation
— save the bolted joints to a database
— delete and print selected bolted joints from the database
— export the displayed bolted joints to different formats
— user management
— change PIN
— delete bolted joints stored in the wrench
System requirements: PC, Microsoft Windows operating system, USB port

Product no.	L m	⚖ g
96583630	1.5	65

7750



Display
- to display the torque
- units of measurement: N·m, ft·lb, in·lb
- modes: Track, Peak Hold, First Peak (for hand tightening only)
- with backlighting for better display of readings
- display of both the first-peak and peak torque on clicking torque wrenches
- can be swivelled to any position via ball joint

Product no.	for model	g
52100050	7707, 7721, 7722, 7723, 7724, 7728	182

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

7161



QuickRelease safety locks
- prevents removal of the insert tools
- is locked with a safety screw on the head of the torque wrench
- after assembly, the insert tool can be inserted but not removed
- interchangeable insert tools can be used again after loosening the safety screw
- a TORX® screwdriver with hole in the tip (No. 4656, T20, product no. 46563020) or a screwdriver bit with hole in the tip (No. 1442, T20, product no. 08160020) can be used to operate the safety screw
- for other torque wrenches on request

Product no.	Size	for model	L mm	g
54100070	1	714/1-4	26	4
54100071	2	712R/6; 713R/6; 714/6-10; 730/10 Quick; 730/10 Fix; 730N/10; 730D/10	27	5
54100072	3	713R/20-40; 714/20-40; 730/12-40 Quick; 730/12-40 Fix; 730N/12-40; 730D/20-40	35	11
54100073	4	730/5 Quick; 730/5 Fix; 730N/5	32	2
54100074	5	714/65-100; 730II/65; 730II/65 Quick; 730II/65 Fix; 730/80-100 Fix; 730NII/65; 730N/80-100; 730DII/65; 730D/80-100	50	30

1299



Screwdriver bit
- for hex socket screws
- to operate the adjustment screws on torque wrenches No. 720, 721, 721 Quick, 730, 730 Quick, 730N, 730 Fix
- hex head DIN 3126 / ISO 1173

Product no.	● "	L mm	g
08090002	1/4	34	4

7301/7302



Plastic boxes, empty

— for safe storage and transport of torque wrenches
— matching foam inserts are available separately
— with practical carrying handle
— made of robust plastic, resistant to most common oils, greases and fuels

Product no.	for model	L mm	W mm	H mm	g
81370002	712R/6; 713R/6; 714/1-10; 721/5-20 Quick; 730/5-20 Quick; 730/5-20 Fix; 730N/5-20; 730D/10	550	81	66	425
81370003	713R/20; 714/20; 721/30 Quick; 730/40 Quick; 730/40 Fix; 730N/40; 730D/20	680	81	66	535

7303/7304

Inserts for plastic boxes

— precisely fitting foam inserts for safe transport and storage of torque wrenches

Product no.	for model	L mm	W mm	H mm	g
83071004	721/5-20 Quick; 730/5-20 Quick; 730/5-20 Fix; 730N/5-20; 730D/10	545	60	48	60
83071002	713R/20; 721/30 Quick; 730/40 Quick; 730/40 Fix; 730N/40; 730D/20	675	55	75	81

TOOLS THAT
... inspire

7311/7312



Plastic boxes, empty

— for safe storage and transport of transducers
— supplied without inlay, foam inlays are available separately
— with practical carrying handle
— made of robust plastic, resistant to most common oils, greases, and fuels

Product no.	for model	L mm	W mm	H mm	g
81500003	7721; 7722; 7723; 7728 1-20	291	100	252	554
81500004	7724-1; 7728 40-100	390	147	310	1346

7313/7314

Inserts for plastic boxes

— precisely fitting foam inserts for safe transport and storage of transducers

Product no.	for model	L mm	W mm	H mm	g
83071030	7721; 7722; 7723; 7728 1-20	275	207	70	77
83071031	7724-1; 7728 40-100	360	250	105	242

TWBE



Textile cases for large torque wrenches

— to safely store and transport large torque wrenches

Product no.	Model	for model	L mm	W mm	H mm	g
81231100	TWBE 65	714/65; 730/65 Quick; 730II/65 Quick; 730N/65; 730NII/65; 730/65 Fix; 730II/65 Fix; 730D/65; 730DII/65	1030	90	50	670
81231101	TWBE 80	714/80; 71/80; 71aR/80; 720Nf/80; 721Nf/80; 730/80; 730D/80	1150	90	50	714
81231102	TWBE 100	714/100; 730N/80; 730/80 Fix; 730N/100; 730D/100	1500	90	50	760
81231103	TWBE 721NF/100	721Nf/100	900	140	50	850

TORQUE TOOL SETS.

TORSIOTRONIC® 10/29



Torque screwdriver sets

Key features of torque screwdriver TORSIOTRONIC®

— electromechanical, indicating and clicking type
— for clockwise and counter-clockwise tightening
— visual, acoustic, and haptic stop signal
— with 1/4" external square drive (6.3 DIN 3120/ISO 1174-1) and integrated ratchet function with 80 teeth, ratchet angle of 4.5°, for 1/4" sockets
— after triggering, the clutch mechanism prevents unintended overshooting of the set tightening torque and overtightening of the screw is not possible
— bright and energy-efficient OLED - colour display readable from virtually any angle
— optical evaluation of the applied torque by traffic light colours on the display and side mounted LEDs
— supported languages: DE, EN, IT, FR, ES
— stores up to 2,500 joint and sequence results, for transfer to the PC via an integrated micro-USB interface
— tolerances for evaluation purposes can be set individually
— short training time thanks to intuitive controls and an easy-to-understand menu structure
— three operating modes (Click, Track, Peak-Hold)
— bolted joints and sequences can be programmed
— with a 1/4" inner square at the end of the handle (6.3 DIN 3120/ISO 1174-1) for accommodating a 1/4" T-handle
— units of measurement: cN·m, N·m, ft·lb, in·lb, in·oz
— the GEN3 version can charge the installed battery via the micro USB cable
— long battery life with battery-saving standby mode
— the batteries are quick and easy to change
— supplied with 3.6 V lithium battery, type 18650, packaged according to UN 3481
— with 2-component handle
— patented
— in a sturdy plastic box
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 4%**

Contains:

1 electromechanical torque screwdriver 1/4" **No. TORSIOTRONIC® 10**: measurement range: 100-1,000 cN·m
8 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10 mm
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2, PH3
3 bits POZIDRIV® 1/4" **No. PZ 1221-1223**: PZ1; PZ2, PZ3
4 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6 mm
5 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20
5 screwdriver sockets TORX® with hole 1/4" **No. 44 KTXB**: T8; T9; T10; T15; T20
1 bit holder 1/4" **No. 412**
+ sturdy plastic box, SensoMaster 4, USB cable, T-handle (size 10), battery 3.6 V, type 18650, packed in accordance with UN 3481

Product no.	L mm	W mm	H mm	Content pcs.	g
96510000	420	227	70	29	2000
96510001 [1]	420	227	70	28	2000

[1] 96510001 - version as 96510000, but without battery **(not hazardous goods)**

701/32/1



Torque tool sets with SENSOTORK®

Key features of torque wrench No. 701/2

— idicating type
— with permanently installed fine-tooth ratchet
— 80 teeth allow for a working angle of just 4.5° - enabling you to work efficiently, even in the tightest spaces
— with QuickRelease safety lock
— very slim and compact design for small torques from 1-20 N·m
— measurement independent of the point of force application
— units of measurement: N·m, cN·m, ft·lb, in·lb
— optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
— results can be documented (with SensoMaster), evaluation of bolted joint by coloured LEDs, buzzer, and vibration
— supplied with 3.6 V lithium-metal battery, type 14500, packaged according to UN3091, Class 9
— adjustable joint parameters
— with 2-component handle
— in a sturdy plastic box
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 4%**

Contains 32-pieces:

1 torque wrench 1/4" **No. 701/2**: measurement range: 1-20 N·m
11 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
1 QuickRelease extension 1/4" **No. 405QR**: L. 54 mm
1 bit holder 1/4" **No. 412**
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2; PH3
3 bits POZIDRIV® 1/4" **No. PZ 1221-1223**: PZ1; PZ2; PZ3
4 bits hex 1/4" **No. 1301-1304**: 4; 5; 6; 8 mm
7 bits TORX® 1/4" **No. 1414-1420**: T10; T15; T20; T25; T27; T30; T40
1 USB cable **No. 7754**

Product no.	L mm	W mm	H mm	Content pcs.	g
96090005	320	135	55	32	923
96090006 [1]	320	135	55	32	923

[1] 96090006 - version as 96090005, but without battery **(not hazardous goods)**

Rad-Set 701



Bicycle tool set
- high quality bicycle tools for standard screw profiles: hex socket, hex and TORX®
- mobile bicycle service kit in practical textile bag with STAHLWILLE logo, for easy and secure attachment to the frame

Key features of torque wrench No. 701/2
- idicating type
- with permanently installed fine-tooth ratchet
- 80 teeth allow for a working angle of just 4.5° - enabling you to work efficiently, even in the tightest spaces
- with QuickRelease safety lock
- very slim and compact design for small torques from 1-20 N·m
- measurement independent of the point of force application
- units of measurement: N·m, cN·m, ft·lb, in·lb
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- results can be documented (with SensoMaster), evaluation of bolted joint by coloured LEDs, buzzer, and vibration
- supplied with 3.6 V lithium-metal battery, type 14500, packaged according to UN3091, Class 9
- adjustable joint parameters
- with 2-component handle
- in a sturdy plastic box
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

Contains 18-pieces:

1 torque wrench 1/4" **No. 701/2**: measurement range: 1-20 N·m
1 USB cable **No. 7754**
3 double open-ended spanners **No. 12**: 6 x 6; 7 x 7; 10 x 10 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
5 screwdriver sockets TORX® 1/4" **No. 44KTX**: T10; T15; T20; T25; T27
1 mini QuickRelease fine-tooth ratchet 1/4" **No. 418QR**: L. 90 mm
1 QuickRelease extension 1/4" **No. 405QR**: L. 54 mm
1 mini water pump pliers **No 6515**: L. 125 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96500001	230	102	40	18	692

Rad-Set 730/2



Bicycle tool set
- high quality bicycle tools for standard screw profiles: hex socket, hex and TORX®
- mobile bicycle service kit in practical textile bag with STAHLWILLE logo, for easy and secure attachment to the frame

Key features of torque wrench No. 730/2 Quick
- clicking type with dual stop signal
- no reset to '0' required
- the measuring element is only under load when a force is applied.
- mount for interchangeable insert tools
- with QuickRelease safety lock
- non-slip adjuster with thumb recess for quick torque adjustment
- fine, tapered pointers
- counter-clockwise tightening by turning the insert tool over
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- easy adjustment without disassembly via 2 external adjustment screws
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

Contains 18-pieces:

1 torque wrench MANOSKOP® **No. 730/2 QUICK**: measurement range: 4-20 N·m
1 QuickRelease ratchet insert tool 1/4" **No. 735/4:** 60 teeth
3 double open-ended spanners **No. 12**: 6 x 6; 7 x 7; 10 x 10 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
5 screwdriver sockets TORX® 1/4" **No. 44KTX**: T10; T15; T20; T25; T27
1 mini QuickRelease fine-tooth ratchet 1/4" **No. 418QR**: L. 90 mm
1 QuickRelease extension 1/4" **No. 405QR**: L. 54 mm
1 mini water pump pliers **No 6515**: L. 125 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96500002	230	102	40	18	692

721QR/20/3/1 Quick



Wheel change set
- high-quality tool set specially designed for wheel changes
- in a sturdy plastic box

Key features of torque wrench No. 721QR/20 Quick
- clicking type with dual stop signal
- quick adjustment thanks to easy-to-operate locking lever in handle
- with permanently installed QuickRelease ratchet
- 36 teeth
- with QuickRelease safety lock
- no reset to '0' required
- the measuring element is only under load when a force is applied
- dual scale N·m/ft·lb
- non-slip adjuster with thumb recess for quick torque adjustment
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- easy adjustment without disassembly via 2 external adjustment screws
- for controlled clockwise tightening
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

Contains 5-pieces:

1 torque wrench standard MANOSKOP® with QuickRelease ratchet 1/2" **No. 721QR/20 Quick**: measurement range: 40-200 N·m; 30-150 ft·lb
3 IMPACT wheel nut sockets with hex 1/2" **No. 51IMP K**: 17 mm (green); 19 mm (blue); 21 mm (red)
1 QuickRelease extension 1/2" **No. 509QR**: L. 130 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96507214	550	81	66	5	2818

750NR/200/3/1



Wheel change set
- high-quality tool set specially designed for wheel changes
- in a sturdy plastic box

Key features of torque wrench No. 750NR/200
- clicking type with dual stop signal
- with permanently installed, reversible fine-tooth ratchet
- 60 teeth
- resilient, long-lasting spring mechanism
- fast, precise adjustment with QuickSelect quick adjustment
- for controlled clockwise tightening
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- fixing of the specified torque via a detent
- dual scale N·m/ft·lb
- ready for operation again immediately after release
- for maximum measuring accuracy and a long service life, it is recommended to reset the torque wrench to '0' after use
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

Contains 5-pieces:

1 torque wrench with fine-tooth ratchet 1/2" **No. 750NR/200**: measurement range: 40-200 N·m; 30-145 ft·lb
3 IMPACT wheel nut sockets with hex 1/2" **No. 51IMP K**: 17 mm (green); 19 mm (blue); 21 mm (red)
1 extension 1/2" **No. 509/5**: L. 130 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96507216	680	81	66	5	2940

TOOLS THAT ... inspire

730R/40/32 Quick



Torque wrench set

— for general maintenance work
— in steel case

Key features of torque wrench No. 730/40 Quick

— clicking type with dual stop signal
— no reset to '0' required, as the measuring element is only under load when a force is applied
— mount for interchangeable insert tools
— with QuickRelease safety lock
— Quick adjustment thanks to easy-to-operate locking lever in handle
— non-slip adjuster with thumb recess for quick torque adjustment
— double scale N·m/ft·lb or N·m/in·lb
— also available on request as a N·m only version without dual scale
— counter-clockwise tightening by turning the insert tools over
— clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
— optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
— easy adjustment without disassembly via 2 external adjustment screws
— with 2-component handle
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 4%**

Contains 32-pieces:

1 torque wrench Service MANOSKOP® **No. 730R/40 Quick**: measurement range: 80-400 N·m
1 ratchet insert tool, reversible 1/2" **No. 735/20**: 60 teeth
1 square drive insert tool 1/2" **No. 734/20**
7 open-ended insert tools **No. 731/40**: 13; 15; 17; 19; 22; 27; 30 mm
1 open-ended insert tool **No. 3731/40**: 24 mm
7 ring insert tools **No. 732/40**: 13; 15; 17; 19; 22; 24; 27 mm
10 sockets with bi-hex 1/2" **No. 50**: 13; 14; 15; 17; 19; 22; 24; 27; 30; 32 mm
1 T-handle 1/2" **No. 506**: L 300 mm
3 extensions 1/2" **No. 509**: L. 55; 130; 255 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96502053	640	240	60	32	9739



ACHIEVE THE CORRECT TIGHTENING TORQUE – even when using insert tools with an extended length.

When you tighten fasteners using inserts whose extension length S deviates from the standard length S_F, it is necessary to recalculate the setting/display value for the torque wrench in use.

Caution! If adaptors are combined with inserts or special tools, use the sum of the extensions = Σ S. Where the special tool is angled to the side, adjusted reading or setting value W_K will have to be determined empirically.

$$W_K = \frac{M_A \cdot L_F}{L_K} \left[\frac{N{\cdot}m \cdot mm}{mm}\right]$$

$$W_K = \frac{M_A \cdot L_F}{L_F - S_F + S \text{ (bzw. } \Sigma S)}$$

M_A = Desired tightening torque

W = Reading/setting $W = M_A$

W_K = Adjusted reading or setting value $W_K \neq M_A$

L_F = Functional length (see dimension table for torque wrenches)

L_K = Adjusted functional length $L_K = L_F - S_F + S$ (or Σ S)

S = Extension of STAHLWILLE inserts or special tools (see dimension table for inserts)


S_F = Standard extension (see dimension table for torque wrenches)

ΣS = Total of all extensions of the attached inserts $S_{adaptor}+S_{insert}+...$



Normal situation

Torque wrench No 730N/10 combined with
square drive insert tool No 734/5 and socket size 13 mm
Required tightening torque for the screw M_A = 40 N·m




Dimension table for torque wrenches: S_F = 17.5 mm, L_F = 336 mm
Dimension table for square drive insert tools: S = 17.5 mm

No adjustment to setting value required on torque wrench. → S = S_F → W = M_A

Example 1: adjusted setting value (1 insert tool)

Torque wrench No 730N/20 combined with
ring insert tool No 732/40 size 36 mm
Required tightening torque for the screw M_A = 190 N·m




Dimension table for torque wrenches: S_F = 25 mm, L_F = 424.5 mm
Dimension table for ring insert tools: S = 28 mm

And this is what it looks like in the catalogue:

730N



Service MANOSKOP® torque wrench
- dual scale N·m/in·lb
- with holder for interchangeable insert tools
- with QuickRelease safety lock
- counter-clockwise tightening by turning the insert tools over
- **accuracy ± 4**




Product no.	Size	N·m	in·lb	N·m	in·lb	fine scale	mm	L_F mm	S_F mm
50181005	5	10-50	7-37	5	1	0,25 N·m	9 x 12	280,5	17,5
50181010	10	20-100	15-75	10	2,5	0,5 N·m	9 x 12	336	17,5
50181012	12	25-130	20-95	10	2,5	0,5 N·m	14 x 18	379	25
50181020	20	40-200	30-150	10	5	1 N·m	14 x 18	424,5	25
50181040	40	80-400	60-300	20	10	2 N·m	14 x 18	564,5	25
50181065 *	65	130-650	100-480	50	20	2,5 N·m	14 x 18	848	25
50181365	II/65	130-650	100-480	50	20	2,5 N·m	22 x 28	900	55
50181080	80	160-800	120-600	100	25	5 N·m	22 x 28	1167	55
50181100	100	200-1000	150-750	100	25	5 N·m	22 x 28	1352	55

L_F S_F

$$W_K = \frac{M_A \cdot L_F}{L_F - S_F + S} = \frac{190\ \text{N·m} \cdot 424{,}5\ \text{mm}}{424{,}5\ \text{mm} - 25\ \text{mm} + 28\ \text{mm}} = \frac{190\ \text{N·m} \cdot 424{,}5\ \text{mm}}{427{,}5\ \text{mm}} = 188{,}7\ \text{N·m}$$

732/40





Product no.	mm	mm	b mm	h mm	S mm
58224013	13	14 x 18	22,5	11	25
58224014	14	14 x 18	23	11	25
58224015	15	14 x 18	24	11	25
58224016	16	14 x 18	25,5	12	25
58224017	17	14 x 18	27	12	25
58224018	18	14 x 18	29	13	25
58224019	19	14 x 18	30,5	13	25
58224021	21	14 x 18	33	15	25
58224022	22	14 x 18	34,5	15	25
58224024	24	14 x 18	37,5	15	25
58224027	27	14 x 18	42,5	17	25
58224028	28	14 x 18	45,5	19	25
58224030	30	14 x 18	46	19	25
58224032	32	14 x 18	47,5	19	25
58224034 *	34	14 x 18	52	19	28
58224036 *	36	14 x 18	54	19	28
58224041 *	41	14 x 18	60	20	30


S

Adjusted setting value W_K = 188.7 N·m
→ value to set 189 N·m

→ S ≠ S_F → W ≠ M_A

Example 2: adjusted reading (insert tool and adaptor)

Torque wrench No 730N/10 combined with
square drive insert tool No 734/5 and adaptor No 447 size 10 mm
Required tightening torque for the screw M_A = 25 N·m



Dimension table for torque wrenches: L_F = 336 mm, S_F = 17.5 mm
Dimension table for square drive insert tools: S_F = 17.5 mm
Dimension table for adaptors: Σ S = 50.8 mm

$$W_K = \frac{M_A \cdot L_F}{L_F - S_F + \Sigma S} = \frac{25\ \text{N·m} \cdot 336\ \text{mm}}{336\ \text{mm} - 17.5\ \text{mm} + 17.5\ \text{mm} + 50.8\ \text{mm}} = \frac{25\ \text{N·m} \cdot 336\ \text{mm}}{386.8\ \text{mm}}$$

Adjusted setting value W_K = 21.7 N·m

→ ΣS ≠ S_F → W ≠ M_A

INSERT TOOLS.


Insert tools for torque wrenches
General information

— external square drives ■ according to DIN 3120
— load capacities on external square drives in accordance with DIN EN ISO 6789
— if larger torque wrenches and tool holders are used, this must not be exceeded

725QR



QuickRelease ratchet insert tools
— for torque wrenches with interchangeable insert system
— reversible
— with QuickRelease safety lock
— size 4: 22 teeth
— sizes 5 and 10: 30 teeth




Product no.	Size	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58253004	4	1/4	9 x 12	22	13.8	17.5	16.4	40	50
58253005 *	5	3/8	9 x 12	29	18	28	12	100	130
58253010 *	10	1/2	9 x 12	29	18	28	12	100	141

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

725B



Bit ratchet insert tools
— for torque wrenches with interchangeable insert system
— reversible
— with internal hex, 1/4" or 5/16", DIN 3126 / ISO 1173 D 6.3 or D8
— for direct mounting of bits with 1/4" or 5/16" external hex C 6.3 or C 8 (size 4: 22 teeth, size 5: 30 teeth)
— hex with collar-thrust spring
— bits are easy to insert, lock securely into place, and can be easily pulled out again; also hex with wide groove (Form E, DIN 3126 / ISO 1173)




Product no.	Size	mm	b mm	h mm	S mm	°	g
58255004	4	9 x 12	22	13.6	17.5	16.4	54
58255005 *	5	9 x 12	29	17.9	28	12	117

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

725/4



Ratchet insert tool
— for torque wrenches with interchangeable insert system
— reversible
— 22 teeth



Product no.	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58254004	1/4	9 x 12	22	13.8	17.5	16.4	40	62




735



Fine-tooth ratchet insert tools

— for torque wrenches with interchangeable insert system
— reversible (also available as a clockwise-only ratchet on request)
— 60 teeth




Product no.	Size	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58250004	4	1/4	9 x 12	24	19	17.5	6	42	82
58250005	5	3/8	9 x 12	33	24	17.5	6	100	150
58250010	10	1/2	9 x 12	33	24	17.5	6	100	147

734



Square drive insert tools

— for torque wrenches with interchangeable insert system
— with secured square drive




Product no.	Size	■ "	mm	b mm	h mm	S mm	max. N·m	g
58240004	4	1/4	9 x 12	20	14	17.5	40	71
58240005	5	3/8	9 x 12	20	14	17.5	80	76
58240010	10	1/2	9 x 12	20	14	17.5	100	82

734F



Square drive insert tools

— for torque wrenches with interchangeable insert system
— with secured square drive




Product no.	Size	■ "	mm	b mm	h mm	S mm	max. N·m	g
58241004	4	1/4	9 x 12	22	14	17.5	40	72
58241005	5	3/8	9 x 12	22	14	17.5	80	75

731/10



Open-ended insert tools

— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable



Product no.	mm	mm	b mm	h mm	S mm	g
58211007	7	9 x 12	22	5	17.5	40
58211008	8	9 x 12	22	5	17.5	39
58211009	9	9 x 12	26	5.5	17.5	38
58211010	10	9 x 12	26	5.5	17.5	42
58211011	11	9 x 12	26	5.5	17.5	41
58211012	12	9 x 12	30	7	17.5	43
58211013	13	9 x 12	30	7	17.5	45
58211014	14	9 x 12	35	8	17.5	52
58211015	15	9 x 12	35	8	17.5	51
58211016	16	9 x 12	38	8.5	17.5	58
58211017	17	9 x 12	38	8.5	17.5	60
58211018 *	18	9 x 12	42	9	20	71
58211019 *	19	9 x 12	42	9	20	74


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

731a/10



Open-ended insert tools

— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable



Product no.	"	mm	b mm	h mm	S mm	g
58611016	1/4	9 x 12	22	5	17.5	36
58611020	5/16	9 x 12	22	5	17.5	53
58611024	3/8	9 x 12	26	5.5	17.5	38
58611028	7/16	9 x 12	26	5.5	17.5	37
58611032	1/2	9 x 12	30	7	17.5	44
58611034	9/16	9 x 12	35	8	17.5	49
58611036	5/8	9 x 12	38	8.5	17.5	64
58611038 *	11/16	9 x 12	42	9	20	76
58611040 *	3/4	9 x 12	42	9	20	73


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

732/10



Ring insert tools

— bi-hex with AS-Drive profile
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	mm	mm	b mm	h mm	S mm	g
58221007	7	9 x 12	13	8	17.5	37
58221008	8	9 x 12	14.2	8	17.5	40
58221010	10	9 x 12	17.2	9	17.5	44
58221011	11	9 x 12	18.5	9	17.5	41
58221012	12	9 x 12	20.5	11	17.5	49
58221013	13	9 x 12	21.5	11	17.5	55
58221014	14	9 x 12	22.5	11	17.5	52
58221015	15	9 x 12	24.5	12	17.5	52
58221016	16	9 x 12	26	12	17.5	54
58221017	17	9 x 12	27	13	17.5	59
58221018	18	9 x 12	28	13	17.5	56
58221019	19	9 x 12	30.5	13	17.5	65
58221021	21	9 x 12	33	15	17.5	71
58221022	22	9 x 12	34.5	15	17.5	74

732a/10



Ring insert tools

— bi-hex with AS-Drive profile
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	"	mm	b mm	h mm	S mm	g
58621016	1/4	9 x 12	13	8	17.5	36
58621020	5/16	9 x 12	14.2	8	17.5	37
58621024	3/8	9 x 12	17.2	9	17.5	37
58621028	7/16	9 x 12	18.5	9	17.5	40
58621032	1/2	9 x 12	21.5	11	17.5	53
58621034	9/16	9 x 12	22.5	11	17.5	52
58621036	5/8	9 x 12	26	12	17.5	54
58621038	11/16	9 x 12	28	13	17.5	58
58621040	3/4	9 x 12	30.5	13	17.5	58
58621042	13/16	9 x 12	33	15	17.5	68
58621044	7/8	9 x 12	34.5	15	17.5	69

732TX/10



TORX® insert tools

— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	Size	mm	b mm	h mm	S mm	g
58291006	E6	9 x 12	13	8	17.5	40
58291008	E8	9 x 12	14.2	8	17.5	45
58291010	E10	9 x 12	17.2	9	17.5	45
58291012	E12	9 x 12	18.5	9	17.5	50
58291014	E14	9 x 12	21.5	11	17.5	60

732G/10



Ring insert tools
- bi-hex with AS-Drive profile
- for torque wrenches with interchangeable insert system
- HPQ® high-performance steel, gunmetal finish




Product no.	mm	mm	b mm	h mm	S mm	g
58620007	7	9 x 12	11.5	6	45	31
58620008	8	9 x 12	12.4	6	45	33
58620009	9	9 x 12	14	8	45	44
58620010	10	9 x 12	15.6	8	45	45
58620013	13	9 x 12	19.3	9.2	45	60

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

732aG/10



Ring insert tools
- bi-hex with AS-Drive profile
- for torque wrenches with interchangeable insert system
- for the assembly and disassembly of engines
- HPQ® high-performance steel, gunmetal finish




Product no.	"	mm	b mm	h mm	S mm	g
58621216	1/4	9 x 12	10.4	6	45	28
58621220	5/16	9 x 12	12.4	6	45	31
58621224	3/8	9 x 12	14.9	8	45	42
58621228	7/16	9 x 12	17	8	45	43
58621232	1/2	9 x 12	19	9.2	45	58
58621234	9/16	9 x 12	21	9.2	45	58
58621236	5/8	9 x 12	23	12	45	74

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

733/10



OPEN RING insert tools
- bi-hex with AS-Drive profile
- for torque wrenches with interchangeable insert system
- special chromium over nickel plating, durable and chip-proof finish
- drop-forged, hardened, and cooled in an oil bath
- extremely strong, exceptionally durable




Product no.	mm	mm	b mm	h mm	W	S mm	g
58231010	10	9 x 12	21.5	11	7.1	17.5	57
58231011	11	9 x 12	22.5	11	8.6	17.5	55
58231012	12	9 x 12	24.5	12	9	17.5	59
58231013	13	9 x 12	26	12	10	17.5	55
58231014	14	9 x 12	27	13	11	17.5	60
58231016	16	9 x 12	30.5	13	13	17.5	65
58231017	17	9 x 12	31.5	13	14	17.5	64
58231018	18	9 x 12	33	15	14.8	17.5	74
58231019	19	9 x 12	34	15	15.8	17.5	70
58231021 *	21	9 x 12	38.5	15	16.2	20	88
58231022 *	22	9 x 12	39.5	15	17	20	92
58231024 *	24	9 x 12	40	15	18	20	75

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

733a/10



OPEN RING insert tools
- bi-hex with AS-Drive profile
- for torque wrenches with interchangeable insert system
- special chromium over nickel plating, durable and chip-proof finish
- drop-forged, hardened, and cooled in an oil bath
- extremely strong, exceptionally durable




Product no.	"	mm	b mm	h mm	W	S mm	g
58631024	3/8	9 x 12	21.5	11	7.1	17.5	55
58631028	7/16	9 x 12	22.5	11	8.6	17.5	56
58631032	1/2	9 x 12	26	12	9.5	17.5	58
58631034	9/16	9 x 12	27.5	13	11	17.5	59
58631036	5/8	9 x 12	30.5	13	12.7	17.5	61
58631038	11/16	9 x 12	33	15	14	17.5	48
58631040	3/4	9 x 12	34	15	15.8	17.5	76

736



Bit holder insert tools

— hex with collar-thrust spring
— for torque wrenches with interchangeable insert system
— bits are easy to insert, lock securely into place, and can be easily pulled out again
— hex socket DIN 3126 / ISO 1173




Product no.	Size	○ mm	○ "	mm	b mm	h mm	S mm	g
58261010	10	D 8	5/16	9 x 12	16	12.5	17.5	47
58262610	10-1	D 6.3	1/4	9 x 12	14	10	17.5	45

737/10



Blank end insert tool

— for welding on custom-made tools
— for torque wrenches with interchangeable insert system
— gunmetal finish
— to avoid damage due to high temperatures, the pin and spring must not be fitted before the tool has been welded
— instructions are provided
— material: 1.2208 - 31CRV3




Product no.	Welding dimensions h_2 x b in mm	mm	L mm	h_2 mm	g
58270010	8 x 14	9 x 12	8	14.5	35

7370/10



Insert tool adaptor

— for use with insert tools with an external size of 14 x 18 mm in torque wrenches with an internal insert system of 9 x 12 mm



Product no.	○ mm	mm	L mm	b mm	h mm	S mm	g
58290010	14 x 18	9 x 12	55	31	26	30.5	118


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

7370/10-2



Insert tool adaptor

— for use with insert tools with a lateral dovetail profile in torque wrenches with an internal system of 9 x 12 mm




Product no.	■ mm	mm	L mm	b mm	h mm	S mm	g
58290012	9.5 x 23.5	9 x 12	40	23.5	9.5	24	51

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

717



Ratchet ring insert tools
- bi-hex
- for torque wrenches with interchangeable insert system
- reversible
- HPQ® high-performance steel, black gunmetal finish



Product no.	mm	mm	b mm	h mm	S mm	°	max. N·m	g
58170108	8	9 x 12	20	7.5	35	5	34	58
58170110	10	9 x 12	22	7.6	42	5	58	70
58170112	12	9 x 12	25	9.1	42	5	89	90
58170113	13	9 x 12	26	9.4	42	5	100	94
58170117	17	9 x 12	32.5	10.6	52	5	160	114
58170119	19	9 x 12	35.5	11.5	52	5	160	126
58170122	22	9 x 12	42	13.8	52	5	160	166

* **Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

1820




Tool holder/disassembly tool
- tool holder without torque function, with tool carrier for insert tools

Product no.	mm	L mm	g
18200001	9 x 12	382.5	490

725QR/20



QuickRelease ratchet insert tool
- for torque wrenches with interchangeable insert system
- reversible
- with QuickRelease safety lock
- 36 teeth




Product no.	Size	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58253020	20	1/2	14 x 18	41	22.3	38.5	10	200	325

* **Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

735



Fine-tooth ratchet insert tools
- for torque wrenches with interchangeable insert system
- reversible (also available as a clockwise-only ratchet on request)
- 60 teeth



Product no.	Size	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58250020	20	1/2	14 x 18	43	26	25	6 °	300	302
58250040	40	3/4	14 x 18	50	31.5	25	6 °	400	515
58250065 *	40HD	3/4	14 x 18	58	36	30	6 °	650	725


* **Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)



734



Square drive insert tools
— for torque wrenches with interchangeable insert system
— with secured square drive




Product no.	Size	■ "	mm	b mm	h mm	S mm	max. N·m	g
58240020	20	1/2	14 x 18	27	18	25	300	205
58240040	40	3/4	14 x 18	40	25	25	650	396

731/40



Open-ended insert tools
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	mm	mm	b mm	h mm	S mm	g
58214013	13	14 x 18	30	7	25	128
58214014	14	14 x 18	35	8	25	129
58214015	15	14 x 18	35	8	25	132
58214016	16	14 x 18	38	9	25	140
58214017	17	14 x 18	38	9	25	130
58214018	18	14 x 18	42	10	25	147
58214019	19	14 x 18	42	10	25	140
58214021	21	14 x 18	50	11	25	171
58214022	22	14 x 18	50	11	25	165
58214024	24	14 x 18	53	12	25	167
58214025	25	14 x 18	53	12	25	170
58214027 *	27	14 x 18	60	13	30	219
58214030 *	30	14 x 18	66	14	30	275
58214032 *	32	14 x 18	66	14	32.5	246
58214034 *	34	14 x 18	66	14	32.5	239
58214036 *	36	14 x 18	74	15	32.5	275
58214038 *	38	14 x 18	74	15	32.5	265
58214041 *	41	14 x 18	82	15	36.5	307

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

731a/40



Open-ended insert tools
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	"	mm	b mm	h mm	S mm	g
58614028	7/16	14 x 18	30	7	25	127
58614032	1/2	14 x 18	30	7	25	125
58614034	9/16	14 x 18	35	8	25	129
58614036	5/8	14 x 18	38	9	25	136
58614038	11/16	14 x 18	42	10	25	148
58614040	3/4	14 x 18	42	10	25	144
58614042	13/16	14 x 18	50	11	25	171
58614044	7/8	14 x 18	50	11	25	165
58614046	15/16	14 x 18	53	12	25	177
58614048 *	1	14 x 18	60	13	30	224
58614052 *	1 1/8	14 x 18	66	14	30	258

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

718



Ratchet ring insert tools
— bi-hex
— for torque wrenches with interchangeable insert system
— reversible
— HPQ® high-performance steel, black gunmetal finish



Product no.	mm	mm	b mm	h mm	S mm	°	max. N·m	g
58170217	17	14 x 18	32.5	10.6	52	5	200	166
58170219	19	14 x 18	35.5	11.5	52	5	200	182
58170221	21	14 x 18	42	13.8	52	5	330	222
58170222	22	14 x 18	42	13.8	52	5	360	216
58170224	24	14 x 18	47	14.6	52	5	360	252
58170227	27	14 x 18	52	15.6	55	5	360	296


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

732/40



Ring insert tools

— bi-hex with AS-Drive profile
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable



Product no.	mm	mm	b mm	h mm	S mm	g
58224013	13	14 x 18	22.5	11	25	130
58224014	14	14 x 18	23	11	25	123
58224015	15	14 x 18	24	11	25	128
58224016	16	14 x 18	25.5	12	25	133
58224017	17	14 x 18	27	12	25	135
58224018	18	14 x 18	29	13	25	134
58224019	19	14 x 18	30.5	13	25	145
58224021	21	14 x 18	33	15	25	144
58224022	22	14 x 18	34.5	15	25	145
58224024	24	14 x 18	37.5	15	25	153
58224027	27	14 x 18	42.5	17	25	162
58224028	28	14 x 18	45.5	19	25	175
58224030	30	14 x 18	46	19	25	182
58224032	32	14 x 18	47.5	19	25	181
58224034 *	34	14 x 18	52	19	28	210
58224036 *	36	14 x 18	54	19	28	203
58224041 *	41	14 x 18	60	20	30	240

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)




732a/40



Ring insert tools

— bi-hex with AS-Drive profile
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	"	mm	b mm	h mm	S mm	g
58624032	1/2	14 x 18	22.5	11	25	122
58624034	9/16	14 x 18	23	11	25	122
58624036	5/8	14 x 18	25.5	12	25	134
58624038	11/16	14 x 18	29	13	25	132
58624040	3/4	14 x 18	30.5	13	25	138
58624042	13/16	14 x 18	33	15	25	142
58624044	7/8	14 x 18	34.5	15	25	147
58624046	15/16	14 x 18	37.5	15	25	151
58624048	1	14 x 18	41	17	25	160

732TX/40



TORX® insert tools

— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	Size	mm	b mm	h mm	S mm	g
58294014	E14	14 x 18	22.5	11	25	130
58294018	E18	14 x 18	24	11	25	135
58294020	E20	14 x 18	29	13	25	150
58294024	E24	14 x 18	30.5	13	25	150

736/40



Bit holder insert tool

— for torque wrenches with interchangeable insert system
— hex with collar-thrust spring
— bits are easy to insert, lock securely into place, and can be easily pulled out again



Product no.	○ "	◪ mm	b mm	h mm	S mm	g
58261040	5/16	14 x 18	16	12.5	25	114

737/40



Blank end insert tool

— for welding on custom-made tools
— for torque wrenches with interchangeable insert system
— gunmetal finish
— to avoid damage due to high temperatures, the pin and spring must not be fitted before the tool has been welded
— instructions are provided
— material: 1.2208 - 31CRV3




Product no.	Welding dimensions h_2 x b in mm	◪ mm	L mm	h_1 mm	g
58270040	11 x 25	14 x 18	12	21.5	98

7370/40



Insert tool adaptor

— for use with insert tools with an external size of 9 x 12 mm in torque wrenches with an internal insert system of 14 x 18 mm



Product no.	○ mm	◪ mm	L mm	b mm	h mm	S mm	g
58290040	9 x 12	14 x 18	60	28	21	21.5	117

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

7370/40-1



Insert tool adaptor

— for use with 24.5 x 28 mm shell tools with torque wrenches with an internal insert system of 14 x 18 mm

Product no.	■ mm	◪ mm	L mm	b mm	h mm	S mm	g
58290041	24.5 x 28	14 x 18	66	75	20	95.9	251


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

7370/40-2



Insert tool adaptor

— for use with insert tools with lateral dovetail profile in torque wrenches with an internal insert system of 14 x 18 mm



Product no.	■ mm	◪ mm	L mm	b mm	h mm	S mm	g
58290042	9.5 x 31.5	14 x 18	50	31.5	9.5	34.6	138

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

1821



Tool holder/disassembly tool

— tool holder without torque function, with tool carrier for insert tools


Product no.	mm	L mm	g
18210001	14 x 18	575	720

735/65



Fine-tooth ratchet insert tool

— for torque wrenches with square drive
— reversible
— 60 teeth




Product no.	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58251065	3/4	22 x 28	61	35	55	6	650	1115

735/100



Ratchet insert tool

— for torque wrenches with interchangeable insert system
— with push-through square drive
— 30 teeth




Product no.	■ "	mm	b mm	h mm	S mm	°	max. N·m	g
58250100	3/4	22 x 28	76	42	55	12	1000	1893

734/100



Square drive insert tool

— for torque wrenches with interchangeable insert system
— with push-through square drive




Product no.	■ "	mm	b mm	h mm	S mm	g
58240100	3/4	22 x 28	43	42	55	1175

731/100



Open-ended insert tools

— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable



Product no.	mm	mm	b mm	h mm	S mm	g
58211024	24	22 x 28	50	13	55	618
58211027	27	22 x 28	56	14	55	640
58211030	30	22 x 28	63	15	55	690
58211032	32	22 x 28	67	15	55	705
58211034	34	22 x 28	72	15	55	731
58211036	36	22 x 28	74	15	55	713
58211041	41	22 x 28	84	16	55	894
58211046	46	22 x 28	94	17	55	934
58211050	50	22 x 28	104	18	55	1073
58211055	55	22 x 28	114	19	55	1172
58211060	60	22 x 28	124	20	55	1241


TOOLS THAT
... inspire

732/100



Ring insert tools

— bi-hex with AS-Drive profile
— for torque wrenches with interchangeable insert system
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	○ mm	mm	b mm	h mm	S mm	g
58221024	24	22 x 28	43	15	55	616
58221027	27	22 x 28	43	15	55	609
58221030	30	22 x 28	46	16	55	617
58221032	32	22 x 28	49	16	55	611
58221034	34	22 x 28	52	17	55	627
58221036	36	22 x 28	54	17	55	620
58221041	41	22 x 28	61	18	55	630
58221046	46	22 x 28	66	19	55	628
58221050	50	22 x 28	75	20	55	701
58221055	55	22 x 28	84	21	55	776
58221060	60	22 x 28	93	22	55	867

737/100



Blank end insert tool

— for welding on custom-made tools
— for torque wrenches with interchangeable insert system
— gunmetal finish
— to avoid damage due to high temperatures, the pin and spring must not be fitted before the tool has been welded
— instructions are provided
— material: 1.2208 - 31CRV3



Product no.	Welding dimensions h_2 x b in mm	mm	L mm	h_1 mm	g
58270100	15 x 50	22 x 28	24	32	483

7370/100



Insert tool adaptor

— for use with 24.5 x 28 mm shell tools with torque wrenches with an internal insert system of 22 x 28 mm

Product no.	■ mm	mm	L mm	b mm	h mm	S mm	g
58291100	24.5 x 28	22 x 28	85	33	30	100	421


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

735/80



Ratchet shell tool

— for torque wrenches with a carrier for shell tools
— with push-through square drive
— 30 teeth




Product no.	■ "	mm	b mm	h mm	S mm	°	g
58250080	3/4	24.5 x 28	76	43	95	12	1930

734/80



Square drive shell tool

— for torque wrenches with a carrier for shell tools
— with push-through square drive




Product no.	■ "	mm	b mm	h mm	S mm	g
58240080	3/4	24.5 x 28	49	42	95	1200

731/80



Open-ended shell tools

— for torque wrenches with a carrier for shell tools
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	mm	mm	b mm	h mm	S mm	g
58218024	24	24.5 x 28	50	13	95	601
58218027	27	24.5 x 28	56	14	95	620
58218030	30	24.5 x 28	63	15	95	655
58218032	32	24.5 x 28	67	15	95	670
58218034	34	24.5 x 28	72	15	95	699
58218036	36	24.5 x 28	74	15	95	620
58218041	41	24.5 x 28	84	16	95	810
58218046	46	24.5 x 28	94	17	95	867
58218050	50	24.5 x 28	104	18	95	1010
58218055	55	24.5 x 28	114	19	95	1150
58218060	60	24.5 x 28	124	20	95	1325

732/80



Ring shell tools

— bi-hex with AS-Drive profile
— for torque wrenches with a carrier for shell tools
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable




Product no.	mm	mm	b mm	h mm	S mm	g
58228024	24	24.5 x 28	36	15	95	605
58228027	27	24.5 x 28	40.5	15	95	610
58228030	30	24.5 x 28	46	16	95	630
58228032	32	24.5 x 28	49	16	95	635
58228034	34	24.5 x 28	52	17	95	650
58228036	36	24.5 x 28	54	17	95	650
58228041	41	24.5 x 28	61	18	95	675
58228046	46	24.5 x 28	66	19	95	700
58228050	50	24.5 x 28	75	20	95	750
58228055	55	24.5 x 28	84	21	95	800
58228060	60	24.5 x 28	93	22	95	850

732a/80



Ring shell tools

— bi-hex with AS-Drive profile
— for torque wrenches with a carrier for shell tools
— special chromium over nickel plating, durable and chip-proof finish
— drop-forged, hardened, and cooled in an oil bath
— extremely strong, exceptionally durable
— for power pack bolts (Airbus A320/A321)




Product no.	"	mm	b mm	h mm	S mm	g
58628046	$^{15}/_{16}$	24.5 x 28	36	14	95	604
58628050	1 $^{1}/_{16}$	24.5 x 28	40.5	14	95	608

7370/80



Shell adaptor

— for torque wrenches with an attachment for insert tools
— for use with 14 x 18 mm insert tools with torque wrenches with an internal insert system of 24.5 x 28 mm



Product no.	mm	mm	b mm	h mm	S mm	g
58290080	24.5 x 28	14 x 18	36	26	70	300

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

1822



Tool holder/disassembly tool

tool holder without torque function, with carrier for shell tools

Product no.	mm	L mm	g
18220003	24.5 x 28	1000	2057


440



Crowring spanners

— bi-hex with AS-Drive profile

— Chrome Alloy Steel, chrome-plated



Product no.	mm	"	L mm	b mm	a mm	W	S mm	g
01190008	8	1/4	23.8	12.7	8	6.3	12.3	11
01190009	9	1/4	28.5	18.2	13.5	6.7	14	21
01190010	10	1/4	28.4	18.2	13.5	7.1	14	16
01190011	11	1/4	28	18.2	13.5	8.6	14	17
01190012	12	1/4	30.8	20.6	14	9	15.7	20
01190013	13	1/4	32	22.2	14	10	16.4	30
01190014	14	1/4	31.7	22.2	14	11.1	16.4	20
02190015	15	3/8	36.5	24.6	17.5	11.9	19.1	34
02190016	16	3/8	36.1	24.6	17.5	13	19.1	27
02190017	17	3/8	39.2	27.3	17.5	14	20.5	40
02190018	18	3/8	40.8	29	18.5	14.8	21.3	45
02190019	19	3/8	40.5	29	18.5	15.8	21.3	40
02190020	20	3/8	42.9	31.3	18.5	15.8	22.5	54
02190021	21	3/8	42.8	31.3	18.5	16.2	22.5	45
02190022	22	3/8	45.3	33.5	19	17	23.6	57
02190023	23	3/8	47.5	35.7	19.5	17.5	24.6	71
02190024	24	3/8	47.3	35.7	19.5	18	24.6	57
02190025	25	3/8	49.3	37.7	20	19	25.7	80
02190026	26	3/8	49.3	37.7	20	19	25.7	63
02190027	27	3/8	52.8	40	21.4	20	28.2	100
03190028	28	1/2	56.8	42.1	22.5	21	29.3	120
03190030	30	1/2	63	48	22.5	22	32.5	155
03190032	32	1/2	62.5	48	22.5	24	32.5	145
03190034	34	1/2	64.2	50	24	27	33.5	146
03190036	36	1/2	66.5	51.9	24	27	34.6	150
03190038	38	1/2	68.1	53.9	24	28.6	35.6	147
03190040	40	1/2	71.8	57.9	24.5	31	37.7	160
03190041	41	1/2	71.8	57.9	24.5	31	37.7	169
03190042	42	1/2	71	57.9	24.5	33.2	37.7	189
03190046	46	1/2	77.7	64.2	26	34.1	40.9	215
03190050	50	1/2	83.2	70.5	27.5	39.7	44.1	295

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

440a




Crowring spanners

— bi-hex with AS-Drive profile

— Chrome Alloy Steel, chrome-plated

— 3/8" for Volvo aircraft engine, type 'JAS'



Product no.	"	"	L mm	b mm	a mm	W	S mm	g
01490024	3/8	1/4	28.4	18.2	13.5	7.1	14	16
01490028	7/16	1/4	28	18.2	13.5	8.6	14	14
01490032	1/2	1/4	30.5	20.6	14	10	15.7	19
01490034	9/16	1/4	31.7	22.2	14	11.1	16.4	23
02490036	5/8	3/8	36.5	24.6	17.5	11.9	19.1	33
02490038	11/16	3/8	39.2	27.3	17.5	14	20.5	36
02490040	3/4	3/8	40.9	29	18.5	14.2	21.3	44
02490042	13/16	3/8	42.9	31.3	18.5	15.8	22.5	51
02490044	7/8	3/8	45.2	33.5	19	17.5	23.6	62
02490046	15/16	3/8	47.2	35.7	19.5	18.3	24.6	63
02490048	1	3/8	49.3	37.7	20	19	25.7	71
02490050	1 1/16	3/8	52.8	40	21.4	20	28.2	84
03490052	1 1/8	1/2	56.8	42.1	22.5	21	29.3	110
03490056	1 1/4	1/2	62.5	48	22.5	23.8	32.5	137
03490058	1 5/16	1/2	62.3	48	22.5	24.6	32.5	130
03490060	1 3/8	1/2	64.2	50	24	27	33.5	138
03490062	1 7/16	1/2	66.5	51.9	24	27	34.6	143
03490064	1 1/2	1/2	68.1	53.9	24	28.6	35.6	152
03490065	1 9/16	1/2	70.1	55.9	24	29.4	36.7	172
03490066	1 5/8	1/2	71.8	57.9	24.5	31	37.7	169
03490068	1 3/4	1/2	75.6	62	25.5	33.2	39.8	199
03490069	1 13/16	1/2	77.7	64.2	26	34.1	40.9	229
03490072	2	1/2	83.2	70.5	27.5	39.7	44.1	277
03490076	2 1/4	1/2	91.2	78.7	29.5	42.8	48.2	337
03490077	2 5/16	1/2	93.3	80.9	30	43.6	49.2	309
03490078	2 3/8	1/2	95.2	83	30.5	46	50.2	385


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

440S MJ



Crowring spanners

— for pipe fittings, with straight cylindrical involute toothing
— EN 4108
— HPQ® high performance steel, chrome-plated



Product no.	Nut thread	mm	"	L mm	b mm	a mm	W	S mm	g
01211010	MJ10	DN04	1/4	31.9	22	8	6.5	17	54
01211014	MJ14	DN06	1/4	36.5	27	8	8.5	19.5	29
02211016	MJ16	DN08	3/8	43.8	31	8	10.5	24	46
02211018	MJ18	DN10	3/8	45.2	33	8	13	25	47
02211020	MJ20	DN12	3/8	46.2	35	8	15	26	49
02211022	MJ22	DN14	3/8	48.4	37	9	17.5	27	54
02211024	MJ24	DN16	3/8	49.5	39	9	19.7	28	56
02211027	MJ27	DN18	3/8	54.4	44	10	21.5	31	70
02211030	MJ30	DN20	3/8	60.8	50	10	23.7	36	93


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

540



Crowfoot spanners

— Chrome Alloy Steel, chrome-plated



Product no.	mm	"	L mm	b mm	a mm	S mm	g
01200008	8	1/4	25.5	19.8	6.3	14.6	19
01200009	9	1/4	25.5	19.8	6.3	14.6	21
01200010	10	1/4	25.5	19.8	6.3	14.6	20
02200011	11	3/8	32	22.2	6.3	17.4	36
02200012	12	3/8	34.3	25.4	6.3	18.2	37
02200013	13	3/8	34.3	25.4	6.3	17.8	36
02200014	14	3/8	37.7	30	6.3	20.8	46
02200015	15	3/8	37.7	30	6.3	20.4	45
02200016	16	3/8	37.7	30	6.3	19.9	45
02200017	17	3/8	42.5	38	6.3	23.8	62
02200018	18	3/8	42.5	38	6.3	22.9	61
02200019	19	3/8	42.5	38	6.3	22.4	64
02200020	20	3/8	42.4	38	6.3	25	55
02200021	21	3/8	44.5	41	6.3	23.6	59
02200022	22	3/8	44.5	41	6.3	24.2	64
02200023	23	3/8	44.5	41	6.3	25.8	64
02200024	24	3/8	44.4	41	6.3	26.3	60
02200025	25	3/8	47	45	8	26.4	75
02200026	26	3/8	47	45	8	27.6	80
02200027	27	3/8	47	45	8	27.6	76
02200028	28	3/8	50	50	8	29.2	78
02200030	30	3/8	50	50	8	29.3	84
02200032	32	3/8	53	57	8	30.5	95
02200034	34	3/8	54.5	60	8	31.6	107
02200036	36	3/8	56.5	62	8	32.8	100
02200040	40	3/8	63	70	8	37.6	130
02200041	41	3/8	63	70	8	37.2	130
02200042	42	3/8	63	70	8	37.7	125
02200046	46	3/8	72	82	8	43.1	191
02200050	50	3/8	75	88	8	45.4	217

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)


TOOLS THAT
... inspire

540a



Crowfoot spanners

— Chrome Alloy Steel, chrome-plated



Product no.	"	"	L mm	b mm	a mm	S mm	g
01500024	3/8	1/4	25.5	19.8	6.3	14.6	17
02500028	7/16	3/8	32	22.2	6.3	17.2	34
02500032	1/2	3/8	34.3	25.4	6.3	18.1	37
02500034	9/16	3/8	37.7	30	6.3	20.9	40
02500036	5/8	3/8	37.7	30	6.3	20.4	44
02500038	11/16	3/8	42.5	38	6.3	24.1	62
02500040	3/4	3/8	42.5	38	6.3	24	66
02500042	13/16	3/8	42.3	38	6.3	24	59
02500044	7/8	3/8	44.5	41	6.3	25.8	65
02500048	1	3/8	47	45	8	26.7	78
02500050	1 1/16	3/8	47	45	8	27.2	78
02500052	1 1/8	3/8	50	50	8	28.5	84
02500054	1 3/16	3/8	50	50	8	29.2	83
02500056	1 1/4	3/8	53	57	8	30.3	101
02500058	1 5/16	3/8	53	57	8	31.2	101
02500060	1 3/8	3/8	54.5	60	8	32.3	105
02500062	1 7/16	3/8	56.5	62	8	33.1	107
02500064	1 1/2	3/8	58	65	8	34.5	118
02500065	1 9/16	3/8	59.5	68	8	35.7	126
02500066	1 5/8	3/8	63	70	8	37.3	140
02500067	1 11/16	3/8	63	70	8	37.7	126
02500068	1 3/4	3/8	68	76	8	40.4	161
02500070	1 7/8	3/8	72	82	8	42	205
02500072	2	3/8	75	88	8	44.8	214
02500074	2 1/8	3/8	75.6	91	10	46	265
02500076	2 1/4	3/8	80.5	96	10	49.5	297
03500078	2 3/8	1/2	81.5	96	8	51.3	214

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

540a HD




Crowfoot spanners heavy-duty

— for particularly high loads, e.g., stainless steel bolted joints

— full use of the open-ended spanner in combination with standard ratchets or torque wrenches with fixed square

— chrome-plated



Product no.	"	"	L mm	b mm	a mm	S mm	g
02501024	3/8	3/8	39	26	11	24	56
02501028	7/16	3/8	40	26	11	25	56
02501032	1/2	3/8	42	30	11	25.8	64
02501034	9/16	3/8	43.4	32	11	26.8	52
02501036	5/8	3/8	45	34.8	11	27.7	58
02501038	11/16	3/8	47.2	38	11	28.6	69
02501040	3/4	3/8	49	41	11	29.6	94
02501042	13/16	3/8	51	46.4	11	30.5	113
02501044	7/8	3/8	52	48	11	31.3	99
02501046	15/16	3/8	54	51.2	11	32.3	129
02501048	1	3/8	56	53.4	11	33.2	133
02501050	1 1/16	3/8	57	53.8	11	34.1	124
02501052	1 1/8	3/8	59	53.8	11	35	128
02501054	1 3/16	3/8	60	56	11	35.9	144
02501056	1 1/4	3/8	62	60	11	36.8	153
02501058	1 5/16	3/8	63	56	11	27.9	156
02501060	1 3/8	3/8	65	62	11	38.7	178
02501062	1 7/16	3/8	66.5	66	11	39.6	172
03501064	1 1/2	1/2	76	70	16	45	310
03501069	1 13/16	1/2	85	84	16	49.6	400
03501072	2	1/2	89	90	16	52.3	451
03501074	2 1/8	1/2	91.5	92.8	16	54.2	460
03501075	2 3/16	1/2	93	96	16	55.1	480
03501076	2 1/4	1/2	95	99	16	56	500

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)


TOOLS THAT
... inspire

447



Adaptors

— bi-hex with AS-Drive profile
— HPQ® high-performance steel, gunmetal finish



Product no.	mm	"	d1 mm	d2 mm	h1 mm	h2 mm	S mm	g
02181007	7	3/8	11.5	19	6	11	50.8	30
02181008	8	3/8	12.4	19	6	11	50.8	30
02181009	9	3/8	14	19	8	11	50.8	40
02181010	10	3/8	15.6	19	8	11	50.8	40
02181013	13	3/8	19.3	19	9.2	11	50.8	55


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

447a



Adaptors

— bi-hex with AS-Drive profile
— SAE AS 954-E
— HPQ® high-performance steel, gunmetal finish



Product no.	"	"	d1 mm	d2 mm	h1 mm	h2 mm	S mm	g
02470016	1/4	3/8	10.4	19	6	11	50.8	27
02470020	5/16	3/8	12.4	19	6	11	50.8	29
02470024	3/8	3/8	14.9	19	8	11	50.8	41
02470028	7/16	3/8	17	19	8	11	50.8	40
02470032	1/2	3/8	19	19	9.2	11	50.8	56
02470034	9/16	3/8	21	19	9.2	11	50.8	61
02470036	5/8	3/8	23	19	12	11	50.8	73


*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

447aSP



Adaptors

— for external Spline-Drive screws
— MS-33787, MIL-W-8982
— HPQ® high-performance steel, gunmetal finish



Product no.	"	"	d1 mm	d2 mm	h1 mm	h2 mm	S mm	g
02480014	7/32	3/8	9.4	19	6	11	50.8	28
02480016	1/4	3/8	10.4	19	6	11	50.8	27
02480018	9/32	3/8	11.5	19	6	11	50.8	29
02480020	5/16	3/8	12.4	19	6	11	50.8	29
02480024	3/8	3/8	14.9	19	8	11	50.8	38
02480028	7/16	3/8	17	19	9.2	11	50.8	39
02480032	1/2	3/8	19	19	9.2	11	50.8	59
02480034	9/16	3/8	21	19	9.2	11	50.8	55
02480036	5/8	3/8	23	19	12	11	50.8	74

*** Caution!** Adjust the setting on the torque wrench (see note on page 58 and 59)

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

TORQUE MULTIPLIERS.

MP100-1500





Torque multiplier MULTIPOWER

- particularly compact design, lightweight and handy
- with ratchet function
- working angle 8°
- with angle of rotation scale
- to be used with a fixed $^1/_2$" square torque wrench
- patented
- in carrying case
- **accuracy ± 5%**

Contains 5-pieces:
3 hex inserts: 30; 32; 36 mm
1 insert with 1" external square
1 reaction arm: L. 400 mm

Product no.	○ "	N·m$_1$	ft·lb$_1$	N·m$_2$	ft·lb$_2$	Gear ratio	Torque ratio	L mm	b mm	h mm	g	g with box
96531500	$^1/_2$	1500	1106	300	221	5.62 : 1	1 : 5	165	105	30	1890	3630

[1] output capacity max. [2] input capacity max.

MP300



MP300-800




MP300-2000



MP300-5000

Torque multipliers MULTIPOWER


- easy transmission of the highest torques
- planetary gears with overload protection
- robust design for high torques up to 5,000 N·m/3,687 ft·lb
- up to 12,000 N·m/8,850 ft·lb available on request
- with anti-backlash protection (models 2,000 N·m onwards)
- with a spare sun wheel (overload protection)
- in carrying case
- **accuracy ± 5%**



Product no.	Size	■ "	○ "	N·m$_1$	ft·lb$_1$	N·m$_2$	ft·lb$_2$	Gear ratio	Torque ratio	L mm	b mm	h mm	g	g with box
53030800	800	$^3/_4$	$^1/_2$	800	590	229	169	4 : 1	1 : 3.5	215	66	85	2000	5838
53031350	1350	$^3/_4$	$^3/_4$	1350	996	375	277	4 : 1	1 : 3.6	265	90	106	3400	7500
53032000 *	2000	1	$^1/_2$	2000	1475	160	118	16 : 1	1 : 12.5	330	95	161	7000	11000
53033000 *	3000	1	$^3/_4$	3000	2212	240	177	16 : 1	1 : 12.5	330	95	161	7000	10805
53035000 *	5000	1 $^1/_2$	$^3/_4$	5000	3687	294	217	20 : 1	1 : 17.0	400	120	180	10400	14000

* with anti-backlash protection [1] output capacity max. [2] input capacity max.

SR290-393



Sun wheels with overload protection

Product no.	Model	for model	g
59030800	SR300-800	MP300-800	45
59031350	SR300-1350	MP300-1350	106
59032000	SR300-2000	MP300-2000	120
59033000	SR300-3000	MP300-3000	130
59035000	SR300-5000	MP300-5000	127
59300039	SR290N	STW 290N	18
59300067	SR295N	STW 295N	95
59300068	SR391N	STW 391N	95
59300069	SR392N	STW 392N	95
59300070	SR393N	STW 393N	105



SPARE PART SETS FOR RATCHETS AND RATCHET INSERT TOOLS.

4150QR

Spare parts set for ratchet
Contains 11-pieces:
1 pinion; 1 locking disc; 2 lever with pin; 1 ball; 2 compression springs; 2 retaining screws M 1.7 x 8; 2 cover plates

Product no.	for model	■ "	Content pcs.	g
19011020	415QR, 725QR/4	1/4	11	24

4220

Spare parts set for ratchet
Contains 5-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 1 screw

Product no.	for model	■ "	Content pcs.	g
19020003	735/5	3/8	5	88

7250/4

Spare parts set for ratchet
Contains 9-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19012021	725/4	1/4	9	26

7250B/4

Spare parts set for bit-ratchet
Contains 9-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19012022	725B/4	1/4	9	21

7250B/5

Spare parts set for bit-ratchet
Contains 9-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19012023	725B/5	5/16	9	48

4350QR

Spare parts set for ratchet
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19020020	435QR, 725QR/5	3/8	8	51

7210/5

Spare parts set for ratchet
Contains 7-pieces:
1 ball; 1 pinion; 2 compression springs; 1 switch button; 1 switch lever pin; 1 locking disc

Product no.	for model	■ "	Content pcs.	g
59191005	721/5, 721/5 Quick	3/8	7	53

7250L/5

Spare parts set for ratchet
Contains 9-pieces:
1 pinion; 1 pawl; 1 button with pin; 1 ball; 2 compression springs; 2 retaining screws; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19021000	725L/5	3/8	9	70

7350/5

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
59251005	422, 735/5	3/8	7	85

5120QR

Spare parts set for ratchet
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 pressure springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19040020	512QR, 512SG-QR, 725QR/20	1/2	8	118

5150

Spare parts set for ratchet
Contains 5-pieces:
1 pinion, 1 locking piece, 1 countersunk screw, 1 switching disc, 1 switching spring

Product no.	for model	■ "	Content pcs.	g
19040002	735/20	1/2	5	130

5120

Spare parts set for ratchet
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 pressure springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19040000	721/15, 721/15 Quick, 721/20, 721/20 Quick	1/2	8	127

7210/30

Spare parts set for ratchet
Contains 8-pieces:
1 ball; 1 pan head screw; 1 switching lever; 2 compression springs; 1 switch lever pin; 1 pawl; 1 pinion

Product no.	for model	■ "	Content pcs.	g
59191030	721/30, 721/30 Quick	1/2	8	134

7250QR/10

Spare parts set for ratchet
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 pressure springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19041020	725QR/10	1/2	8	64

7350/10

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
59251010	735/10	1/2	7	96

7350/20

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
59251020	515, 735/20	1/2	7	140

7210/80

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 2 locking parts; 2 clamping pressure springs; 2 spring heads

Product no.	for model	■ "	Content pcs.	g
59191080	721Nf/80, 721Nf/100, 735/80, 735/100	3/4	7	443

7350/40

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
59251040	735/40	3/4	7	219

7350/40HD-65

Spare parts set for ratchet
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
59251065	735/40HD; 735/65	3/4	7	429

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

SQUARE DRIVES.

70V




502 1/2



70V 16

Square drives

— for torque wrenches and insert tools



Product no.	Size	for model	a "	b "	L mm	g
59010001	1	71...V/1	1/4	1/4	17.5	5
59010014	11	734/4	3/8	1/4	22	12
59010003	3	734/5	3/8	3/8	25.8	17
59010005	5	734/10	3/8	1/2	30	28
59010011	502 1/2	720/30; 734/20	1/2	1/2	33.5	40
59010007	7	721/30, 721/30 Quick	1/2	1/2	44.3	52
59010008	8	734/40	3/4	3/4	52.2	138
59010015	12	720Nf/80; 721Nf/80+100; 734/80; 734/100; 735/80; 735/100	3/4	3/4	65	179
59010016 *	16	720Nf/80; 721Nf/80+100; 734/40; 734/80; 734/100; 735/80; 735/100	3/4	3/4	88	240

* extra-long, firmly locked and can be used on both sides



CALIBRATION CERTIFICATES.

WKS

Factory calibrations

— for torque wrenches

Product no.	N·m	Tightening direction
58950001	1-400	clockwise
58950016	1-400	clockwise/counter-clockwise
58950002	401-600	clockwise
58950017	401-600	clockwise/counter-clockwise
58950003	601-1000	clockwise
58950018	601-1000	clockwise/counter-clockwise
58950013	1001-3000	clockwise
58950019	1001-3000	clockwise/counter-clockwise

WKS

Factory calibrations

— for torque screwdrivers

Product no.	N·m	Tightening direction
58950009	0.02-10	clockwise
58950010	0.02-10	clockwise/counter-clockwise

WKS

Factory calibration

— for test equipment

Product no.	N·m
58950004	0.2-3000

WBS

Factory certificate

— for angle-controlled torque wrenches

Product no.	for model
58950025	713; 714

WBS 7395-1

Works certificate

— for angle of rotation module

Product no.	
58950026	per measurement unit

DAkkS

DAkkS calibrations

— for torque wrenches

Product no.	N·m	Tightening direction
58950005	1-400	clockwise
58950015	1-400	clockwise/counter-clockwise
58950006	401-600	clockwise
58950020	401-600	clockwise/counter-clockwise
58950007	601-1000	clockwise
58950021	601-1000	clockwise/counter-clockwise
58950014	1001-2000	clockwise
58950022	1001-2000	clockwise/counter-clockwise

DAkkS

DAkkS calibrations

— for torque screwdrivers

Product no.	N·m	Tightening direction
58950011	0.2-10	clockwise
58950012	0.2-10	clockwise/counter-clockwise

DAkkS

DAkkS calibration

— for test equipment

Product no.	
58950008	per measurement unit

TOOLS THAT
... inspire

STAHLWILLE TEST EQUIPMENT –
For added safety.

Test equipment from STAHLWILLE helps to ensure quality and minimise risks. They can be used to test torque and angle-controlled torque wrenches for compliance with tolerances between calibration intervals – daily if necessary, because the test is quick and easy.
A suitable, highly precise test device is available for every application and torque range – whether it's for use at base or in the field.

FLEXIBLE



Compact.

The SmartCheck test device can be positioned virtually anywhere. Sophisticated mounting points, a compact design and a rotatable display allow both vertical and horizontal mounting.

Rotatable.

Not only the display, but also the display holder and body can be rotated 180°. For optimal adjustment of the viewing angle of the display.

USB port.

The integrated USB interface allows the test values stored in the device to be read out. This means they can also be transferred to external systems.

Intuitive.

Easy to understand operation and user guidance. For faster work, reliable results and increased safety. CheckMaster, an application from STAHLWILLE, ensures a fast connection between PC and SmartCheck testing devices. The testing devices can then be configured and results analysed from the computer. Test certificates can also be created via CheckMaster.

MADE IN CRONENBERG
MADE IN GERMANY



Flexible.

The SENSOTORK® 7707 W testing device is not only compact, it is also extremely flexible thanks to its easily interchangeable transducers. The measured values are shown on a display that is connected with a cable.

Versatile.

Clockwise and counter-clockwise measurements with a particularly broad measuring range from 2 to 100 % of the nominal value, and interchangeable square drive adaptors integrated into the mounting block.


TEST EQUIPMENT AND CALIBRATION SYSTEMS.

SmartCheck Angle



Angle of rotation tester

- for checking the angle of rotation measurement of angle-controlled torque wrenches for compliance with the specified tolerances
- angle of rotation measurements up to 720° with setpoint specifications
- immediate evaluation of the measurement results directly on the device using the traffic light principle
- with interchangeable square drive adaptors ($^1/_4$"- $^3/_8$"-$^1/_2$")
- for angle-controlled torque wrenches with a measuring range of up to 400 Nm
- large LCD for optimum readability
- the display, the display holder, and the base can be rotated 180°
- the display and keypad are splash-proof, the case is made of impact-resistant plastic
- simple installation thanks to pre-drilled holes in the mounting bracket
- the rotating arm can be easily locked in the zero position for transport
- for controlled clockwise and counter-clockwise torque testing
- 2 operating modes: running display of the applied torque (Track), peak value display (Peak-Hold)
- customised input of target torques and tolerances for evaluating the measured value
- micro USB interface for data export and for power supply (if required)
- data storage for up to 2,500 data records, including date and time stamp
- CheckMaster documentation software for transferring values and creating test certificates is available free of charge at www.stahlwille.com
- operation via included power supply, batteries or rechargeable batteries (4 x AAA or 1 x 9 V block, adaptor included)
- with factory certificate
- in a sturdy plastic box
- delivered with USB power supply and square drive adaptors $^1/_4$" and $^3/_8$"



Product no.	N·m	L mm	t mm	b mm	h mm	kg
96521400	-400	263	171	452	326	11.5

SmartCheck USB








DESIGN AWARD 2017

Torque testers

- for testing indicating and clicking type torque wrenches
- with interchangeable square drive adaptors for square drives (from $^{3}/_{8}$" to $^{1}/_{4}$" with SmartCheck 100 USB; from $^{3}/_{4}$" to $^{1}/_{2}$" for SmartCheck 400 USB)
- large LCD for optimum readability
- the display, the display holder, and the base can be rotated 180°
- compact design
- display and keypad are splash-proof; the housing is made of impact-resistant plastic
- simple installation thanks to pre-drilled holes in the mounting bracket
- horizontal or vertical orientation
- for controlled clockwise and counter-clockwise torque testing
- 3 operating modes: running display of the applied torque (Track), display of the torque on click point detection (First-Peak), peak value display (Peak-Hold)
- customised input of target torques and tolerances for evaluating the measured value
- with integrated visual and acoustic overload protection
- 3 measuring units (N·m, ft·lb, in·lb)
- micro USB interface for data export and for power supply (if required)
- data storage for up to 200 data records, including date and time stamp
- CheckMaster documentation software for transferring values and creating test certificates is available free of charge at www.stahlwille.com
- operation via included power supply, batteries or rechargeable batteries (4 x AAA or 1 x 9 V block, adaptor included)
- with factory certificate
- delivered in a sturdy plastic box
- **accuracy ± 1%**





Product no.	Model	N·m	ft·lb	in·lb	"	t mm	b mm	h mm	g	g with box
96521206 *	SmartCheck 10S USB	1-10	0.74-7.4	8.9-88.5	$^{1}/_{4}$	167	120	124	5210	6556
96521207	SmartCheck 10 USB	1-10	0.74-7.4	8.9-88.5	$^{1}/_{4}$	167	120	124	5210	6556
96521208	SmartCheck 100 USB	10-100	7-74	89-885	$^{3}/_{8}$	167	120	124	5310	6656
96521209	SmartCheck 400 USB	40-400	30-295	354-3540	$^{3}/_{4}$	167	120	124	5690	7036
96521210	SmartCheck 800 USB	80-800	59-590	708-7081	$^{3}/_{4}$	167	120	124	5690	7036
96521211	SmartCheck 1500 USB	150-1500	111-1106	1328-13276	1	167	120	124	5912	7258

* for checking torque screwdrivers

WHICH TRANSDUCER IS FOR WHICH TORQUE TOOL?

For manually operated testing, calibration technology.

	7721	7721-0	7721-1	7722	7723-1	7723-2	7723-3	7724-1
760	○							
775	○							
TORSIOTRONIC®	○							
71/80							○	○
71aR/80							○	○
73Nm/15			○	○				
755R/1			○					
755/4				○	○			
755/10					○	○		
755/20					○	○	○	
755/30						○	○	
750NR				○	○	○		
730/5				○	○			
730/10					○	○		
730/12					○	○	○	
730/20					○	○	○	
730/40						○	○	
730/65							○	
730II/65							○	
730a/5				○	○			
730a/10					○	○		
730a/12					○	○	○	
730a/20					○	○	○	
730/2			○	○				
730/4				○	○	○		
730a/2-1		○	○					
730a/2			○	○				
730a/4				○	○			
730/80							○	○
721/5				○	○			
721/15					○	○	○	
721/20					○	○	○	
721/30						○	○	
721QR/15					○	○	○	
721QR/20					○	○	○	
720Nf/80							○	○
721Nf/80							○	○
721Nf/100							○	○

	7721	7721-0	7721-1	7722	7723-1	7723-2	7723-3	7724-1
730N/2			○	○				
730N/5				○	○	○		
730N/10					○	○		
730N/12					○	○	○	
730N/20					○	○		
730N/40						○	○	
730N/65							○	
730NII/65							○	
730N/80							○	○
730N/100							○	○
730Na/2			○	○				
730Na/5				○	○	○		
730Na/10					○	○		
730Na/20					○	○		
730Na/40						○	○	
701/2			○					
730D/10				○	○	○		
730D/20					○	○		
730D/40						○	○	
730D/65							○	
730DII/65							○	
730D/80							○	
730D/100							○	
714/1		○	○					
714/2			○	○				
714/4				○	○			
714/6				○	○			
714/10				○	○	○		
714/20					○	○		
714/40						○	○	
714/65							○	
714/80							○	
714/100							○	
713R/6				○				
713R/20					○	○		
713R/40						○		
712R/6				○				

Note


Torque testers are measurement devices! They have to be regularly calibrated and, where necessary, adjusted, using suitable calibration equipment. We recommend recalibrating every 12 months. DAkkS certificates must be ordered separately see p. 81.

7707 W



Electronic workshop testing devices SENSOTORK®

— for testing indicating and clicking type torque wrenches
— compact electronic testing device consisting of:
1 patented transducer
1 safety lock
1 display
1 stand with 1.5 metre cable for the display unit
1 spiral cable
1 power supply (110-230 V with interchangeable power outlet adaptors)
4 interchangeable square drive adaptors
— large LCD for optimum readability
— horizontal or vertical orientation
— for controlled clockwise and counter-clockwise measurements
— 3 operating modes: running display of the applied torque (Track), display of the torque on click point detection (First-Peak), peak value display (Peak-Hold)
— for clicking type torque wrenches, the actual final torque applied is also displayed, in addition to the first peak
— with QuickRelease safety lock
— not affected by transverse forces due to its particularly low-profile design
— automatic detection of transducers
— particularly broad measurement range from about 2-100 % of the nominal value
— 3 measuring units (N·m, ft·lb, in·lb)
— software no. 7759-4, including USB adaptor and jack-push/pull cable, allows the measured values to be transmitted to a PC (no additional external power source required, power from the PC), not included, order separately (see page 51)
— when recalibrating a transducer, the test equipment remains on site and available for use with another transducer
— complies with the specifications of guideline DKD-R 10-8
— with factory certificate
— delivered in a sturdy plastic box
— **accuracy ± 1%**



Product no.	Model	N·m	○ "	t mm	b mm	h_1 mm	h_2 mm	g	g with box
96521086 [1]	7707-1-3W	0.2-10	1/4	180	180	79	215	6255	9500
96521085	7707-1-2W	0.2-10	1/4	180	180	79	215	6255	9500
96521080	7707-1W	0.4-20	1/4	180	180	79	215	6255	9500
96521072 [2]	7707-2W	2-100	3/8	180	180	79	215	7025	10300
96521083 [3]	7707-2-1W	4-200	1/2	180	180	79	215	7511	10975
96521084 [4]	7707-2-2W	8-400	3/4	180	180	79	215	7654	11100
96521082	7707-3W	25-1100	3/4	180	180	79	215	7495	11000

[1] for checking torque screwdrivers
[2] with square drive adaptor No. 409M (1/4" ○ x 1/2" ■)
[3] with square drive adaptor No. 7798-4 (1/4" ○ x 1/2" ■), No. 7789-5 (3/8" ○ x 1/2" ■)
[4] with square drive adaptor No. 7787 (1/4" ○ x 3/4" ■), No. 7788 (3/8" ○ x 3/4" ■), No. 7789 (1/2" ○ x 3/4" ■)

STAHLWILLE CALIBRATION SYSTEMS – Calibration made easy.

Companies that use many torque and angle-controlled torque wrenches can reduce their tool costs and tool downtime by calibrating their measuring equipment in-house: With our mechanical and motorised/automated calibration systems, tools are calibrated quickly and efficiently to established industry standards.

PRECISE



Efficient.

The electronic perfectControl® calibration systems reduce the effort and time required for calibrations and adjustments and prevent inaccurate measurements. In combination with the TorkMaster software, calibration certificates are issued in no time.

Quick.

QuickRelease technology enables the transducers to be changed quickly. The handle support for torque wrenches can be adjusted with one hand using an eccentric tensioner.

Precise.

Take measurements without shifting the force application point. The transducer accurately detects, digitises the measured values and transmits them to the PC.



More features.

The perfectControl® 7794-3 also enables the calibration and adjustment of torque and angle-controlled torque wrenches. Thanks to an integrated motor, the working height can be adjusted and optimised quickly and easily by the user.

MADE IN CRONENBERG
MADE IN GERMANY

Comfortable.

Driven by an electric motor with automatic speed adjustment, the perfectControl® 7794-2 measures clockwise and counter-clockwise. Operation is via buttons.

Modular.

The base version calibrates torque wrenches up to 400 N·m. Calibrations up to 1,000 N·m are possible with the 7791-1 extension.

STAHLWILLE CALIBRATION SYSTEMS –
Coordinated – down to the last detail.




Mechanical loader



Laboratory transducers



USB adaptor 7757-1
+ Cable 7751-1



PC/printer not included

	No for full system	7706-8 PC	7706-9 PC	7706-10 PC	7706-11 PC
	Product no.	**96521068**	**96521069**	**96521070**	**96521074**
	Weight in kg	14.2	67.6	70.6	108.4
	Range N·m	1–10	2–100	2–1.000	20–3.000
	Mechanical loader	–	7791	7791	7792
	'Stand alone' mechanical loader for torque screwdrivers	7790	–	–	–
	Extension	–	–	7791-1	7792-1
	Laboratory transducers	7728-1S (1–10 N·m)	7728-2 (2–20 N·m) 7728-10 (10–100 N·m)	7728-2 (2–20 N·m) 7728-10 (10–100 N·m) 7728-40 (40–400 N·m) 7728-100 (100–1.000 N·m)	7728-20 (20–200 N·m) 7728-100 (100–1.000 N·m) 7728-300 (300–3.000 N·m)
	USB adaptor	7757-1	7757-1	7757-1	7757-1
	Jack cable	7751	7751	7751	7751
	Cable for 7728 (transducer to USB adaptor)	7751-1	7751-1	7751-1	7751-1
	Square drive adaptors	431 (3/8" O x 1/4" ■)	431 (3/8" O x 1/4" ■) 409M (1/4" O x 3/8" ■)	7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 409M (1/4" O x 3/8" ■)	7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 7789-2 (3/4" O x 1 1/2" ■) 7789-3 (1" O x 1 1/2" ■) 7789-4 (1/4" O x 1/2" ■) 7789-5 (3/8" O x 1/2" ■)
	Calibration square drive insert tools	–	734K/4 (1/4" ■) 734K/5 (3/8" ■)	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■)	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■)
	Bit connectors	3116 (1/4" ■ x 1/4" ⬣ E 6.3) 3116/1 (1/4" ■ x 1/4" ⬣ C 6.3)	– –	–	–
	Calibration software	TorkMaster	TorkMaster	TorkMaster	TorkMaster
	DAkkS calibration certificates	1	2	4	3

PERFECTCONTROL® CALIBRATION SYSTEMS –
Precisely matched products.

Motorised calibration system 7794-2



Manual calibration system 7794-1


Laboratory transducers



USB adaptor 7757-1 + Cable 7751-1



PC/printer not included



	No for full system	7794-2/400	7794-2/1000	7794-1/400	7794-1/1000
	Product no.	**96521078**	**96521079**	**96521076**	**96521077**
	Weight in kg	62.1	69.8	53.2	60.9
	Range N·m	1–400	1–1.000	1–400	1–1.000
	Motorised calibration system	7794-2	7794-2	–	–
	Manual calibration system	–	–	7794-1	7794-1
	Extension	–	7791-1	–	7791-1
	Laboratory transducers	7728-1 (1–10 N·m) 7728-6 (6–60 N·m) 7728-40 (40–400 N·m)	7728-1 (1–10 N·m) 7728-6 (6–60 N·m) 7728-40 (40–400 N·m) 7728-100 (100–1.000 N·m)	7728-1 (1–10 N·m) 7728-6 (6–60 N·m) 7728-40 (40–400 N·m)	7728-1 (1–10 N·m) 7728-6 (6–60 N·m) 7728-40 (40–400 N·m) 7728-100 (100–1.000 N·m)
	USB adaptor	7757-1	7757-1	7757-1	7757-1
	Jack cable	7751	7751	7751	7751
	Jack-push/pull cable	7752	7752	7752	7752
	Square drive adaptors	409M (1/4" O x 3/8" ■) 7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 7789-4 (1/4" O x 1/2" ■) 7789-5 (3/8" O x 1/2" ■)	409M (1/4" O x 3/8" ■) 7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 7789-4 (1/4" O x 1/2" ■) 7789-5 (3/8" O x 1/2" ■)	409M (1/4" O x 3/8" ■) 7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 7789-4 (1/4" O x 1/2" ■) 7789-5 (3/8" O x 1/2" ■)	409M (1/4" O x 3/8" ■) 7787 (1/4" O x 3/4" ■) 7788 (3/8" O x 3/4" ■) 7789 (1/2" O x 3/4" ■) 7789-4 (1/4" O x 1/2" ■) 7789-5 (3/8" O x 1/2" ■)
	Calibration square drive insert tools	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/12 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■) 734K/100 (3/4" ■)	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/12 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■) 734K/100 (3/4" ■)	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/12 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■) 734K/100 (3/4" ■)	734K/4 (1/4" ■) 734K/5 (3/8" ■) 734K/12 (3/8" ■) 734K/20 (1/2" ■) 734K/40 (3/4" ■) 734K/100 (3/4" ■)
	Calibration software	TorkMaster	TorkMaster	TorkMaster	TorkMaster
	DAkkS calibration certificates	3	4	3	4

7794-1





perfectControl®

Manual calibration system

The perfectControl® calibration system with manual drive reduces the effort and time required for calibrations and adjustments of torque wrenches.

— measures without shifting the point of application of force
— avoid incorrect measurements with the precise bearing spindle and ergonomically shaped handwheel
— extremely precise calibration thanks to optimisation of the bearings and the square drives of the transducers
— clicking and indicating torque wrenches can be calibrated
— quick and easy switching of transducers with QuickRelease locking system
— bridge support with an eccentric clamp designed for single-handed operation reduces time and effort
— automatic transfer of measured values via USB interface to PC for further processing and archiving
— a calibration certificate can be printed and/or saved as a PDF file after calibration
— 'as found' and 'as left' calibrations can be documented
— DIN EN ISO 6789 calibration is supported in numerous languages. Additional standards and factory specifications available upon request
— calibrations up to 1,000 N·m with easy-to-assemble extension No. 7791-1.
— calibration of transducers using torque reference wrenches is possible on request
— the interface adaptor set 7761/3 is required for automated calibration of electromechanical torque wrenches and screwdrivers (730D eClick, 714, 766 DAPTIQ®, TORSIOTRONIC®, TORSIOTRONIC® DAPTIQ®)
— protected by national and international patents

Contains 19-pieces:

1 manual calibration system **No. 7794-1**
Calibration accessory set:
6 calibration square drive insert tools **No. 734K**: Size 4; 5; 12; 20; 40; 100
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 TorkMaster software **No. 7731-1**
1 jack cable **No. 7751**
1 jack-push/pull cable **No. 7752**
1 jack-push/pull cable **No. 7751-3**
1 hex L-Key **No. 10760**: 2 mm
included USB adaptor with TorkMaster software **No. 7731-1**

Product no.	Range N·m	for transducers	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	Content pcs.	kg
96521092	1-400	7728 (size 1-100)	815	180	1060	705	355	19	46.4

7794-1 Sets







perfectControl®

Manual calibration systems in a set

The perfectControl® calibration system with manual drive reduces the effort and time required for calibrations and adjustments of torque wrenches.

— measures without shifting the point of application of force
— avoid incorrect measurements with the precise bearing spindle and ergonomically shaped handwheel
— extremely precise calibration thanks to optimisation of the bearings and the square drives of the transducers
— clicking and indicating torque wrenches can be calibrated
— quick and easy switching of transducers with QuickRelease locking system
— bridge support with an eccentric clamp designed for single-handed operation reduces time and effort
— automatic transfer of measured values via USB interface to PC for further processing and archiving
— a calibration certificate can be printed and/or saved as a PDF file after calibration
— 'as found' and 'as left' calibrations can be documented
— DIN EN ISO 6789 calibration is supported in numerous languages. Additional standards and factory specifications available upon request
— calibrations up to 1,000 N·m with easy-to-assemble extension No. 7791-1.
— calibration of transducers using torque reference wrenches is possible on request
— the interface adaptor set 7761/3 is required for automated calibration of electromechanical torque wrenches and screwdrivers (730D eClick, 714, 766 DAPTIQ®, TORSIOTRONIC®, TORSIOTRONIC® DAPTIQ®)
— protected by national and international patents

Contents:

1 manual calibration system **No. 7794-1**
4 transducers (96521076: 3 transducers)
Calibration accessory set:
6 calibration square drive insert tools **No. 734K**: Size 4; 5; 12; 20; 40; 100
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 jack cable **No. 7751**
1 jack-push/pull cable **No. 7752**
1 jack-push/pull cable **No. 7751-3**
1 hex L-Key **No. 10760**: 2 mm
included USB adaptor with TorkMaster software **No. 7731-1**

Product no.	Range N·m	L mm	W mm	H mm	Content pcs.	kg
96521076	1-400	1200	800	950	21	57.2
96521077 *	1-1000	1200	800	820	23	101.7

* includes extension **No. 7791-1**

TOOLS THAT ... inspire

7794-2





perfectControl®

Motorised calibration and adjustment system

The electronic perfectControl® calibration system with motorised drive significantly reduces the time and effort required for calibrations and adjustments of torque wrenches

- measures without shifting the point of application of force
- avoid inaccurate measurements with the precise bearing spindle and the fine-controlled motor
- extremely precise calibration thanks to optimisation of the bearings and the square drives of the transducers
- clicking and indicating torque wrenches can be calibrated
- quick and easy switching of transducers with QuickRelease locking system
- convenient button operation for clockwise and counter-clockwise measurements with motorised loading and automatic speed adjustment
- bridge support with an eccentric clamp designed for single-handed operation reduces time and effort
- automatic transfer of measured values via USB interface to PC for further processing and archiving
- a declaration of conformity or calibration certificate can be printed or saved as a PDF file after calibration
- 'as found' and 'as left' calibrations can be documented
- DIN EN ISO 6789 calibration is supported in numerous languages. Additional standards and factory specifications available upon request
- upgradeable to the perfectControl® calibration system No. 7794-3 for angle controlled torque wrenches
- calibrations up to 1,000 N·m with easy-to-assemble extension No. 7791-1.
- calibration of transducers with torque reference wrench is possible on request
- recommended transducer laboratory No. 7728
- the interface adaptor set 7761/3 is required for automated calibration of electromechanical torque wrenches and screwdrivers (730D eClick, 714, 766 DAPTIQ®, TORSIOTRONIC®, TORSIOTRONIC® DAPTIQ®)
- registered design
- protected by national and international patents

Contains 19-pieces:

1 motorised calibration and adjustment system **No. 7794-2**
Calibration accessory set:
6 calibration square drive insert tools **No. 734K**: Size 4, 5, 12, 20, 40, 100
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 jack cable **No. 7751**
1 jack-push/pull cable **No. 7752**
1 jack-push/pull **No. 7751-3**
1 power adaptor set
1 hex L-Key **No. 10760**: 2 mm

Product no.	Range N·m	for transducers	for torque wrenches with functional length (LF) max. mm	profile width mm	L mm	W mm	H mm	Content pcs.	kg
96521093	1-400	7728 (size 1-100)	815	180	1060	640	328	19	51.5

7794-2 Sets



perfectControl®

Motorised calibration and adjustment systems in a set

The electronic perfectControl® calibration system No. 7794-2 with motorised drive significantly reduces the effort and time required for calibrations and adjustments of torque wrenches.

— measures without shifting the point of application of force
— avoid inaccurate measurements with the precise bearing spindle and the fine-controlled motor
— extremely precise calibration thanks to optimisation of the bearings and the square drives of the transducers
— clicking and indicating torque wrenches can be calibrated
— quick and easy switching of transducers with QuickRelease locking system
— bridge support with an eccentric clamp designed for single-handed operation reduces time and effort
— automatic transfer of measured values via USB interface to PC for further processing and archiving
— a calibration certificate can be printed and/or saved as a PDF file after calibration
— 'as found' and 'as left' calibrations can be documented
— DIN EN ISO 6789 calibration is supported in numerous languages. Additional standards and factory specifications available upon request
— calibrations up to 1,000 N·m with easy-to-assemble extension No. 7791-1.
— calibration of transducers with torque reference wrench is possible on request
— the interface adaptor set 7761/3 is required for automated calibration of electromechanical torque wrenches and screwdrivers (730D eClick, 714, 766 DAPTIQ®, TORSIOTRONIC®, TORSIOTRONIC® DAPTIQ®)
— registered design
— protected by national and international patents
— torque wrench and laptop not included

Contents:

1 motorised calibration and adjustment system **No. 7794-2**
4 transducers (96521078: 3 transducers)
Calibration accessory set:
6 calibration square drive insert tools **No. 734K**: Size 4; 5; 12; 20; 40; 100
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 jack cable **No. 7751**
1 jack-push/pull cable **No. 7752**
1 jack-push/pull cable **No. 7751-3**
1 power adaptor set
1 hex L-Key **No. 10760**: 2 mm

Product no.	Range N·m	for transducers	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	Content pcs.	kg
96521078	1-400	7728 (size 1-100)	815	180	1200	800	820	23	71.3
96521079 *	1-1000	7728 (size 1-100)	1390	180	1200	800	950	24	76.3

* includes extension **No. 7791-1**

7794-3





perfectControl®

Automatic calibration and adjustment system

The electronic perfectControl® calibration system No. 7794-3 with motorised drive for calibrations and adjustments of torque and angle-controlled torque wrenches.

— automatically calibrates electronic and electromechanical STAHLWILLE torque and angle-controlled torque wrenches
— design like perfectControl® No. 7794-2, but also suitable for calibrating angle-controlled torque wrenches
— optimum working height adjustment with motorised height adjustment
— calibrations up to 1,000 N·m with easy-to-assemble extension No. 7791-1 and mounting bracket set No. 7791-4
— the interface adaptor set 7761/3 is required for automated calibration of electromechanical torque wrenches and screwdrivers (730D eClick, 714, 766 DAPTIQ®, TORSIOTRONIC®, TORSIOTRONIC® DAPTIQ®).
— registered design
— protected by national and international patents

Contains 19-pieces:

1 motorised calibration and adjustment system **No. 7794-2**
Calibration accessory set:
6 calibration square drive insert tools **No. 734K** (size 4, 5, 12, 20, 40, 100)
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 jack cable **No. 7751**
1 jack-push/pull cable **No. 7752**
1 jack-push/pull cable **No. 7751-3**
1 power adaptor set
1 hex L-Key **No. 10760**: 2 mm

Product no.	Range N·m	for transducers	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	variable height	Content pcs.	kg
96521094	1-400	7728 (size 1-100)	815	180	1060	640	884-1134 mm	19	230

7791-4

Mounting bracket set

— mounting bracket for attaching extension No. 7791-1 to the angle of rotation calibration system No. 7794-3
— the extension allows the measuring range to be extended from 400 N·m to 1,000 N·m

Contains:

1 mounting bracket, 4 screws: M8 x 30, 4 oval-head screws: M8 x 20, 8 x washers M8, 4 captive nuts: M8


Product no.	for model	Content pcs.	kg
52110491	7794-3	21	1.5

IS IT WORTH HAVING YOUR OWN CALIBRATION UNIT?
Calculate the ROI easily online.

The topic of calibration of torque wrenches is becoming ever more relevant for manufacturing companies or those involved in maintenance. After all, DIN EN ISO 9001 requires regular testing and calibration of measuring equipment as proof of capability. Furthermore, DIN EN ISO 6789 explicitly recommends an interval of no more than twelve months or 5,000 loads.

In addition to commissioning external calibration service providers, there is also the option of investing in an in-house calibration system. This usually pays off faster than you would expect. In addition to the cost aspect, companies with sufficient calibration volume also gain time, increase tool availability and reduce their administrative effort.

ROI





Calibration in-house – the advantages.

Reliable.


With a calibration system from STAHLWILLE, companies benefit from maximum process reliability, reliable quality control and maximum efficiency.

Efficient.

Your own calibration unit will unburden your team and reduce your tool downtime! The administrative effort for sending a tool to an external calibration laboratory is also removed – saving you valuable work time.

Flexible.

With an in-house calibration laboratory, more frequent and particularly strict calibrations are no problem – and incur no extra costs. Calibrations can be planned and performed when the tool is not in use.



Is it worth having your own calibration system? Determine your ROI now!
qr.stahlwille.com/calibration-technology

7728




Laboratory transducers

- for laboratory use
- not affected by transverse forces due to its particularly low-profile design
- with optimised measurement ranges
- for calibration of torque wrenches and torque screwdrivers
- to be used with the perfectControl® calibration systems No. 7794 or the calibration systems No. 7706, No. 7791
- processing and digitisation occurs directly in the transducer, ensuring a high level of accuracy
- with a high-quality precision connection plug with locking function
- accredited calibration
- patented
- delivered in a sturdy plastic box
- **accuracy ± 0.5% of the measured value**

Product no.	Size	○ "	Accuracy ± 0.5% of the measured value N·m	Accuracy ± 0.5% of the measured value ft·lb	Accuracy ± 0.5% of the measured value in·lb	g	g with box
96524011 [1]	1S	1/4	1-10	0.74-7.4	8.9-88.5	1735	2415
96524001	1	1/4	1-10	0.74-7.4	8.9-88.5	1735	2415
96524002	2	1/4	2-20	1.5-15	18-177	1735	2415
96524004	4	3/8	4-40	3-30	35-354	2486	3136
96524006	6	3/8	6-60	4.5-45	53-531	2486	3136
96524010	10	3/8	10-100	7-74	89-885	2486	3136
96524020	20	1/2	20-200	15-148	177-1770	2983	3170
96524040	40	3/4	40-400	30-295	354-3540	4846	5507
96524065	65	3/4	65-650	48-479	575-5753	4846	5507
96524080	80	3/4	80-800	59-590	708-7081	4846	5507
96524100	100	3/4	100-1000	74-738	885-8851	4846	5507
96524300 [2]	300	1 1/2	300-3000	221-2214	2655-26553	10500	12000

[1] for calibrating torque screwdrivers

[2] for use with mechanical calibration systems No. 7792, 7792-1




MANUTORK® 7791



Manual calibration system

— the special power transmission system prevents the force application point from shifting
— the handwheel drives a lever linearly via a spindle, whereby this movement is converted into a rotary movement of the transducer
— 2 ball-bearing bushings ensure a friction-free contact surface and enable the horizontal alignment of the wrench
— the torque wrench remains in position whilst the load is being applied
— minimal transverse forces and reduced friction minimise measurement errors
— protected by national and international patents




Product no.	Range N·m	for transducers	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	kg
52110091	up to 400	size 1-100	815	180	1069	704	323	44.8

7791-1



Extension unit for No. 7791, 7794-1 and No. 7794-2 to 1.000 N·m

— with 1 pair of adaptor plates No. 7770-3 for height compensation between the extension No. 7791-1 and the perfectControl® calibration systems No. 7794-1, 7794-2



Product no.	for model	Range N·m	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	kg
52110191	7791; 7794-1; 7794-2	up to 1000	1390	180	673	308	135	7.97

7706



Manual calibration systems

— the special power transmission system prevents the force application point from shifting
— the handwheel drives a lever linearly via a spindle, whereby this movement is converted into a rotary movement for the transducer
— 2 ball-bearing bushings ensure a friction-free contact surface and enable the horizontal alignment of the wrench
— the torque wrench remains in position whilst the load is being applied
— minimal transverse forces and reduced friction minimise measurement errors
— protected by national and international patents

Contains:

transducer, square adaptor, USB adaptor, cable, management software for calibration certificates

Product no.	Range N·m	L mm	W mm	H mm	kg
96521068	1-10	605	323	535	14.4
96521069	2-100	1200	800	520	67.6
96521070	2-1000	1200	800	520	75.6
96521074	20-3000	1780	690	600	110.5

MANUTORK® 7792



Mechanical calibration system

— the special power transmission system prevents the force application point from shifting
— the handwheel drives a lever linearly via a spindle, whereby this movement is converted into a rotary movement for the transducer
— 2 ball-bearing bushings ensure a friction-free contact surface and enable the horizontal alignment of the wrench
— the torque wrench remains in position whilst the load is being applied
— minimal transverse forces and reduced friction minimise measurement errors
— protected by national and international patents

Product no.	Range N·m	for transducers	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	kg
52110092	up to 1000	size 20; 100; 300	1390	270	1668.5	722	323	55.7

7792-1



Extension unit for No. 7792 to 3,000 N·m

Product no.	for model	Range N·m	for torque wrenches with functional length (L_F) max. mm	profile width mm	L mm	W mm	H mm	kg
52110192	7792	20-3000	2390	270	1073	558	135	18.5

7721-7724



Transducers

- for testing of torque wrenches and torque screwdrivers
- processing and digitisation occurs directly in the transducer, ensuring a high level of accuracy
- not affected by transverse forces due to its particularly low-profile design
- for use with calibration systems or 7707 W workshop testing device
- with factory certificate
- patented
- delivered in a sturdy plastic box
- **accuracy ± 1% of the measured value**

Product no.	Model	"	Accuracy ± 1 % of the measured value N·m	Accuracy ± 1 % of the measured value ft·lb	Accuracy ± 1 % of the measured value in·lb	g	g with box
96521021 [1]	7721	1/4	0.2-10	0.15-7.4	1.8-88.5	1735	2411
96521000	7721-0	1/4	0.2-10	0.15-7.4	1.8-88.5	1735	2411
96521026	7721-1	1/4	0.4-20	0.3-15	3.5-177	1735	2411
96521022	7722	3/8	2-100	1.5-74	18-885	2486	3223
96521023	7723-1	1/2	4-200	3-148	35-1770	2983	3605
96522023	7723-2	3/4	8-400	6-295	71-3540	3134	3745
96521028	7723-3	3/4	25-1100	18-812	221-9736	2998	3761
96521029 [2]	7724-1	1 1/2	150-3000	111-2214	1328-26553	10500	12000

[1] for calibration of torque screwdrivers


[2] for use with mechanical calibration systems No. 7792, 7792-1

7790



Stand alone mechanical loader for torque screwdrivers

— the torque screwdriver to be calibrated is inserted into the transducer and fixed in place using the universal centre clamps
— the force can be applied in a controlled manner using the handwheel
— transducer and torque screwdriver are not included
— can be attached to the mechanical calibration system No. 7792



Product no.	Range N·m	for transducers	t mm	b mm	h mm	kg
58521090	up to 10	7728-1S	351	250	442-593	8.95

7750-1



Bracket

— for display device No. 7750
— can be attached to the testing systems


Product no.	for model	L mm	g
52101050	7750	110	165

7791-2



Hand wheel attachment for torque screwdrivers

— can be attached to the manual calibration system No. 7791
— the torque screwdriver to be calibrated is inserted into the transducer and fixed in place using the universal centre clamps
— the force can be applied in a controlled manner using the handwheel



Product no.	Range N·m	t mm	b mm	h mm	kg
52110291	up to 10	351	250	442-593	3.74

7789-734K




Calibration accessory set
Contains 17-pieces:
6 calibration square drive insert tools **No. 734K**: size 4; 5; 12; 20; 40; 100
6 square drive adaptors **No. 409M, No. 7787, No. 7788, No. 7789, No. 7789-4, No. 7789-5**
1 USB adaptor **No. 7757-1**
1 jack cable **No. 7751**: L. 1.5 m
1 jack-push/pull cable **No. 7752**: L. 1.5 m
1 jack-push/pull cable **No. 7751-3**: L. 0.25 m
1 hex L-Key **No. 10760**: 2 mm

Product no.	Content pcs.	g
96585224	17	1980

STAHLWILLE DAKKS CALIBRATION LABORATORY – Audited. Documented. Certified.

STAHLWILLE's DAkkS calibration laboratory for torque is accredited by the German Accreditation Service (DAkkS) in accordance with DIN EN ISO/IEC 17025:2005. The transfer torque wrenches and torque transducers in use in the calibration laboratory are subject to regular examination by the German Federal Physics Institute (PTB) in Braunschweig.

The accuracy of the torque wrenches must be proved in a series of steps and these must be traceable. Only in this way can the reliability of the readings be guaranteed. At ground level, the end-user checks the accuracy of the torque tools in-house using suitable calibrated testing equipment. At the next level, this test equipment is checked in STAHLWILLE's DAkkS accredited calibration laboratory. This accreditation by the German Calibration Service (DKD) in accordance with DIN EN ISO/IEC 17025:2005 guarantees the direct link between the measuring equipment and the national standard as laid down in DIN EN ISO 9001:2008.



Relationship between the national standard and the equipment



Conforms to standards.

The accreditation means the specific requirements listed in Technical Specification ISO/TS 16949 relating to testing laboratories are fulfilled. This is absolutely essential for all suppliers in the automotive sector.

409M



Square drive adaptor

— 1/4 to 3/8"

— Chrome Alloy Steel, chrome-plated

Product no.	■ "	O "	L mm	g
11030010	3/8	1/4	13	14

7789-2



Square drive adaptor

— 3/4 to 1 1/2"

Product no.	■ "	O "	L mm	g
58523089	1 1/2	3/4	44	380

7787




Square drive adaptor

— 1/4 to 3/4"

Product no.	■ "	O "	L mm	g
58521087	3/4	1/4	15.5	41

7789-3




Square drive adaptor

— 1 to 1 1/2"

Product no.	■ "	O "	L mm	g
58524089	1 1/2	1	44	280

7788



Square drive adaptor

— 3/8 to 3/4"

Product no.	■ "	O "	L mm	g
58521088	3/4	3/8	23.5	50

7789-4




Square drive adaptor

— 1/4 to 1/2"

Product no.	■ "	O "	L mm	g
58524090	1/2	1/4	15.5	25

7789




Square drive adaptor

— 1/2 to 3/4"

Product no.	■ "	O "	L mm	g
58521089	3/4	1/2	23.5	40

7789-5



Square drive adaptor

— 3/8 to 1/2"


Product no.	■ "	O "	L mm	g
58524091	1/2	3/8	15.5	28

734K



Calibration square drive insert tools

— without ball or pin (only suitable for calibration)
— optimum measurement results during calibration by reduction of transverse forces




Product no.	Size	■ "	mm	b mm	h mm	S mm	g
58243004	4	1/4	9 x 12	20	16.7	17.5	76
58243005	5	3/8	9 x 12	20	16.7	17.5	76
58243012	12	3/8	14 x 18	27	21.5	25	199
58243020	20	1/2	14 x 18	27	21.5	25	218
58243040	40	3/4	14 x 18	40	29.3	25	410
58241100	100	3/4	22 x 28	43	29.3	55	907

70VK



Calibration square drives

— without ball or pin (only suitable for calibration)
— optimum measurement results during calibration by reduction of transverse forces



Product no.	Size	for model	■ "	■ "	L mm	g
59011014	11	734/4	3/8	1/4	24.7	12
59011003	3	735/5	3/8	3/8	27.6	17
59011012	12	734/10; 734/20	1/2	3/8	32.5	34
59011011	502 1/2	734/20	1/2	1/2	36.9	60
59011008	8	734/40; 734/80; 734/100	3/4	3/4	52.2	138




STAHLWIL

2 Spanners

110 **Double open-ended spanners and sets**

114 **Combination spanners and sets**

120 **Mixed spanner sets**

121 **Double-ended ring spanners and sets**

127 **Combination ratchet spanners and sets**

130 **Double-ended ratchet ring spanners and sets**

132 **FastRatch spanners and sets**

134 **Open-ended striking spanners and open-ended spanners**

135 **Heavy-duty and striking ring spanners**

137 **Double-ended flexi-joint spanners and sets**

138 **Box spanners and sets**

139 **Hook spanners**

139 **Spanner accessories**


STAHLWILLE SPANNERS –
Extremely durable.

Thanks to the use of high-quality special steels and a sofisticated forging process, STAHLWILLE spanners are particularly durable and robust. The non-slip finish means that all wrenches sit comfortably in the hand, even after prolonged use and the exertion of greater forces.

STRONG







Thinner.

The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.

More varied.

STAHLWILLE offers a particularly large variety of metric, imperial, Spline-Drive and TORX® wrenches.

More precise.

Extremely tight manufacturing tolerances with reproducible measurement accuracy make it possible for each wrench to be identical to the next. This ensures that both the jaw and the ring are always securely seated on the screw and that the best possible connection is achieved.



More stable.

Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted – namely where the jaw meets the shank – in order to prevent deformation.

MADE IN CRONENBERG
MADE IN GERMANY

Lighter.

Our open-ended, combination and ring spanners have an additional recess in the middle of the tool. Similar to the principle of a double T-beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.

Stronger.

The special AS-Drive profile makes high force transmission to the flats of nuts and bolts possible without damaging them. This also prevents stripping of the screw head.


DOUBLE OPEN-ENDED SPANNERS AND SETS.

MOTOR 10



Double open-ended spanners

— **metric, differing** end sizes
— straight design, jaws angled 15°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 3110 / ISO 10102




Product no.	mm	L mm	a mm	b_1 mm	b_2 mm	g
40030405	4 x 5	100	3.4	12.5	14	11
40035507	5.5 x 7	120	3.7	14.8	17	17
40030607	6 x 7	120	3.7	15.5	17	17
40030708	7 x 8	140	4.0	17	18	25
40030809	8 x 9	140	4.0	18	21	27
40030810	8 x 10	140	4.5	18	23	33
40031011	10 x 11	155	4.8	23	26	47
40031012	10 x 12	170	5.3	23	28	51
40031013	10 x 13	170	5.3	23	30	57
40031113	11 x 13	170	5.3	26	30	55
40031213	12 x 13	170	5.3	28	30	75
40031214	12 x 14	170	5.3	28	32	63
40031314	13 x 14	190	5.3	30	32	70
40031315	13 x 15	190	5.3	30	35	73
40031317	13 x 17	205	5.8	30	38	92
40031415	14 x 15	190	5.3	32	35	81
40031417	14 x 17	205	5.8	32	38	99
40031617	16 x 17	205	5.8	36	38	100
40031618	16 x 18	220	6.7	36	40	125
40031719	17 x 19	220	6.7	38	42	131
40031819	18 x 19	220	6.7	40	42.5	147
40031821	18 x 21	235	7.3	40	47	170
40031922	19 x 22	235	7.3	42	49	179
40032022	20 x 22	235	7.3	45	49	185
40032123	21 x 23	250	7.8	47	51	225
40032124	21 x 24	250	7.8	47	53	215
40032224	22 x 24	250	7.8	49	53	225
40032426	24 x 26	270	8.3	53	57.5	293
40032427	24 x 27	280	8.3	53	60	299
40032528	25 x 28	285	8.3	55	62	309
40032730	27 x 30	300	9.4	60	66	412
40032732	27 x 32	300	9.4	60	70	418
40033032	30 x 32	300	9.4	66	70	450
40033034	30 x 34	300	9.4	66	75	480
40033236	32 x 36	325	10	70	80	546
40033436	34 x 36	325	10	75	80	619
40033641	36 x 41	375	11	80	88	800
40034146	41 x 46	425	12	88	94.5	980

MOTOR 10a



Double open-ended spanners

— **imperial, differing** end sizes
— straight design, jaws angled 15°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	"	L mm	a mm	b_1 mm	b_2 mm	g
40431620	1/4 x 5/16	140	4	16	18	21
40432024	5/16 x 3/8	140	4.5	18	23	34
40432428	3/8 x 7/16	155	4.8	23	26	48
40432832	7/16 x 1/2	170	5.3	26	30	58
40433234	1/2 x 9/16	190	5.3	30	32	73
40433436	9/16 x 5/8	205	5.8	32	36	96
40433538	19/32 x 11/16	205	5.8	35	40	105
40433638	5/8 x 11/16	205	5.8	36	40	101
40433640	5/8 x 3/4	220	6.7	36	42	135
40433840	11/16 x 3/4	220	6.7	40	42	135
40433842	11/16 x 13/16	235	7.3	40	47	167
40434044	3/4 x 7/8	235	7.3	42	49	177
40434142	25/32 x 13/16	235	7.3	45	47	190
40434446	7/8 x 15/16	250	7.8	49	53	235
40434648	15/16 x 1	270	8.3	53	55	270
40435258	1 1/8 x 15/16	300	9.4	64	75	502



Offset Shaft Design

Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted - namely where the jaw meets the shank - in order to prevent deformation.

MOTOR 10



Double open-ended spanner sets
- — **metric, differing** end sizes
- — in robust polyester roll-up tool pouch with hook-and-loop fastener
- — mesh inserts allow visibility of the tools
- — a compact storage solution to keep your tools safe
- — embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96400304	10/5	8 x 9; 10 x 11; 12 x 13; 14 x 15; 17 x 19 mm	5	490
96400305	10/8	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm	8	745
96400307	10/10	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm	10	1540
96400306	10/12	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm	12	2125

MOTOR 10



Double open-ended spanner set
- — **metric, differing** end sizes in cardboard packaging

Product no.	Model	Contents	Content pcs.	g
96400314	10/9N	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm	9	918

MOTOR 10a



Double open-ended spanner sets
- — **imperial, differing** end sizes
- — in robust polyester roll-up tool pouch with hook-and-loop fastener
- — mesh inserts allow visibility of the tools
- — a compact storage solution to keep your tools safe
- — embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96404306	10a/7	$^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{11}/_{16}$ x $^{13}/_{16}$; $^{7}/_{8}$ x $^{15}/_{16}$; 1 $^{1}/_{8}$ x 1 $^{5}/_{16}$ "	7	1242
96404307	10a/11	$^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{9}/_{16}$ x $^{5}/_{8}$; $^{19}/_{32}$ x $^{11}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{11}/_{16}$ x $^{13}/_{16}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{25}/_{32}$ x $^{13}/_{16}$; $^{7}/_{8}$ x $^{15}/_{16}$; 1 $^{1}/_{8}$ x 1 $^{5}/_{16}$ "	11	2100

TCS MOTOR 10/10 6x7-24x27





Double open-ended spanner set
- — **metric, differing** end sizes
- — safely integrated in the modular Tool Control System (TCS)

Contains 10-pieces:

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24; 24 x 27 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838187	350	175	66	1/3	10	1287

TOOLS THAT
... inspire

TCS MOTOR 10/10 6x7-30x32



Double open-ended spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838182	350	350	30	2/3	10	1550

TCS MOTOR 10/11 6x7-34x36



Double open-ended spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 11-pieces:
11 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32; 34 x 36 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830167	350	175	80	1/3	11	2056

TCS MOTOR 10/10 6x7-30x32MF



Double open-ended spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830353	350	175	75	1/3	10	1437

TCS MOTOR 10a/9



Double open-ended spanner set
— **imperial, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 9-pieces:
9 double open-ended spanners **No. 10a**: $^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{19}/_{32}$ x $^{11}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{25}/_{32}$ x $^{13}/_{16}$; $^{15}/_{16}$ x 1; 1 $^{1}/_{8}$ x 1 $^{5}/_{16}$"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838779	350	175	70	1/3	9	1555




ELECTRIC 12



Small double open-ended spanners

— **metric, identical** end sizes
— straight design, jaws angled 15° and 75°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— Chrome Alloy Steel, chrome-plated




Product no.	mm	L mm	a mm	b mm	g
40063232	3.2	70	2	10.5	5
40063535	3.5	70	2	10.5	5
40060404	4	70	2	10.5	5
40064545	4.5	70	2	10.5	5
40060505	5	78	2	12.6	7
40065555	5.5	78	2	12.6	7
40060606	6	78	2	12.6	6
40060707	7	91	2	14.7	9
40060808	8	96	3	16.8	16
40060909	9	103	3	18.9	19
40061010	10	105	3	21	22
40061111	11	116	3	24.2	27
40061212	12	116	3	24.2	27
40061313	13	131	3	28.3	37
40061414	14	131	3	28.3	36

ELECTRIC 12a



Small double open-ended spanners

— **imperial, identical** end sizes
— straight design, jaws angled 15° and 75°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— Chrome Alloy Steel, chrome-plated



Product no.	"	L mm	a mm	b mm	g
40461010	5/32	70	2	10,5	5
40461212	3/16	70	2	10,5	5
40461313	13/64	78	2	12,6	7
40461414	7/32	78	2	12,6	6
40461515	15/64	78	2	12,6	6
40461616	1/4	91	2	14,7	9
40461818	9/32	91	2	14,7	9
40462020	5/16	96	3	16,8	16
40462222	11/32	103	3	18,9	19
40462424	3/8	105	3	21	22
40462828	7/16	116	3	24,2	28
40463232	1/2	131	3	28,3	37
40463434	9/16	131	3	28,3	36

ELECTRIC 12



Double open-ended spanner sets

— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96400653	12/10	4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11 mm	10	161
96400651	12/15	3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm	15	296

ELECTRIC 12a



Double open-ended spanner set

— **imperial, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 13-pieces:

13 double open-ended spanners **No. 12a**: 5/32; 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

Product no.	Model	Content pcs.	g
96404654	12a/13	13	320


COMBINATION SPANNERS AND SETS.

OPEN BOX 13



Combination spanners

— **metric, identical** end sizes
— jaw angled 15°
— ring with bi-hex and AS-Drive profile
— ring-end cranked 15°
— reinforced connection between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 3113 Form A / ISO 7738 Form A




Product no.	mm	L mm	b mm	d mm	a1 mm	a2 mm	t mm	g
40085500	5.5	100	14.8	9.2	3.5	5.8	13	15
40080606	6	105	15.5	9.9	3.6	6	15	15
40080707	7	110	15.5	9.9	3.9	6	20	10
40080808	8	115	18	12.4	4.2	7	21	21
40080909	9	120	21	13.4	4.5	7	10	27
40081010	10	125	23	14.8	4.8	7	10	35
40081111	11	135	26	16.4	4.8	8	10	43
40081212	12	140	28	17.8	5.3	8.5	10	46
40081313	13	160	30	19.1	5.3	8.5	10	57
40081414	14	165	32	20.6	5.3	8.5	10	68
40081515	15	170	35	21.9	5.3	8.5	10	80
40081616	16	180	37	23.2	5.8	10	10	89
40081717	17	190	38	24.6	5.8	10	10	100
40081818	18	200	40	26	6.7	11.5	10	126
40081919	19	230	42	27.5	6.7	11.5	10	140
40082020	20	230	45	29	7	13	10	176
40082121	21	260	47	30.3	7.3	13	10	216
40082222	22	260	49	31.8	7.3	13	10	220
40082323	23	280	53	33.5	7.8	14	5	251
40082424	24	280	53	34.9	7.8	14	5	254
40082525	25	300	55	36.3	8.4	14.5	5	281
40082626	26	300	57.5	37.8	8.4	14.5	5	325
40082727	27	300	60	39.2	8.4	14.5	5	335
40082828	28	320	62	40.6	8.4	14.5	5	368
40082929	29	330	64	41.9	8.9	16	5	385
40083030	30	330	66	43.2	8.9	16	5	404
40083232	32	360	70	45.8	9.4	16.5	5	484
40083434	34	450	75	48	9.4	17	1	683
40083636	36	460	80	50.8	10	18	1	780
40083838	38	480	87	53.6	11	19	1	915
40084141	41	480	88	57.8	11	19	1	1020
40084646	46	500	94.5	65.2	13	20	1	1330
40085050	50	530	103	73	14	21	1	1600
40085555	55	560	114	81	15	22	1	2065
40086060	60	590	125	89.8	16	24	1	2725

OPEN BOX 13a



Combination spanners

— **imperial, identical** end sizes
— jaw angled 15°
— ring with bi-hex and AS-Drive profile
— ring-end cranked 15°
— reinforced connection between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	"	L mm	b mm	d mm	a1 mm	a2 mm	g
40481212	3/16	95	14	9.8	3	3.2	10
40481313	13/64	95	14	9.8	3	3.2	10
40481414	7/32	95	14	9.8	3	3.2	10
40481515	15/64	95	14	9.8	3	3.2	10
40481616	1/4	105	15.5	10.2	3.6	6	14
40481818	9/32	110	17	11.3	3.9	6	15
40482020	5/16	115	18	12.4	4.2	7	20
40482222	11/32	120	21	13.4	4.5	7	26
40482424	3/8	125	23	14.3	4.8	7	32
40482828	7/16	135	26	16.4	4.8	8	41
40483232	1/2	160	30	18.8	5.3	8.5	57
40483434	9/16	165	32	20.6	5.3	8.5	70
40483535	19/32	170	35	21.9	5.3	8.5	74
40483636	5/8	180	37	23.2	5.8	10	88
40483838	11/16	200	40	25.3	6.7	11.5	116
40484040	3/4	230	42	27.5	6.7	11.5	144
40484141	25/32	235	45	29	7	13	175
40484242	13/16	260	47	30	7.3	13	204
40484444	7/8	260	49	31.8	7.3	13	217
40484646	15/16	280	53	34.9	7.8	14	255
40484848	1	300	55	37.2	8.4	14.5	286
40485050	1 1/16	300	60	39.2	8.4	14.5	327
40485252	1 1/8	330	64	41.4	8.9	16	380
40485454	1 3/16	332	66	43.2	8.9	16.5	398
40485656	1 1/4	360	70	45.8	9.4	16.5	504
40485858	1 5/16	450	74	47	9.6	17	617
40486060	1 3/8	460	80	49.3	10	18	796
40486262	1 7/16	461	80	51.4	10	18	760
40486464	1 1/2	480	87	53.6	11	19	950
40486666	1 5/8	480	88	58	11	19	1021
40486969	1 13/16	500	94.5	65.3	13	20	1343
40487070	1 7/8	530	103	68.4	14	21	1640
40487272	2	530	103	74	14	21	1700

OPEN BOX 13



Combination spanner sets

— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96400813	13/6	7; 8; 10; 13; 17; 19 mm	6	650
96400801	13/9	9; 10; 11; 12; 13; 14; 17; 19; 22 mm	9	758
96400802	13/11	8; 9; 10; 11; 12; 13; 14; 15; 17; 19; 22 mm	11	915
96400803	13/15	6; 7; 8; 9; 10; 11; 12; 13; 17; 19; 22; 24; 27; 30; 32 mm	15	2236
96400804	13/17	6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm	17	1480

OPEN BOX 13



Combination spanner sets

— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96400808	13/10	8; 9; 10; 11; 12; 13; 14; 15; 17; 19 mm	10	746
96400816 [1]	13/16	7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm	16	1620
96400805 [1]	13/26	6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 29; 30; 32 mm	26	4705

[1] loosely packed



OPEN BOX 13a



Combination spanner sets
— **imperial, identical** end sizes in cardboard packaging
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96404803 [1]	13a/8	7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8 "	8	900
96404812	13a/10	1/4; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4 "	10	750
96404804 [1]	13a/20	1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 1/4 "	20	3180

[1] loosely packed

TCS OPEN BOX 13/17 6-24



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
17 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830164	350	350	60	2/3	17	1615

TCS OPEN BOX 13/17 6-24MF



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
17 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830351	350	350	60	2/3	17	1700

TCS OPEN BOX 13/18 6-24



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
18 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838183	350	530	35	3/3	18	2040



TCS OPEN BOX 13/21 6-34



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 21-pieces:
21 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 34 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830174	350	530	75	3/3	21	3710

TCS OPEN BOX 13a/19



Combination spanner set
— **imperial, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 19-pieces:
19 combination spanners **No. 13a**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{19}/_{32}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{25}/_{32}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838778	350	350	55	2/3	19	2000


TCS OPEN BOX 13/25 5.5-34



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 25-pieces:
25 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 27; 29; 30; 32; 34 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96832096	350	530	80	3/3	25	4500

TCS OPEN BOX 13a/23 3/16-1 1/8



Combination spanner set
— **imperial, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 24-pieces:
23 combination spanners **No. 13a**: $^{3}/_{16}$; $^{13}/_{64}$; $^{7}/_{32}$; $^{15}/_{64}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{19}/_{32}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{25}/_{32}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1; 1 $^{1}/_{16}$; 1 $^{1}/_{8}$"
1 adjustable spanner **No. 4025**: max. 34 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830885	350	530	35	3/3	24	2800

MADE IN CRONENBERG
MADE IN GERMANY


For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

130a



Combination spanners

— **imperial, identical** end sizes
— jaw angled 15°
— ring with bi-hex and AS-Drive profile
— ring-end cranked 15°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— HPQ® high performance steel, chrome-plated
— Fed. Spec. GGG-W-636 E




Product no.	"	L mm	b mm	d mm	a_1 mm	a_2 mm	g
40571616	1/4	105	14.2	9.8	3.6	6	15
40571818	9/32	110	15.5	10.9	4.1	6	16
40572020	5/16	115	17	12	4.5	7	20
40572222	11/32	120	19	13.1	4.9	7	25
40572424	3/8	125	20.5	14.1	5.2	7	32
40572828	7/16	135	23	16.2	6	8	42
40573232	1/2	150	27	18.2	6.5	8.5	61
40573434	9/16	165	30.5	20.6	7	8.5	78

130aSP



Combination spanners

— **imperial, identical** end sizes
— jaw angled 15°
— with Spline-Drive profile
— ring-end cranked 15°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— HPQ® high performance steel, chrome-plated
— Fed. Spec. GGG-W-636 E / MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	b mm	d mm	a_1 mm	a_2 mm	g
40581616	8	1/4	105	14.2	10	3.6	5.6	13
40582020	10	5/16	115	17	12.2	4.5	6.4	21
40582424	12	3/8	125	20.5	14.8	5.2	7	31
40582828	14	7/16	135	23	16.5	6	8	43
40583232	16	1/2	150	27	18.7	6.5	8.5	59
40583434	18	9/16	165	30.5	20.8	7	8.5	84

OPEN BOX 14



Combination spanners

— **metric, identical** end sizes
— extra-long version for hard-to-reach bolted joints and greater force transmission
— jaw angled 15°
— ring with bi-hex and AS-Drive profile
— ring-end cranked 10°
— reinforcement between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 3113 Form B / ISO 7738 Form B



Product no.	mm	L mm	b mm	d mm	a_1 mm	a_2 mm	t mm	g
40100606	6	125	14	9.5	4.5	6	7	18
40100707	7	135	16	10.8	5	7	8	25
40100808	8	145	17.5	12.1	5	7	8	28
40100909	9	155	19	13.3	5.5	8	9	34
40101010	10	165	21	14.6	5.5	8	9	43
40101111	11	180	23.5	15.9	6	9	10	55
40101212	12	180	25.5	17.3	6	9	10	61
40101313	13	195	27.5	18.6	6.5	10	11	85
40101414	14	210	29.5	20.1	6.5	10	11	88
40101515	15	215	31	21.4	7	11	13	109
40101616	16	230	33	22.7	7	11	14	108
40101717	17	240	35	24.1	7.5	12	15	155
40101818	18	255	37	25.5	7.5	12	16	151
40101919	19	265	39.5	27	8	13	18	190
40102020	20	280	41.5	28.5	8	13	19	219
40102121	21	280	43	29.8	8.5	13	19	244
40102222	22	300	45	31.3	8.5	14	20	268
40102424	24	330	50	34.3	9.5	14	22	363
40102727	27	385	56	38.6	10.5	16	24	502
40103030	30	415	63	42.6	12	18	26	645
40103232	32	430	67	45.2	12	18	27	666
40103434	34	460	72	48	13	18	27	900
40103636	36	480	74	50.8	13	19	28	951
40104141	41	560	84	57.8	14	20	32	1322

High Performance Quality (HPQ®)

Our HPQ® tool is made of wear-resistant high-performance steel, yet is thin-walled and lightweight. It withstands high torques and is ideal for work in confined spaces such as turbines.

OPEN BOX 14



Combination spanner sets
— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96401006	14/11	8; 9; 10; 11; 12; 13; 14; 15; 17; 19; 22 mm	11	1137
96401004	14/15	6; 7; 8; 9; 10; 11; 12; 13; 17; 19; 22; 24; 27; 30; 32 mm	15	3370
96401005	14/17	6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm	17	1874

OPEN BOX 14




Combination spanner set
— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96401007	14/10	8; 10; 11; 12; 13; 14; 16; 17; 18; 19 mm	10	1235



Anti-Slip-Drive
The special AS-Drive profile makes high force transmission to the flats of screws and bolts possible without damaging them. This also prevents stripping of the screw head.

TCS OPEN BOX 14/21 6-36



Combination spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)


Contains 21-pieces:
21 combination spanners **No. 14**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 36 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838771	350	530	75	3/3	21	4988

4014



Combination spanners
— **metric, identical** end sizes
— jaw angled 15°
— ring with bi-hex
— ring-end cranked 10°
— Chrome Alloy Steel, chrome-plated




Product no.	mm	L mm	b mm	d mm	a_1 mm	a_2 mm	t mm	g
40146565	65	710	133	98	22	33	49.5	4500
40147070	70	760	143	105	24	35	53.5	5500
40147575	75	810	153	110	26	38	57.5	6500
40148080	80	860	163	119	28	41	63.5	8000

OPEN BOX 16



Combination spanners
— **metric, identical** end sizes
— jaw angled 15°
— ring with hex
— ring-end cranked 15°
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— Chrome Alloy Steel, chrome-plated
— ISO 3318



Product no.	mm	L mm	b mm	d mm	a_1 mm	a_2 mm	g
40093232	3.2	75	10	6.6	3	3.2	6
40093535	3.5	75	10	6.6	3	3.2	6
40094040	4	85	12.5	7.8	3	3.2	9
40094545	4.5	85	12.5	7.8	3	3.2	8
40095050	5	95	14	9.8	3	3.2	11

OPEN BOX 16/5



Combination spanner set
— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 5-pieces:
5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm

Product no.	Model	Content pcs.	g
96400902	16/5	5	46

MIXED SPANNER SETS.

TCS 9 821/28



Spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 28-pieces:
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830272	350	530	70	3/3	28	4143

TCS 4 821/22



Spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 22-pieces:
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830267	350	350	40	2/3	22	2700


TCS 10/13/24/30



Spanner set
— **metric** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 30-pieces:
9 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm
20 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
1 double-ended open-ring spanner, angled **No. 24**: 10 x 11 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830605	350	530	75	3/3	30	3724

TCS 12/13/14/29



Spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 29-pieces:
6 double open-ended spanners **No. 12**: 5.5; 12; 14 mm (x 2)
22 combination spanners **No. 13**: 6; 7 (x 2); 8; 9; 10; 11 (x 2); 12; 13; 14; 15; 16; 17; 18; 19; 20; 22; 24; 30; 32; 36 mm
1 combination spanner **No. 14**: 17 mm


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830193	350	530	80	3/3	29	3752

DOUBLE-ENDED RING SPANNERS AND SETS.


StahlwilleSTABIL® 20



Double-ended ring spanners
— **metric, differing** end sizes
— deeply cranked
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	mm	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	t mm	g
41040607	6 x 7	165	10.5	11.8	6	7	18	46
41040809	8 x 9	180	13.1	14.5	7	8	20	62
41040810	8 x 10	180	13.1	15.8	7	9	21	61
41041011	10 x 11	200	15.8	17.2	9	9	23	93
41041013	10 x 13	220	15.8	20	9	10	25	122
41041213	12 x 13	220	18.6	20	9	10	25	126
41041317	13 x 17	245	20	25.3	10	12	27	169
41041415	14 x 15	245	21.3	22.6	10	12	27	163
41041617	16 x 17	255	23.9	25.3	11	12	27	181
41041719	17 x 19	270	25.3	28	12	13	29	220
41041819	18 x 19	275	26.6	28	12	13	29	220
41041821	18 x 21	300	26.6	30.7	12	13	31	279
41041922	19 x 22	300	28	32.1	13	14	31	315
41042022	20 x 22	300	29.4	32.1	13	14	31	317
41042123	21 x 23	315	30.7	33.4	13	14	31	312
41042124	21 x 24	330	30.7	34.7	13	14	34	384
41042224	22 x 24	330	32.1	34.7	14	14	34	368
41042426	24 x 26	330	34.7	37.3	14	15	34	427
41042427	24 x 27	330	34.7	38.6	14	15	34	447
41042528	25 x 28	350	36	40	14	15	34	414
41042730	27 x 30	360	38.3	42.6	15	15	37	595
41042732	27 x 32	360	39.3	47.2	15	16	37	596
41043032	30 x 32	365	42.6	45.4	15	16	37	640
41043034	30 x 34	365	42.6	48	15	16	37	660
41043641	36 x 41	440	53	60	17	18	40	1015
41044650	46 x 50	535	65.2	73	19	20	45	1709




Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, workshop trolleys and workshop benches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

StahlwilleSTABIL® 20a




Double-ended ring spanners
— **imperial, differing** end sizes
— deeply cranked
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	"	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	t mm	g
41441620	$^{1}/_{4}$ x $^{5}/_{16}$	180	11.8	13.1	7	7	20	55
41442428	$^{3}/_{8}$ x $^{7}/_{16}$	200	15.8	17.2	9	9	23	88
41443234	$^{1}/_{2}$ x $^{9}/_{16}$	220	20	21.3	9	10	25	120
41443436	$^{9}/_{16}$ x $^{5}/_{8}$	245	21.3	25.3	10	12	27	168
41443538	$^{19}/_{32}$ x $^{11}/_{16}$	255	23.9	25.3	11	12	27	175
41443640	$^{5}/_{8}$ x $^{3}/_{4}$	270	23.9	28	12	13	29	235
41443842	$^{11}/_{16}$ x $^{13}/_{16}$	300	25.3	30.7	12	13	31	280
41444044	$^{3}/_{4}$ x $^{7}/_{8}$	300	28	32.1	13	14	31	299
41444142	$^{25}/_{32}$ x $^{13}/_{16}$	300	29.4	32.1	13	14	31	333
41444446	$^{7}/_{8}$ x $^{15}/_{16}$	330	32.1	34.7	14	14	34	363
41444648	$^{15}/_{16}$ x 1	330	34.7	37.3	14	15	34	419
41445258	1 $^{1}/_{8}$ x 1 $^{5}/_{16}$	365	42.6	45.4	15	16	37	581

StahlwilleSTABIL® 20



Double-ended ring spanner sets
— **metric, differing** end sizes in cardboard packaging

Product no.	Model	Contents	Content pcs.	g
96410408	20/7	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19 mm	7	930
96410405	20/8	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm	8	1220
96410409	20/9	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm	9	1615
96410407	20/10	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm	10	2331
96410406	20/12	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm	12	3137

StahlwilleSTABIL® 20a

Double-ended ring spanner sets
— **imperial, differing** end sizes in cardboard packaging

Product no.	Model	Contents	Content pcs.	g
96414402	20a/6	$^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{11}/_{16}$ x $^{13}/_{16}$; $^{7}/_{8}$ x $^{15}/_{16}$"	6	1200
96414405	20a/10	$^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{9}/_{16}$ x $^{5}/_{8}$; $^{19}/_{32}$ x $^{11}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{11}/_{16}$ x $^{13}/_{16}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{25}/_{32}$ x $^{13}/_{16}$; $^{7}/_{8}$ x $^{15}/_{16}$"	10	2200

TCS StahlwilleSTABIL® 20/10 6x7-30x32



Double-ended ring spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)

Contains 10-pieces:
10 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830166	350	350	45	2/3	10	2500

TCS StahlwilleSTABIL® 20/8 6x7-19x22MF



Double-ended ring spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)

Contains 8-pieces:
8 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22 mm


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830356	350	175	45	1/3	8	1323

CORONA 23



Double-ended ring spanners

— **metric, differing** end sizes
— flat cranked
— bi-hex
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 897 / ISO 10104



Product no.	mm	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	t_1 mm	t_2 mm	g
41070607	6 x 7	170	9.5	10.8	6	7	7	8	41
41070809	8 x 9	179	12.1	13.3	7	8	8	9	49
41071011	10 x 11	188	14.6	15.9	8.5	9.5	9	10	66
41071213	12 x 13	203	17.3	18.6	9.5	10.5	10	11	78
41071415	14 x 15	219	20.1	21.4	10.5	11.5	11	13	109
41071617	16 x 17	248	22.7	24.1	11.5	12.5	14	15	144
41071719	17 x 19	250	24.1	27	12.5	13.5	15	18	162
41071819	18 x 19	251	25.5	27	12.5	13.5	16	18	157
41072022	20 x 22	280	28.5	31.3	13.5	14.5	19	20	223
41072123	21 x 23	328	29.8	32.9	13.5	14.5	19	22	281
41072427	24 x 27	376	34.3	38.6	14.5	16	22	24	426
41073032	30 x 32	429	42.6	45.2	18	18	26	27	608

CORONA 23/8



Double-ended ring spanner set

— **metric, differing** end sizes in cardboard packaging


Product no.	Model	Contents	Content pcs.	g
96410704	23/8	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm	8	870

STARTER 27



Double-ended ring spanners

— **metric, differing** end sizes
— suitable for working in confined spaces
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— ISO 3318




Product no.	mm	L mm	a mm	d_1 mm	d_2 mm	r_1 mm	r_2 mm	g
41091012	10 x 12	150	6.5	16.5	19.5	35	60	53
41091113	11 x 13	150	6.5	16.5	19.5	35	60	50
41091416	14 x 16	179	7.5	21	24.5	36	64	91
41091417	14 x 17	179	7.5	21	24.5	36	64	89
41091517	15 x 17	184	7.5	22.5	25	38	66	96
41091618	16 x 18	200	8.5	25.3	27.5	47	68	130
41091922	19 x 22	225	9	28	32	48	67	164

180a



Double-ended ring spanners

— **imperial, differing** end sizes
— short, flat cranked
— bi-hex
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— HPQ® high performance steel, chrome-plated
— Fed. Spec. GGG-W-636 E / S.B.A.C. Techn. Spec. T.S. 48 up to 1/2"




Product no.	"	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	t_1 mm	t_2 mm	g
41601620	1/4 x 5/16	107	10.2	11.8	7	8	7.2	7.4	26
41602428	3/8 x 7/16	122	14.6	16.7	6.7	7.8	9	10	42
41603234	1/2 x 9/16	141	18.5	20.7	8.7	9.5	11	12	62
41603436	9/16 x 5/8	148	20.7	22.6	9.5	10.5	11.5	12.5	90

230a



Double-ended ring spanners

— **imperial, differing** end sizes
— flat cranked
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— HPQ® high performance steel, chrome-plated
— SAE AS 954 (dimensions and test values) / Fed. spec. GGG-W-636E / S.B.A.C. Techn. spec. T.S. 48 to 1/2"




Product no.	"	L mm	d1 mm	d2 mm	a1 mm	a2 mm	t1 mm	t2 mm	g
41611620	1/4 x 5/16	180	10.2	11.9	5.2	6	7.9	8.8	45
41612022	5/16 x 11/32	195	11.9	13.5	7	8	8	9	45
41612024	5/16 x 3/8	195	11.9	14.6	6	7.9	10.8	12.4	54
41612428	3/8 x 7/16	215	14.6	16.7	7.9	8.7	11.4	11.7	74
41612832	7/16 x 1/2	225	16.7	19.5	8.7	9.1	11.9	12.6	105
41613234	1/2 x 9/16	235	19.5	20.7	9.1	9.5	12.2	12.9	110
41613436	9/16 x 5/8	245	20.7	22.6	9.5	11.5	13.8	13.9	122
41613640	5/8 x 3/4	274	22.6	27.5	11.1	12	14.8	15.8	160
41613840	11/16 x 3/4	275	25.4	27.5	11.1	12	15.2	15.8	190
41614244	13/16 x 7/8	301	29.5	31.7	13.5	14.5	19	20	260
41614648	15/16 x 1	340	34.1	36.5	14.5	15	22	23	375
41614850	1 x 1 1/16	368	36.5	38.6	15	16	23	24	460
41615256	1 1/8 x 1 1/4	403	40.8	45	16	18	25	27	620

220



Double-ended ring spanners

— **metric, differing** end sizes
— cranked 15°
— bi-hex with AS-Drive profile
— extra long design for less effort with constant torque
— suitable for working in confined spaces
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— HPQ® high performance steel, chrome-plated




Product no.	mm	L mm	d1 mm	d2 mm	a1 mm	a2 mm	g
41035507	5.5 x 7	185	8.8	11	5.3	5.8	28
41030608	6 x 8	205	9.8	12.1	5.6	6	34
41030911	9 x 11	250	14.2	16.7	8	8.7	80
41031011	10 x 11	250	15.5	16.7	8	8.7	80
41031214	12 x 14	290	18.3	20.7	9.5	9.5	162
41031314	13 x 14	290	18.7	20.7	9.5	9.5	160
41031719	17 x 19	365	25	27.5	11	12	296
41031819	18 x 19	365	25.5	27.5	11	12	295
41031922	19 x 22	408	27.5	31.5	13	14.3	520
41032022	20 x 22	409	28.5	31.5	13	14.3	515

220a



Double-ended ring spanners

— **imperial, differing** end sizes
— cranked 15°
— bi-hex with AS-Drive profile
— extra long design for less effort with constant torque
— suitable for working in confined spaces
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— HPQ® high performance steel, chrome-plated
— SAE AS 954-E (test values)




Product no.	"	L mm	d1 mm	d2 mm	a1 mm	a2 mm	g
41431416	7/32 x 1/4	184	9	9.9	5.3	5.8	29
41431620	1/4 x 5/16	205	9.9	12.2	5.6	6	33
41432428	3/8 x 7/16	250	14	16	8	8.7	79
41433234	1/2 x 9/16	290	18.5	21	9.5	9.5	160
41433640	5/8 x 3/4	363	22.6	27	11	12	298
41433840	11/16 x 3/4	365	25	27	11	12	291

220aSP



Double-ended ring spanners

— **imperial, differing** end sizes
— with Spline-Drive profile
— cranked 15°
— extra long design for less effort with constant torque
— suitable for working in confined spaces
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— HPQ® high performance steel, chrome-plated
— MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	a1 mm	a2 mm	g
41160709	7 x 9	7/32 x 9/32	185	9.4	11.5	5.3	5.8	28
41160810	8 x 10	1/4 x 5/16	205	10.4	12.4	5.6	6	33
41161214	12 x 14	3/8 x 7/16	250	14.9	17	8	8.7	79
41161618	16 x 18	1/2 x 9/16	290	19	21	9.5	9.5	161
41161820	18 x 20	9/16 x 5/8	315	21	23	10	11	205
41162224	22 x 24	11/16 x 3/4	365	25	27.5	11	12	310
41162630	26 x 30	13/16 x 15/16	410	29.5	34	13	14.3	496
41162832	28 x 32	7/8 x 1	430	32	36.5	13.5	15	582

StahlwilleSTABIL®21



Double-ended ring spanners

— **metric, differing** end sizes
— straight version
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 837 / ISO 10103



Product no.	mm	L mm	a mm	d1 mm	d2 mm	g
41050607	6 x 7	100	4.5	9.6	11	14
41050809	8 x 9	115	5.5	12.5	14	19
41050810	8 x 10	115	6	12.5	15.4	18
41051011	10 x 11	130	6	15.4	16.6	30
41051213	12 x 13	150	6.5	18.2	19.5	42
41051317	13 x 17	165	8	19.5	25	57
41051415	14 x 15	165	7.5	21	22.5	55
41051617	16 x 17	170	8	23.8	25	68
41051719	17 x 19	185	8	25	27.6	78
41051819	18 x 19	185	9	26.3	27.6	84
41051821	18 x 21	210	9	26.3	30.5	107
41051922	19 x 22	210	9	27.6	32.4	109
41052022	20 x 22	210	9	29	32.4	109
41052124	21 x 24	235	10	30.5	34.7	128
41052427	24 x 27	290	11	34.7	38.5	225
41052732	27 x 32	320	12	38.5	45.5	283
41053032	30 x 32	325	12	43	45.5	289
41053034	30 x 34	325	12	43	48.5	307

StahlwilleSTABIL® 21



Double-ended ring spanner sets

— **metric, differing** end sizes in cardboard packaging


Product no.	Model	Contents	Content pcs.	g
96410503	21/7	8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm	7	397
96410501	21/10	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm	10	943

21TX



Double-ended ring spanners

— **differing** end sizes
— straight version
— for external TORX® screws
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L mm	d1 mm	d2 mm	a1 mm	a2 mm	g
41250608	E6 x E8	115.5	9.6	11.6	4.5	5.5	17
41251012	E10 x E12	149.5	13.7	15.7	6.5	7.5	33
41251418	E14 x E18	185	17.8	22.5	8	9.5	71
41252024	E20 x E24	227	24.7	29.2	10.5	12.5	129

OPEN RING 24



Double-ended open-ring spanners, angled

— **metric, differing** end sizes
— cranked 10°
— hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 3118 / ISO 3318




Product no.	mm	L mm	d1 mm	d2 mm	a1 mm	a2 mm	m1 mm	m2 mm	g
41080810	8 x 10	145	17.5	19.5	7	8.5	6.3	7.1	39
41080911	9 x 11	155	18.5	21.5	8.5	9	6.7	8.6	54
41081011	10 x 11	155	19.5	21.5	8.5	9	7.1	8.6	55
41081012	10 x 12	160	19.5	22.5	8.5	9.5	7.1	9	59
41081113	11 x 13	170	21.5	24	9	10	8.6	10	80
41081214	12 x 14	180	24	26	9.5	10.5	9	11	89

OPEN RING 24



Double-ended open-ring spanners, angled
— **metric, differing** end sizes
— cranked 10°
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated
— DIN 3118 / ISO 3318




Product no.	mm	L mm	d1 mm	d2 mm	a1 mm	a2 mm	m1 mm	m2 mm	g
41081417	14 x 17	200	26	30	10.5	12	11	14	115
41081719	17 x 19	220	30	33	12	13	14	15.8	150
41081922	19 x 22	230	33	37	13	15	15.8	17	192
41082224	22 x 24	245	37	40.5	15	16	17	18	251
41082427	24 x 27	270	40.5	44.5	16	17.5	18	20	310
41082736	27 x 36	300	42	54	16	19	20	27	414
41083032	30 x 32	300	48.5	50.5	20	22	22	24	455

OPEN RING 24a



Double-ended open-ring spanners, angled
— **imperial, differing** end sizes
— cranked 10°
— hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated




Art. No.	"	L mm	d1 mm	d2 mm	a1 mm	a2 mm	m1 mm	m2 mm	g
41481620	1/4 x 5/16	105	16.5	18	5.5	7	3.7	5	32
41482024	5/16 x 3/8	145	17.5	19.5	7	8.5	6.3	7.1	39
41482428	3/8 x 7/16	155	19.5	21.5	8.5	9	7.1	8.6	57
41483234	1/2 x 9/16	180	24	26	9.5	10.5	9.5	11	87

OPEN RING 24a



Double-ended open-ring spanners, angled
— **imperial, differing** end sizes
— cranked 10°
— bi-hex with AS-Drive profile
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Art. No.	"	L mm	d1 mm	d2 mm	a1 mm	a2 mm	m1 mm	m2 mm	g
41483640	5/8 x 3/4	218	29	33	12	13	12.7	15.8	148
41484048	3/4 x 1	232	33	40.2	13	16	15.8	19	199

TCS OPEN RING 24/7 8x10-19x22





Double-ended open-ring spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)

Contains 7-pieces:

7 double-ended open-ring spanners, angled **No. 24**: 8 x 10; 10 x 11; 11 x 13; 12 x 14; 14 x 17; 17 x 19; 19 x 22 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96838758	350	175	35	7	780


COMBINATION RATCHET SPANNERS AND SETS.

OPEN RATCH 17



Combination ratchet spanners

— **metric, identical** end sizes
— jaw angled 15°
— ring with bi-hex
— ring-end cranked 15°
— integrated ratchet with 72 teeth, with a working angle of 5°
— controlled right/left tightening using the switch on the ring
— reinforced connection between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	mm	L mm	b mm	d mm	a_1 mm	a_2 mm	g
41170808	8	144	17	18.0	4.7	7.4	45
41170909	9	150	18.8	19.5	5.3	7.4	54
41171010	10	158	21.7	21.0	5.7	8.4	65
41171111	11	165	23	22.0	6.1	8.4	71
41171212	12	173	25.2	23.5	6.4	8.4	85
41171313	13	182	26.5	25.0	6.6	8.4	94
41171414	14	190	29.5	26.5	7.3	8.4	117
41171515	15	202	31.3	28.0	7.5	8.4	131
41171616	16	215	33.4	29.0	7.7	10.0	156
41171717	17	229	36.3	30.5	7.9	10.0	178
41171818	18	240	38	32.0	8.4	11.5	212
41171919	19	252	39	34.0	8.7	11.5	235
41172121	21	275	43.5	38.0	9.0	12.5	294
41172222	22	285	46.5	41.0	10.0	13.5	339
41172424	24	296	48.5	45.0	11.0	13.5	425

OPEN RATCH 17



Combination ratchet spanner sets

— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96411705	17/5	8; 10; 13; 17; 19 mm	5	732
96411712	17/12	8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm	12	1745
96411715	17/15	8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm	15	3060

TCS OPEN RATCH 17/5



Combination ratchet spanner set

— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)


Contains 5-pieces:

5 combination ratchet spanners **No. 17**: 8; 10; 13; 17; 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830650	350	175	40	1/3	5	780



TCS OPEN RATCH 17/12




Combination ratchet spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 12-pieces:
12 combination ratchet spanners **No. 17:** 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830649	350	175	80	1/3	12	1460

OPEN RATCH 17a



Combination ratchet spanners
— **imperial, identical** end sizes
— jaw angled 15°
— ring with bi-hex
— ring-end cranked 15°
— integrated ratchet with 72 teeth, with a working angle of 5°
— controlled right/left tightening using the switch on the ring
— reinforced connection between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	"	L mm	b mm	d mm	g
41471616	1/4	134	18	17.5	34
41472020	5/16	141	18	18	36
41472424	3/8	156	22	21	64
41472828	7/16	160	22	22	68
41473232	1/2	180	26	25	86
41473434	9/16	190	29	26.5	104
41473636	5/8	210	28	29	150
41473838	11/16	226	35	30.5	168
41474040	3/4	252	39	34.5	218
41474242	13/16	272	43	38	288
41474444	7/8	281	46	41	370
41474848	1	295	48	45	426

OPEN RATCH 17a



Combination ratchet spanner sets
— **imperial, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo


Product no.	Model	Contents	Content pcs.	g
96411709	17a/5	1/4; 5/16; 3/8; 7/16; 9/16"	5	450
96411713	17a/12	1/4; 5/16; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8; 1"	12	2440

TCS OPEN RATCH 17a/5



Combination ratchet spanner set
— **imperial, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 5-pieces:
5 combination ratchet spanners **No. 17a**: 1/4; 5/16; 3/8; 7/16; 9/16"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830653	350	175	40	1/3	5	350



Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, workshop trolleys and workshop benches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

TCS OPEN RATCH 17a/12



Combination ratchet spanner set
— **imperial, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)


Contains 12-pieces:
12 combination ratchet spanners **No. 17a**: 1/4; 5/16; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8; 1"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830654	350	175	50	1/3	12	2100

OPEN RATCH 17F



Combination ratchet spanners
— **metric, identical** end sizes
— flat version
— ring with bi-hex
— jaw angled 15°
— integrated ratchet with 72 teeth, with a working angle of 5°
— change direction by flipping the spanner over
— reinforced connection between jaw and shaft
— durable, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated



Product no.	mm	L mm	b mm	d mm	g
40170808	8	145	15	18.0	38
40170909	9	150	20	19.5	50
40171010	10	160	20	21.0	58
40171111	11	165	20	22.0	69
40171212	12	170	25	23.5	88
40171313	13	180	25	25.0	98
40171414	14	185	25	26.5	115
40171515	15	200	30	28.0	133
40171616	16	225	30	29.0	154
40171717	17	230	35	30.5	176
40171818	18	240	40	32.0	210
40171919	19	255	40	34.0	241
40172121	21	275	42	38.0	283
40172222	22	285	45	41.0	343
40172424	24	295	47	45.0	447

OPEN RATCH 17F



Combination ratchet spanner sets
— **metric, identical** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96401705	17F/5	8; 10; 13; 17; 19 mm	5	744
96411708	17F/6	8; 10; 12; 13; 17; 19 mm	6	860
96401712	17F/12	8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm	12	1700
96401715	17F/15	8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm	15	3060

TCS OPEN RATCH 17F/5




Combination ratchet spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)

Contains 5-pieces:
5 combination ratchet spanners, flat **No. 17F:** 8; 10; 13; 17; 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830652	350	175	30	1/3	5	722

TCS OPEN RATCH 17F/12



Combination ratchet spanner set
— **metric, identical** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 12-pieces:
12 combination ratchet spanners, flat **No. 17F:** 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830651	350	175	30	1/3	12	1550

DOUBLE-ENDED RATCHET RING SPANNERS AND SETS.

25



Double-ended ratchet ring spanners
— **metric, differing** end sizes
— bi-hex with AS-Drive profile
— straight version
— 22 teeth
— chrome-plated




Product no.	mm	L mm	a mm	d_1 mm	d_2 mm	g
41130708	7 x 8	109	9	15	17	55
41130910	9 x 10	139	9	20	23	80
41131011	10 x 11	170	12	26	30	144
41131213	12 x 13	170	12	26	30	135
41131415	14 x 15	170	12	26	30	126
41131618	16 x 18	205	12	33	36	196
41131719	17 x 19	205	12	33	36	188

25a



Double-ended ratchet ring spanners
— **imperial, differing** end sizes
— bi-hex with AS-Drive profile
— straight version
— 22 teeth
— made completely of steel, chrome-plated
— Fed. Spec. GGG-W-001405



Product no.	"	L mm	a mm	d_1 mm	d_2 mm	g
41561620	1/4 x 5/16	109	9	15	17	60
41562022	5/16 x 11/32	109	9	15	17	60
41562428	3/8 x 7/16	139	9	20	23	90
41563234	1/2 x 9/16	174	12	26	30	160
41563638	5/8 x 11/16	205	12	33	36	257
41564044	3/4 x 7/8	235	13	36	40	296
41564246	13/16 x 15/16	235	12	36	40	281

25



Double-ended ratchet ring spanner sets
— **metric, differing** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96411302	25/4	9 x 10; 12 x 13; 14 x 15; 17 x 19 mm	4	556
96411301	25/7	7 x 8; 9 x 10; 10 x 11; 12 x 13; 14 x 15; 16 x 18; 17 x 19 mm	7	1150

25a



Double-ended ratchet ring spanner set
— **imperial, differing** end sizes
— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 7-pieces:
7 double-ended ratchet ring spanners **No. 25a**: $^{1}/_{4}$ x $^{5}/_{16}$; $^{5}/_{16}$ x $^{11}/_{32}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{5}/_{8}$ x $^{11}/_{16}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{13}/_{16}$ x $^{15}/_{16}$"

Product no.	Model	Content pcs.	g
96415601	25a/7	7	1271

TCS 25/7





Double-ended ratchet ring spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)


Contains 7-pieces:
7 double-ended ratchet ring spanners **No. 25**: 7 x 8; 9 x 10; 10 x 11; 12 x 13; 14 x 15; 16 x 18; 17 x 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838751	350	175	30	1/3	7	1015

25aSP



Double-ended ratchet ring spanners
— **imperial, differing** end sizes
— straight
— with Spline-Drive profile
— 22 teeth
— chrome-plated




Product no.	Size	"	L mm	a mm	d_1 mm	d_2 mm	g
41570810	8 x 10	$^{1}/_{4}$ x $^{5}/_{16}$	109	9	15	17	59
41571214	12 x 14	$^{3}/_{8}$ x $^{7}/_{16}$	139	9	20	23	84
41571618	16 x 18	$^{1}/_{2}$ x $^{9}/_{16}$	174	12	26	30	153
41572022	20 x 22	$^{5}/_{8}$ x $^{11}/_{16}$	205	12	33	36	250
41572428	24 x 28	$^{3}/_{4}$ x $^{7}/_{8}$	235	13	36	40	279

26a



Double-ended ratchet ring spanners
— **imperial, differing** end sizes
— reversible
— bi-hex with AS-Drive profile
— cranked
— 22 teeth
— chrome-plated



Product no.	"	L mm	a mm	d_1 mm	d_2 mm	g
41551620	$^{1}/_{4}$ x $^{5}/_{16}$	109	9	15	17	55
41552428	$^{3}/_{8}$ x $^{7}/_{16}$	139	9	20	23	80
41553234	$^{1}/_{2}$ x $^{9}/_{16}$	170	12	26	30	140

TOOLS THAT
... inspire


FASTRATCH SPANNERS AND SETS.

FastRatch 240



Ratchet spanners

— particularly suitable for union joints
— suitable for both metric and imperial nuts/bolts
— slim ergonomic design
— made from stainless, tempered steel
— DBGM (German Federal Utility Model)
— patented



Product no.	mm	"	L mm	a mm	b mm	g
41100808	8	5/16	121.4	4	16	60
41101010	10	3/8	133.3	4	20	70
41101111	11	7/16	140.4	5	23	103
41101212	12	15/32	146.3	5	25	100
41101313	13	1/2	168.4	6	26.8	154
41101414	14	9/16	174.6	6	29.6	180
41101616	16	5/8	191.3	7	32.8	270
41101717	17	21/32	201.7	7	34.3	292
41101818	18	11/16	212.8	7	36.2	310
41101919	19	3/4	238.5	7	38.5	367

FastRatch 240



Ratchet spanner sets

— in robust polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Product no.	Model	Contents	Content pcs.	g
96411003	240/4	8 mm - 5/16"; 10 mm - 3/8"; 11 mm - 7/16"; 14 mm - 9/16"	4	510
96411005	240/5	10 mm - 3/8"; 11 mm - 7/16"; 14 mm - 9/16"; 17 mm - 21/32"; 19 mm - 3/4"	5	1122
96411006	240/6	8 mm - 5/16", 10 mm - 3/8", 13 mm – 1/2", 14 mm - 9/16", 17 mm - 21/32", 19 mm - 3/4"	6	1230

TCS FastRatch 240/6



Ratchet spanner set

— safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:

6 ratchet spanners **No. 240**: 10-3/8; 11-7/16; 13-1/2; 14-9/16; 17-21/32; 19-3/4 mm-"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838774	350	175	35	1/3	6	1163




STAHLWILLE FASTRATCH 240 –
The spanner with a difference.

FAST
RATCH



Slim.

The particularly slim design of the FastRatch 240 enables work in confined spaces.



Quick.

No more repositioning, thanks to patented ratchet technology. Our video shows you exactly how this works.

qr.stahlwille.com/cqng8w



Reliable.

Placed over the nut or screw, it enables safe and quick tightening – without repositioning. The 'self-clamping effect' ensures safety and stops slips, preventing the rounding off of the head. Thanks to the integrated closing spring, it reliably grips screws and nuts, even when tension is released.



Unique.

The STAHLWILLE FastRatch 240 combines the advantages of an open-ended spanner with those of a ratchet ring spanner. Thanks to the patented 'opening ring' technology, the FastRatch can operate without problems even on tricky jobs such as pipe fittings, where only an open-ended spanner could otherwise be used.


OPEN-ENDED STRIKING SPANNERS AND OPEN-ENDED SPANNERS.

4204



Open-ended striking spanners

— special steel, steel grey
— DIN 133



Product no.	mm	L mm	a mm	b mm	g
42040027	27	180	16	56	321
42040030	30	190	17	62	451
42040032	32	190	17	62	395
42040036	36	215	17.5	76	698
42040041	41	235	18.5	86	923
42040046	46	255	20	98	1245
42040050	50	275	21	105	1445
42040055	55	300	23	116	2057
42040060	60	320	24.5	128	2559
42040065	65	342	27	138	3285
42040070	70	375	30	154	4573
42040075	75	375	30	154	4163
42040080	80	408	34	174	6059
42040085	85	408	34	174	5871
42040090	90	445	38	194	7390
42040095	95	445	38	194	7600
42040100	100	485	44	215	11500




4004



Open-ended spanners

— special steel, steel grey
— DIN 894 up to 85 mm




Product no.	mm	L mm	a mm	b mm	g
40040240	24	215	8.9	50	147
40040270	27	238	9.8	56	193
40040300	30	261	10.8	62	275
40040320	32	273	11.8	66	315
40040360	36	300	12.8	74	421
40040410	41	335	12.8	83.5	555
40040460	46	369	14.8	93	770
40040500	50	412	17	102	1003
40040550	55	457	18	112	1235
40040600	60	492	18	122	1650
40040650	65	528	19	132	1900
40040700	70	572	20	142	2035
40040750	75	608	21	152	2758
40040800	80	645	22	162	2963
40040850	85	690	23	173	3510
40040900	90	690	23	173	3425
40040950	95	847	25	195	5943
40041000	100	847	25	195	5500

4025



Adjustable spanners

— clockwise adjustment screw
— jaw angled 22.5°
— Chrome Alloy Steel, chrome-plated
— DIN 3117 / ISO 6787 Form B / ASME B107,100




Product no.	Size	max. mm	L mm	a mm	b mm	g
40250104	4	13	115	9.5	35	52
40250106	6	24	161	10.8	50	155
40250108	8	30	207	14	62	310
40250110	10	34	259	15.8	74	490
40250112	12	39	311	19	84	805
40250115	15	44	386	25	106	1320
40250118	18	53	462	30	124	2040

4026



Adjustable spanners
— counter-clockwise adjustment screw
— jaw angled 22.5°
— Chrome Alloy Steel, phosphated
— DIN 3117 / ISO 6787 Form B / ASME B 107.100



Product no.	Size	max. mm	L mm	a mm	b mm	g
40260104	4	13	115	9.5	35	52
40260106	6	24	161	10.8	50	155
40260108	8	30	207	14	62	310
40260110	10	34	259	15.8	74	490
40260112	12	39	311	19	84	805
40260115	15	44	386	25	106	1320
40260118	18	53	462	30	124	2040

TCS 4025/3





Adjustable spanner set
— safely integrated in the modular Tool Control System (TCS)
Contains 3-pieces:
3 adjustable spanners **No. 4025**: 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838797	350	175	30	1/3	3	920

TCS 4026/3





Adjustable spanner set
— safely integrated in the modular Tool Control System (TCS)
Contains 3-pieces:
3 adjustable spanners **No. 4026**: 6; 8; 10 mm


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838796	350	175	30	1/3	3	908

HEAVY-DUTY AND STRIKING RING SPANNERS.

5



Heavy-duty ring spanners
— bi-hex
— without handle
— L_2 = length with handle No. 5 1/2
— Chrome Alloy Steel, chrome-plated




Product no.	Handle no. 5 1/2	mm	L_1 mm	L_2 mm	a mm	b mm	h mm	g
42020024	1	24	180	555	17	38	29.5	381
42020027	1	27	190	560	17	41	31.5	421
42020030	1	30	200	565	18	47	33.5	525
42020032	2	32	235	730	18	49	34	712
42020036	2	36	245	735	20	54	35.5	816
42020038	2	38	250	740	21	56	37.5	810
42020041	2	41	265	750	22	62	39.5	910
42020042	2	42	265	750	22	62	39.5	919
42020046	3	46	280	910	23	69	40	1192
42020050	3	50	290	920	25.5	76	42.5	1426
42020055	3	55	300	925	28	81	45.5	1505
42020060	4	60	345	1050	30.5	90	49	2260
42020065	4	65	355	1060	33	98	53	2495
42020070	4	70	365	1065	35.5	105	55	2700
42020075	4	75	375	1070	38	110	57.6	2905
42020080	4	80	385	1075	40.5	125	59	3745
42020085	4	85	385	1075	40.5	125	59	3648
42020090	4	90	410	1100	45	140	63	5238
42020095	4	95	410	1100	45	140	63	4630
42020100	4	100	412	1100	45	143	63	4895

5 1/2



Handles

— for heavy-duty ring spanners No. 5



Product no.	Size	Suitable for	L mm	d mm	g
48030001	1	24-30 mm & 1-1 3/16"	460	19	605
48030002	2	32-42 mm & 1 1/4-1 11/16"	610	22	1562
48030003	3	46-55 mm & 1 3/4-2 1/4"	760	25	2820
48030004	4	60-100 mm & 2 3/8-3 7/8"	860	30	3705

StahlwilleSTABIL® 8



Striking ring spanners

— for heavy assembly work
— bi-hex
— slim ring wall thickness for work in tight spaces
— reinforced striking end for a larger striking surface
— Chrome Alloy Steel, drop-forged, green lacquered




Product no.	mm	L mm	a mm	b mm	g
42010032	32	195	24	47	661
42010036	36	195	26	52.4	684
42010041	41	200	29	59	896
42010046	46	250	32	65	1218
42010050	50	280	35	70	1555
42010055	55	300	38	76	2087
42010060	60	300	42	82.5	2394
42010065	65	325	45	90.5	3209
42010070	70	355	48	97	3649
42010075	75	360	51	103.5	4428
42010080	80	440	57	110	5895
42010085	85	440	57	117	6033
42010090	90	445	60	124	6885
42010095	95	450	67	131	7875
42010100	100	455	72	137	10224

4205



Striking ring spanners

— bi-hex
— special steel, grey
— DIN 7444



Product no.	mm	L mm	a mm	b mm	g
42050024	24	160	15	42.5	200
42050026	26	160	15	42.5	200
42050027	27	180	16	46	260
42050030	30	190	16.5	51.5	365
42050032	32	195	16.5	53	353
42050036	36	205	19.5	60	505
42050038	38	205	19.5	60	500
42050041	41	225	20.5	66	730
42050042	42	225	20.5	66	671
42050046	46	240	22.5	75	915
42050048	48	240	22.5	75	920
42050050	50	250	23.5	80	1120
42050055	55	270	25	87.5	1375
42050060	60	270	26	93.5	1565
42050065	65	290	29	101	2100
42050070	70	320	33	109.5	2930
42050075	75	325	34	114.5	2780
42050080	80	345	35	126	4100
42050085	85	360	37	129	3835
42050090	90	400	41.5	152	5180
42050095	95	400	41.5	152	4900
42050100	100	400	41.5	152	6560




DOUBLE-ENDED FLEXI-JOINT SPANNERS AND SETS.

FLEXI 29



Double-ended flexi-joint spanner
— **metric, differing** end sizes
— swivelling head, hex with AS-Drive profile
— robust, slim and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop-forged, hardened, and cooled in an oil bath
— Chrome Alloy Steel, chrome-plated




Product no.	mm	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	g
43010607	6 x 7	180	9.5	11	23	23	51

FLEXI 29



Double-ended flexi-joint spanners
— **metric, differing** end sizes
— swivelling head, bi-hex with AS-Drive profile
— durable, slim, and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop forged, hardened and cooled in oil bath
— Chrome Alloy Steel, chrome plated




Product no.	mm	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	g
43010809	8 x 9	201	26	27.5	11.9	13.4	81
43011011	10 x 11	202	30.5	32	14.7	15.9	102
43011013	10 x 13	230.5	30	33.5	14.7	18.4	137
43011213	12 x 13	228	33	33.5	17.2	18.4	153
43011415	14 x 15	227	35	37	19.7	20.9	197
43011617	16 x 17	247	38.5	39	22.2	23.7	234
43011618	16 x 18	249	38.5	40	22.2	24.7	267
43011719	17 x 19	250	39	41	23.7	26.3	277
43011819	18 x 19	246.5	40	41	24.7	26.3	294
43012022	20 x 22	287.5	45.5	48	27.3	29.8	430
43012123	21 x 23	286.5	46.5	50	28.6	31.1	447
43012427	24 x 27	349.5	50.5	60.5	32.4	36.1	716

FLEXI 29a



Double-ended flexi-joint spanners
— **imperial, differing** end sizes
— swivelling head, hex with AS-Drive profile
— durable, slim, and lightweight design
— high flexural strength due to double-T profile
— STAHLWILLE's rounded finish ensures a non-slip, pleasant feel
— drop forged, hardened and cooled in oil bath
— Chrome Alloy Steel, chrome plated



Product no.	"	L mm	d_1 mm	d_2 mm	a_1 mm	a_2 mm	g
43412428	$^3/_8$ x $^7/_{16}$	202	14	16	30.5	32	98
43413234	$^1/_2$ x $^9/_{16}$	227	18.1	20	35	37	195
43413638	$^5/_8$ x $^{11}/_{16}$	249.5	22.1	24	39	40	269

FLEXI 29/7



Double-ended flexi-joint spanner set
— **metric, differing** end sizes
— in cardboard packaging

Contains 7-pieces:
7 double-ended flexi-joint spanners **No. 29**: 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm

Product no.	Content pcs.	g
96430101	7	1503

TCS FLEXI 29/6 8x9-18x19



Double-ended flexi-joint spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
6 double-ended flexi-joint spanners **No. 29**: 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838764	350	175	35	1/3	6	1079

TCS FLEXI 29/7 8x9-20x22



Double-ended flexi-joint spanner set
— **metric, differing** end sizes
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
7 double-ended flexi-joint spanners **No. 29**: 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830195	350	175	40	1/3	7	1520

BOX SPANNERS AND SETS.

10750



Box spanners
— **metric, differing** end sizes
— hex
— made of seamlessly drawn precision steel tubing
— recessed at both ends
— Chrome Alloy Steel, surface polished and chrome plated
— DIN 896 Form B



Product no.	mm	L mm	d_1 mm	d_2 mm	Rotary pin no.	g
43330607	6 x 7	110	10.5	11.5	6	26
43330809	8 x 9	110	13	14.5	6	38
43331011	10 x 11	125	16	17	6	50
43331213	12 x 13	145	19	20.5	6	78
43331415	14 x 15	145	21.5	22.5	6	78
43331617	16 x 17	155	24	26	7	127
43331719	17 x 19	160	26	28.5	7	199
43331819	18 x 19	160	27.5	28.5	7	199
43332022	20 x 22	170	29.5	32	7	232
43332123	21 x 23	170	30.5	33	7	251
43332426	24 x 26	190	34.5	37	7	300
43332427	24 x 27	190	34.5	38.5	7	301
43332428	24 x 28	196	32.1	36.7	7	320
43333032	30 x 32	205	42	45	8	382
43333236	32 x 36	225	45	50	8	535
43333641	36 x 41	225	50	56	8	648
43334146	41 x 46	245	56	62	8	845
43334650	46 x 50	245	62	68	8	878
43335560	55 x 60	245	70	76	8	1178

TOOLS THAT
... inspire

10750



Box spanner sets
— **metric, differing** end sizes
— hex
— made of seamlessly drawn precision steel tubing
— recessed at both ends
— Chrome Alloy Steel, surface polished and chrome plated
— DIN 896 Form B

Product no.	Model	Contents	Content pcs.	g
96431202	10750/7	8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm	7	830
96431205	10750/11	6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 30 x 32 mm	11	1830

10750 1/2



Tommy bars
— for No. 10750
— stepped

Product no.	Size	Suitable for	L mm	g
48010006	6	6 x 7-14 x 15 mm	180	49
48010007	7	16 x 17-24 x 28 mm	320	305
48010008	8	30 x 32-55 x 60 mm	630	1400

HOOK SPANNERS.

12910



Adjustable hook spanners
— for slotted nuts
— adjustable
— with teeth
— DIN 1810

Product no.	Size	Span mm	g
44010001	1	20-42	90
44010002	2	45-90	245
44010003	3	95-165	686


SPANNER ACCESSORIES.

12950/11



Spanner holder
— for 11 spanners
— with lockable flap for securing the tools
— with EURO perforation, for hanging
— robust plastic design, with folding carrying handle

Product no.	L mm	g
89932000	125	152


MADE IN GERMANY

3 Socketry

144 1/4" Socketry

169 3/8" Socketry

187 1/2" Socketry

212 3/4" Socketry

217 1" Socketry

219 Adaptor sets

219 Socket accessories

221 Control cabinet keys

222 Empty boxes and inlays

STAHLWILLE SOCKETRY –
Reliable and safe.

Whether it's ratchets, drive tools or accessories – top quality awaits the user in every instance. Our STAHLWILLE tool boxes made of sturdy ABS plastic make everyday work easier thanks to their lightweight and well thought-out design. In addition, STAHLWILLE sockets made of HPQ® high-performance steel are characterised by high load-bearing capacity. And the wide portfolio of ratchets, as well as drive tools and accessories, always ensures the perfect choice of tool.

ROBUST



Robust.

STAHLWILLE set cases are particularly resilient thanks to their torsionally rigid housing design and robust ABS plastic. The high-quality, chemical-resistant hard foam insert holds the tools securely.

Resilient.

Our High Performance Quality (HPQ®) tools are made of wear-resistant high-performance steel, but are thin-walled and lightweight. They withstand high torques and are ideal for work in confined spaces such as turbines.

Gentle.

The special AS-Drive profile makes high force transmission to the flats of nuts and bolts possible without damaging them. This also prevents stripping of the screw head.



MADE IN CRONENBERG
MADE IN GERMANY

Efficient.

Our fine-tooth ratchets with 80 teeth re-engage after just 4.5° for maximum precision in confined spaces. Eight pairs of teeth engage simultaneously to ensure maximum load-bearing capacity and particularly smooth running, even at high torques.

Varied.

STAHLWILLE fine-tooth ratchets are available in the common drive sizes of ¼", ⅜" and ½" with 2-component handle or slim steel handle. The mini fine-tooth bit ratchet, the fine-tooth flexible head ratchet and the Hi-LOK™ variant round off the range of fine tooth ratchets.

Reliable.

The QuickRelease safety lock prevents unintentional loss of attached tools and accessories. These lock securely into place, and are only released again at the push of a button for a quick tool change.

FOD preventative.


STAHLWILLE protects against FOD (Foreign Object Damage). Thanks to the screwless design, these tools are ideal for use in safety-relevant areas.

1/4" SOCKETRY.

40



Sockets
- hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01010003	3	23	5.6	10.7	2.5	2	15	7
01010032	3.2	23	5.6	10.7	2.5	2	15	8
01010035	3.5	23	6	10.7	2.5	2.5	15	8
01010004	4	23	6.7	10.7	3.2	3.5	15	9
01010045	4.5	23	7.3	10.7	3.7	4	15	9
01010005	5	23	7.9	10.7	4	4.5	15	8
01010055	5.5	23	8.5	10.7	4.5	6	15	9
01010006	6	23	9.2	10.7	5	6	15	9
01010007	7	23	10.7	10.7	6	6.5	13.4	10
01010008	8	23	11.6	11.6	7	8	13.1	11
01010009	9	23	12.8	12.8	8	8	12.8	14
01010010	10	23	14.3	14.3	9	8	14.9	17
01010011	11	23	15.5	15.5	10	9	14.6	19
01010012	12	23	16.5	16.5	11	9.5	14.3	24
01010013	13	23	17.8	17.8	12	9.5	14	26
01010014	14	24	18.8	18.8	13	10	14.7	30



40a



Sockets
- hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1/Fed. Spec. GGG-W-641/SAE AS 954-E




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01410008	1/8	23	5.6	10.7	2.5	2	15	7
01410010	5/32	23	6.7	10.7	3.2	3.5	15	9
01410012	3/16	23	7.6	10.7	4	4.5	15	9
01410014	7/32	23	8.6	10.7	5	6	15	9
01410016	1/4	23	9.4	10.7	5.5	6	15	9
01410018	9/32	23	10.7	10.7	6.6	6.5	13.2	10
01410020	5/16	23	11.6	11.6	7	8	13.1	12
01410022	11/32	23	12.7	12.7	8.1	8	13.3	14
01410024	3/8	23	13.7	13.7	8.3	8	13.3	16
01410028	7/16	23	15.8	15.8	10	9	14.6	15
01410032	1/2	23	17.3	17.3	11.5	9.5	14.1	27
01410034	9/16	24	18.8	18.8	13.1	10	14.7	31

40D



Sockets
- bi-hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01030005	5	23	7.9	10.7	4	4.5	15	9
01030055	5.5	23	8.5	10.7	4.5	6	15	9
01030006	6	23	9.2	10.7	5	6	15	9
01030007	7	23	10.7	10.7	6	6.5	13.4	10
01030008	8	23	11.6	11.6	7	8	13.1	11
01030009	9	23	12.8	12.8	8	8	12.8	13
01030010	10	23	14.3	14.3	9	8	14.9	16
01030011	11	23	15.5	15.5	10	9	14.6	19
01030012	12	23	16.5	16.5	11	9.5	14.3	23
01030013	13	23	17.8	17.8	12	9.5	14	25
01030014	14	24	18.8	18.8	13	10	14.7	30

40aD



Sockets
- bi-hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1/Fed. Spec. GGG-W-641/SAE AS 954-E (test values)




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01530010	5/32	23	6.7	10.7	3.2	3.5	15	7
01530012	3/16	23	7.6	10.7	4	4.5	15	7
01530014	7/32	23	8.6	10.7	5	6	15	9
01530016	1/4	23	9.4	10.7	5.5	6	15	8
01530018	9/32	23	10.7	10.7	6.6	6.5	13.2	8
01530020	5/16	23	11.6	11.6	7	8	13.1	11
01530022	11/32	23	12.7	12.7	8.1	8	13.3	13
01530024	3/8	23	13.7	13.7	8.3	8	13.3	16
01530028	7/16	23	15.8	15.8	10	9	14.6	21
01530032	1/2	23	17.3	17.3	11.5	9.5	14.1	26
01530034	9/16	24	18.8	18.8	13.1	10	14.7	30

40aDL



Sockets
- long version
- bi-hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01640010	5/32	50	6.7	10.7	3.2	4.5	42	13
01640012	3/16	50	7.6	10.7	4	4.5	42	15
01640014	7/32	50	8.6	10.7	5	6	42	16
01640016	1/4	50	9.4	10.7	5.2	6	42	19
01640018	9/32	50	10.7	10.7	6.5	8	40.2	20
01640020	5/16	50	11.6	11.6	7	8	40.1	24
01640022	11/32	50	12.7	12.7	8.1	9	39.7	26
01640024	3/8	50	13.7	13.7	8.3	9	39.7	33
01640028	7/16	50	15.8	15.8	10	10.5	41.6	42
01640032	1/2	50	17.3	17.3	11.5	12	41.1	44
01640034	9/16	50	18.8	18.8	13.1	15	40.7	55

40DL



Sockets
- long version
- bi-hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN EN 3710/DIN EN 3709/DIN 3124/ISO 2725-1/ASME B 107.5M




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01240005	5	50	7.9	10.7	4	4.5	42	15
01240055	5.5	50	8.5	10.7	4.5	6	42	16
01240006	6	50	9.2	10.7	5	6	42	18
01240007	7	50	10.7	10.7	6	6.5	40.9	21
01240008	8	50	11.6	11.6	7	8	40.1	23
01240009	9	50	12.8	12.8	8	8	39.8	30
01240010	10	50	14.3	14.3	9	9	41.9	35
01240011	11	50	15.5	15.5	10	10.5	41.6	40
01240012	12	50	16.5	16.5	11	12	41.3	47
01240013	13	50	17.8	17.8	12	12	41	50
01240014	14	50	18.8	18.8	13	15	40.7	57

40aDV



Sockets
- bi-hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- SAE AS 954-E / S.B.A.C. AS 40605/40606




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01650014	7/32	31.8	8.6	10.7	5	6	23.8	12
01650016	1/4	31.8	9.4	10.7	5.2	6	23.8	13
01650018	9/32	31.8	10.7	10.7	6.6	6.5	22	13
01650020	5/16	31.8	11.6	11.6	7	8	21.9	15

40L



Sockets
- long version
- hex with AS-Drive profile
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124/ISO 2725-1 / ASME B 107.5M / DIN EN 3710 / DIN EN 3709




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01020032	3.2	50	5.6	10.7	2.5	2	37.5	12
01020004	4	50	6.7	10.7	3.2	3.5	42	14
01020045	4.5	50	7.3	10.7	3.7	4	42	15
01020005	5	50	7.9	10.7	4	4.5	42	16
01020055	5.5	50	8.5	10.7	4.5	6	42	17
01020006	6	50	9.2	10.7	5	6	42	18
01020007	7	50	10.7	10.7	6	6.5	40.9	24
01020008	8	50	11.6	11.6	7	8	40.1	27
01020009	9	50	12.8	12.8	8	8	39.8	31
01020010	10	50	14.3	14.3	9	9	41.9	38
01020011	11	50	15.5	15.5	10	10.5	41.6	43
01020012	12	50	16.5	16.5	11	12	41.3	49
01020013	13	50	17.8	17.8	12	12	41	56

40TX



Sockets
- for external TORX® screws
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	Size	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01270004	E4	23	5.6	10.7	2	4.5	15	8
01270005	E5	23	6.7	10.7	2.8	5	15	7
01270006	E6	23	8	10.7	3.6	5.5	15	10
01270007	E7	23	9.6	10.7	3.8	6.5	15	10
01270008	E8	23	10.5	11.6	4.3	7	15	10
01270010	E10	23	12.7	12.7	5.6	9	15	17

40aSP



Sockets
- for external Spline-Drive screws
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01011007	7	7/32	22.2	8.6	10.7	5	6	14.2	7
01011008	8	1/4	22.2	9.5	10.7	5.6	7	14.2	10
01011009	9	9/32	22.2	11.2	11.2	6.6	8	12.4	10
01011010	10	5/16	22.2	11.6	11.6	7.1	8	12.2	12
01011012	12	3/8	23	13.8	13.8	8.6	8.7	12.6	18
01011014	14	7/16	25	15.7	15.7	10.4	10.7	14.1	24

40aLSP



Sockets
- long version, deep drilled
- for external Spline-Drive screws
- 1/4" internal square drive
- HPQ® high performance steel, chrome-plated
- MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01021007	7	7/32	50.8	8.6	10.7	5	6	42.8	18
01021008	8	1/4	50.8	9.5	10.7	5.6	8	42.8	24
01021010	10	5/16	50.8	11.6	11.6	7.1	8	40.8	27

402



Uniflex sockets

— bi-hex with AS-Drive profile
— 1/4" internal square drive
— HPQ® high performance steel, chrome-plated




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01140006	6	32	9.2	12.7	5	5.5	10	16
01140007	7	33.5	10.4	12.7	6	6	11.5	16
01140008	8	35	11.6	12.7	6.7	8	13	17
01140009	9	36	13	12.7	8	8	12	20
01140010	10	38	14.2	12.7	9	12	14	21

402aK



Uniflex sockets

— extra short version
— bi-hex with AS-Drive profile
— 1/4" internal square drive
— HPQ® high performance steel, chrome-plated




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01541024	3/8	34	13.6	12.7	6.7	9.1	12.0	19
01541034	9/16	37.5	19	12.7	13.1	10.3	11.8	25

402a



Uniflex sockets

— bi-hex with AS-Drive profile
— 1/4" internal square drive
— HPQ® high performance steel, chrome-plated
— SAE AS 954-E / ASME B 107.1




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01540014	7/32	32	8.6	12.7	4.8	5.5	10	17
01540016	1/4	32	9.6	12.7	5.2	5.5	10	16
01540018	9/32	32	11	12.7	6.4	6.5	10	19
01540020	5/16	35	11.6	12.7	6.7	8	13	17
01540022	11/32	35	12.7	12.7	8	7.5	11.5	19
01540024	3/8	38	13.6	12.7	9	8.6	13.1	20
01540028	7/16	39.5	15.7	12.7	10.5	10.7	15	23
01540032	1/2	41.5	17.3	12.7	12	11.1	16.5	27

402aSP



Uniflex sockets

— for external Spline-Drive screws
— 1/4" internal square drive
— HPQ® high performance steel, chrome-plated
— MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
01542016	8	1/4	32	9.5	12.7	5.6	6.4	9.8	16
01542020	10	5/16	38	11.6	12.7	7.1	8	13	18

41K



Screwdriver sockets
— for slotted screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated
— blades according to DIN 5264




Product no.	a mm	b mm	L1 mm	L2 mm	∅ (d) mm	g
01280006	0.6	3.5	28	16	11.6	10
01280008	0.8	4	28	16	11.6	10
01280010	1	5.5	28	16	11.6	11
01280012	1.2	8	28	16	11.6	12

44



INHEX screwdriver sockets
— for hex socket head screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422




Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
01050025	2.5	55	30	10.7	18
01050003	3	55	30	10.7	20
01050004	4	55	30	10.7	20
01050005	5	55	30	10.7	25
01050006	6	55	30	11.6	30

44a



INHEX screwdriver sockets
— for hex socket head screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422




Product no.	"	L1 mm	L2 mm	∅ (d) mm	g
01450004	1/16	55	30	10.7	11
01450005	5/64	55	30	10.7	12
01450006	3/32	55	30	10.7	14
01450007	7/64	55	30	10.7	17
01450008	1/8	55	30	10.7	12
01450009	9/64	55	30	10.7	13
01450010	5/32	55	30	10.7	14
01450012	3/16	55	30	10.7	17
01450014	7/32	55	30	10.7	19
01450016	1/4	55	30	11.6	24

44K



INHEX screwdriver sockets
— short version
— for hex socket head screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422




Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
01120003	3	28	16	11.6	10
01120004	4	28	16	11.6	10
01120005	5	28	16	11.6	10
01120006	6	28	16	11.6	10
01120008	8	28	16	11.6	15

44PH



Screwdriver sockets
— for PHILLIPS® screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated
— tips according to DIN 5260




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
01290001	PH1	28	16	11.6	12
01290002	PH2	28	16	11.6	11
01290003	PH3	28	16	11.6	12
01290004	PH4	28	16	11.6	14

44PZ



Screwdriver sockets
— for POZIDRIV® screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
01300001	PZ1	28	16	11.6	10
01300002	PZ2	28	16	11.6	11

44KTX



Screwdriver sockets
— for recessed TORX® screws
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
01350008	T8	28	16	11.6	10
01350009	T9	28	16	11.6	10
01350010	T10	28	16	11.6	10
01350015	T15	28	16	11.6	10
01350020	T20	28	16	11.6	11
01350025	T25	28	16	11.6	11
01350027	T27	28	16	11.6	11
01350030	T30	28	16	11.6	12
01350040	T40	28	16	11.6	12


44KTXB



Screwdriver sockets
— for recessed TORX® screws
— with hole in drive tip (TORX® Tamper Resistant)
— 1/4" internal square drive
— Chrome Alloy Steel, chrome-plated



Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
01351008	T8	28	16	11.6	10
01351009	T9	28	16	11.6	10
01351010	T10	28	16	11.6	10
01351015	T15	28	16	11.6	10
01351020	T20	28	16	11.6	10
01351025	T25	28	16	11.6	11
01351027	T27	28	16	11.6	10
01351030	T30	28	16	11.6	11
01351040	T40	28	16	11.6	10



1/4" drive tools
Explanation of table headings

L = Overall length
a = Head height (excluding square drive)
b = Head width

411



Fine-tooth ratchet
— 1/4" external square drive
— reversible
— 60 teeth
— for working in tight spaces, with a working angle of just 6°
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11231011	1/4	118	19.5	24	6 °	100

415-2K



Ratchet
— 1/4" external square drive
— reversible
— 22 teeth
— working angle 16.5°
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11111010	1/4	117	13	22	16.5 °	80

415QR N



QuickRelease fine-tooth ratchet
— 1/4" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11111020	1/4	117	10.7	22.6	4.5 °	79

415SG-QR N



QuickRelease fine-tooth ratchet
— 1/4" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with steel handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11111030	1/4	117	10.7	22.6	4.5 °	86



415QRL N



QuickRelease fine-tooth ratchet

— long version
— 1/4" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11111040	1/4	153	10.7	22.6	4.5 °	94

418QR



Mini QuickRelease fine-tooth ratchet

— short version
— 1/4" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with steel handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11111050	1/4	90	12.2	22.5	4.5 °	74

416QR



QuickRelease fine-tooth flexible ratchet

— 1/4" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— handle can be swivelled up and down by approximately 90°, engages and locks in the following positions: straight, 30° up, 60° up, 30° down
— easy release of the lock at the push of a button
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠	g
11261010	1/4	170	12	22.5	4.5 °	170

4110

Ratchet spare parts set
Contains 7-pieces:
1 pinion; 1 locking part; 1 switching disc; 1 spring; 3 screws

Product no.	for model	■ "	Content pcs.	g
19200001	411	1/4	7	47

4150

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 screws M 1.7 x 8; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19010000	415	1/4	9	26

4150QR

Ratchet spare parts set
Contains 11-pieces:
1 pinion; 1 locking disc; 2 gear lever with pin; 1 ball; 2 compression springs; 2 retaining screws M 1.7 x 8; 2 cover plates

Product no.	for model	■ "	Content pcs.	g
19011020	415QR, 725QR/4	1/4	11	24

4150QR N

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 pin; 1 ball; 1 compression spring; 2 circlips; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19012020	415QR N, 415QRL N, 415SG-QR N, 416QR, 418QR	1/4	9	21

4151B

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 pin; 1 ball; 1 compression spring; 2 circlips; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19010012	415B	1/4	9	22

400N



Drive handle
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
11050010	1/4	150	70

400QR



QuickRelease drive handle
— with QuickRelease safety lock
— with ball locking function
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
11051010	1/4	150	80

400 DRALL®



Drive handle
— with 1/4" internal square drive in end of handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
11050011	1/4	150	105

401



Flexible drive handle
— only for clockwise tightening
— max. torque: 5 N·m
— with 3-component handle
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
11053002	1/4	240	130

403



Flexible handle
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
11061010	1/4	154.5	70

404



T-handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
11070000	1/4	116	38

404QR



QuickRelease T-handle
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
11071000	1/4	116	50

404/1QR



QuickRelease T-handle
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316


Product no.	■ "	L mm	g
11071500	1/4	116	50

413QR



QuickRelease speeder brace
— with QuickRelease safety lock
— with ball locking function
— with steel handle
— separate palm piece can be attached for greater axial force transmission
— working radius: 70 mm
— Chrome Alloy Steel, chrome-plated
— patented

Product no.	■ "	L mm	g
11100005	1/4	440	354



1/4" extensions
Explanation of table headings

L = Overall length
d = Diameter of head

405



Extensions
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
11010001	2	1/4	54	11.6	29
11010006	4	1/4	100	11.6	46
11010002	6	1/4	150	11.6	65
11010010	10	1/4	254	11.6	115
11010014	14	1/4	356	11.6	155

405QR



QuickRelease extensions
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
11011001	2	1/4	54	11.6	28
11011006	4	1/4	102	11.6	49
11011002	6	1/4	150	11.6	65
11011013	13	1/4	330	11.6	145
11011005	14	1/4	356	11.6	150

405W



Wobble-Drive extensions
— swivel angle 8° to each side
— max. torque: 40 N·m
— Chrome Alloy Steel, chrome-plated

Product no.	Size	■ "	L mm	∅ (d) mm	g
11010011	2	1/4	54	11.6	28
11010012	6	1/4	150	11.6	55
11010016	4	1/4	100	11.6	45
11010020	10	1/4	254	11.6	110
11010024	14	1/4	356	11.6	155

406



Flexible extension
— only for clockwise tightening
— max. torque: 5 N·m
— Chrome Alloy Steel, chrome-plated


Product no.	■ "	L mm	∅ (d) mm	g
11040000	1/4	152	11.6	61

408QR



QuickRelease extensions
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
11011502	2	1/4	55	11.6	20
11011504	4	1/4	99	11.6	40
11011506	6	1/4	150	11.6	70
11011513	13	1/4	330	11.6	140
11011514	14	1/4	355	11.6	150



1/4" universal joints
Explanation of table headings

L = Overall length
d = Diameter of head

407



Universal joint
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
11020000	1/4	37	12.8	23

407QR



QuickRelease universal joint
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
11021000	1/4	45	13	35

407/1QR



QuickRelease universal joint
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
11021500	1/4	45	30

409



Square drive adaptor
— 1/4 to 3/8"
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
11030002	3/8	25	12.8	18

409M



Square drive adaptor
— $^{1}/_{4}$ to $^{3}/_{8}$"
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
11030010	$^{3}/_{8}$	13	28	14

410



Square drive adaptor
— $^{1}/_{4}$ to $^{1}/_{2}$"
— HPQ® high performance steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
11030003	$^{1}/_{2}$	28	16.5	36

417/1



Locking adaptor
— with hex L-Key $^{3}/_{32}$" No. 10760a

Product no.	■ "	L mm	∅ (d) mm	g
96112701	$^{1}/_{4}$	42	13	23

TOOLS THAT
... inspire

40a/40aD/16/2



HI-LOK™ socket set
— for HI-LOK™ bolts
— in a sturdy, stackable ABS plastic case with TCS inlay
Contains 18-pieces:
1 HI-LOK™ fine-tooth ratchet $^{1}/_{4}$" **Nr. 415SGH N**: L. 117 mm
1 HI-LOK™ extension $^{1}/_{4}$" **No. 414H:** L. 54 mm
5 sockets with bi-hex $^{1}/_{4}$" **No. 40aD**: $^{7}/_{16}$; $^{3}/_{8}$; $^{11}/_{32}$; $^{5}/_{16}$; $^{1}/_{4}$"
5 sockets with hex $^{1}/_{4}$" **No. 40a**: $^{7}/_{16}$; $^{3}/_{8}$; $^{11}/_{32}$; $^{5}/_{16}$; $^{1}/_{4}$"
3 L-Keys hex **No. 10759a/1**: $^{3}/_{32}$; $^{5}/_{64}$; $^{1}/_{16}$"; L. 50 mm
3 L-Keys hex **No. 10759a/2**: $^{3}/_{32}$; $^{5}/_{64}$; $^{1}/_{16}$"; L. 100 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96016304	$^{1}/_{4}$	230	130	60	18	685

415SGH N



HI-LOK™ fine-tooth ratchet
— $^{1}/_{4}$" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with steel handle
— with hole drilled through the square drive, and ball locking of the sockets
— for working on HI-LOK™ bolts in the aerospace industry
— FOD-preventive due to screwless design
— Chrome Alloy Steel, chrome-plated
— patented

Product no.	■ "	L mm	a mm	b mm	∠	g
11110010	$^{1}/_{4}$	117	10.7	22.6	4.5 °	88

4152

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 pin; 1 ball; 1 compression spring; 2 circlips; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19010013	415SGH N	$^{1}/_{4}$	9	21

414H




HI-LOK™ extensions
— with locking system like ratchet No. 415SGH N
— Chrome Alloy Steel, chrome-plated

Product no.	Size	■ "	L mm	∅ (d) mm	g
11240011	2	1/4	54	13	34
11240012	4	1/4	102	13	49
11240013	6	1/4	152	13	66

10759



HI-LOK™ L-Keys
— for **metric** hex socket head screws
— with hex tip, for use with ratchet No. 415SGH N
— with round shaft for locking the retaining ball




Product no.	Size	◉ mm	L_1 mm	L_2 mm	g
43062002	1	2	50	100	5
43064002	2	2	100	100	8

10759a



HI-LOK™ L-Keys
— for **inch** hex socket head screws
— with hex tip, for use with ratchet No. 415SGH N
— with round shaft for locking the retaining ball



Product no.	Size	◉ "	L_1 mm	L_2 mm	g
43560004	1	1/16	50	50	5
43560005	1	5/64	50	50	5
43560006	1	3/32	50	50	5
43564004	2	1/16	50	100	8
43564005	2	5/64	50	100	8
43564006	2	3/32	50	100	8

44KTX/9



Screwdriver socket set
— for recessed TORX® screws
— Chrome Alloy Steel, chrome-plated
— in a carton
Contains 9-pieces:
9 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96017709	9	110

40D/10-12916



Socket set on clip rail
— bi-hex with AS-Drive profile
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel
— HPQ® high performance steel, chrome-plated
— DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5M
Contains 10-pieces:
10 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 10; 11; 12; 13; 14 mm
+ socket clip rail **No. 12916/10**

Product no.	Content pcs.	g
96051010	10	200



40aDL/10-12916



Socket set on clip rail
— bi-hex with AS-Drive profile
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel
— HPQ® high performance steel, chrome-plated
— ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E

Contains 10-pieces:
10 sockets long, with bi-hex 1/4" **No. 40aDL**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
+ socket clip rail **No. 12916/10**

Product no.	Content pcs.	g
96016410	10	350

40aD/10-12916



Socket set on clip rail
— bi-hex with AS-Drive profile
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel
— HPQ® high performance steel, chrome-plated
— ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E

Contains 10-pieces:
10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
+ socket clip rail **No. 12916/10**

Product no.	Content pcs.	g
96015310	10	200

12916/10



Socket clip rail
— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel

Product no.	■ "	L mm	Retaining clips	g
80400003	1/4	255	10	46

12916/12917/12918



Socket clip rail set
— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— attachments can be combined with each other
— can be mounted on a wall or perforated wall/panel

Contains 3-pieces:
1 socket clip rail 1/4" (6.3 mm)
1 socket clip rail 3/8" (10 mm)
1 socket clip rail 1/2" (12.5 mm)

Product no.	L mm	Retaining clips	Content pcs.	g
96003010	315	30	3	190

40/9/4




Socket set
— in a sturdy, stackable ABS plastic box

Contains 13-pieces:
9 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 10; 11; 13 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011119	1/4	230	130	60	13	696

40a/9/4



Socket set

— in a sturdy, stackable ABS plastic box

Contains 13-pieces:

9 sockets with hex $^{1}/_{4}$" **No. 40a**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$"


1 ratchet $^{1}/_{4}$" **No. 415-2K**: L. 117 mm

2 extensions $^{1}/_{4}$" **No. 405**: L. 54; 150 mm

1 universal joint $^{1}/_{4}$" **No. 407**: L. 37 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96015107	$^{1}/_{4}$	230	130	60	13	702

40aD/9/4



Socket set

— in a sturdy, stackable ABS plastic box

Contains 13-pieces:

9 sockets with bi-hex $^{1}/_{4}$" **No. 40aD**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$"

1 ratchet $^{1}/_{4}$" **No. 415-2K**: L. 117 mm

2 extensions $^{1}/_{4}$" **No. 405**: L. 54; 150 mm

1 universal joint $^{1}/_{4}$" **No. 407**: L. 37 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96016302	$^{1}/_{4}$	230	130	60	13	700

40aD/12/7QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 19-pieces:

11 sockets with bi-hex $^{1}/_{4}$" **No. 40aD**: $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"

1 socket with hex $^{1}/_{4}$" **No. 40a**: $^{1}/_{8}$"

1 QuickRelease fine-tooth ratchet $^{1}/_{4}$" **No. 415SG-QR N**: L. 117 mm

3 QuickRelease extensions $^{1}/_{4}$" **No. 405QR**: L. 54 (2x); 150 mm

1 QuickRelease universal joint $^{1}/_{4}$" **No. 407QR**: L. 45 mm

1 QuickRelease drive handle $^{1}/_{4}$" **No. 400QR**: L. 150 mm

1 bit holder $^{1}/_{4}$" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96015208	$^{1}/_{4}$	230	130	60	19	872

40/13/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 19-pieces:

13 sockets with hex $^{1}/_{4}$" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm

1 ratchet $^{1}/_{4}$" **No. 415-2K**: L. 117 mm

2 extensions $^{1}/_{4}$" **No. 405**: L. 54; 150 mm

1 universal joint $^{1}/_{4}$" **No. 407**: L. 37 mm

1 drive handle $^{1}/_{4}$" **No. 400N**: L. 150 mm

1 T-handle $^{1}/_{4}$" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011124	$^{1}/_{4}$	230	130	60	19	850

40/13/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 19-pieces:

13 sockets with hex 1/4" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 37 mm

1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm

1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011180	1/4	230	130	60	19	876

40/20/4QR SCI



QuickRelease socket set

— in soft case with hard foam inlay

Contains 24-pieces:

10 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm

2 bits PHILLIPS® 1/4" **No. PH 1221, PH 1222**: PH1; PH2

3 bits hex 1/4" **No. 1301-1303**: 4; 5; 6 mm

5 bits TORX® 1/4" **No. 1414-1417, 1419**: T10; T15; T20; T25; T30

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm

1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96010127	1/4	235	100	50	24	605

40/23/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 29-pieces:

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm

5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4

1 ratchet 1/4" **No. 415-2K**: L. 117 mm

2 extensions 1/4" **No. 405**: L. 54; 150 mm

1 universal joint 1/4" **No. 407**: L. 37 mm

1 drive handle 1/4" **No. 400N**: L. 150 mm

1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011136	1/4	230	130	60	29	998

40/23/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 29-pieces:

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm

5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 37 mm

1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm

1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011137	1/4	230	130	60	29	998

40/23/7



Socket set
— in a sturdy, stackable ABS plastic box
Contains 30-pieces:
12 sockets with hex 1/4" **No. 40**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2; PH3
4 bits slotted 1/4" **No. 1162, 1164, 1166, 1168**: 0.6 x 3.5; 0.8 x 4; 1.0 x 5.5; 1.6 x 8 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011134	1/4	325	135	60	30	1138

40/24/6QR



QuickRelease socket set
— in a sturdy, stackable ABS plastic box
Contains 30-pieces:
12 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2
2 screwdriver sockets POZIDRIV® 1/4" **No. 44PZ**: PZ1; PZ2
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 37 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011182	1/4	230	130	60	30	1018

40/24/6



Socket set
— in a sturdy, stackable ABS plastic box
Contains 30-pieces:
12 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2
2 screwdriver sockets POZIDRIV® 1/4" **No. 44PZ**: PZ1; PZ2
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011138	1/4	230	130	60	30	998

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

40ma/25/8



Socket set

— in a sturdy, stackable ABS plastic box

Contains 33-pieces:

25 sockets with hex 1/4"

No. 40: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm;

No. 40a: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

1 ratchet 1/4" **No. 415-2K**: L. 117 mm

2 extensions 1/4" **No. 405**: L. 54; 150 mm

1 flexible extension 1/4" **No. 406**: L. 152 mm

1 universal joint 1/4" **No. 407**: L. 37 mm

1 drive handle 1/4" **No. 400N**: L. 150 mm

1 flexible handle 1/4" **No. 403**: L. 154.5 mm

1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011162	1/4	325	135	60	33	1316

40ma/25/8QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 33-pieces:

25 sockets with hex 1/4"

No. 40: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm;

No. 40a: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm

1 flexible extension 1/4" **No. 406**: L. 152 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 37 mm


1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm

1 flexible handle 1/4" **No. 403**: L. 154.5 mm

1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96010107	1/4	325	135	55	33	1324

40aD/30/7QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 37-pieces:

11 sockets with bi-hex 1/4" **No. 40aD**: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

11 sockets long, with bi-hex 1/4" **No. 40aDL**: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

1 socket with hex 1/4" **No. 40a**: 1/8"

7 flex sockets with bi-hex 1/4" **No. 402a**: 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2"

1 QuickRelease fine-tooth ratchet 1/4" **No. 415SG-QR**: L. 117 mm


3 QuickRelease extensions 1/4" **No. 405**: L. 54 (2x); 150 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 37 mm


1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm

1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96015205	1/4	420	230	60	37	1920



TCS 40/35/9



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 44-pieces:
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
12 sockets long, with hex 1/4" **No. 40L**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
3 extensions 1/4" **No. 405**: L. 54; 100; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm


Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830601	1/4	350	175	40	1/3	44	1045

TCS 40/35/9QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 44-pieces:
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
12 sockets long, with hex 1/4" **No. 40L**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
3 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 100: 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830366	1/4	350	175	40	1/3	44	1045



40D/40TX/44KTX/32/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 38-pieces:

10 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm

6 sockets TORX® 1/4" **No. 40TX**: E4, E5; E6; E7; E8; E10

5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5, 6; 8 mm

9 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25; T27; T30; T40

2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm


1 QuickRelease T-handle with sliding head 1/4" **No. 404QR**: L. 116 mm

2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96010120	1/4	230	130	60	38	1070

TCS 40/41/44/8



Socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 33-pieces:

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm

5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4

2 bits POZIDRIV® 1/4" **No. PZ 1221; PZ 1222**: PZ1; PZ2

1 drive handle 1/4" **No. 400N**: L. 150 mm

1 T-handle 1/4" **No. 404**: L. 116 mm

2 extensions 1/4" **No. 405**: L. 54; 150 mm

1 universal joint 1/4" **No. 407**: L. 38 mm

1 square drive adaptor **No. 409**: 1/4 to 3/8"

1 bit holder 1/4" **No. 412**: L. 25 mm

1 ratchet 1/4" **No. 415-2K**: L. 117 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830217	1/4	350	175	45	1/3	33	803

TOOLS THAT
... inspire

86TX



Socket set

— in a sturdy, stackable ABS plastic box

Contains 63-pieces:

9 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
10 sockets with hex 1/2" **No. 52**: 13; 16; 17; 18; 19; 21; 22; 24; 27; 30 mm
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
7 sockets TORX® 1/2" **No. 50TX**: E10; E12; E14; E16; E18; E20; E24
3 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5 mm
5 screwdriver sockets INHEX 1/2" **No. 54**: 6; 8; 10; 12; 14 mm
6 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25
7 screwdriver sockets TORX® 1/2" **No. 54TX**: T27; T30; T40; T45; T50; T55; T60
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 drive handle **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 T-handle 1/2" **No. 506**: L. 300 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96013702	1/4, 1/2	483	289	83	63	6500



88TX



Socket set

— in a sturdy, stackable ABS plastic box

Contains 36-pieces:

10 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
6 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8; E10
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
9 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25; T27; T30; T40
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
98819801	1/4	325	135	60	36	1190

89TX



Socket set

— in a sturdy, stackable ABS plastic box

Contains 34-pieces:

3 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6
2 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9
4 sockets TORX® 3/8" **No. 45TX**: E7; E8; E10; E12
5 screwdriver sockets TORX® 3/8" **No. 49TX**: T10; T15; T20; T25; T27
6 sockets TORX® 1/2" **No. 50TX**: E11; E14; E16; E18; E20; E24
6 screwdriver sockets TORX® 1/2" **No. 54TX**: T30; T40; T45; T50; T55; T60
7 bits TORX®, with hole **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40
1 bit holder 1/4" **No. 442**: L. 32 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
98811908	1/4, 3/8, 1/2	417	230	60	34	2420

40/44/17/5



Socket set
— in a sturdy, stackable ABS plastic box
Contains 22-pieces:
13 sockets with hex 1/4" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 extension 1/4" **No. 405**: L. 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011113	1/4	230	130	60	22	896


40/44/17/5QR



QuickRelease socket set
— in a sturdy, stackable ABS plastic box
Contains 22-pieces:
13 sockets with hex 1/4" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 QuickRelease extension 1/4" **No. 405QR**: L. 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011181	1/4	230	130	60	22	914

40/45/36/12



Socket set
— in a sturdy, stackable ABS plastic box
Contains 48-pieces:
12 sockets with bi-hex 3/8" **No. 45**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
8 sockets with hex 1/4" **No. 40**: 4; 4.5; 5; 5.5; 6; 7; 8; 9 mm
1 socket long, with bi-hex and rubber insert 3/8" **No. 4600**: 16 mm-5/8"
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2; PH3
1 bit POZIDRIV® 1/4" **No. PZ 1222**: PZ2
6 bits slotted 1/4" **1160, 1162, 1164, 1166, 1166/1, 1168**: 0.5 x 3; 0.6 x 3.5; 0.8 x 4; 1 x 5.5; 1.2 x 6.5; 1.6 x 8 mm
5 bits hex 1/4" **1300-1304**: 3; 4; 5; 6; 8 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
1 extension 1/4" **No. 405**: L. 150 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 425**: L. 165 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit holder 1/4" **No. 442**: L. 32 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96012047	1/4, 3/8	420	230	60	48	2712

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

40/52/45/12QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 57-pieces:

9 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
3 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle **No. 404QR**: L. 116 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2; PH3
3 bits POZIDRIV® 1/4" **No. PZ 1221-1222**: PZ1; PZ2
3 bits slotted 1/4" **No. 1160, 1164, 1166:** 0.5 x 3; 0.8 x 4; 1.0 x 5.5 mm
3 bits hex 1/4" **No. 1300-1302**: 3; 4; 5 mm
7 bits TORX® 1/4" **No. 1414-1419**: T10; T15; T20; T25; T27; T30; T40
10 sockets with hex 1/2" **No. 52**: 13; 16; 17; 18; 19; 21; 22; 24; 27; 30 mm
5 screwdriver sockets INHEX 1/2" **No. 54**: 6; 8; 10; 12; 14 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 QuickRelease T-handle **No. 506QR**: L. 300 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
91222607	1/4, 1/2	290	480	85	57	5398

40/52/27/11



Socket set

— in a sturdy, stackable ABS plastic box


Contains 38-pieces:

9 sockets with hex 1/4" **No. 40** : 4; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
3 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
2 extensions 1/4" **No. 405:** L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
10 sockets with hex 1/2" **No. 52**: 13; 16; 17; 18; 19; 21; 22; 24; 27; 30 mm
5 screwdriver sockets INHEX 1/2" **No. 54**: 6; 8; 10; 12; 14 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 T-handle 1/2" **No. 506**: L. 300 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96011160	1/4, 1/2	458	254	65	38	4915



TCS 40/41/44/8QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 33-pieces:
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
2 bits POZIDRIV® 1/4" **No. PZ 1221, PZ 1222**: PZ1; PZ2
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830365	1/4	350	175	45	1/3	33	715





High Performance Quality (HPQ®)
Our HPQ® tool is made of wear-resistant high-performance steel, yet is thin-walled and lightweight. It withstands high torques and is ideal for work in confined spaces such as turbines.

TCS 40/52/6QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 38-pieces:
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 adaptor, hand-operated 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830264	1/4, 1/2	350	350	55	2/3	38	3890


TCS 54/54TX/44/44K/44KTX/40



Screwdriver socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 40-pieces:
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830274	1/4, 1/2	350	350	50	2/3	40	3340

TCS 40/456/52/78/19



Socket set


— safely integrated in the modular Tool Control System (TCS)

Contains 97-pieces:

11 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
2 sockets TORX® 1/4" **No. 40TX**: E8; E10
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
8 screwdriver sockets TORX®, with hole 1/4" **No. 44KTXB**: T8; T10; T15; T20; T25; T27; T30; T40
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
2 extensions 1/4" **No. 405**: L. 54; 100 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
4 sockets TORX® 3/8" **No. 45TX**: E8; E10; E12; E14
3 screwdriver sockets INHEX 3/8" **No. 49**: 5; 6; 8 mm
2 sockets TORX® 3/8" **No. 49TX**: T25; T45
1 T-handle 3/8" **No. 425**: L. 165 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
15 sockets with hex 3/8" **No. 456**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 34 mm
2 screwdriver sockets INHEX 1/2" **No. 54**: 10; 12 mm
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T40; T50; T55; T60
1 T-handle 1/2" **No. 506**: L. 300 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T50; T55
2 screwdriver sockets TORX® 1/2" **No. 2054TX**: T40; T45

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96832095	1/4, 3/8, 1/2	350	530	60	3/3	97	7000

TCS 40/45/50/89/19



Socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 108-pieces:

13 sockets with bi-hex 1/4" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 extension 1/4" **No. 405**: L. 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
12 sockets with bi-hex 3/8" **No. 45**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
1 socket with bi-hex 3/8" **No. 46**: 20.8 mm-13/16"
6 screwdriver sockets INHEX 3/8" **No. 49**: 4; 5; 6; 7; 8; 10 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
7 sockets with bi-hex 1/2" **No. 50**: 19; 21; 22; 24; 27; 30; 32 mm
5 sockets TORX® 1/2" **No. 50TX**: E11; E16; E18; E20; E24
9 sockets with hex 1/2" **No. 52**: 16; 17; 18; 19; 22; 24; 27; 30; 32 mm
4 screwdriver sockets INHEX 1/2" **No. 54**: 6; 7; 8; 10 mm
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T45; T50; T55; T60
4 screwdriver sockets XZN® 1/2" **No. 54X**: M6; M8; M12; M14
1 T-handle 1/2" **No. 506**: L. 300 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 514M**: 1/2 to 3/4"
5 bits TORX® **No. 1410-1427**: T6; T7; T8; T9; T25
7 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40


Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830192	1/4, 3/8, 1/2, 3/4	350	530	70	3/3	108	7770

3/8" SOCKETRY.

45



Sockets
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / ASME B 107.5M / DIN EN 3709



Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02010007	7	24	10.5	16.5	6	6	12.5	19
02010008	8	25	11.7	16.5	7	7	13.5	19
02010009	9	25	13	16.5	8	7	13.5	19
02010010	10	27	14.3	16.5	9	8.5	15.5	20
02010011	11	27	15.6	16.5	10	8.5	13.7	21
02010012	12	28	16.9	17.5	11	9.5	14.4	24
02010013	13	30	18	17.5	12	11.5	16.1	30
02010014	14	30	19.4	17.5	13	11.5	15.8	28
02010015	15	31	20.6	19	14	12.5	19.2	40
02010016	16	31	21.7	19	15	13.5	18.9	33
02010017	17	31	23	19	16	12.5	18.6	44
02010018	18	32	24.2	19	17	13.5	19.3	39
02010019	19	32	25.2	19	18	13.5	19	39
02010020	20	34	26.2	20	19	15.5	20.7	51
02010021	21	34	27.7	21	20	15.5	20.5	53
02010022	22	35	28.7	21	21	17	21.2	61
02010024	24	35	31.5	24	21	18	21.2	92






Anti-Slip-Drive
The special AS-Drive profile makes high force transmission to the flats of screws and bolts possible without damaging them. This also prevents stripping of the screw head.

45a



Sockets
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E (test values)




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02410016	1/4	24	9.7	16.5	5.2	6	12.5	18
02410020	5/16	25	11.7	16.5	7	7	13.5	19
02410022	11/32	25	12.5	16.5	8.1	7	13.5	19
02410024	3/8	27	13.7	16.5	8.4	8.5	15.5	20
02410028	7/16	28	15.7	16.5	10	9.5	15.1	20
02410032	1/2	30	18	17.5	11.5	11.5	16.5	24
02410034	9/16	31	20.2	19	13.1	12.7	16.8	28
02410035	19/32	31	20.6	19	14	13	19.2	36
02410036	5/8	31	21.7	19	15	13.5	18.9	31
02410038	11/16	32	23.4	19	16.3	14.7	19.5	34
02410040	3/4	32	25.2	19	18	15.9	19	41
02410042	13/16	34	27.2	20.5	19.4	16.5	20.5	52
02410044	7/8	35	28.7	22	21	18	21	59
02410046	15/16	35	31.5	24	22.6	18.5	20.7	95
02410048	1	35	33	25.5	24.2	18.5	20.2	97

45aP



Socket
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, gunmetal finish
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E (test values)




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02430020	5/16	25	11.9	16.5	8.1	7	13.5	19

45aSP



Sockets
- for external Spline-Drive screws
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02011012	12	3/8	26.5	13.7	16.5	8.6	9	15	24
02011014	14	7/16	28	16	17.3	10.4	11	14.5	37
02011016	16	1/2	28	18	18.3	12.2	11.5	14	28

45aPSP



Socket
- for external Spline-Drive screws
- 3/8" internal square drive
- HPQ® high performance steel, gunmetal finish
- MS-33787 / MIL-W-8982




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
22410028	14	7/16	28	18.8	18.8	10.4	11	14.5	36

45TX



Sockets
- for external TORX® screws
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	Size	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02270005	E5	28	7	16.5	2.8	5	16.5	23
02270006	E6	28	8	16.5	3.6	5.5	16.5	23
02270007	E7	28	9	16.5	3.8	6.5	16.5	24
02270008	E8	28	10.5	16.5	4.3	7	16.5	22
02270010	E10	28	13	16.5	5.6	8	16.5	27
02270012	E12	28	14.9	16.5	7.2	9.5	16.5	30
02270014	E14	28	16.5	17.3	8	10	16.5	34



46



Sockets
- long version
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- size 20.8: with rubber insert for spark plugs
- DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02020008	8		54	11.7	16.5	7	9	42.5	36
02020010	10		54	14.3	16.5	9	20	42.5	41
02020011	11		54	15.6	16.5	10	20	40.7	51
02020012	12		54	16.9	17.5	11	20	40.4	57
02020013	13		54	18	17.5	12	20	40.1	61
02020014	14		60	19.4	17.5	13	25	45.8	75
02020015	15		60	20.6	19	14	25	48.2	85
02020016	16		60	21.7	19.5	15	25	47.9	81
02020017	17		65	23	21	16	30	52.6	97
02020018	18		65	24.2	22	17	30	52.3	121
02020019	19		65	25.2	23	18	30	52	112
02020208	20.8	13/16	65	27.2	25	-	18	-	151
02020021	21		65	27.7	25.5	20	30	51.5	137
02020022	22		65	28.7	26.5	21	30	51.2	178

46a



Sockets
- long version
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02420016	1/4	54	9.7	16.5	5.2	9	42.5	33
02420020	5/16	54	11.7	16.5	7	9	42.5	35
02420022	11/32	54	12.5	16.5	8.1	9	42.5	56
02420024	3/8	54	13.7	16.5	8.4	20	42.5	45
02420028	7/16	54	15.7	16.5	10	20	40.7	53
02420032	1/2	54	18	17.5	11.5	20	40.2	64
02420034	9/16	60	20.2	19	13.1	25	45.8	80
02420035	19/32	60	20.6	19	14	25	48.2	84
02420036	5/8	60	21.7	19.5	15	25	47.9	81
02420038	11/16	65	23.4	21.5	16.3	30	52.5	114
02420040	3/4	65	25.2	23	18	30	52	137
02420042	13/16	65	27.2	25	19.4	30	51.6	130
02420044	7/8	65	28.7	26.5	21	30	51.2	184
02420046	15/16	65	31.5	29	22.6	30	50.7	195
02420048	1	65	33	31	24.2	30	50.2	205

46aSP



Sockets
- long version, deep drilled
- for external Spline-Drive screws
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- MS-33787 / MIL-W-8982



Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t2 mm	g
02021012	12	3/8	54	13.7	16.5	8.6	42.5	52
02021014	14	7/16	54	16	17.3	10.4	42.5	63


MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

456



Sockets
- hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / ASME B 107.5M / DIN EN 3709




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02110007	7	24	10.5	16.5	6	6	12.5	19
02110008	8	25	11.7	16.5	7	7	13.5	19
02110009	9	25	13	16.5	8	7	13.5	20
02110010	10	27	14.3	16.5	9	8.5	15.5	20
02110011	11	27	15.6	16.5	10	8.5	13.7	21
02110012	12	28	16.9	17.5	11	9.5	14.4	24
02110013	13	30	18	17.5	12	11.5	16.1	25
02110014	14	30	19.4	17.5	13	11.5	15.8	29
02110015	15	31	20.6	19	14	12.5	19.2	30
02110016	16	31	21.7	19	15	13.5	18.9	34
02110017	17	31	23	19	16	12.5	18.6	45
02110018	18	32	24.2	19	17	13.5	19.3	42
02110019	19	32	25.2	19.6	18	13.5	19	43
02110020	20	34	26.2	20.5	19	15.5	20.7	53
02110021	21	34	27.7	21.8	20	15.5	20.5	59
02110022	22	35	28.7	21	21	17	21.2	59

460a



Sockets
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- SAE AS 954-E / S.B.A.C. AS 40610/40611 / ASME B 107.1



Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02620016	1/4	32	9.9	16.5	5.2	7	20.5	21
02620020	5/16	32	11.5	16.5	7	8.5	20.5	22
02620024	3/8	38	13.7	16.5	8.5	9	26.5	29
02620028	7/16	38	15.7	16.5	10	11	24.5	33
02620032	1/2	44	17.5	17.8	11.5	12	30	44

3046




Oil filter wrenches
- hex
- 3/8" internal square drive
- for removing and mounting the oil filter housing cover when changing the oil filter insert

Product no.	"	mm	L mm	g
02111032	3/8	32	43	130
02111036	3/8	36	50	160

3466



Spark plug socket
- long version, with magnet
- hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	mm	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
02140036	16	5/8	85	21.8	25.5	15	7	72.9	180

TOOLS THAT
... inspire

4600



Spark plug socket
- long version, with rubber insert
- bi-hex with AS-Drive profile
- $^3/_8$" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	mm	"	L mm	d_1 mm	d_2 mm	t_1 mm	t_2 mm	g
02120036	16	$^5/_8$	60	21.7	19.5	15	47.8	84

4606



Spark plug socket
- long version, with rubber insert
- hex with AS-Drive profile
- $^3/_8$" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	mm	"	L mm	d_1 mm	d_2 mm	t_1 mm	t_2 mm	g
02130018	18	$^{11}/_{16}$	65	24.2	22	18	52.8	132



47



Uniflex sockets
- bi-hex with AS-Drive profile
- $^3/_8$" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	mm	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
02040010	10	45.5	14.3	17.5	9	7	12	51
02040011	11	47.5	15.6	17.5	10	11	14	55
02040012	12	48	16.9	17.5	11	11	14.5	54
02040013	13	48	18.3	17.5	12	12	14.5	53
02040014	14	48.5	19.4	17.5	13	13	14.5	55
02040015	15	48.5	20.6	17.5	14	13	14.5	56
02040016	16	51.5	21.8	17.5	15	14	17	58
02040017	17	53.5	23	17.5	16	15	18.5	65
02040018	18	54.5	24.2	17.5	17	16	18.5	61
02040019	19	57	25.5	17.5	18	16	21	68

47a



Uniflex sockets
- bi-hex with AS-Drive profile
- $^3/_8$" internal square drive
- HPQ® high performance steel, chrome-plated
- SAE AS 954-E




Product no.	"	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
02440020	$^5/_{16}$	45.5	11.7	17.5	7	7	12.5	50
02440024	$^3/_8$	45.5	13.7	17.5	8.5	7	12	50
02440028	$^7/_{16}$	47.5	15.8	17.5	10	11	14	50
02440032	$^1/_2$	47.5	18.3	17.5	11.5	11.5	14	57
02440034	$^9/_{16}$	48.5	19.7	17.5	13.1	13	14.5	55
02440036	$^5/_8$	51.5	21.6	17.5	15	14	17	59
02440038	$^{11}/_{16}$	53.5	23.5	17.5	16.3	16	18.5	58
02440040	$^3/_4$	57	25.5	17.5	18	16	21	67

47TX



Uniflex sockets
— for external TORX® screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L mm	d_1 mm	d_2 mm	g
02070008	E8	43	11.5	19	56
02070010	E10	44	13.8	19	61
02070012	E12	46	16	19	66
02070014	E14	48	17.8	19	75

49



INHEX screwdriver sockets
— for hex socket head screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422




Product no.	mm	L_1 mm	L_2 mm	∅ (d) mm	g
02050003	3	52	20	17.8	38
02050004	4	52	20	17.8	40
02050005	5	52	20	17.8	44
02050006	6	52	20	17.8	46
02050007	7	52	20	17.8	51
02050008	8	52	20	17.8	55
02050010	10	52	20	17.8	62

49a



INHEX screwdriver sockets
— for hex socket head screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422



Product no.	"	L_1 mm	L_2 mm	∅ (d) mm	g
02450008	1/8	52	20	17.8	39
02450009	9/64	52	20	17.8	40
02450010	5/32	52	20	17.8	40
02450012	3/16	52	20	17.8	44
02450014	7/32	52	20	17.8	46
02450016	1/4	52	20	17.8	48
02450020	5/16	52	20	17.8	55
02450024	3/8	52	20	17.8	61

1049/3049



INHEX screwdriver sockets
— special lengths
— for hex socket head screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422

Product no.	mm	L_1 mm	L_2 mm	∅ (d) mm	g
02151007	7	100	68	17.8	66
02151009	9	57	25	17.8	62
02152408	8	24	6.5	19	28



2049




INHEX screwdriver sockets
— extra long design
— for hex socket head screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422

Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
02151004	4	100	68	17.8	45
02151005	5	100	68	17.8	50
02151006	6	100	68	17.8	50
02151208	8	120	88	17.8	85
02151210	10	120	88	17.8	106

49X



Screwdriver sockets
— for tri-square socket head screws XZN®
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 2324



Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
02060005	M5	52	20	17.8	45
02060006	M6	52	20	17.8	47
02060008	M8	52	20	17.8	56
02060010	M10	52	20	17.8	63

3049X




Screwdriver sockets
— extra long design
— for tri-square socket head screws XZN®
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 2324

Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
02261206	M6	120	88	17.8	72
02261208	M8	120	88	17.8	80
02261210	M10	120	88	17.8	106


49TX



Screwdriver sockets
— for recessed TORX® screws
— 3/8" internal square drive
— Chrome Alloy Steel, chrome-plated



Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
02100009	T9	49	17	17.8	45
02100010	T10	49	17	17.8	45
02100015	T15	49	17	17.8	45
02100020	T20	49	17	17.8	46
02100025	T25	49	17	17.8	46
02100027	T27	49	17	17.8	46
02100030	T30	49	17	17.8	47
02100040	T40	49	17	17.8	48
02100045	T45	49	17	17.8	49



3/8" drive tools
Explanation of table headings

L = Overall length
a = Head height (excluding square drive)
b = Head width

422



Fine-tooth ratchet
— 3/8" external square drive
— reversible
— 60 teeth
— for working in tight spaces, with a working angle of just 6°
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	"	L mm	a mm	b mm	°	g
12231011	3/8	194	24	32	6 °	236

435-2K



Ratchet
— 3/8" external square drive
— reversible
— 30 teeth
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
12111010	3/8	193	18	29	12 °	235

435QR N



QuickRelease fine-tooth ratchet
— 3/8" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
12111020	3/8	193	15	30	4.5 °	235

435SG-QR N



QuickRelease fine-tooth ratchet
— 3/8" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with steel handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
12111030	3/8	193	15	30	4.5 °	272

445



Ratchet adaptor
— 3/8" external square drive
— reversible
— 20 teeth
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	b mm	∠°	g
12140000	3/8	43	30	18 °	135

452QR



QuickRelease fine-tooth flexible ratchet
— 3/8" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— handle can be swivelled up and down by approximately 90°, locking in the following positions: straight, 30° up, 60° up, 30° down
— lock releases at the push of a button
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
12261010	3/8	300	14.5	28.2	4.5 °	350

4350

Ratchet spare parts set
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19020000	435	3/8	8	50

4350QR

Ratchet spare parts set
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19020020	435QR, 725QR/5	3/8	8	51

4350QR N

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 pin; 1 ball; 1 compression spring; 2 circlips; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19021020	435QR N, 435SG-QR N, 452QR	3/8	9	48

424



Flexible handle
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
12061010	3/8	253.5	222

425



T-handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
12070000	3/8	165	130

425QR



QuickRelease T-handle
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
12071000	3/8	165	148

425/1QR



QuickRelease T-handle
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
12071500	3/8	165	145

421



Speeder brace
— working radius: 85 mm
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315


Product no.	■ "	L mm	g
12100010	3/8	386.5	385

453QR



QuickRelease speeder brace
— with QuickRelease safety lock
— with steel handle
— with ball locking function
— separate palm piece can be attached for greater axial force transmission
— working radius: 85 mm
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
12100005	3/8	408	650



3/8" extensions
Explanation of table headings

L = Overall length
d = Diameter of head

426QR



QuickRelease extensions
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
12011503	3	3/8	75	17	70
12011506	6	3/8	160	17	127
12011510	10	3/8	240	17	190
12011514	14	3/8	355	17	270

427



Extensions
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
12010005	1.5	3/8	38	17	36
12010001	3	3/8	76	17	69
12010006	5	3/8	125	17	104
12010002	6	3/8	160	17	127
12010003	10	3/8	240	17	188
12010004	18	3/8	455	17	345

427QR



QuickRelease extensions
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
12011001	3	3/8	76	17	66
12011002	6	3/8	160	17	127
12011003	10	3/8	240	17	185

427W



Wobble-Drive extensions
— swivel angle up to 15° to each side
— max. torque: 80 N·m
— Chrome Alloy Steel, chrome-plated

Product no.	Size	■ "	L mm	∅ (d) mm	g
12010007	3	3/8	76	17	67
12010008	5	3/8	125	17	104
12010009	6	3/8	160	17	127

434



Flexible extension
— only for clockwise tightening
— max. torque: 7 N·m
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
12040000	3/8	194	14	109

1225



Special extension
— cranked
— Chrome Alloy Steel, chrome-plated


Product no.	■ "	L mm	∅ (d) mm	g
12250001	3/8	150	17	128

13220



Special extension
— to remove boroscope stoppers
— with locking of the borescope plugs
— with 16 mm external hex
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
12270020	3/8	355	330



3/8" universal joints

Explanation of table headings

L = Overall length
d = Diameter of head

428



Universal joint
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
12020000	3/8	46	18.8	55

428QR



QuickRelease universal joint
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
12021000	3/8	60	19	66

428/1QR



QuickRelease universal joint
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— patented
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
12021500	3/8	60	70

431



Square drive adaptor
— 3/8 to 1/4"
— max. torque: 62 N·m
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
12030001	1/4	28	17.2	26

432



Square drive adaptor
— 3/8 to 1/2"
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
12030003	1/2	31	17.2	36

432M



Square drive adaptor
— 3/8 to 1/2"
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
12030010	1/2	16	22

433/1



Locking adaptor

— with hex L-Key 1/8" No. 10760a

Product no.	■ "	L mm	∅ (d) mm	g
96122701	3/8	52	18	57

45/10-12917



Socket set on clip rail

— bi-hex with AS-Drive profile
— HPQ® high performance steel, chrome-plated
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel
— DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5M

Contains 10-pieces:

10 sockets with bi-hex 3/8" **No. 45**: 8; 10; 13; 14; 15; 17; 19; 21; 22, 24 mm
+ socket clip rail **No. 12917/10**

Product no.	Content pcs.	g
96052010	10	512

12917/10



Socket clip rail

— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel

Product no.	■ "	L mm	Retaining clips	g
80450003	3/8	255	10	54

12916/12917/12918



Socket clip rail set

— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— attachments can be combined with each other
— can be mounted on a wall or perforated wall/panel

Contains 3-pieces:

1 socket clip rail 1/4" (6.3 mm)
1 socket clip rail 3/8" (10 mm)
1 socket clip rail 1/2" (12.5 mm)

Product no.	L mm	Retaining clips	Content pcs.	g
96003010	315	30	3	190

45/11/4



Socket set

— in a sturdy, stackable ABS plastic box

Contains 15-pieces:

11 sockets with bi-hex 3/8" **No. 45**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96021109	3/8	325	135	60	15	1444

TOOLS THAT
... inspire

45a/12/5



Socket set
— in a sturdy, stackable ABS plastic box
Contains 17-pieces:
11 sockets with bi-hex $^{3}/_{8}$" **No. 45a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{13}/_{16}$"
1 socket long, with bi-hex and rubber insert $^{3}/_{8}$" **No. 4600**: 16 mm-$^{5}/_{8}$"
1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm
2 extensions $^{3}/_{8}$" **No. 427**: L. 76; 240 mm
1 T-handle $^{3}/_{8}$" **No. 425**: L. 165 mm
1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96025204	$^{3}/_{8}$	325	135	60	17	1652

45/14/5I



Socket set
— in a sturdy, stackable ABS plastic box
Contains 19-pieces:
14 sockets with bi-hex $^{3}/_{8}$" **No. 45**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm
2 extensions $^{3}/_{8}$" **No. 427**: L. 76; 240 mm
1 T-handle $^{3}/_{8}$" **No. 425**: L. 165 mm
1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96024132	$^{3}/_{8}$	325	135	60	19	1678

45/14/5I QR



QuickRelease socket set
— in a sturdy, stackable ABS plastic box
Contains 19-pieces:
14 sockets with bi-hex $^{3}/_{8}$" **No. 45**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
1 QuickRelease fine-tooth ratchet $^{3}/_{8}$" **No. 435QR N**: L. 193 mm
2 QuickRelease extensions $^{3}/_{8}$" **No. 427QR**: L. 76; 240 mm
1 QuickRelease T-handle $^{3}/_{8}$" **No. 425QR**: L. 165 mm
1 QuickRelease universal joint $^{3}/_{8}$" **No. 428QR**: L. 60 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96021180	$^{3}/_{8}$	325	135	60	19	1738

45a/22/8QR



QuickRelease socket set
— in a sturdy, stackable ABS plastic box
Contains 30-pieces:
14 sockets with bi-hex $^{3}/_{8}$" **No. 45a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1"
8 flex sockets with bi-hex $^{3}/_{8}$" **No. 47a**: $^{5}/_{16}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$"
1 QuickRelease fine-tooth ratchet $^{3}/_{8}$" **No. 435SG-QR N**: L. 193 mm
3 QuickRelease extensions $^{3}/_{8}$" **No. 427**: L. 76; 160; 240 mm
1 QuickRelease universal joint $^{3}/_{8}$" **No. 428QR**: L. 60 mm
2 bit holders $^{3}/_{8}$" **No. 442; 443** L. 32 mm
1 speeder brace $^{3}/_{8}$" **No. 453**: L. 408 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96025207	$^{3}/_{8}$	458	257	65	30	3685

45ma/28/5



Socket set

— in a sturdy, stackable ABS plastic box

Contains 33-pieces:

28 sockets with bi-hex $^{3}/_{8}$"

No. 45: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm

No. 45a: $^{1}/_{4}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{13}/_{16}$; $^{7}/_{8}$"

1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm

2 extensions $^{3}/_{8}$" **No. 427**: L. 76; 240 mm

1 T-handle $^{3}/_{8}$" **No. 425**: L. 165 mm

1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96021122	$^{3}/_{8}$	417	230	60	33	2660

45ma/28/5QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 33-pieces:

28 sockets with bi-hex $^{3}/_{8}$"

No. 45: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm

No. 45a: $^{1}/_{4}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{13}/_{16}$; $^{7}/_{8}$"

1 QuickRelease fine-tooth ratchet $^{3}/_{8}$" **No. 435QR N**: L. 193 mm


2 QuickRelease extensions $^{3}/_{8}$" **No. 427QR**: L. 76; 240 mm

1 QuickRelease T-handle $^{3}/_{8}$" **No. 425QR**: L. 165 mm

1 QuickRelease universal joint $^{3}/_{8}$" **No. 428QR**: L. 60 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96020107	$^{3}/_{8}$	415	230	60	33	2710

45/49/19/5



Socket set

— in a sturdy, stackable ABS plastic box

Contains 24-pieces:

11 sockets with bi-hex $^{3}/_{8}$" **No. 45**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm

1 socket long, with bi-hex and rubber insert $^{3}/_{8}$" **No. 4600**: 16 mm-$^{5}/_{8}$"

7 screwdriver sockets INHEX $^{3}/_{8}$" **No. 49**: 3; 4; 5; 6; 7; 8; 10 mm

1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm


2 extensions $^{3}/_{8}$" **No. 427**: L. 76; 240 mm

1 T-handle $^{3}/_{8}$" **No. 425**: L. 165 mm

1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96021223	$^{3}/_{8}$	417	230	60	24	2428

45/49/32/5TX



Socket set

— in a sturdy, stackable ABS plastic box

Contains 37-pieces:

11 sockets with bi-hex $^{3}/_{8}$" **No. 45**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm

7 sockets TORX® $^{3}/_{8}$" **No. 45TX**: E5; E6; E7; E8; E10; E12; E14

6 screwdriver sockets INHEX $^{3}/_{8}$" **No. 49**: 4; 5; 6; 7; 8; 10 mm

8 screwdriver sockets TORX® $^{3}/_{8}$" **No. 49TX**: T9; T10; T15; T20; T25; T27; T30; T40

1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm

2 extensions $^{3}/_{8}$" **No. 427**: L. 76; 240 mm

1 T-handle $^{3}/_{8}$" **No. 425**: L. 165 mm

1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96022119	$^{3}/_{8}$	417	230	60	37	2860

45TX/7



TORX® socket set
— for external TORX® screws
— precisely fitting foam inlay
— in cardboard packaging
Contains 7-pieces:
7 sockets TORX® 3/8" **No. 45TX**: E5; E6; E7; E8; E10; E12; E14

Product no.	■ "	Content pcs.	g
96022702	3/8	7	219

49TX/8



TORX® screwdriver socket set
— for recessed TORX® screws
— precisely fitting foam inlay
— in cardboard packaging
Contains 8-pieces:
8 screwdriver sockets TORX® 3/8" **No. 49TX**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	■ "	Content pcs.	g
96021001	3/8	8	456

High Performance Quality (HPQ®)
Our HPQ® tool is made of wear-resistant high-performance steel, yet is thin-walled and lightweight. It withstands high torques and is ideal for work in confined spaces such as turbines.

TCS 49/1049/2049/45TX/49TX



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 24-pieces:
6 screwdriver sockets INHEX 3/8" **No. 49**: 4; 5; 6; 7; 8; 10 mm
1 screwdriver socket INHEX 3/8" **No. 1049**: 7 mm
5 screwdriver sockets INHEX 3/8" **No. 2049**: 4; 5; 6; 8; 10 mm
6 screwdriver sockets TORX® 3/8" **No. 45TX**: E5; E6; E7; E8; E10; E12
6 screwdriver sockets TORX® 3/8" **No. 49TX**: T10; T15; T20; T25; T30; T40

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838772	3/8	350	175	40	1/3	24	1188

456/11/4



Socket set
— in a sturdy, stackable ABS plastic box
Contains 15-pieces:
11 sockets with hex 3/8" **No. 456**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96022133	3/8	325	135	60	15	1458

456/14/5I



Socket set
— in a sturdy, stackable ABS plastic box
Contains 19-pieces:
14 sockets with hex 3/8" **No. 456**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
1 universal joint 3/8" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96023132	3/8	325	135	60	19	1758

TCS 456/31/8






Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 39-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
4 sockets with bi-hex 3/8" **No. 46**: 10; 11; 12; 13 mm
7 uniflex sockets with bi-hex 3/8" **No. 47**: 10; 11; 12; 13; 14; 15; 16 mm
1 screwdriver socket INHEX 3/8" **No. 1049**: 9 mm
3 screwdriver sockets XZN® 3/8" **No. 49X**: M6; M8; M10
3 extensions 3/8" **No. 427**: L. 76; 125; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
1 QuickRelease fine-tooth flexible ratchet 3/8" **No. 452QR**: L. 300 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830602	3/8	350	350	32	2/3	39	2701

456/49/19/5



Socket set
— in a sturdy, stackable ABS plastic box
Contains 24-pieces:
11 sockets with hex 3/8" **No. 456**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
1 socket long, with bi-hex and rubber insert 3/8" **No. 4600**: 16 mm-5/8"
7 screwdriver sockets INHEX 3/8" **No. 49**: 3; 4; 5; 6; 7; 8; 10 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
1 universal joint 3/8" **No. 428**: L. 46 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96021236	3/8	417	230	60	24	2456

TCS 456/16/6





Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 22-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
3 extensions 3/8" **No. 427**: L. 76; 160; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838752	3/8	350	175	40	1/3	22	1465

TCS 456/16/6QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 22-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
1 QuickRelease T-handle 3/8" **No. 425QR**: L. 165 mm
3 QuickRelease extensions 3/8" **No. 427QR**: L. 76; 160; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 46 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830367	3/8	350	175	40	1/3	22	1465

TCS 456/16/7QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 23-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
3 QuickRelease extensions 3/8" **No. 427QR**: L. 76; 160; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830370	3/8	350	175	40	1/3	23	1400

TCS 456/16/7



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 23-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
3 extensions 3/8" **No. 427**: L. 76; 125; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830218	3/8	350	175	40	1/3	23	1400

TCS 456/16/4 MF



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 20-pieces:
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
2 extensions 3/8" **No. 427**: L. 125; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 ratchet 3/8" **No. 435-2K**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830357	3/8	350	175	45	1/3	20	1123

TCS 456/16/4QR MF



QuickRelease socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 20-pieces:

16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm

2 QuickRelease extensions 3/8" **No. 427QR**: L. 160; 240 mm

1 QuickRelease universal joint 3/8" **No. 428QR**: L. 46 mm

1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830371	3/8	350	175	45	1/3	20	1123




1/2" SOCKETRY.

50



Sockets
- bi-hex with AS-Drive profile
- $^1/_2$" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5 M




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03010008	8	38	13	22	7	9	22	56
03010009	9	38	13.7	22	8	9	22	57
03010010	10	38	14.5	22	9	9	22	50
03010011	11	38	15.8	22	10	9.5	22	50
03010012	12	38	17	22	11	13	22	58
03010013	13	38	18.3	22	12	13	22	50
03010014	14	38	19.9	22.7	13	13	20.5	60
03010015	15	38	21.2	22.7	14	13.5	20.2	62
03010016	16	38	22.4	23.7	15	13.5	19.6	63
03010017	17	38	24	23.7	15.2	15	19.6	66
03010018	18	38	24.7	23.7	17	15.5	19.1	71
03010019	19	38	26.2	25	18	16	21.7	78
03010020	20	42	27.2	25	19	15	25.5	89
03010021	21	42	28.7	26	20	16	25.2	100
03010022	22	42	29.7	26	21	16.5	24.9	113
03010023	23	42	30.7	26	20	18	25.4	114
03010024	24	42	32	26	21	18.5	24.9	117
03010025	25	42	33.2	25	22	18.5	24.6	119
03010026	26	42	34.4	25	23	18.5	24.3	122
03010027	27	45	36.2	26	24	19.5	27	150
03010028	28	45	37.4	27	25	19.5	26.7	158
03010030	30	45	39.7	28	27	20.5	26.1	171
03010031	31	47	42.2	28	28	22	27.9	215
03010032	32	47	42.2	28	29	22	27.6	189
03010034	34	47	45	28	31	22	27	210
03010036	36	52	48	31	34	24	30.9	286

50a



Sockets
- bi-hex with AS-Drive profile
- $^1/_2$" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E (test values)




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03410024	$^3/_8$	38	14.3	22	8.3	9	22	51
03410028	$^7/_{16}$	38	16.3	22	9.9	9	22	52
03410032	$^1/_2$	38	18.3	22	11.5	13	22	53
03410034	$^9/_{16}$	38	20.3	22.7	13.1	13	20.2	58
03410035	$^{19}/_{32}$	38	21.3	22.7	13.5	13.5	20.1	61
03410036	$^5/_8$	38	22.4	23.7	15	13.5	19.6	65
03410038	$^{11}/_{16}$	38	24.2	23.7	16.5	15.5	19.2	68
03410040	$^3/_4$	38	26.2	25	18	16	21.7	78
03410041	$^{25}/_{32}$	41	27	25	18.6	16	24.6	90
03410042	$^{13}/_{16}$	41	28.2	25	19.4	16.5	24.3	95
03410044	$^7/_8$	42	29.7	26	21	18	24.9	111
03410046	$^{15}/_{16}$	42	32	26	22.6	18.5	24.4	121
03410048	1	42	33.7	27	24.2	18.5	24	135
03410050	1 $^1/_{16}$	45	36.2	26	25.8	19.5	26.5	155
03410052	1 $^1/_8$	45	38.1	28	27.4	20	26	167
03410054	1 $^3/_{16}$	45	39	28	28	20.5	25.9	178
03410056	1 $^1/_4$	45	40	28	30.5	21	25.1	196
03410058	1 $^5/_{16}$	47	41.8	28	32.1	22	26.7	170
03410060	1 $^3/_8$	50	46	28	33.7	23	29.2	232
03410062	1 $^7/_{16}$	54	49.4	31	34	26	33.1	320
03410064	1 $^1/_2$	54	51	31	35	26	32.8	325

52



Sockets

— hex with AS-Drive profile
— $^{1}/_{2}$" internal square drive
— HPQ® high performance steel, chrome-plated
— DIN 3124 / ISO 2725-1 / ASME B 107.5M / DIN EN 3709




Product no.	mm	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
03030008	8	38	13	22	7	9	22	56
03030009	9	38	13.7	22	8	9	22	56
03030010	10	38	14.5	22	9	9	22	51
03030011	11	38	15.8	22	10	9.5	22	58
03030012	12	38	17	22	11	13	22	52
03030013	13	38	18.3	22	12	13	22	51
03030014	14	38	19.9	22.7	13	13	20.5	59
03030015	15	38	21.2	22.7	14	13.5	20.2	60
03030016	16	38	22.4	23.7	15	13.5	19.6	65
03030017	17	38	24	23.7	15.2	15	19.6	70
03030018	18	38	24.7	23.7	17	15.5	19.1	73
03030019	19	38	26.2	25	18	16	21.7	80
03030020	20	42	27.2	25	19	15	25.5	95
03030021	21	42	28.7	26	20	16	25.2	110
03030022	22	42	29.7	26	21	16.5	24.9	115
03030023	23	42	30.7	26	20	18	25.4	119
03030024	24	42	32	26	21	18.5	24.9	125
03030025	25	42	33.2	26	22	18.5	24.6	128
03030026	26	42	34.4	25	23	18.5	24.3	132
03030027	27	45	36.2	26	24	19.5	27	161
03030028	28	45	37.4	27	25	19.5	26.7	166
03030030	30	45	39.7	28	27	20.5	26.1	186
03030032	32	47	42.2	28	29	22	27.6	200
03030034	34	47	45	28	31	22	27	235
03030036	36	52	48	31	34	24	30.9	305

51



Sockets

— long version
— bi-hex with AS-Drive profile
— $^{1}/_{2}$" internal square drive
— size 16 mm-$^{5}/_{8}$", 20.8 mm-$^{13}/_{16}$": with rubber insert for spark plugs
— HPQ® high performance steel, chrome-plated
— DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	"	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
03020010	10		83	14.5	22	9	19	67	90
03020013	13		83	18.3	22	12	35	67	122
03020014	14		83	19.9	22.7	13	35	65.2	129
03020015	15		83	21.2	22.7	14	35	64.9	125
03020016	16		83	22.4	23.7	15	35	64.6	145
03020216	16	$^{5}/_{8}$	83	22.4	23.7	15.4	19	64.5	137
03020017	17		83	24	23.7	16	35	64.3	145
03020018	18		83	24.7	23.7	17	35	64.1	170
03020019	19		83	26.2	25	18	35	66.7	165
03020208	20.8	$^{13}/_{16}$	83	27.7	26	20	22	66.2	194
03020021	21		83	28.7	26.5	20	35	66.2	231
03020022	22		83	29.7	27.5	21	35	65.5	200
03020024	24		83	32	30	21	35	66.1	251
03020026	26		83	34.4	32.5	23	35	65.3	334
03020027	27		83	36.2	34	27	20	60	280
03020030	30		83	39.7	37.5	30.2	35	65	341
03020032	32		83	42.4	40	29	35	63.9	435

TOOLS THAT
... inspire

51a



Sockets
- long version
- bi-hex with AS-Drive profile
- 1/2" internal square drive
- HPQ® high performance steel, chrome-plated
- ASME B 107.1 / Fed. Spec. GGG-W-641 / SAE AS 954-E




Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03420024	3/8	83	14.3	22	8.3	19	67	93
03420028	7/16	83	16.3	22	9.9	19	67	102
03420032	1/2	83	18.3	22	11.5	35	67	122
03420034	9/16	83	20.3	22.7	13.1	35	65.2	131
03420036	5/8	83	22.4	23.7	15	35	64.6	135
03420038	11/16	83	24.2	23.7	16.5	35	64.2	158
03420040	3/4	83	26.2	25	18	35	66.7	188
03420042	13/16	83	27.7	26	19.5	35	66.3	170
03420044	7/8	83	29.7	27.5	21	35	65.9	200
03420046	15/16	83	32	30	22.6	35	65.7	281
03420048	1	83	33.7	32	24.2	35	65	260
03420050	1 1/16	83	36.2	34	25.8	35	64.5	359
03420052	1 1/8	83	38.1	36	27.4	35	64	300
03420054	1 3/16	83	39	37	28	35	63.9	377
03420056	1 1/4	83	40	38	30.5	35	63.1	340
03420058	1 5/16	83	41.8	40	32.1	35	62.7	375
03420060	1 3/8	83	46	44	33.7	35	62.2	506
03420062	1 7/16	83	49.4	47	34	35	62.1	635
03420064	1 1/2	83	51	49	35	35	61.8	675

51S



Sockets
- long version
- hex with AS-Drive profile
- 1/2" internal square drive
- HPQ® high performance steel, chrome-plated
- size 20.8 mm - 13/16": with rubber insert for spark plugs
- DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709




Product no.	mm	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03240017	17		83	24	23.7	16	35	64.3	157
03240019	19		83	26.2	25	18	35	66.7	190
03240208	20.8	13/16	83	27.7	26	20	22	66.2	196
03240022	22		83	29.7	27.5	21	35	65.9	210

50aPSP



Sockets
- for external Spline-Drive screws
- 1/2" internal square drive
- HPQ® high performance steel, gunmetal finish
- MS-33787




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03012024	12	3/8	38	15.5	22	8.6	9.5	22	55
03012028	14	7/16	38	18	23.7	10.4	11	22	65
03012034	18	9/16	38	22	23.7	13.5	12	20	71

50aPLSP



Socket
- long version, deep drilled
- for external Spline-Drive screws
- 1/2" internal square drive
- HPQ® high performance steel, gunmetal finish
- MS-33787




Product no.	Size	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03013028	14	7/16	50	18	23.7	10.4	11	34	83

50TX



Sockets
- for external TORX® screws
- 1/2" internal square drive
- HPQ® high performance steel, chrome-plated




Product no.	Size	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
03270010	E10	38	13	22	5.6	9.5	22	55
03270011	E11	38	14	22	6	9.5	22	55
03270012	E12	38	14.9	22	7.2	9.5	22	60
03270014	E14	38	16.7	22	8	11	22	56
03270016	E16	38	19	22	9.3	12.5	22	60
03270018	E18	38	21	26.5	10.4	13.5	22	92
03270020	E20	38	23.5	26.5	12	15	22	98
03270024	E24	41.2	27.8	26	14.1	17.5	23.6	123

53



Uniflex sockets
- hex with AS-Drive profile
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated



Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t2 mm	g
03040010	10	70	14.7	25	9	20	136
03040013	13	70	18.4	25	12	20	140
03040016	16	69	22.4	25	15	17	141
03040017	17	70	23.5	25	16	18	141
03040018	18	70	25	25	17	18	145
03040019	19	70	26.3	25	18	17.5	148

1062



Socket
- bi-hex with AS-Drive profile
- 1/2" internal square drive
- for injection nozzles on diesel engines

Product no.	mm	L mm	g
03830027	27	83	255

3678




4-pin socket
- with 4 pins
- 1/2" internal square drive
- for removing, mounting or retightening the pressure nut on the injector

Product no.	L mm	g
03810001	72	151

54



INHEX screwdriver sockets
- for hex socket head screws
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated
- DIN 7422




Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
03050004	4	60	22	22.7	68
03050005	5	60	22	22.7	68
03050006	6	60	22	22.7	71
03050007	7	60	22	22.7	75
03050008	8	60	22	22.7	70
03050010	10	60	22	22.7	97
03050012	12	60	20	23.7	122
03050014	14	60	20	23.7	135
03050017	17	60	20	27.5	186
03050019	19	60	20	31	242

54a



INHEX screwdriver sockets
- for hex socket head screws
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated
- DIN 7422




Product no.	◉ "	L1 mm	L2 mm	∅ (d) mm	g
03450014	7/32	60	22	22.7	70
03450016	1/4	60	22	22.7	75
03450020	5/16	60	22	22.7	81
03450024	3/8	60	22	22.7	90
03450028	7/16	60	22	22.7	103
03450032	1/2	60	20	23.7	125
03450034	9/16	60	20	23.7	137
03450036	5/8	60	20	27.5	169
03450040	3/4	60	20	31	244

54IC



INHEX screwdriver sockets
- for hex socket head screws, with pin guide
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated




Product no.	◉ mm	L1 mm	L2 mm	∅ (d) mm	g
03070005	5	60	22	22.7	65
03070006	6	60	22	22.7	71
03070008	8	60	22	22.7	80
03070010	10	60	22	22.7	95
03070012	12	60	20	23.7	120
03070014	14	60	20	23.7	131

54KK



INHEX screwdriver sockets
- ball-ended
- for hex socket head screws
- 1/2" internal square drive
- swivel angle up to 25° to each side
- Chrome Alloy Steel, chrome-plated



Product no.	◉ mm	L1 mm	L2 mm	∅ (d) mm	g
03280005	5	100	62	22.7	75
03280006	6	100	62	22.7	80
03280007	7	100	62	22.7	85
03280008	8	100	62	22.7	95
03280010	10	100	62	22.7	120

1054/2054



INHEX screwdriver sockets
- extra long design
- for hex socket head screws
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated
- DIN 7422

Product no.	◉ mm	L1 mm	L2 mm	∅ (d) mm	g
03151205	5	120	82	22.7	80
03151206	6	120	82	22.7	84
03151207	7	120	82	22.7	96
03151208	8	120	82	22.7	104
03151410	10	140	102	22.7	150
03151412	12	140	100	23.7	200
03151414	14	140	100	23.7	231

1054/3054



INHEX screwdriver sockets
- extra long design
- special lengths
- for hex socket head screws
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated
- DIN 7422

Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
03151805	5	180	20	22	118
03150706	6	70	32	22.7	72
03151006	6	100	62	22.7	80
03152206	6	220	182	22.7	108
03151007	7	100	62	22.7	87
03150808	8	80	42	22.7	88
03151408	8	140	102	22.7	114
03150713	13	70	25	24	130

1054KK




INHEX screwdriver sockets
- special lengths
- ball-ended
- for hex socket head screws
- 1/2" internal square drive
- swivel angle up to 25° to each side
- Chrome Alloy Steel, chrome-plated

Product no.	mm	L1 mm	L2 mm	∅ (d) mm	g
03310005	5	238	200	22.7	145
03310008	8	238	200	22.7	154

54TX



Screwdriver sockets
- for recessed TORX® screws
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03100020	T20	55	17	22.7	71
03100025	T25	55	17	22.7	71
03100027	T27	55	17	22.7	72
03100030	T30	55	17	22.7	72
03100040	T40	55	17	22.7	75
03100045	T45	55	17	22.7	74
03100050	T50	55	17	22.7	87
03100055	T55	58	18	23.7	110
03100060	T60	58	18	23.7	113
03100070	T70	60	20	27.5	155

54TXB



Screwdriver sockets
- for recessed TORX® screws
- with hole in the drive tip (TORX® Tamper Resistant)
- 1/2" internal square drive
- Chrome Alloy Steel, chrome-plated




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03110020	T20	55	17	22.7	70
03110025	T25	55	17	22.7	65
03110027	T27	55	17	22.7	71
03110030	T30	55	17	22.7	71
03110040	T40	55	17	22.7	71
03110045	T45	55	17	22.7	72
03110050	T50	55	17	22.7	86
03110055	T55	58	18	23.7	111
03110060	T60	58	18	23.7	113

54CV



Screwdriver sockets
— for spline socket screws RIBE-CV®
— 1/2" internal square drive
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03090005	M5	60	22	22.7	69
03090006	M6	60	22	22.7	71
03090007	M7	60	22	22.7	70
03090008	M8	60	22	22.7	78
03090010	M10	60	22	22.7	95
03090012	M12	60	20	23.7	119
03090013	M13	60	20	23.7	125
03090014	M14	60	20	23.7	126
03090016	M16	63	23	27.5	163

54X



Screwdriver sockets
— for tri-square socket head screws XZN®
— 1/2" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 2324



Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03060005	M5	60	22	22.7	67
03060006	M6	60	22	22.7	74
03060008	M8	60	22	22.7	79
03060010	M10	60	22	22.7	94
03060012	M12	60	20	23.7	120
03060014	M14	60	20	23.7	128
03060016	M16	60	20	27.5	174

1054X/2054X




Screwdriver sockets
— special lengths
— for tri-square socket head screws XZN®
— 1/2" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 2324

Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03160808	M8	80	42	22.7	86
03161208	M8	120	82	22.7	104
03161110	M10	110	72	22.7	130
03161112	M12	110	70	23.7	168

3054X



Screwdriver sockets
— extra long design
— for tri-square socket head screws XZN®
— 1/2" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 2324




Product no.	Size	L1 mm	L2 mm	∅ (d) mm	g
03261408	M8	140	102	22.7	109
03261410	M10	140	102	22.7	142
03261412	M12	140	102	22.7	160
03261414	M14	140	100	23.7	225

1054TX/2054TX



Screwdriver sockets
— extra long design
— for recessed TORX® screws
— 1/2" internal square drive
— Chrome Alloy Steel, chrome-plated




Product no.	Size	L_1 mm	L_2 mm	∅ (d) mm	g
03131070	T70	107	67	23.7	201
03131230	T30	120	82	22.7	99
03131240	T40	120	82	22.7	100
03131245	T45	120	82	22.7	100
03131440	T40	140	102	22.7	110
03131445	T45	140	102	22.7	111
03131450	T50	140	102	22.7	140
03131455	T55	140	102	22.7	159
03131460	T60	140	100	23.7	221

3004



Screwdriver socket
— for tri-square socket head screws XZN®
— 1/2" internal square drive

Product no.	Size	L mm	g
03230012	M12	55	71



1/2" drive tools
Explanation of table headings

L = Overall length
a = Head height (excluding square drive)
b = Head width

512-2K



Ratchet
— 1/2" external square drive
— reversible
— 36 teeth
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
13111010	1/2	265.5	22.5	41	10 °	600

512QR N80



QuickRelease fine-tooth ratchet
— 1/2" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with 2-component handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
13111120	1/2	265.5	23	41	4.5 °	572

512SG-QR N




QuickRelease fine-tooth ratchet
— 1/2" external square drive
— reversible
— 80 teeth
— for working in tight spaces, with a working angle of just 4.5°
— with QuickRelease safety lock
— with steel handle
— FOD-preventive due to screwless design
— DBGM (German Federal Utility Model)
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
13111030	1/2	265.5	22.5	41	4.5 °	654

516



Telescopic ratchet
- — 1/2" external square drive
- — reversible
- — 36 teeth
- — increased torque when the handle is extended
- — can be locked in at any one of five lengths: 410, 465, 520, 575, 630 mm
- — convenient, easy and fast length adjustment via a rocker switch
- — compact size when unextended
- — ideal for mobile tool storage
- — durable thanks to maintenance-free slide bearing and a secure limit stop
- — with 2-component handle
- — a convenient alternative to the wheel brace
- — Chrome Alloy Steel, chrome-plated
- — DIN 3122 / ISO 3315



Product no.	■ "	L mm	a mm	b mm	∠°	g
13160000	1/2	410-630	22.5	40	10 °	1100

515-2K



Fine-tooth ratchet
- — 1/2" external square drive
- — reversible
- — 60 teeth
- — for working in tight spaces, with a working angle of just 6°
- — with 2-component handle
- — Chrome Alloy Steel, chrome-plated
- — DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
13231011	1/2	265	26.2	40	6 °	515

517QR



QuickRelease fine-tooth flexible ratchet
- — 1/2" external square drive
- — reversible
- — 80 teeth
- — for working in tight spaces, with a working angle of just 4.5°
- — with QuickRelease safety lock
- — handle can be swivelled up and down by approximately 90°, locking in the following positions: straight, 30° up, 60° up, 30° down
- — lock releases at the push of a button
- — with 2-component handle
- — FOD-preventive due to screwless design
- — DBGM (German Federal Utility Model)
- — Chrome Alloy Steel, chrome-plated
- — DIN 3122 / ISO 3315

Product no.	■ "	L mm	a mm	b mm	∠°	g
13261010	1/2	416	22	41	4.5 °	920

522



Ratchet adaptor
- — 1/2" external square drive
- — reversible
- — 20 teeth
- — Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	b mm	∠°	g
13140000	1/2	67.5	40	18 °	316

532-2K



Ratchets
- — 1/2" external square drive
- — reversible
- — 36 teeth
- — with longer lever length for better power transmission
- — simple loosening of jammed screws
- — with 2-component handle
- — Chrome Alloy Steel, chrome-plated
- — DIN 3120 / ISO 1174

Product no.	■ "	L mm	a mm	b mm	∠°	g
13121010	1/2	380	22.5	41	10 °	821
13121020	1/2	497	37.6	41	10 °	980
13121030	1/2	612	37.6	41	10 °	1140

5040

Ratchet spare parts set
— for version with chrome-plated PHILLIPS® screw
Contains 3-pieces:
1 drive piece; 1 screw; 1 spring washer

Product no.	for model	■ "	Content pcs.	g
96190800	504	1/2	3	75

5040N

Ratchet spare parts set
— for version with black, manganese-phosphate TORX® screw
Contains 3-pieces:
1 drive piece; 1 screw; 1 spring washer

Product no.	for model	■ "	Content pcs.	g
96190801	504	1/2	3	80

5120G

Ratchet spare parts set
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19040030	512G, 532G	1/2	8	120

5120QR

Ratchet spare parts set
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19040020	512QR, 512SG-QR, 725QR/20	1/2	8	118

5120QR N

Ratchet spare parts set
— for ratchet No. 512QR N version with screws
Contains 8-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19040040	512QR N	1/2	8	140

5120QR N80

Ratchet spare parts set
Contains 9-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 pin; 1 ball; 1 compression spring; 2 circlips; 1 cover plate

Product no.	for model	■ "	Content pcs.	g
19042020	512QR N80, 512SG-QR N, 517QR	1/2	9	120

504



Flexible handles
— with 2-component handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	Size	■ "	L mm	g
13061015	15	1/2	397	735
13061018	18	1/2	469	831
13061024	24	1/2	610	1051

506



T-handle
— Chrome Alloy Steel, chrome-plated
— DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
13070000	1/2	300	436

506QR



QuickRelease T-handle
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
13071000	1/2	300	470

506/1QR



QuickRelease T-handle
- with QuickRelease safety lock
- with **recessed** button
- with ball locking function
- Chrome Alloy Steel, chrome-plated
- DIN 3123 / ISO 3316

Product no.	■ "	L mm	g
13071500	1/2	300	460

501



Speeder brace
- working radius: 105 mm
- Chrome Alloy Steel, chrome-plated
- DIN 3122 / ISO 3315


Product no.	■ "	L mm	g
13100010	1/2	456	620

501QR



QuickRelease speeder brace
- with QuickRelease safety lock
- with ball locking function
- with steel handle
- separate palm piece can be attached for greater axial force transmission
- working radius: 105 mm
- Chrome Alloy Steel, chrome-plated
- patented
- DIN 3122 / ISO 3315

Product no.	■ "	L mm	g
13100005	1/2	456	872



1/2" extensions
Explanation of table headings

L = Overall length
d = Diameter of head

503QR



QuickRelease extensions
- with QuickRelease safety lock
- with **recessed** button
- with ball locking function
- Chrome Alloy Steel, chrome-plated
- DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
13011502	2	1/2	51	23	90
13011503	3	1/2	76	23	123
13011505	5	1/2	130	23	187
13011510	10	1/2	255	23	341

509



Extensions
- Chrome Alloy Steel, chrome-plated
- DIN 3123 / ISO 3316 6

Product no.	Size	■ "	L mm	∅ (d) mm	g
13010001	2	1/2	52	23	88
13010004	3	1/2	75	23.2	120
13010002	5	1/2	130	23.2	191
13010003	10	1/2	255	23.2	341

509QR



QuickRelease extensions
- with QuickRelease safety lock
- with ball locking function
- Chrome Alloy Steel, chrome-plated
- DIN 3123 / ISO 3316

Product no.	Size	■ "	L mm	∅ (d) mm	g
13011001	2	1/2	52	23	90
13011004	3	1/2	75	23	123
13011002	5	1/2	130	23	187
13011003	10	1/2	255	23	341

509W



Wobble-Drive extensions
— swivel angle up to 15° to each side
— max. torque: 200 N·m
— Chrome Alloy Steel, chrome-plated


Product no.	Size	■ "	L mm	∅ (d) mm	g
13010005	2	1/2	52	23	80
13010006	3	1/2	75	23.2	120
13010007	5	1/2	130	23.2	191
13010008	10	1/2	255	23.2	341

3505



Special extension
— cranked
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
13210001	1/2	120	23.2	186



1/2" universal joints
Explanation of table headings

L = Overall length
d = Diameter of head

510



Universal joint
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
13020000	1/2	71	25	146

510QR



QuickRelease universal joint
— with QuickRelease safety lock
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
13021000	1/2	80	25	155

510/1QR



QuickRelease universal joint
— with QuickRelease safety lock
— with **recessed** button
— with ball locking function
— Chrome Alloy Steel, chrome-plated
— patented
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
13021500	1/2	80	25	158


513



Square drive adaptor
— 1/2 to 3/8"
— max. torque: 202 N·m
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
13030002	3/8	35	22.7	60

514



Square drive adaptor
— 1/2 to 3/4"
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
13030005	3/4	44	25	110


514M



Square drive adaptor
— 1/2 to 3/4"
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
13030010	3/4	22	40

7789-1



Square drive adaptor
— 1/2 to 1"
— HPQ® high performance steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
58522089	1	35	36.5	175

50/10-12918



Socket set on clip rail
— bi-hex with AS-Drive profile
— HPQ® high performance steel, chrome-plated
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel
— DIN 3124 / ISO 2725-1 / DIN EN 3709 / ASME B 107.5M

Contains 10-pieces:
10 sockets with bi-hex 1/2" **No. 50**: 10; 13; 14; 17; 19; 22; 24; 27; 30; 32 mm
+ socket clip rail **No. 12918/10**

Product no.	Content pcs.	g
96053010	10	1120

12918/10



Socket clip rail
— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel

Product no.	■ "	L mm	Retaining clips	g
80500005	1/2	307	10	80

12916/12917/12918



Socket clip rail set
— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— attachments can be combined with each other
— can be mounted on a wall or perforated wall/panel

Contains 3-pieces:
1 socket clip rail 1/4" (6.3 mm)
1 socket clip rail 3/8" (10 mm)
1 socket clip rail 1/2" (12.5 mm)

Product no.	L mm	Retaining clips	Content pcs.	g
96003010	315	30	3	190

50/12/3



Socket set

— in a sturdy, stackable ABS plastic box

Contains 15-pieces:

12 sockets with bi-hex 1/2" **No. 50**: 10; 13; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

2 extensions 1/2" **No. 509**: L. 130; 255 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031435	1/2	415	227	67	15	3300

50/16/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 22-pieces:

16 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031447	1/2	458	254	65	22	4502

50/16/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 22-pieces:

16 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm

1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031446	1/2	458	254	65	22	4502

50a/17/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 23-pieces:

17 sockets with bi-hex 1/2" **No. 50a**: 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 3/16; 1 1/4"

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 52; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96035125	1/2	458	254	65	23	4640

50/22/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 28-pieces:

22 sockets with bi-hex 1/2" **No. 50**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 26; 27; 28; 30; 32 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031407	1/2	458	254	65	28	5076

50ma/39/6N



Socket set

— in a sturdy steel case

Contains 45-pieces:

22 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34 mm

17 sockets with bi-hex 1/2" **No. 50a**: 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 3/16; 1 1/4"

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96030140	1/2	540	292	53	45	9020

50ma/39/6QR



QuickRelease socket set

— in a sturdy steel case

Contains 45-pieces:

22 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34 mm

17 sockets with bi-hex 1/2" **No. 50a**: 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 3/16; 1 1/4"

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm

1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96030107	1/2	540	290	55	45	8890

50/43/7N



Socket set

— in a sturdy steel case

Contains 50-pieces:

23 sockets with bi-hex 1/2" **No. 50**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34 mm

7 sockets long, with bi-hex 1/2" **No. 51**: 13; 17; 18; 19; 22; 24; 27 mm

2 sockets long, with bi-hex and rubber insert 1/2" **No. 51**: 16 mm-5/8"; 20.8 mm-13/16"

6 uniflex sockets with hex 1/2" **No. 53**: 10; 13; 16; 17; 18; 19 mm

5 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 8; 10 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 flexible handle 1/2" **No. 504**: L. 397 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031136	1/2	540	290	53	50	11000

50/43/7QR



QuickRelease socket set
— in a sturdy steel case
Contains 50-pieces:
23 sockets with bi-hex 1/2" **No. 50**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34 mm
7 sockets long, with bi-hex 1/2" **No. 51**: 13; 17; 18; 19; 22; 24; 27 mm
2 sockets long, with bi-hex and rubber insert 1/2" **No. 51**: 16 mm-5/8"; 20.8 mm-3/16"
6 uniflex sockets with hex 1/2" **No. 53**: 10; 13; 16; 17; 18; 19 mm
5 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 8; 10 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm
1 flexible handle 1/2" **No. 504**: L. 397 mm
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031236	1/2	540	292	53	50	11115

50/54/25/6



Socket set
— in a sturdy, stackable ABS plastic box
Contains 31-pieces:
17 sockets with bi-hex 1/2" **No. 50**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
8 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm
1 T-handle 1/2" **No. 506**: L. 300 mm
1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031439	1/2	458	254	65	31	5270

50/54/25/6QR



QuickRelease socket set
— in a sturdy, stackable ABS plastic box
Contains 31-pieces:
17 sockets with bi-hex 1/2" **No. 50**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
8 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031440	1/2	458	254	65	31	5270

52/12/3



Socket set
— in a sturdy, stackable ABS plastic box
Contains 15-pieces:
12 sockets with hex 1/2" **No. 52**: 10; 13; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031436	1/2	415	227	67	15	3412

52/16/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 22-pieces:

16 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031448	1/2	458	254	65	22	4586

52/22/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 28-pieces:

22 sockets with hex 1/2" **No. 52**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 26; 27; 28; 30; 32 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031409	1/2	458	254	65	28	5138

52/16/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 22-pieces:

16 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm

1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031480	1/2	458	254	65	22	4606

52/54/25/6



Socket set

— in a sturdy, stackable ABS plastic box

Contains 31-pieces:

17 sockets with hex 1/2" **No. 52**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

8 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031239	1/2	458	254	65	31	5306

52/54/25/6QR



QuickRelease socket set

— in a sturdy, stackable ABS plastic box

Contains 31-pieces:

17 sockets with hex 1/2" **No. 52**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm

8 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14 mm

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm


3 QuickRelease extensions 1/2" **No. 509QR**: L. 75; 130; 255 mm

1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031240	1/2	458	254	65	31	5306

54/8/4



Socket set

— in a sturdy, stackable ABS plastic box

Contains 12-pieces:

8 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 8; 10; 12; 14; 17 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

2 extensions 1/2" **No. 509**: L. 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031501	1/2	417	230	60	12	3370

876



Socket set

— in a sturdy, stackable ABS plastic box

Contains 47-pieces:

19 sockets with hex 1/2" **No. 52**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 34 mm

13 combination spanners **No. 13**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm

2 sockets long, with bi-hex and rubber insert 1/2" **No. 51**: 16 mm-5/8"; 20.8 mm-13/16"

7 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96032301	1/2	483	289	83	47	7600

876TX



Socket set

— in a sturdy, stackable ABS plastic box

Contains 39-pieces:

12 sockets with hex 1/2" **No. 52**: 8; 10; 13; 16; 17; 18; 19; 21; 22; 24; 27; 30 mm

6 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 8; 10; 12; 14 mm

7 sockets TORX® 1/2" **No. 50TX**: E10; E12; E14; E16; E18; E20; E24

9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

2 extensions 1/2" **No. 509**: L. 130; 255 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
98811909	1/2	483	289	83	39	6255

50TX/8



TORX® socket set
— for external TORX® screws
— in a sturdy, stackable ABS plastic box
Contains 8-pieces:
8 sockets TORX® 1/2" **No. 50TX**: E10; E11; E12; E14; E16; E18; E20; E24

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96033704	1/2	230	130	60	8	980

50TX/7



TORX® socket set
— for external TORX® screws
— precisely fitting foam inlay
— in cardboard packaging
Contains 7-pieces:
7 sockets TORX® 1/2" **No. 50TX**: E10; E12; E14; E16; E18; E20; E24

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96032703	1/2	307	84	40	7	623

51/8



Socket set
— in soft case with hard foam inlay
Contains 8-pieces:
8 sockets long, with bi-hex 1/2" **No. 51**: 13; 17; 19; 22; 24; 27; 30; 32 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96030212	1/2	345	190	55	8	2378

54TX/9



TORX® screwdriver socket set
— for recessed TORX® screws
— precisely fitting foam inlay
— in cardboard packaging
Contains 9-pieces:
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031004	1/2	308	85	40	9	820

54TX/10



TORX® screwdriver socket set
— for recessed TORX® screws
— in a sturdy, stackable ABS plastic box
Contains 10-pieces:
10 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40 (2x); T45; T50; T55; T60

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96032005	1/2	230	130	60	10	1170

54/10



INHEX screwdriver socket set
— for hex socket head screws
— in a sturdy, stackable ABS plastic box
Contains 10-pieces:
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031508	1/2	230	130	60	10	1525

54/12



INHEX screwdriver socket set
— for hex socket head screws
— in a sturdy, stackable ABS plastic box
Contains 12-pieces:
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
1 screwdriver socket INHEX 1/2" **No. 3054**: 8 mm
1 screwdriver socket INHEX 1/2" **No. 1054**: 10 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96031503	1/2 "	327	135	60	12	1894

3054X/54X/8



Screwdriver socket set
— for tri-square socket head screws XZN®
— in a sturdy, stackable ABS plastic box
Contains 8-pieces:
3 screwdriver sockets XZN® 1/2" **No. 3054X**: M8; M10; M12
5 screwdriver sockets XZN® 1/2" **No. 54X**: M6; M8; M10; M12; M14

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96033606	1/2	230	130	60	8	1288

TCS 1054/2054



INHEX screwdriver socket set
— for hex socket head screws
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
3 screwdriver sockets INHEX 1/2" **No. 1054**: 8; 10; 12 mm
3 screwdriver sockets INHEX 1/2" **No. 2054**: 5; 6; 14 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838117	1/2	175	175	30	1/6	6	900


TCS 54KK/5



INHEX screwdriver socket set
— ball-ended
— for hex socket head screws
— swivel angle up to 25° to each side
— safely integrated in the modular Tool Control System (TCS)
Contains 5-pieces:
5 screwdriver sockets INHEX 1/2" **No. 54KK**: 5; 6; 7; 8; 10 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838116	1/2	175	175	30	1/6	5	505


TCS 54/54KK/14



INHEX screwdriver socket set
— for hex socket head screws
— safely integrated in the modular Tool Control System (TCS)
Contains 14-pieces:
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
4 screwdriver sockets INHEX 1/2" **No. 54KK**: 5; 6; 8; 10 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830877	1/2	350	175	30	1/3	14	1561

TCS 54/54X/16



Screwdriver socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 16-pieces:
9 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17 mm
7 screwdriver sockets XZN® 1/2" **No. 54X**: M5; M6; M8; M10; M12; M14; M16

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838762	1/2	350	175	35	1/3	16	1745


TCS 54/2309K/12506



INHEX wheel nut socket, nut spinner set
— safely integrated in the modular Tool Control System (TCS)
Contains 13-pieces:
9 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 IMPACT wheel nut sockets with hex 1/2" **No. 2309IMP K**: 17; 19 mm
2 nut spinners **No. 12506**: 6; 7 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830163	1/2	350	175	40	1/3	13	1830


TCS 50TX/54TX/17



TORX® socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
8 sockets TORX® 1/2" **No. 50TX**: E10; E11; E12; E14; E16; E18; E20; E24
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838763	1/2	350	175	40	1/3	17	1415


TCS 1054/2054/10



Screwdriver socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
3 screwdriver sockets INHEX 1/2" **No. 1054**: 8; 10; 12 mm
2 screwdriver sockets INHEX 1/2" **No. 2054**: 5; 6 mm
3 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50; T55
2 screwdriver sockets TORX® 1/2" **No. 2054TX**: T40; T45

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838760	1/2	350	175	40	1/3	10	1272


TCS 54/54TX/18



Screwdriver socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
9 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17 mm
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838782	1/2	350	175	40	1/3	18	1665


TCS 52/17



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838177	1/2	350	175	40	1/3	17	1605


TCS 51/11



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 11-pieces:
11 sockets long, with bi-hex 1/2" **No. 51**: 10; 13; 15; 17; 18; 19; 22; 24; 27; 30; 32 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838776	1/2	350	175	50	1/3	11	2345


TCS 50a/17



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
17 sockets with bi-hex 1/2" **No. 50a**: 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 3/16; 1 1/4"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838780	1/2	350	175	40	1/3	17	1685

TCS 50/51/52/32



Socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 32-pieces:

13 sockets with bi-hex 1/2" **No. 50**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 30 mm

2 sockets long, with bi-hex 1/2" **No. 51**: 22; 27 mm

17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838191	1/2	350	175	50	1/3	32	2950

TCS 52/14/4QR



QuickRelease socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 18-pieces:

14 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 22; 24; 27; 30 mm

2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830352	1/2	350	175	50	1/3	18	2510

TCS 50/52/30/6QR



QuickRelease socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 36-pieces:

11 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 30 mm

13 sockets with hex 1/2" **No. 52**: 12; 13; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 34 mm

6 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 7; 8; 10; 12 mm

1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm

2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm

1 QuickRelease universal joint 1/2" **No. 510QR**: L. 71 mm

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

1 square drive adaptor **No. 513**: 1/2 to 3/8"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830360	1/2	350	350	70	2/3	36	4604

TCS 50/52/30/6 MF



Socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 36-pieces:

11 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 30 mm

13 sockets with hex 1/2" **No. 52**: 12; 13; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 34 mm

6 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 7; 8; 10; 12 mm

1 T-handle 1/2" **No. 506**: L. 300 mm

2 extensions 1/2" **No. 509**: L. 130; 255 mm

1 universal joint 1/2" **No. 510**: L. 71 mm

1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

1 square drive adaptor **No. 513**: 1/2 to 3/8"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830354	1/2	350	350	70	2/3	36	4604

TCS 52/14/4



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
14 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 22; 24; 27; 30 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838781	1/2	350	175	50	1/3	18	2510

TCS 512/6



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
1 T-handle 1/2" **No. 506**: L. 300 mm
3 extensions 1/2" **No. 509**: L. 52; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96838175	1/2	350	175	35	1/3	6	1845


TCS 512/6QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
3 QuickRelease extensions 1/2" **No. 509QR**: L. 52; 130; 255 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830362	1/2	350	175	35	1/3	6	1845

TCS 512/9



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 9-pieces:
1 T-handle 1/2" **No. 506**: L. 300 mm
4 extensions 1/2" **No. 509**: L. 52; 130; 255 (2x) mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830603	1/2	350	175	40	1/3	9	2364

TCS 512/9QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 9-pieces:
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
4 QuickRelease extensions 1/2" **No. 509QR**: L. 52; 130; 255 (2x) mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830363	1/2	350	175	40	1/3	9	2364

TCS 40/52/6QR



QuickRelease socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 38-pieces:
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 adaptor, hand-operated 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830264	1/4, 1/2	350	350	55	2/3	38	3890

TCS 54/54TX/44/44K/44KTX/40



Screwdriver socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 40-pieces:
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830274	1/4, 1/2	350	350	50	2/3	40	3340


QuickRelease
The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change.

3/4" SOCKETRY.

55



Sockets
- hex with AS-Drive profile
- 3/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / ASME B 107.5 M




Product no.	mm	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
05010019	19	50	28.5	34.7	17	16	26	183
05010021	21	50	31	34.7	18	16	26	190
05010022	22	51	32	34.7	19	17	25.2	199
05010024	24	51	34	34.7	21	18.5	24.6	200
05010027	27	54	38.5	38	24	20	26.8	263
05010030	30	58	42	38	27	21	33.6	313
05010032	32	58	44.5	38	29	22	33	326
05010033	33	60	46	40	30	22	34.7	372
05010034	34	60	47	40	31	24	34.4	363
05010036	36	60	49.5	40	33	24	33.9	386
05010038	38	64	52	40	35	30	37.3	429
05010041 *	41	67	55.5	40	33	30	37.5	510
05010046 *	46	73	61	40	33	34	43.5	600
05010050 *	50	80	66	40	33	34	48.5	769
05010055 *	55	80	72	45	33	36	49.5	970
05010060 *	60	80	78	45	33	40	50.5	1025

* AS-Drive and HPQ® high performance steel up to 38 mm, chrome-plated

55a



Sockets
- bi-hex with AS-Drive profile
- 3/4" internal square drive
- HPQ® high performance steel, chrome-plated
- SAE AS 954-E (test values) / ASME B 107.1



Product no.	"	L mm	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	g
05410040	3/4	50	28.5	34.7	18.6	16	26	176
05410042	13/16	51	31	34.7	19.4	16.5	25.1	190
05410044	7/8	51	33	34.7	21	18	24.5	240
05410046	15/16	51	34	34.7	22.5	18.5	24.2	248
05410048	1	52	37	38	24	20	24.8	251
05410050	1 1/16	54	38.5	38	26	20	26.2	265
05410052	1 1/8	57	41	38	27.5	20	32.5	297
05410056	1 1/4	58	44.5	38	30.5	22	32.6	339
05410058	1 5/16	59	46.5	40	32.1	24	33.1	348
05410060	1 3/8	59	48.5	40	33.7	24	32.7	375
05410062	1 7/16	60	50	40	35.3	27	33.2	395
05410064	1 1/2	64	52	40.5	36.8	30	36.8	415
05410066 *	1 5/8	67	56	40	33	30	37.5	469
05410067 *	1 11/16	70	58	40	33	32	40.5	524
05410068 *	1 3/4	70	59.5	40	33	32	40.5	524
05410069 *	1 13/16	73	61.5	40	33	34	43.5	605
05410070 *	1 7/8	76	63.5	40	33	34	45	660
05410072 *	2	80	67	40	33	34	48.5	757


* AS-Drive and HPQ® high performance steel up to 1 1/2", chrome-plated



56



Sockets
- long version
- hex with AS-Drive profile
- 3/4" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / ASME B 107.5 M




Product no.	mm	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
05020022	22	90	32	34.7	19	40	64.2	374
05020024	24	90	34	34.7	21	40	63.6	341
05020027	27	90	38.5	38	24	40	62.8	443
05020030	30	90	42	38	27	40	65.6	477
05020032	32	90	44.5	38	29	40	65	526
05020034	34	90	47	40	31	40	64.4	562
05020036	36	90	49.5	40	33	40	63.9	570
05020041 *	41	90	55.5	40	38	40	58.5	714

* AS-Drive and HPQ® high performance steel up to 36 mm, chrome-plated

59



INHEX screwdriver sockets
- for hex socket head screws
- 3/4" internal square drive
- Chrome Alloy Steel, chrome-plated
- DIN 7422




Product no.	mm	L_1 mm	L_2 mm	∅ (d) mm	g
05050014	14	80	25	34.7	272
05050017	17	80	25	34.7	311
05050019	19	80	25	34.7	346
05050022	22	80	25	40	510

59X



Screwdriver sockets
- for tri-square socket head screws XZN®
- 3/4" internal square drive
- Chrome Alloy Steel, chrome-plated




Product no.	Size	L_1 mm	L_2 mm	∅ (d) mm	g
05060014	M14	90	35	34.7	281
05060016	M16	80	25	34.7	302
05060018	M18	100	45	34.7	375


59TX



Screwdriver sockets
- for recessed TORX® screws
- 3/4" internal square drive
- Chrome Alloy Steel, chrome-plated



Product no.	Size	L_1 mm	L_2 mm	∅ (d) mm	g
05100060	T60	80	25	34.7	260
05100070	T70	80	25	34.7	285
05100080	T80	80	25	34.7	300
05100090	T90	80	25	34.7	331
05100100	T100	80	25	40	474



3/4" drive tools

Explanation of table headings

L = Overall length
a = Head height (excluding square drive)
b = Head width

552



Ratchet head

— 3/4" external square drive
— reversible
— 36 teeth
— with QuickRelease safety lock
— to be used with handle No. 558
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	a mm	b mm	∠°	g
15110000	3/4	165	55	70	10 °	1670

563



Ratchet adaptor

— 3/4" external square drive
— reversible
— 44 teeth
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	b mm	∠°	g
15140000	3/4	105.5	63	8.2 °	1257

5520

Ratchet spare parts set

Contains 7-pieces:

1 pinion; 1 locking disc; 1 switching lever; 1 ball; 1 compression spring; 2 retaining screws


Product no.	for model	■ "	Content pcs.	g
19050000	552	3/4	7	536

559



Extensions

— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316



Product no.	Size	■ "	L mm	∅ (d) mm	g
15010003	4	3/4	95	35	369
15010001	8	3/4	200	35	705
15010002	16	3/4	400	35	1255

554



Flexible head

— with QuickRelease safety lock
— to be used with handle No. 558
— Chrome Alloy Steel, chrome-plated


Product no.	■ "	L mm	∅ (d) mm	g
15060000	3/4	132	40	795

561



Universal joint

— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316



Product no.	■ "	L mm	∅ (d) mm	g
15020000	3/4	109	40	566

556



Sliding head
— can be used as a T-handle in combination with handle No. 558
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
15070000	3/4	61.5	318

558

Handle
— can be used as a T-handle in combination with sliding head No. 556
— Chrome Alloy Steel, chrome-plated

Product no.	for model	L mm	∅ (d) mm	g
15170000	552; 554; 556	510	20	1259

568



Square drive adaptor
— 3/4 to 1/2"
— max. torque: 512 N·m
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
15030003	1/2	55	34.7	203

569



Square drive adaptor
— 3/4 to 1"
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
15030006	1	61	34.7	315

55/9/6N



Socket set
— in a sturdy steel case
Contains 15-pieces:
9 sockets with hex 3/4" **No. 55**: 32; 34; 36; 38; 41; 46; 50; 55; 60 mm
1 ratchet head 3/4" **No. 552**: L. 165 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 flexible head 3/4" **No. 554**: L. 132 mm
1 sliding head 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96050103	3/4	584	240	90	15	15731

55/10/6



Socket set
— in a sturdy steel case
Contains 16-pieces:
10 sockets with hex 3/4" **No. 55**: 22; 24; 27; 30; 32; 34; 36; 41; 46; 50 mm
1 ratchet head 3/4" **No. 552**: L. 165 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 flexible head 3/4" **No. 554**: L. 132 mm
1 sliding head 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96050104	3/4	580	245	90	16	13965

55a/10/5



Socket set
— in a sturdy steel case
Contains 15-pieces:
10 sockets with bi-hex 3/4" **No. 55a**: 1 1/16; 1 1/8; 1 1/4; 1 3/8; 1 7/16; 1 1/2; 1 5/8; 1 3/4; 1 13/16; 1 7/8"
1 ratchet head 3/4" **No. 552**: L. 165 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 sliding head 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96054101	3/4	540	190	90	15	12620

55a/16/6



Socket set
— in a sturdy steel case
Contains 22-pieces:
16 sockets with bi-hex 3/4" **No. 55a**: 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 1/4; 1 5/16; 1 3/8; 1 7/16; 1 1/2; 1 5/8; 1 11/16; 1 3/4; 1 13/16; 1 7/8; 2"
1 ratchet head 3/4" **No. 552**: L. 165 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 flexible head 3/4" **No. 554**: L. 132 mm
1 sliding head 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96054103	3/4	538	243	93	22	16750

TCS 55/11/6



Socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
11 sockets with hex 3/4" **No. 55**: 22; 24; 27; 30; 32; 34; 36; 38; 41; 46; 50 mm
1 ratchet head 3/4" **No. 552**: L. 165 mm
1 sliding head 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 square drive adaptor **No. 568**: 3/4 to 1/2"

Product no.	■ "	L mm	W mm	H mm	Size	Content pcs.	g
96830221	3/4	350	530	60	3/3	17	10100




Anti-Slip-Drive
The special AS-Drive profile makes high force transmission to the flats of screws and bolts possible without damaging them. This also prevents stripping of the screw head.

1" SOCKETRY.

60



Sockets
— bi-hex with AS-Drive profile
— 1" internal square drive
— HPQ® high performance steel, chrome-plated
— DIN 3124 / ISO 2725-1



Product no.	⌀ mm	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
06010030	30	65	42.5	43	27	20	33.1	371
06010032	32	67	45	43	29	24	34.6	374
06010034	34	67	47	43	31	24	34	398
06010036	36	67	49.5	48	33	24	33.4	493
06010041 *	41	70	55.5	48	36	30	37.5	530
06010046 *	46	75	61	49	40	32	43.5	622
06010050 *	50	80	66	48	43	34	47.5	707
06010055 *	55	85	72	48	49	36	49.5	920
06010060 *	60	90	78	48	53	40	56.5	992

* AS-Drive and HPQ® high performance steel up to 36 mm, chrome-plated


MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

60



Sockets
— hex
— 1" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 3124




Product no.	⌀ mm	L mm	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	g
06010065	65	105	87	60	58	40	68.5	1917
06010070	70	110	94	60	63	42	72.5	2210
06010075	75	115	101	60	68	45	78.5	2525
06010080	80	120	108	60	73	48	83.5	2865

64



INHEX screwdriver sockets
— for hex socket head screws
— 1" internal square drive
— Chrome Alloy Steel, chrome-plated
— DIN 7422



Product no.	◉ mm	L_1 mm	L_2 mm	∅ (d) mm	g
06050014	14	85	25	43	390
06050017	17	85	25	43	417
06050019	19	85	25	43	445
06050022	22	90	25	48	661
06050024	24	90	25	48	719
06050027	27	90	25	49	827

884




Flexible head
— with QuickRelease safety lock
— to be used with handle No. 888
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	∅ (d) mm	g
16060000	1	195	48	1848


859



Extensions
— Chrome Alloy Steel, chrome-plated
— DIN 3123 / ISO 3316



Product no.	Size	■ "	L mm	∅ (d) mm	g
16010001	8	1	200	43	1004
16010002	16	1	410	43	1794



1" drive tools
Explanation of table headings

L = Overall length
a = Head height (excluding square drive)
b = Head width

882



Ratchet head
— 1" external square drive
— reversible
— 36 teeth
— with QuickRelease safety lock
— to be used with handle No. 888
— Chrome Alloy Steel, chrome-plated



Product no.	■ "	L mm	a mm	b mm	∠ °	g
16110000	1	185	60	70	10 °	1984

888



Handle
— can be used as a T-handle in combination with sliding head No. 886
— Chrome Alloy Steel, chrome-plated

Product no.	for model	■ "	L mm	∅ (d) mm	g
16170000	882; 884; 886	1	700	28	3337

8820

Ratchet spare parts set
Contains 7-pieces:
1 pinion; 1 locking disc; 1 switching lever; 1 ball; 1 compression spring; 2 retaining screws

Product no.	for model	■ "	Content pcs.	g
19070000	882	1	7	609

866



Square drive adaptor
— 1 to $^3/_4$"
— max. torque: 1.412 N·m
— HPQ® high performance steel, chrome-plated
— DIN 3123 / ISO 3316

Product no.	■ "	L mm	∅ (d) mm	g
16030005	$^3/_4$	70	43	347

886



Sliding head
— can be used as a T-handle in combination with handle No. 888
— Chrome Alloy Steel, chrome-plated

Product no.	■ "	L mm	g
16070000	1	80	616

60/6/6/882



Socket set
— in a sturdy steel case
Contains 12-pieces:
6 sockets with bi-hex 1" **No. 60**: 36; 41; 46; 50; 55; 60 mm
1 ratchet head 1" **No. 882**: L. 185 mm
2 extensions 1" **No. 859**: L. 200; 410 mm
1 flexible head 1" **No. 884**: L. 195 mm
1 sliding head 1" **No. 886**: L. 80 mm
1 handle 1" **No. 888**: L. 700 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96060101	1	810	193	95	12	19720

60/8/6/882



Socket set
— in a sturdy steel case
Contains 14-pieces:
4 sockets with bi-hex 1" **No. 60**: 46; 50; 55; 60 mm
4 sockets with hex 1" **No. 60**: 65; 70; 75; 80 mm
1 ratchet head 1" **No. 882**: L. 185 mm
2 extensions 1" **No. 859**: L. 200; 410 mm
1 flexible head 1" **No. 884**: L. 195 mm
1 sliding head 1" **No. 886**: L. 80 mm
1 handle 1" **No. 888**: L. 700 mm

Product no.	■ "	L mm	W mm	H mm	Content pcs.	g
96060103	1	830	222	127	14	30000

ADAPTOR SETS.

5513



Square drive adaptor set
— in a sturdy, stackable ABS plastic box
Contains 5-pieces:
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"

Product no.	Content pcs.	g
96121003	5	648

409M/432M/514M/3



Square drive adaptor set
Contains 3-pieces:
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 square drive adaptor **No. 514M**: 1/2 to 3/4"

Product no.	Content pcs.	g
96121002	3	120

SOCKET ACCESSORIES.

5100



Rubber insert
— for 20.8 mm (No. 46; 51; 51S)

Product no.	L mm	Internal diameter mm	External diameter mm	Hardness	g
09010001	25	11	20	30 Shore	6

12916/10, 12917/10, 12918/10



Socket clip rails

— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— can be mounted on a wall or perforated wall/panel

Product no.	■ "	L mm	Retaining clips	g
80400003	1/4	255	10	46
80450003	3/8	255	10	54
80500005	1/2	307	10	80

12916/12917/12918



Socket clip rail set

— for organised and safe storage of sockets and accessories
— secure fixing to plastic clips with ball locking function
— attachments can be combined with each other
— can be mounted on a wall or perforated wall/panel

Contains 3-pieces:

1 socket clip rail 1/4" (6.3 mm)
1 socket clip rail 3/8" (10 mm)
1 socket clip rail 1/2" (12.5 mm)

Product no.	L mm	Retaining clips	Content pcs.	g
96003010	315	30	3	190



CONTROL CABINET KEYS.

172

VBW



Profi-Key

— universal keys for all shut-off and locking systems, including new buildings, utility locks and heating ventilation
— can also be used for door handle and window handle mounts
— functions: stepped square drive 6-10 mm; internal square drive 7-8 mm; internal triangle drive 9, 10 mm; ventilation square drive 5 mm
— also for PH size 2 and slot 7 mm
— with chain and bit adaptor 6.3 mm (1/4")
— made from diecast zinc
— supplied in clear packaging with enclosed description

Product no.		g
87172190		93

172

VBW



Control cabinet key SuBMaster 9 in 1

— universal key for all locking systems in electrical engineering, gas and water supplies, air conditioning and ventilation technology, industry and much more
— functions: internal square drive 5, 6, 7-8, 9-10 mm; internal triangle drive 7, 8-9, 10-11 mm; deadlock 3-5 mm; crescent 6 mm
— with carabiner on the chain and 6.3 mm (1/4") bit adaptor
— made from diecast zinc
— supplied in clear packaging with enclosed description

Product no.		g
87172100		175

173

VBW



Control cabinet key

— universal key for all locking systems in electrical engineering, gas and water supplies, air conditioning and ventilation technology, industry and much more
— functions: internal square drive 5, 6, 7-8 mm; internal triangle drive 7, 9 mm; double cam 3-5 mm
— also for PH size 2 and slot 7 mm
— with chain and bit adaptor 6.3 mm (1/4")
— made from diecast zinc
— supplied in clear packaging with enclosed description

Product no.		g
87173071		87

EMPTY BOXES AND INLAYS.

■ "	Product no.	Model	L	B	H	Case	Inlays
1/4	**96010120**	40D/40TX/44KTX/32/6QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40D/40TX/44KTX/32/6QR 83828793 Inlay 40D/40TX/44KTX/32/6 QR 83820024
1/4, 3/8, 1/2	**98811908**	89TX	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 89TX KN 83828870 Inlay 89TX KN 83092013
1/4	**98819801**	88TX	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 88 TX KN 83828847 Inlay 88TX KN 83022017
1/4, 1/2	**96013702**	86TX	483	289	83	Case 50/6 KN 81271019	Soft foam inlay for lid 86TX KN 83828896 Inlay 86TX KN 83012002
1/4	**96010107**	40ma/25/8QR	325	135	55	Case 45/1 KN 81261011	Soft foam inlay for lid 40MA/25/8QR KN 83828901 Inlay 40MA/25/8QR KN 83012006
1/4	**96011162**	40ma/25/8	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 40MA/25/8 KN 83828832
1/4	**96015205**	40aD/30/7QR	420	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 40AD/30/7QR KN SG 83828854 Inlay 40AD/30/7QR KN SG 83012112
1/4	**96015208**	40aD/12/7QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40AD/12/7QR KN SG 83828807 Inlay 40AD/12/7QR KN SG 83012116
1/4	**96016302**	40aD/9/4	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40AD/9/4 KN 83828808 Inlay 40A/9/4 KN 83012013
1/4	**96015107**	40a/9/4	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/A/9/4 KN 83828806 Inlay 40A/9/4 KN 83012013
1/4	**96011181**	40/44/17/5QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/44/17/5 QR KN 83828801 Inlay 40/44/17/5QR KN 83022084
1/4	**96011113**	40/44/17/5	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/44/17/5 KN 83828795 Inlay 40/44/17/5 KN 83012081
1/4	**96011182**	40/24/6QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/24/6 QR KN 83828802 Inlay 40/24/6QR KN 83012083
1/4	**96011138**	40/24/6	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/24/6 KN 83828799 Inlay 40/24/6 KN 83012082
1/4	**96011134**	40/23/7	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 40/23/7 KN 83828961 Inlay 40/23/7 KN 83012017
1/4	**96011137**	40/23/6QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/23/6QR KN 83828959 Inlay 40/23/6QR KN 83011015
1/4	**96011136**	40/23/6	230	130	60	Case 40/9 KN 81251019	Inlay 40/23/6 KN 83012014
1/4	**96011180**	40/13/6QR	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/13/6 QR KN 83828800 Inlay 40/13/6QR KN 83012182
1/4	**96011124**	40/13/6	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/13/6 KN 83828797 Inlay 40/13/6 KN 83012080

■ "	Product no.	Model	L	B	H	Case	Inlays
1/4	**96011119**	40/9/4	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40/9/4 KN 83828796 Inlay 40/9/4 KN 83013012
1/4	**96016304**	40a/40aD/16/2	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 40A/40AD/16/2 83828969 Inlay 40A/40AD/16/2 61010562
1/4, 3/8	**96012047**	40/45/36/12	420	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 40/45/36/12 KN 83828853 Inlay 40/45/36/12 KN 83012010
1/4, 1/2	**96011160**	40/52/27/11	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 40/52/27/11 KN 83828872 Inlay 40/52/27/11/1 KN 83012005
1/4, 1/2	**91222607**	40/52/45/12QR	290	480	85	Case 50/6 KN 81271019	Soft foam inlay for lid 40/52/45/12 KN 83828976 Inlay 40/52/45/12 61008439
3/8	**96021236**	456/49/19/5	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 456/49/19/5 KN 83828858 Inlay 45/49/19/5 KN 83022021
3/8	**96023132**	456/14/5I	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 456/14/5 I KN 83828841 Inlay 45/14/5I KN 83022080
3/8	**96022133**	456/11/4	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 456/11/4 KN 83828842 Inlay 45/11/4 KN 83022013
3/8	**96020107**	45ma/28/5QR	415	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 45MA/28/5QR KN 83828955 Inlay 45MA/28/5QR KN 83022007
3/8	**96021122**	45ma/28/5	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 45MA/28/5 KN 83828856 Inlay 45MA/28/5 KN 83022027
3/8	**96025207**	45a/22/8QR	458	257	65	Case 50/4 KN 81271034	Soft foam inlay for lid 45A/22/8QR KN SG 83828874 Inlay 45A/22/8QR KN SG 83022112
3/8	**96025204**	45a/12/5	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 45A/12/5 KN 83828843 Inlay 45A/12/5 KN 83022006
3/8	**96022119**	45/49/32/5TX	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 45/49/32/5 TX KN 83828855 Inlay 45/49/32/5TX KN 83022009
3/8	**96021223**	45/49/19/5	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 45/49/19/5 KN 83828857 Inlay 45/49/19/5 KN 83022021
3/8	**96021180**	45/14/5I QR	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 45/14/5 I QR KN 83828838 Inlay 45/14/5I QR KN 83022081
3/8	**96024132**	45/14/5I	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 45/14/5 I KN 83828837 Inlay 45/14/5I KN 83022080
3/8	**96021109**	45/11/4	325	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 45/11/4 KN 83828836 Inlay 45/11/4 KN 83022013
1/2	**96031508**	54/10	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 54/10 KN 83828810 Inlay 54/10 KN 83032403

■ "	Product no.	Model	L	B	H	Case	Inlays
1/2	**96031503**	54/12	327	135	60	Case 45/1 KN 81261011	Soft foam inlay for lid 40/21/8 FIN. KN 83828884 Inlay 54/12 KN 83034409
1/2	**96032005**	54TX/10	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 54TX/10 KN 83828812 Inlay 54TX/10 KN 83032402
1/2	**96033606**	3054X/54X/8	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 3054X/54X/8 KN 83828814 Inlay 3054X/54X/8 KN 83033612
1/2	**96031136**	50/43/7N	540	290	53	Case 50/5 empty for set 81270005	Inlay 50/43/7 83031511
1/2	**98811909**	876TX	483	289	83	Case 50/6 KN 81271019	Soft foam inlay for lid 876 KN 83828900 Inlay 876TX KN 83092011
1/2	**96032301**	876	483	289	83	Case 50/6 KN 81271019	Inlay-2, 876KN top spanners 83093211 Inlay-1, 876KN bottom inlay 83093111
1/2	**96031501**	54/8/4	417	230	60	Case 40/7 KN 81251014	Soft foam inlay for lid 54/8/4 KN 83828868 Inlay 54/8/4 KN 83033413
1/2	**96031240**	52/54/25/6QR	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 52/54/25/6QR KN 83828958 Inlay 50/54/25/6QR KN 83032400
1/2	**96031440**	50/54/25/6QR	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50/54/25/6QR KN 83828957 Inlay 50/54/25/6QR KN 83032400
1/2	**96031239**	52/54/25/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 52/54/25/6 KN 83828894 Inlay 52/54/25/6 KN 83032417
1/2	**96031439**	50/54/25/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50/54/25/6 KN 83828895 Inlay 52/54/25/6 KN 83032417
1/2	**96031409**	52/22/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 52/22/6 KN 83828877 Inlay 50/22/6 KN 83031407
1/2	**96031480**	52/16/6QR	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 52/16/6QR KN 83828880 Inlay 52/16/6QR KN 83032481
1/2	**96031448**	52/16/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 52/16/6 KN 83828879 Inlay 52/16/6 KN 83032480
1/2	**96031436**	52/12/3	415	227	67	Case 50/3 KN 81271013	Soft foam inlay for lid 52/12/3 KN 83828867 Inlay 50/12/3 KN 83031412
1/2	**96030107**	50ma/39/6QR	540	290	55	Case 50/5 empty for set 81270005	Inlay 50MA/39/6QR 83031405
1/2	**96030140**	50ma/39/6N	540	292	53	Case 50/5 empty for set 81270005	Inlay 50MA/39/6 S 83031426
1/2	**96035125**	50a/17/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50A/17/6 KN 83828882 Inlay 50A/17/6 KN 83031441
1/2	**96031236**	50/43/7QR	540	292	53	Case 50/5 empty for set 81270005	Inlay 50/43/7 83031511
1/2	**96031407**	50/22/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50/22/6 KN 83828876 Inlay 50/22/6 KN 83031407

■ "	Product no.	Model	L	B	H	Case	Inlays
1/2	**96031446**	50/16/6QR	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50/16/6QR KN 83828956
1/2	**96031447**	50/16/6	458	254	65	Case 50/4 KN 81271034	Soft foam inlay for lid 50/16/6 KN 83828878 Inlay 52/16/6 KN 83032480
1/2	**96031435**	50/12/3	415	227	67	Case 50/3 KN 81271013	Soft foam inlay for lid 50/12/3 KN 83828866 Inlay 50/12/3 KN 83031412
	96033704	50TX/8	230	130	60	Case 40/9 KN 81251019	Soft foam inlay for lid 50TX/8 KN 83828815 Inlay 50TX/8 KN 83033411
3/4	**96054103**	55a/16/6	538	243	93	Case 55/7 empty for set 81290008	Inlay 55A/16/6 PC-Inlay for socket set 83040004
3/4	**96054101**	55a/10/5	540	190	90	Case 55/6 empty for set 81290007	Inlay 55A/10/5 PC-Inlay for socket set 83040003
3/4	**96050104**	55/10/6	580	245	90	Case 55/7 empty for set 81290008	Inlay 55/10/6 PC-Inlay for socket set 83040002
3/4	**96050103**	55/9/6N	584	240	90	Case 55/7 empty for set 81290008	Inlay 55/9/6N PC-Inlay for socket set 83040001
1	**96060101**	60/6/6/882	810	193	95	Case 60/1 empty for set 81300001	
1	**96060103**	60/8/6/882	830	222	127	Case 60/2 empty for set 81300002	


STAHLWILLE
CHROME ALLOY
GERMANY

4 IMPACT tools

230 1/2" IMPACT tools

234 3/4" IMPACT tools

236 1" IMPACT tools

237 Bit adaptors, machine-operated

STAHLWILLE IMPACT TOOLS –
Concentrated power under control.

The tools in the IMPACT product range are designed for particularly heavy-duty use with IMPACT wrenches and are characterised by maximum load capacities and a long service life. The name IMPACT stands for top quality from professionals for professionals in all areas of industry and trades.

SOLID





Resilient.

IMPACT sockets are made of high quality Chrome Alloy Steel. They are stress and distortion-free and hardened in an oil bath, resulting in extremely tight tolerances.

Exact.


The precise dimensional accuracy due to extremely tight tolerances guarantees optimal, clearance-free transmission of forces from the IMPACT wrench to the socket as well as significantly increased durability.

Gentle.

The special IMPACT sockets with plastic sleeve enable quick wheel changes and protect sensitive alloy wheels.

Individual.

IMPACT sets in TCS inlays – for individual storage solutions, e.g. in our tool boxes, tool trolleys or workbenches.



Reliable.

All IMPACT sockets have a straight-through hole for the locking pin and a deep groove for the rubber ring. The locking pin is not under load during use.



Varied.


IMPACT quality is available individually or as a set. No matter what specialists choose: Extensions, bit adaptors, universal joints and sockets always fit together perfectly. Simply combine individually, connect together – and you're done.

1/2" IMPACT TOOLS.

50IMP



IMPACT sockets
— with hex
— 1/2" internal square drive
— DIN 3129 / ISO 1711-2
— Chrome Alloy Steel, gunmetal finish




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
23010008	8	1/2	14.3	25	38	21.5	86
23010010	10	1/2	16.8	25	38	21.5	89
23010011	11	1/2	18.1	25	38	21.5	88
23010012	12	1/2	19.5	25	38	21.5	88
23010013	13	1/2	20.8	25	38	21.5	85
23010014	14	1/2	22.1	25	38	21.5	86
23010015	15	1/2	23.5	30	38	23	132
23010016	16	1/2	24.8	30	38	23	130
23010017	17	1/2	26.2	30	38	22.9	132
23010018	18	1/2	27.5	30	38	22.6	130
23010019	19	1/2	28.8	30	40	24.6	133
23010021	21	1/2	31.3	30	40	23	135
23010022	22	1/2	32.5	30	42	25	141
23010023	23	1/2	33.8	30	40	24.5	144
23010024	24	1/2	35	30	44	28	164
23010025	25	1/2	36.3	30	44	25	167
23010027	27	1/2	38.8	30	45	29	190
23010030	30	1/2	42	30	50	34	199
23010032	32	1/2	44	30	50	34	210



50D IMP



IMPACT sockets
— with bi-hex
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish




Product no.	mm	"	d_1 mm	d_2 mm	L mm	g
23011032	32	1/2	50	30	43	251
23011036	36	1/2	49	30	50	313

51IMP



IMPACT sockets
— deep version
— with hex
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish
— DIN 3129 / ISO 1711-2




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
23020013	13	1/2	20.8	25	85	68.5	222
23020015	15	1/2	23.5	30	85	68	340
23020016	16	1/2	24.8	30	85	68	338
23020017	17	1/2	26.2	30	85	68	318
23020018	18	1/2	27.5	30	85	68	309
23020019	19	1/2	28.8	30	85	67.5	292
23020021	21	1/2	31.3	30	85	66.5	291
23020022	22	1/2	32.5	30	85	66.5	323
23020024	24	1/2	35	30	85	66	340
23020027	27	1/2	38.8	30	85	65	385

2308TX



IMPACT sockets
— for external TORX® screws
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish




Product no.		mm	"	d_1 mm	d_2 mm	L mm	g
23080010	E10	9.4	1/2	14	25	38	67
23080012	E12	11.1	1/2	15.9	25	38	73
23080014	E14	12.9	1/2	17.7	25	38	73
23080016	E16	14.7	1/2	20	25	38	77
23080018	E18	16.6	1/2	22	30	38	115
23080020	E20	18.4	1/2	24.5	30	38	120
23080024	E24	22.1	1/2	30	30	41.2	149

2309



IMPACT sockets
— deep version, with reduced diameter
— with hex
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish



Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
23090017	17	1/2	25.7	30	85	68	242
23090019	19	1/2	28.2	30	85	67.5	257
23090221	21	1/2	30.7	30	85	66.5	272
23090022	22	1/2	32	30	85	66.5	311

2309IMP K




IMPACT wheel nut sockets
— with hex
— 1/2" internal square drive
— protruding plastic sleeve protects alloy wheels from accidental damage
— Chrome Alloy Steel, gunmetal finish
— DIN 3129 / ISO 1711-2

Product no.	mm	"	d mm	L mm	g
23091017	17	1/2	27	86	235
23091019	19	1/2	29	86	250
23091221	21	1/2	31	86	265

54IMP



IMPACT INHEX screwdriver sockets
— for hex socket screws
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish




Product no.	mm	"	d mm	L_1 mm	L_2 mm	g
23050005	5	1/2	25	40	20	58
23050006	6	1/2	25	40	20	59
23050007	7	1/2	25	40	20	60
23050008	8	1/2	25	40	20	60
23050010	10	1/2	25	40	20	70
23050012	12	1/2	25	40	20	111
23050014	14	1/2	25	40	20	118
23050017	17	1/2	25	40	20	134
23050019	19	1/2	25	40	20	164

2307TX



IMPACT screwdriver sockets
— for recessed TORX® screws
— 1/2" internal square drive
— Chrome Alloy Steel, gunmetal finish




Product no.		mm	"	d mm	L_1 mm	L_2 mm	g
23070030	T30	5.5	1/2	25	40	21	57
23070040	T40	6.6	1/2	25	40	21	58
23070045	T45	7.8	1/2	25	40	21	59
23070050	T50	8.8	1/2	25	40	22	57
23070055	T55	11.2	1/2	25	40	22	61
23070060	T60	13.2	1/2	25	40	22	66

509IMP



IMPACT extensions
— 1/2" square drive
— Chrome Alloy Steel, gunmetal finish



Product no.	Size	■ "	○ "	d mm	L mm	g
33010001	2	1/2	1/2	30	52	155
33010002	5	1/2	1/2	30	130	271
33010003	10	1/2	1/2	30	255	452

510IMP



IMPACT universal joint
— 1/2" square drive
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	○ "	d mm	L mm	g
33020000	1/2	1/2	28	60	228

513IMP



IMPACT square drive adaptor
— 1/2" internal square drive
— 1/2 to 3/8"
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	○ "	d mm	L mm	g
33030002	3/8	1/2	30	37	109

514IMP



IMPACT square drive adaptor
— 1/2" internal square drive
— 1/2 to 3/4"
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	○ "	d mm	L mm	g
33030005	3/4	1/2	30	49	174

5091IMP



IMPACT rubber rings
— for IMPACT socket tools

Product no.	Size	suitable for	○ "	g
39011940	1IMP	8-14 mm; E10-E16; T30-T60	1/2	1
39012440	2IMP	15-36 mm; E18-E 24	1/2	2

5092IMP



IMPACT locking pins
— for IMPACT socket tools

Product no.	Size	suitable for	○ "	g
39022030	1IMP	8-14 mm, E10-E16, T30-T60	1/2	1
39022530	2IMP	15-36 mm, E18-E24	1/2	2

50IMP/6/2



IMPACT tool set
— in a sturdy, stackable ABS plastic box
Contains 12-pieces:
6 IMPACT sockets with hex 1/2" **No. 50IMP**: 13; 17; 19; 21; 22; 24 mm
1 IMPACT extension 1/2" **No. 509/5IMP**: L. 125 mm
1 IMPACT universal joint 1/2" **No. 510IMP**: L. 60 mm
1 IMPACT rubber ring each 1/2" **No. 5091/1IMP, 5091/2IMP**
1 IMPACT locking pin each 1/2" **No. 5092/1IMP, 5092/2IMP**

Product no.	"	Content pcs.	g
96231101	1/2	12	1810

TCS 50IMP/19/2



IMPACT tool set
— safely integrated in the modular Tool Control System (TCS)
Contains 21-pieces:
19 IMPACT sockets with hex **No. 50IMP**: 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 23; 24; 25; 27; 30; 32 mm
1 IMPACT extension 1/2" **No. 509/5IMP**: L. 125 mm
1 IMPACT universal joint 1/2" **No. 510IMP**: L. 68 mm

Product no.	"	L mm	W mm	H mm	Module size	Content pcs.	g
96838791	1/2	350	175	50	1/3	21	3055

54IMP/9



IMPACT INHEX screwdriver socket set
— in a sturdy, stackable ABS plastic box
Contains 13-pieces:
9 IMPACT screwdriver sockets INHEX 1/2" **No. 54IMP**: 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
1 IMPACT rubber ring each 1/2" **No. 5091/1IMP, 5091/2IMP**
1 IMPACT locking pin each 1/2" **No. 5092/1IMP**, **5092/2IMP**

Product no.	"	Content pcs.	g
96231501	1/2	13	1208

TCS 50IMP/51IMP/19




IMPACT socket set
— safely integrated in the modular Tool Control System (TCS)
Contains 19-pieces:
11 IMPACT sockets with hex 1/2" **No. 50IMP**: 10; 13; 15; 16; 17; 18; 19; 21; 22; 24; 27 mm
8 IMPACT sockets, deep, with hex 1/2" **No. 51IMP**: 13; 15; 17; 18; 19; 21; 22; 24 mm

Product no.	"	L mm	W mm	H mm	Module size	Content pcs.	g
96838777	1/2	350	175	50	1/3	19	3960



TCS 54IMP/2307TX/15



IMPACT screwdriver socket set

— safely integrated in the modular Tool Control System (TCS)

Contains 15-pieces:


9 IMPACT screwdriver sockets INHEX 1/2" **No. 54IMP**: 5; 6; 7; 8; 10; 12; 14; 17; 19 mm

6 IMPACT screwdriver sockets TORX® 1/2" **No. 2307TX**: T30; T40; T45; T50; T55; T60

Product no.	"	L mm	W mm	H mm	Module size	Content pcs.	g
96838792	1/2	350	175	40	1/3	15	1285

3/4" IMPACT TOOLS.

55IMP




IMPACT sockets

— with hex

— 3/4" internal square drive

— Chrome Alloy Steel, gunmetal finish

— DIN 3129 / ISO 1711-2



Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
25010017	17	3/4	29	44	48	23	365
25010018	18	3/4	30.5	44	48	23	345
25010019	19	3/4	32	44	48	23	359
25010021	21	3/4	35	44	50	25	375
25010022	22	3/4	36.5	44	50	25	377
25010024	24	3/4	39.5	44	50	24.5	382
25010027	27	3/4	43.5	44	51	24.5	387
25010028	28	3/4	45	44	54	27	417
25010029	29	3/4	46	44	54	26.5	425
25010030	30	3/4	47.4	44	54	26.5	438
25010032	32	3/4	49.9	44	54	26	456
25010033	33	3/4	51.5	44	54	25.5	477
25010034	34	3/4	52.4	44	54	29	490
25010036	36	3/4	54.9	44	57	32	545
25010038	38	3/4	58	44	58	33	600
25010041	41	3/4	60	44	58	34.5	500
25010046	46	3/4	67	44	63	36.5	746

56IMP



IMPACT sockets


— deep version

— with hex

— 3/4" internal square drive

— Chrome Alloy Steel, gunmetal finish

— DIN 3129 / ISO 1711-2



Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
25020017	17	3/4	28.2	38	90	75	783
25020019	19	3/4	30	38	90	75	780
25020021	21	3/4	35	44	100	75	895
25020022	22	3/4	36.5	44	100	75	854
25020024	24	3/4	39.5	44	100	74.5	838
25020027	27	3/4	43.5	44	100	72.5	800
25020030	30	3/4	47.4	44	100	72.5	860
25020032	32	3/4	49.9	44	100	72	922
25020034	34	3/4	52.4	44	100	71.5	983
25020036	36	3/4	54.9	44	100	71	1038
25020041	41	3/4	60	44	92	64	899
25020046	46	3/4	67	44	92	64	1340

2509



IMPACT sockets

— deep version, with reduced diameter


— with hex

— 3/4" internal square drive

— for bolted joints of e.g. TRILEX® wheels

— Chrome Alloy Steel, gunmetal finish

— DIN 3129 / ISO 1711-2




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
25090027	27	3/4	40.5	44	100	72.5	672
25090030	30	3/4	44.3	44	100	72.5	728
25090032	32	3/4	46.8	44	100	72	778
25090033	33	3/4	48	44	100	72	803

560IMP



IMPACT extensions
— 3/4" square drive
— Chrome Alloy Steel, gunmetal finish



Product no.	Size	■ "	O "	d mm	L mm	g
35010001	7	3/4	3/4	44	180	805
35010002	10	3/4	3/4	44	250	1050
35010003	13	3/4	3/4	44	330	1305

561IMP



IMPACT universal joint
— 3/4" square drive
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	O "	d mm	L mm	g
35020000	3/4	3/4	44	99	657

568IMP



IMPACT square drive adaptor
— 3/4" internal square drive
— 3/4 to 1/2"
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	O "	d mm	L mm	g
35030003	1/2	3/4	44	56	335

569IMP



IMPACT square drive adaptor
— 3/4" internal square drive
— 3/4 to 1"
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	O "	d mm	L mm	g
35030006	1	3/4	44	65	477

5591IMP



IMPACT rubber ring
— for IMPACT socket tools

Product no.	suitable for	O "	g
39013650	17-46 mm	3/4	3

5592IMP



IMPACT locking pin
— for IMPACT socket tools

Product no.	suitable for	O "	g
39023540	17-46 mm	3/4	3

MADE IN GERMANY


For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

1" IMPACT TOOLS.

60IMP



IMPACT sockets
— with hex
— 1" internal square drive
— DIN 3129 / ISO 1711-2
— Chrome Alloy Steel, gunmetal finish




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
26010024	24	1	41.5	54	58	28	638
26010027	27	1	45	54	60	30	654
26010030	30	1	49	54	62	32	688
26010032	32	1	51.5	54	63	32	694
26010033	33	1	52.5	54	63	31.5	695
26010036	36	1	56.5	54	67	34.5	754
26010038	38	1	59	54	70	37	836
26010041	41	1	63	54	70	36.5	892
26010042	42	1	64.5	54	73	39	970
26010046	46	1	69.5	54	76	41	1106
26010050	50	1	74.5	54	82	52	1362
26010055	55	1	81	54	87	57	1669
26010060	60	1	87	54	91	61	1960
26010065	65	1	93	54	80	55	1678
26010070	70	1	98	54	85	43	1803
26010075	75	1	104	86	95	50	2674
26010080	80	1	109	86	100	55	2949



66IMP



IMPACT sockets
— deep version
— with hex
— 1" internal square drive
— Chrome Alloy Steel, gunmetal finish
— DIN 3129 / ISO 1711-2




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
26020024	24	1	41.5	54	110	80	1431
26020027	27	1	45	54	110	80	1393
26020030	30	1	49	54	110	79.5	1338
26020032	32	1	51.5	54	110	79	1296
26020033	33	1	52.5	54	110	78.5	1274
26020036	36	1	56.5	54	110	78	1312
26020038	38	1	59	54	110	77	1355
26020041	41	1	63	54	110	76	1504
26020046	46	1	69.5	54	110	72	1711

2609



IMPACT sockets
— deep version, with reduced diameter
— with hex
— 1" internal square drive
— for wheel nuts
— Chrome Alloy Steel, gunmetal finish
— DIN 3129 / ISO 1711-2




Product no.	mm	"	d_1 mm	d_2 mm	L mm	t mm	g
26090027	27	1	42.3	54	110	80	1001
26090030	30	1	46	54	110	79.5	1047
26090032	32	1	48.5	54	110	79	1015
26090033	33	1	49.8	54	110	78.5	1102

859IMP



IMPACT extensions
— 1" square drive
— Chrome Alloy Steel, gunmetal finish



Product no.	Size	■ "	O "	d mm	L mm	g
36010001	7	1	1	54	180	1361
36010002	13	1	1	54	330	2168

871IMP



IMPACT universal joint
— 1" square drive
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	O "	d mm	L mm	g
36020000	1	1	54	125	1244

866IMP



IMPACT square drive adaptor
— 1" internal square drive
— 1 to $^{3}/_{4}$"
— Chrome Alloy Steel, gunmetal finish

Product no.	■ "	O "	d mm	L mm	g
36030005	$^{3}/_{4}$	1	54	70	565

6091IMP



IMPACT rubber ring
— for IMPACT socket tools

Product no.	suitable for	O "	g
39014850	24-70 mm	1	8

6092IMP



IMPACT locking pin
— for IMPACT socket tools up to 70 mm and additional tools


Product no.	suitable for	O "	g
39025050	24-70 mm	1	7

BIT ADAPTORS, MACHINE-OPERATED.

3116/1QR-3316/1QR



QuickRelease bit adaptors
— with external hex drive
— for machine-operated IMPACT sockets DIN 3129 / ISO 2725-2 with internal square DIN 3121 / ISO 1174-2
— with a larger diameter for improved contact with the IMPACT sockets
— Chrome Alloy Steel, gunmetal finish



Product no.	Model	■ "	mm	L mm	H mm	g
31161001	3116/1QR	$^{1}/_{4}$	E 6.3	50	11.2	18
32161001	3216/1QR	$^{3}/_{8}$	E 6.3	50	14.6	26
33161001	3316/1QR	$^{1}/_{2}$	E 6.3	50	19.2	46



5 Screwdrivers and bit tools

242 **Screwdrivers**

251 **Screwdriver sets**

258 **L-Keys**

264 **L-Key sets in TCS**

265 **Bit tools**

STAHLWILLE SCREWDRIVERS AND BIT TOOLS – The great variety.

For professionals who are consistently meeting new demands in their daily work: STAHLWILLE offers a variety of screwdrivers for the most diverse applications and drive profiles – individually or in useful sets. Bit ratchets, bit holders and screwdriver bits complete the product range.



Safe.

Our DRALL+ handle is non-slip and ergonomic. An extended grip zone protects the fingers and a hand stop prevents the tool from accidentally slipping or rolling away.

Optimised.

The DRALL+ handle with 3-components combines hard and soft elements, which give it its optimised ergonomics, maximum power transmission and increased safety during daily use.

Practical.

Always find the right tip-profile thanks to the useful marking on the handle. For use in extreme conditions, DRALL+ screwdrivers are also available with metal impact caps.



Space-saving.

Perfect for work in confined spaces. The 1/4" bit fine-tooth mini ratchet with steel handle impresses with its slim design and special 80-tooth mechanism that allows a working angle of only 4.5°.

MADE IN CRONENBERG
MADE IN GERMANY

5

Fitting.

STAHLWILLE also offers screwdriver bits with different drive profiles – Made in Germany. Special hardening processes and high performance alloy steels guarantee a long service life.

Compact.


Stored in the practical soft case or in the robust plastic box, users have all the important bits, sockets and the drive tool right at hand.

SCREWDRIVERS.

4620



Slotted screwdrivers DRALL+
- for slotted screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 2380-1 / DIN ISO 2380-2 / DIN 5264




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
46203035	1	0.6	3.5	75	160	25
46203040	2	0.8	4	100	185	34
46203055	3	1.0	5.5	125	240	79
46203065	4	1.2	6.5	150	265	109
46203080	5	1.6	8	175	300	136
46203100	6	1.6	10	200	325	163
46203120	7	2.0	12	250	375	215

4621



Slotted screwdrivers DRALL+
- for slotted screws
- parallel blades
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- blades according to VSM (Swiss Standard)




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
46213025	0	0.4	2.5	80	165	27
46213035	1	0.5	3.5	90	175	26
46213040	2	0.6	4	100	185	34
46213055	3	0.8	5.5	120	235	78
46213065	4	1.0	6.5	140	255	96
46213080	5	1.2	8	160	275	117

4622



Slotted screwdrivers DRALL+
- with hex shank profile
- for slotted screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 2380-1 / DIN ISO 2380-2 / DIN 5264




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	⬢ mm	g
46223555	1	1.0	5.5	100	215	8	85
46223565	2	1.2	6.5	125	240	10	100
46223580	3	1.2	8	150	275	13	159
46223500	4	1.6	10	175	300	13	174
46223520	5	2.0	12	200	325	13	240
46223540	6	2.5	14	250	375	13	310

4622SK



Slotted screwdrivers DRALL+
- with impact cap
- with hex shank profile
- for slotted screws
- black tip
- with 3-component handle
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	⬢ mm	g
46223440	1	0.8	4	90	195	6	50
46223355	2	1.0	5.5	100	215	8	106
46223365	3	1.2	6.5	125	240	10	135
46223208	4	1.2	8	150	275	13	191
46223210	5	1.6	10	175	300	13	226
46223212	6	2.0	12	200	325	13	267
46223314	7	2.5	14	250	375	13	340

4628



Electrician's slotted screwdrivers DRALL+

— for slotted screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— DIN ISO 2380-1 / DIN ISO 2380-2 / DIN 5264




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
46283025	1	0.4	2.5	60	145	20
46283035	2	0.6	3.5	75	160	40
46283040	4	0.8	4	125	210	36
46283055	5	1.0	5.5	150	265	92
46283135	3	0.6	3.5	100	185	41
46283155	6	1.0	5.5	200	315	102

4724



Slotted screwdrivers DRALL®

— short version
— for slotted screws
— black tip
— Chrome Alloy Steel, matt chrome-plated
— DIN ISO 2380-1 / DIN ISO 2380-2 / DIN 5264




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
47241045	1	0.6	3.5	25	80	34
47241060	2	1.0	5.5	25	80	32
47241080	3	1.2	8	25	80	39

4820



Slotted screwdrivers 3K DRALL®

— for slotted screws
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
— DIN 5264 / ISO 2380




Product no.	a mm	b mm	L_1 mm	L_2 mm	g
48201035	0.6	3.5	75	170	63
48201040	0.8	4	100	195	32
48202055	1.0	5.5	125	220	58
48201065	1.2	6.5	150	265	100
48201080	1.6	8	175	290	120
48201100	1.6	10	200	315	158
48202100	2.0	12	250	375	218

4751



Electronic slotted screwdrivers

— for slotted screws
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
47513001	1	0.16	0.8	40	140	12
47513002	2	0.18	1	40	140	12
47513003	3	0.25	1.2	40	140	12
47513004	4	0.3	1.5	40	140	12
47513005	5	0.3	1.8	60	160	12
47513006	6	0.4	2	60	160	12
47513007	7	0.4	2.5	75	175	12
47513008	8	0.5	3	75	175	14

TOOLS THAT
... inspire

10503



Slotted screwdriver DRALL+
- long version, for adjustment work
- for slotted screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN 2380




Product no.	a mm	b mm	L_1 mm	L_2 mm	g
73213101	0.8	5	250	365	100

10506



Slotted screwdriver DRALL+
- long version, for adjustment work
- for slotted screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN 2380




Product no.	a mm	b mm	L_1 mm	L_2 mm	g
73013001	0.8	4	300	380	48

10518



Slotted screwdriver DRALL+
- long version, for adjustment work
- for slotted screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN 2380




Product no.	a mm	b mm	L_1 mm	L_2 mm	g
73213102	1.0	5.5	410	525	159

4630



PH cross-head screwdrivers DRALL+
- for PHILLIPS® screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764




Product no.	Size	L_1 mm	L_2 mm	g
46303000	PH0	60	145	20
46303001	PH1	80	185	35
46303002	PH2	100	215	90
46303003	PH3	150	275	146

4631



PH cross-head screwdrivers DRALL+
- long version
- for PHILLIPS® screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764




Product no.	Size	L_1 mm	L_2 mm	g
46313001	PH1	250	355	110
46313002	PH2	250	365	122

4632



PH cross-head screwdrivers DRALL+
- with hex shank profile
- for PHILLIPS® screws
- black tip
- 3-component handle with laser marking
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764




Product no.	Size	L_1 mm	L_2 mm	⬣ mm	g
46323301	PH1	80	185	6	45
46323302	PH2	100	215	10	100
46323303	PH3	150	275	13	170
46323304	PH4	200	325	13	237

4830



PH cross-head screwdrivers 3K DRALL®
- for PHILLIPS® screws
- black tip
- 3-component handle with non-slip fibre coating and hanging hole
- Chrome Alloy Steel, matt chrome-plated
- DIN 5262 / ISO 8764




Product no.	Size	L_1 mm	L_2 mm	g
48301000	PH0	60	155	28
48301001	PH1	80	175	50
48301002	PH2	100	215	70
48301003	PH3	150	275	126
48301004	PH4	200	325	251

4632SK



PH cross-head screwdrivers DRALL+
- with impact cap
- with hex shank profile
- for PHILLIPS® screws
- black tip
- with 3-component handle
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764




Product no.	Size	L_1 mm	L_2 mm	⬣ mm	g
46323201	PH1	85	190	6	58
46323202	PH2	100	215	10	120
46323203	PH3	150	275	13	194

4734



PH cross-head screwdrivers DRALL®
- short version
- for PHILLIPS® screws
- black tip
- Chrome Alloy Steel, matt chrome-plated
- DIN ISO 8764



Product no.	Size	L_1 mm	L_2 mm	g
47341001	PH1	25	80	27
47341002	PH2	25	80	31


DRALL+
Our DRALL+ handle is non-slip and ergonomic. An extended grip zone protects the fingers and a hand stop prevents the tool from accidentally slipping or rolling away.

4752



Electronic PH cross-head screwdrivers

— for PHILLIPS® screws
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking
— DIN ISO 2380




Product no.	Size	Ø mm	L_1 mm	L_2 mm	g
47523010	PH00	2.5	40	140	12
47523020	PH0	3	60	160	14
47523001	PH1	4.5	80	180	24

4840



PZ cross-head screwdrivers 3K DRALL®

— for POZIDRIV® screws
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
— DIN 5262 / ISO 8764




Product no.	Size	L_1 mm	L_2 mm	g
48401001	PZ1	80	175	33
48401002	PZ2	100	215	70

4640



PZ cross-head screwdrivers DRALL+

— for POZIDRIV® screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— DIN ISO 8764




Product no.	Size	L_1 mm	L_2 mm	g
46403000	PZ0	60	145	35
46403001	PZ1	80	185	44
46403002	PZ2	100	215	89
46403003	PZ3	150	275	145

4744




PZ cross-head screwdrivers DRALL®

— short version
— for POZIDRIV® screws
— black tip
— Chrome Alloy Steel, matt chrome-plated
— DIN ISO 8764



Product no.	Size	L_1 mm	L_2 mm	g
47441001	PZ1	25	80	28
47441002	PZ2	25	80	34




4650



TORX® screwdrivers DRALL+

— for recessed TORX® screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	Size	L_1 mm	L_2 mm	g
46503005	T5	60	145	30
46503006	T6	60	145	35
46503007	T7	60	145	35
46503008	T8	60	145	33
46503009	T9	60	145	35
46503010	T10	80	165	35
46503015	T15	80	165	38
46503020	T20	100	205	50
46503025	T25	100	205	50
46503027	T27	115	230	90
46503030	T30	115	230	90
46503040	T40	115	240	131
46503045	T45	130	255	136

4650L



TORX® screwdrivers DRALL+

— long version
— for recessed TORX® screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	Size	L_1 mm	L_2 mm	g
46503115	T15	250	335	45
46503120	T20	250	355	180
46503125	T25	250	355	180
46503130	T30	250	365	125

4754



Electronic TORX® screwdrivers

— for recessed TORX® screws
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking




Product no.	Size	L_1 mm	L_2 mm	g
47540004	T4	50	150	17
47540005	T5	50	150	17
47540006	T6	50	150	17
47540007	T7	50	150	17
47540008	T8	60	160	19
47540009	T9	60	160	19
47540010	T10	60	160	22
47540015	T15	80	180	22

4656



TORX® Tamper Resistant screwdrivers DRALL+

— for recessed TORX® screws
— with hole in the drive tip (TORX® Tamper Resistant)
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	Size	L_1 mm	L_2 mm	g
46563008	T8	60	145	35
46563009	T9	60	145	35
46563010	T10	80	165	39
46563015	T15	80	165	39
46563020	T20	100	205	42
46563025	T25	100	205	50
46563027	T27	115	230	90
46563030	T30	115	230	90
46563040	T40	115	240	120
46563045	T45	130	255	118

4856



TORX® Tamper Resistant screwdrivers 3K DRALL®

— for recessed TORX® screws
— with hollow tip (TORX® Tamper Resistant)
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated



Product no.	Size	L1 mm	L2 mm	g
48560006 *	T6	50	145	45
48560007	T7	50	145	37
48560008	T8	60	155	39
48560009	T9	60	155	50
48560010	T10	80	175	26
48560015	T15	80	175	52
48560020	T20	100	215	32
48560025	T25	100	215	55
48560027	T27	115	230	58
48560030	T30	115	230	63
48560040	T40	115	240	86


* without hole

4636



TORQ-SET® screwdrivers DRALL+

— for TORQ-SET® screws
— with hex shaft
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	Size	"	L1 mm	L2 mm	g
46363002	TQ2	1/4	100	215	92
46363004	TQ4	1/4	100	215	93
46363006	TQ6	1/4	100	215	93
46363008	TQ8	1/4	100	215	93
46363010	TQ10	1/4	100	215	93
46363016	TQ1/4"	5/16	150	265	138

10507N KK



Hex ball-ended screwdrivers DRALL+

— for hex socket screws
— pivoting angle of up to 25° to each side
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	mm	L1 mm	L2 mm	g
73103003	3	300	385	56
73103005	5	300	415	132

4753




Electronic hex screwdrivers

— for hex socket screws
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking



Product no.	mm	"	L1 mm	L2 mm	g
47533007	0.7	0,028	40	140	12
47533009	0.9	0,035	40	140	12
47533013	1.3	0.05	40	140	12
47533015	1.5	0,059	50	150	12




12500N



Nut spinners DRALL+

— hex profile
— 3-component handle with laser marking
— Chrome Alloy Steel, chrome-plated
— DIN 3125




Product no.	mm	Ø mm	L_1 mm	L_2 mm	g
43093004	4	6.9	125	230	58
43093045	4.5	7.5	125	230	49
43093005	5	8.2	125	230	58
43093055	5.5	8.8	125	230	58
43093006	6	9.4	125	240	98
43093007	7	11	125	240	114
43093008	8	12.2	125	240	115
43093009	9	13.5	125	240	118
43093010	10	14.7	125	240	122
43093011	11	16	125	250	160
43093012	12	17.2	125	250	168
43093013	13	18.5	125	250	170

12506



Nut spinners DRALL+

— hex profile
— with flexible shaft
— max. torque 8 N·m
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated




Product no.	mm	Ø mm	L_1 mm	L_2 mm	g
43103206	6	11	175	290	167
43103207	7	11	175	290	168
43103208	8	11	175	290	170

10768



Hex screwdrivers

— for hex socket screws
— with 2 outputs
— black tip
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated



Product no.	mm	L_1 mm	L_2 mm	g
43253020	2	100	125	33
43253025	2.5	100	125	42
43253030	3	150	174	42
43253040	4	150	176	50
43253050	5	200	227	73
43253060	6	200	228	92
43253080	8	200	235	178
43253100	10	200	235	247

MADE IN GERMANY


For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

10769



TORX® screwdrivers

— for recessed TORX® screws
— with 2 outputs
— black tip
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated




Product no.	Size	L_1 mm	L_2 mm	g
43293008	T8	80	96	12
43293009	T9	80	96	13
43293010	T10	100	116	14
43293015	T15	100	116	16
43293020	T20	100	125	36
43293025	T25	110	135	41
43293027	T27	110	135	49
43293030	T30	130	155	59
43293040	T40	130	165	102
43293045	T45	130	165	119
43293050	T50	130	165	137

12507



Nut spinners

— hex profile
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated




Product no.	mm	L_1 mm	L_2 mm	g
43233060	6	175	224	83
43233070	7	175	234	115
43233080	8	175	234	135
43233090	9	175	234	137
43233100	10	175	234	160
43233110	11	175	240	169
43233120	12	175	240	171
43233130	13	175	240	176



SCREWDRIVER SETS.

TCS 4620/4630/7



Screwdriver set DRALL+
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
4 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838278	350	175	40	1/3	7	590

TCS 4620-4734/8



Screwdriver set DRALL+
— black tip
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 8-pieces:
3 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838769	350	175	35	1/3	8	503

TCS 4620/4640



Screwdriver set DRALL+
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
4 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 PZ cross-head screwdrivers **No. 4640**: PZ1; PZ2; PZ3

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838784	350	175	35	1/3	7	410


TCS 4620/4660 VDE/10767



Screwdriver set DRALL+
— Chrome Alloy Steel
— safely integrated in the modular Tool Control System (TCS)
Contains 27-pieces:
6 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175; 1.6 x 10.0 x 200; 2.0 x 12.0 x 200 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 PH cross-head screwdriver **No. 4632**: PH4
3 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2
1 VDE slotted screwdriver **No. 4660 VDE**: 0.4 x 2.5 x 75 mm
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 PZ cross-head screwdriver **No. 4744**: PZ1
1 hex L-Key set **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96831168	350	530	90	3/3	27	2200

TCS 4620/4660 VDE



Screwdriver set DRALL+
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)

Contains 18-pieces:
6 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175; 1.6 x 10.0 x 200; 2.0 x 12.0 x 200 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 PH cross-head screwdriver **No. 4632**: PH4
3 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2
1 VDE slotted screwdriver **No. 4660 VDE**: 0.4 x 2.5 x 75 mm
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 PZ cross-head screwdriver **No. 4744**: PZ1

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96831179	350	530	90	3/3	18	1689

TCS 4621/4734/16



Screwdriver set DRALL+
— safely integrated in the modular Tool Control System (TCS)

Contains 16-pieces:
5 slotted screwdrivers **No. 4621**: 0.4 x 2.5 x 80; 0.5 x 3.5 x 90; 0.6 x 4.0 x 100; 1.0 x 6.5 x 140; 1.2 x 8.0 x 160 mm
2 PH cross-head screwdrivers **No. 4631**; PH1; PH2
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 10506**: 0.8 x 4.0 x 300 mm
1 slotted screwdriver **No. 10518**: 1.0 x 5.5 x 410 mm
1 magnet lifter **No. 12600**: 500 g
1 claw gripper **No. 12922**: Ø 6 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96832098	350	530	40	3/3	16	1490

TCS 4622-4632/4650/10760/10766/20




Screwdriver set DRALL+
— Chrome Alloy Steel
— safely integrated in the modular Tool Control System (TCS)

Contains 35-pieces:
4 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.6 x 10.0 x 175; 2.0 x 12.0 x 200 mm
1 PH cross-head screwdriver **No. 4630**: PH1
1 PH cross-head screwdriver **No. 4632**: PH3
10 TORX® screwdrivers **No. 4650**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 hex L-Key set **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 TORX® L-Key set **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96831196	350	530	90	3/3	35	1895

TCS 4650



TORX® screwdriver set DRALL+
— for recessed TORX® screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)

Contains 8-pieces:
8 TORX® screwdrivers **No. 4650**: T8; T9; T10; T15; T20; T25; T27; T30

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838767	350	175	35	1/3	8	340

TCS 4820/4830



Screwdriver set 3K DRALL®
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)

Contains 7-pieces:
4 slotted screwdrivers **No. 4820**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 PH cross-head screwdrivers **No. 4830**: PH1; PH2; PH3

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838184	350	175	90	1/3	7	555

TCS 12500N/5



Nut spinner set DRALL+
— hex profile
— 3-component handle with laser marking
— Chrome Alloy Steel, chrome-plated
— DIN 3125
— safely integrated in the modular Tool Control System (TCS)

Contains 5-pieces:
5 nut spinners **No. 12500N**: 7; 8; 10; 12; 13 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838757	350	175	45	1/3	5	730

TCS 4724/4840/10767




Screwdriver set
— safely integrated in the modular Tool Control System (TCS)

Contains 24-pieces:
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 PZ cross-head screwdriver **No. 4744**: PZ1
5 slotted screwdrivers **No. 4820**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150; 1.6 x 10.0 x 200; 2.0 x 12.0 x 250 mm
3 PH cross-head screwdrivers **No. 4830**: PH1; PH2; PH3
1 PZ cross-head screwdriver **No. 4840**: PZ1
1 automotive voltage tester **No. 7756**
1 hex L-Key set **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 claw gripper **No. 12922**: Ø 6 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830706	350	530	35	3/3	24	1755

TCS 4856



TORX® screwdriver set 3K DRALL®
— for recessed TORX® screws
— with hollow tip (TORX® Tamper Resistant)
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)

Contains 7-pieces:
7 TORX® screwdrivers with hole **No. 4856**: T8; T9; T10; T15; T20; T25; T30

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838755	350	175	40	1/3	7	447

TCS 10768/6



Hex screwdriver set
— for hex socket screws
— with 2 outputs
— black tip
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
6 hex screwdrivers **No. 10768**: 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838753	350	350	40	2/3	6	792


TCS 10769/10771/10



TORX® screwdriver set
— for recessed TORX® screws
— with 2-component T-handle
— Chrome Alloy Steel
— safely integrated in the modular Tool Control System (TCS)
Contains 17-pieces:
9 TORX® screwdrivers with T-handle **No. 10769**: T9; T10; T15; T20; T25; T30; T40; T45; T50
1 TORX® L-Key set **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96832099	350	350	30	2/3	17	940

TCS 10768/8



Hex screwdriver set
— for hex socket screws
— with two outputs
— black tip
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 8-pieces:
8 hex screwdrivers **No. 10768**: 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838786	350	350	40	2/3	8	800

TCS 12507/5



Nut spinner set
— hex profile
— with 2-component T-handle
— Chrome Alloy Steel, matt chrome-plated
— safely integrated in the modular Tool Control System (TCS)
Contains 5-pieces:
5 nut spinners **No. 12507**: 7; 8; 10; 12; 13 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838761	350	350	65	2/3	5	792

Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, workshop trolleys and workshop benches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

4691/7



Screwdriver set DRALL+
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
Contains 7-pieces:
4 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2

Product no.	Content pcs.	g
96469115	7	580

4693/9



Screwdriver set DRALL+
— black tip
— Chrome Alloy Steel, matt chrome-plated
Contains 9-pieces:
4 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.2 x 8.0 x 150; 1.6 x 10.0 x 175 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4632**: PH1; PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2

Product no.	Content pcs.	g
96469316	9	1020

4692/8



Screwdriver set DRALL+
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
Contains 8-pieces:
5 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3

Product no.	Content pcs.	g
96469215	8	840

4696SK/6



Screwdriver set DRALL+
— with impact cap
— with hex shank profile
— black tip
— with 3-component handle
— Chrome Alloy Steel, matt chrome-plated
Contains 6-pieces:
4 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.2 x 8.0 x 150 mm
2 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2

Product no.	Content pcs.	g
96469625	6	870

4694/9



TORX® screwdriver set DRALL+
— for recessed TORX® screws
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
Contains 9-pieces:
9 TORX® screwdrivers **No. 4650**: T8; T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96469415	9	730

4699/9



TORX® screwdriver set DRALL+
— for recessed TORX® screws
— with hollow tip (TORX® Tamper Resistant)
— black tip
— 3-component handle with laser marking
— Chrome Alloy Steel, matt chrome-plated
Contains 9-pieces:
9 TORX® screwdrivers with hollow tip **No. 4656**: T8; T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96469915	9	740

4891



Screwdriver set 3K DRALL®
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
Contains 6-pieces:
4 slotted screwdrivers **No. 4820**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
2 PHILLIPS® screwdrivers **No. 4830**: PH1; PH2

Product no.	Content pcs.	g
96489110	6	530



TOOLS THAT
... inspire

4892



Screwdriver set 3K DRALL®
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
Contains 8-pieces:
5 slotted screwdrivers **No. 4820**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
3 PH cross-head screwdrivers **No. 4830**: PH1; PH2; PH3

Product no.	Content pcs.	g
96489210	8	745

4899



TORX® screwdriver set 3K DRALL®
— for recessed TORX® screws
— with hollow tip (TORX® Tamper Resistant)
— black tip
— 3-component handle with non-slip fibre coating and hanging hole
— Chrome Alloy Steel, matt chrome-plated
Contains 9-pieces:
9 TORX® screwdrivers with hole **No. 4856**: T8; T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96489910	9	513

4797



Electronic screwdriver set
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking
— in roll-up tool pouch with hook-and-loop fastener made of polyester
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 7-pieces:
4 electronic slotted screwdrivers **No. 4751**: 0.3 x 1.5 x 40; 0.4 x 2.0 x 60; 0.4 x 2.5 x 75; 0.5 x 3.0 x 75 mm
3 electronic PH cross-head screwdrivers **No. 4752**: PH00; PH0; PH1

Product no.	Content pcs.	g
96479715	7	234

4754/7



Electronic TORX® screwdriver set
— for recessed TORX® screws
— rotating cap with ergonomic recess
— narrow, practical, fast rotating handle
— with laser marking
— in roll-up tool pouch with hook-and-loop fastener closure made of polyester
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 7-pieces:
7 electronic TORX® screwdrivers **No. 4754**: T4; T5; T6; T7; T8; T9; T10

Product no.	Content pcs.	g
96479716	7	262

4798



Reversible screwdriver set
— in roll-up tool pouch with hook-and-loop fastener made of polyester
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 12-pieces:
1 reversible handle (3-component)
2 reversible slotted blades: 0.6 x 3.5; 0.8 x 4.0; 1.0 x 5.5; 1.2 x 6.5 mm
1 reversible PH cross-head blade: PH1; PH2
1 reversible PZ cross-head blade: PZ1; PZ2
2 reversible hex blades: 3; 4; 5; 6 mm
2 reversible hex blades: 3; 4; 5; 6 mm (ball-ended)
3 reversible TORX® blades: T10; T15; T20; T25; T30; T40

Product no.	Content pcs.	g
96479803	12	745

TCS 4620/4640/4734/10554/8



Screwdriver set
— safely integrated in the modular Tool Control System (TCS)

Contains 8-pieces:
1 slotted screwdriver **No. 4620**: 1.0 x 5.5 x 125 mm
4 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2; PZ3
2 PH cross-head screwdrivers **No. 4734**: PH1; PH2
1 voltage tester **No. 10554**: 125-250 V


Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830275	350	175	40	1/3	8	678

L-KEYS.

10546



Slotted offset screwdrivers
— for slotted screws
— Chrome Alloy Steel, nickel-plated
— Made in Germany
— DIN 5200




Product no.	Size	L mm	a mm	b mm	g
73273001	1	90	0.6	3.5	9
73273002	2	100	0.8	4	12
73273003	3	125	1	5.5	29
73273004	4	150	1.2	8	69

10551



PH cross-head offset screwdrivers
— for PHILLIPS® screws
— Chrome Alloy Steel, nickel-plated
— Made in Germany
— DIN 5208




Product no.	Size	L mm	g
73282001	PH1; PH2	100	29
73282002	PH3; PH4	150	73

10759



HI-LOK™ L-Keys
— for **metric** hex socket screws
— with hex tip for ratchet No. 415SGH N
— with round shaft for locking the retaining ball




Product no.	Size	mm	L_1 mm	L_2 mm	g
43062002	1	2	50	100	5
43064002	2	2	100	100	8

10759a



HI-LOK™ L-Keys
— for **inch** hex socket screws
— with hex tip for ratchet No. 415SGH N
— with round shaft for locking the retaining ball




Product no.	Size	"	L_1 mm	L_2 mm	g
43560004	1	1/16	50	50	5
43560005	1	5/64	50	50	5
43560006	1	3/32	50	50	5
43564004	2	1/16	50	100	8
43564005	2	5/64	50	100	8
43564006	2	3/32	50	100	8

10760



Hex L-Keys
— for **metric** hex socket screws
— Chrome Alloy Steel, nickel-plated (0.9 mm gunmetal finish)
— DIN ISO 2936



Product no.	mm	L_1 mm	L_2 mm	g
43153090	0,9	11	33	5
43153130	1,3	13	41	7
43153150	1,5	15,5	46,5	1
43153002	2	18	52	2
43153250	2,5	20,5	58,5	4
43153003	3	23	66	5
43153004	4	29	74	10
43153005	5	33	85	18
43153006	6	38	96	30
43153007	7	41	102	43
43153008	8	44	108	59
43153010	10	50	122	103
43153012	12	57	137	169
43153014	14	70	154	261
43153017	17	80	177	442
43153019	19	89	199	603
43153022	22	102	222	895
43153024	24	114	248	1220
43153027	27	127	277	1692

10760/8




Hex L-Key set
— for **metric** hex socket screws
— Chrome Alloy Steel, nickel-plated
— DIN ISO 2936
— sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 8-pieces:
8 hex L-Keys **No. 10760**: 3; 4; 5; 6; 8; 10; 12; 14 mm

Product no.	Content pcs.	g
96435505	8	708

10760/9



Hex L-Key set
— for **metric** hex socket screws
— Chrome Alloy Steel, nickel-plated
— DIN ISO 2936
— in a labelled plastic holder for quicker identification


Contains 9-pieces:
9 hex L-Keys **No. 10760**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	Content pcs.	g
96431500	9	244

10760a



Hex L-Keys
— for **inch** hex socket screws
— Chrome Alloy Steel, nickel-plated



Product no.	"	L_1 mm	L_2 mm	g
43553003	3/64	13	41	1
43553004	1/16	16	47	1
43553005	5/64	18	52	2
43553006	3/32	20	58	3
43553008	1/8	23	66	5
43553009	9/64	26	72	7
43553010	5/32	29	74	10
43553012	3/16	33	85	15
43553014	7/32	36	91	23
43553016	1/4	38	96	32
43553020	5/16	44	108	59
43553024	3/8	50	122	75
43553032	1/2	63	145	201
43553036	5/8	76	176	380

10760a/8



Hex L-Key set
— for **inch** hex socket screws
— Chrome Alloy Steel, nickel-plated
— sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 8-pieces:
8 hex L-Keys **No. 10760a**: 3/32; 1/8; 5/32; 3/16; 7/32; 1/4; 3/8"

Product no.	Content pcs.	g
96435506	8	300

10760a/9



Hex L-Key set
— for **inch** hex socket screws
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification

Contains 9-pieces:
9 hex L-Keys **No.10760a**: 1/16; 5/64; 3/32; 1/8; 5/32, 3/16; 1/4; 5/16; 3/8"


Product no.	Content pcs.	g
96435500	9	234



10765




Hex L-Keys
— extra long design
— for **metric** hex socket screws
— Chrome Alloy Steel, nickel-plated
— DIN ISO 2936



Product no.	mm	L_1 mm	L_2 mm	g
43213015	1.5	15.5	91.5	3
43213002	2	18	102	3
43213025	2.5	20.5	114.5	5
43213003	3	23	129	9
43213004	4	29	144	20
43213005	5	33	165	31
43213006	6	38	186	50
43213007	7	41	197	74
43213008	8	44	208	100
43213010	10	50	234	179
43213012	12	57	262	287
43213014	14	70	294	440
43213017	17	80	337	742
43213019	19	89	379	1048

10765/9



Hex L-Key set
— extra long design
— for **metric** hex socket screws
— Chrome Alloy Steel, nickel-plated
— DIN ISO 2936
— in a labelled plastic holder for quicker identification


Contains 9-pieces:
9 hex L-Keys **No. 10765**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	Content pcs.	g
96432100	9	120

10766



TORX® L-Keys
— for recessed TORX® screws
— Chrome Alloy Steel, nickel-plated



Product no.	Size	L_1 mm	L_2 mm	g
43223009	T9	19	59	3
43223010	T10	20	65	3
43223015	T15	20.5	75.5	5
43223020	T20	22	87	7
43223025	T25	22.5	94.5	9
43223027	T27	25.5	105.5	15
43223030	T30	30	76	20
43223040	T40	33	119	29

10766/8



TORX® L-Key set
— for recessed TORX® screws
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification


Contains 8-pieces:
8 TORX® L-Keys **No. 10766**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96432200	8	146

10771



TORX® ball-ended L-Keys
— for recessed TORX® screws
— ball-ended at the long end of the shaft
— pivoting angle of up to 25° to each side
— Chrome Alloy Steel, nickel-plated



Product no.	Size	L_1 mm	L_2 mm	g
43273009	T9	19	67	4
43273010	T10	20	76	10
43273015	T15	20.5	86.5	10
43273020	T20	22	98	20
43273025	T25	22.5	100.5	24
43273027	T27	22.5	111.5	28
43273030	T30	30	125	30
43273040	T40	33	139	35

10771/8



TORX® ball-ended L-Key set
— for recessed TORX® screws
— ball-ended at the long end of the shaft
— pivoting angle of up to 25° to each side
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification


Contains 8-pieces:
8 TORX® L-Keys **No. 10771:** T9; T10; T15; T20; T25; T27; T30; T40

Product no.	Content pcs.	g
96432700	8	278

10767



Hex ball-ended L-Keys
— for **metric** hex socket screws
— ball-ended at the long end of the shaft
— pivoting angle of up to 25° to each side
— Chrome Alloy Steel, nickel-plated




Product no.	mm	L_1 mm	L_2 mm	g
43263130	1.3	13	81	1
43263015	1.5	15.5	91.5	2
43263002	2	18	102	3
43263025	2.5	20.5	114.5	5
43263003	3	23	129	8
43263004	4	29	144	17
43263005	5	33	165	30
43263006	6	38	186	50
43263008	8	44	208	99
43263010	10	50	234	175
43263012	12	57	262	280

10767a



Hex ball-ended L-Keys
— for **inch** hex socket screws
— ball-ended at the long end of the shaft
— pivoting angle of up to 25° to each side
— Chrome Alloy Steel, nickel-plated




Product no.	"	L_1 mm	L_2 mm	g
43573004	1/16	16	92	2
43573005	5/64	18	102	4
43573006	3/32	20	114	5
43573007	7/64	23	129	8
43573008	1/8	23	129	10
43573009	9/64	26	140	13
43573010	5/32	29	144	17
43573012	3/16	33	165	26
43573014	7/32	36	176	39
43573016	1/4	38	186	60
43573020	5/16	44	208	100
43573024	3/8	50	234	157

10767H



Hex ball-ended L-Keys
— for **metric** hex socket screws
— ball-ended and retaining ring on the long end of the shaft
— pivoting angle of up to 25° to each side
— to work quickly and safely even in hard-to-reach places
— attached screws are held reliably in place
— Chrome Alloy Steel, nickel-plated



Product no.	mm	L_1 mm	L_2 mm	g
46233003	3	23	129	8
46233004	4	29	144	17
46233005	5	33	165	30
46233006	6	38	186	50
46233008	8	44	208	100
46233010	10	50	234	175

10767H/9



Hex ball-ended L-Key set
— for **metric** hex socket screws
— ball-ended and retaining ring on the long end of the shaft
— pivoting angle of up to 25° to each side
— to work quickly and safely even in hard-to-reach places
— attached screws are held reliably in place
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification

Contains 9-pieces:
9 hex L-Keys **No. 10767H**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	Content pcs.	g
96432603	9	290

10767/9



Hex ball-ended L-Key set
— for **metric** hex socket screws
— ball-ended on the long end of the shaft
— pivoting angle of up to 25° to each side
— to work quickly and safely even in hard-to-reach places
— attached screws are held reliably in place
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification

Contains 9-pieces:
9 hex L-Keys **No. 10767**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	Content pcs.	g
96432600	9	401

10767a/13




Hex ball-ended L-Key set
— for **inch** hex socket screws
— ball-ended on the long end of the shaft
— pivoting angle of up to 25° to each side
— to work quickly and safely even in hard-to-reach places
— attached screws are held reliably in place
— Chrome Alloy Steel, nickel-plated
— in a labelled plastic holder for quicker identification

Contains 13-pieces:
13 hex L-Keys **No. 10767a**: 0.05; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"

Product no.	Content pcs.	g
96435700	13	280

L-KEY SETS IN TCS.

TCS 10760-10771/26



L-Key set
— safely integrated in the modular Tool Control System (TCS)
Contains 26-pieces:
1 hex L-Key set **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 hex ball-ended L-Key set **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 TORX® L-Key set **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838788	350	175	35	1/3	26	1000

TCS 1202/4000/10766/39



L-Key bit set
— safely integrated in the modular Tool Control System (TCS)
Contains 39-pieces:
1 bit box **No. 1202**: 1 bit holder | SL0.6 x 3.5; 0.8 x 4.0; 1.0 x 5.5; 1.2 x 6.5 mm | PH1;2; 3 |PZ1;2; 3 | T15;20;25;30 | T BO20;25;30 | INHEX 4;5;6 mm | 21-pcs.
1 bit holder ¼" **No. 4000**: L. 190 mm
1 TORX® L-Key set **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 hex ball-ended L-Key set **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838768	350	175	45	1/3	39	863



BIT TOOLS.

PH 1220-1223 PH 1231-1234



Screwdriver bits
— for PHILLIPS® screws
— external hex DIN 3126 / ISO 1173
— DIN ISO 2351-2 / ISO 8764

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08010000	PH 1220	PH0	C 6.3	1/4	25	5
08010001	PH 1221	PH1	C 6.3	1/4	25	5
08010002	PH 1222	PH2	C 6.3	1/4	25	5
08010003	PH 1223	PH3	C 6.3	1/4	25	5
08030001	PH 1231	PH1	C 8	5/16	32	9
08030002	PH 1232	PH2	C 8	5/16	32	10
08030003	PH 1233	PH3	C 8	5/16	32	10
08030004	PH 1234	PH4	C 8	5/16	32	12

PZ 1221-1223



Screwdriver bits
— for POZIDRIV® screws
— external hex DIN 3126 / ISO 1173
— ISO 8764

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08050001	PZ 1221	PZ1	C 6.3	1/4	25	5
08050002	PZ 1222	PZ2	C 6.3	1/4	25	5
08050003	PZ 1223	PZ3	C 6.3	1/4	25	5

1160-1169



Screwdriver bits
— for slotted screws
— external hex DIN 3126 / ISO 1173
— DIN ISO 2351-1 / ISO 2380-1

Product no.	Model	a x b mm	⬢ mm	⬢ "	L mm	g
08070120	1160	0.5 x 3,0	C 6.3	1/4	25	4
08070121	1161	0.5 x 4,0	C 6.3	1/4	25	4
08070122	1162	0.6 x 3,5	C 6.3	1/4	25	4
08070123	1163	0.6 x 4,5	C 6.3	1/4	25	4
08070124	1164	0.8 x 4,0	C 6.3	1/4	25	4
08070125	1165	0.8 x 5,5	C 6.3	1/4	25	6
08070126	1166	1.0 x 5,5	C 6.3	1/4	25	4
08070130	1166/1	1.2 x 6,5	C 6.3	1/4	25	6
08070127	1167	1.2 x 8,0	C 6.3	1/4	25	6
08070128	1168	1.6 x 8,0	C 6.3	1/4	25	6
08070129	1169	1.6 x 10,0	C 6.3	1/4	25	14

1350-1360



Screwdriver bits
— for internal tri-square screws XZN®
— external hex DIN 3126 / ISO 1173
— DIN 2325 (M4, M5, M6)

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08200004	1350	M4	C 6.3	1/4	25	4
08200010	1356	M5	C 6.3	1/4	25	5
08200011	1357	M6	C 6.3	1/4	25	5
08200012	1358	M8	C 8	5/16	28	10
08200013	1359	M10	C 8	5/16	38	15
08200014	1360	M12	C 8	5/16	38	20

1410-1421 1430-1435



Screwdriver bits
— for recessed TORX® screws
— external hex DIN 3126 / ISO 1173

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08130006	1410	T6	C 6.3	1/4	25	5
08130007	1411	T7	C 6.3	1/4	25	5
08130008	1412	T8	C 6.3	1/4	25	5
08130009	1413	T9	C 6.3	1/4	25	5
08130010	1414	T10	C 6.3	1/4	25	5
08130015	1415	T15	C 6.3	1/4	25	5
08130020	1416	T20	C 6.3	1/4	25	5
08130025	1417	T25	C 6.3	1/4	25	6
08130027	1418	T27	C 6.3	1/4	25	6
08130030	1419	T30	C 6.3	1/4	25	6
08130040	1420	T40	C 6.3	1/4	25	7
08130045	1421	T45	C 6.3	1/4	25	8
08140027	1430	T27	C 8	5/16	35	11
08140030	1431	T30	C 8	5/16	35	11
08140040	1432	T40	C 8	5/16	35	12
08140045	1433	T45	C 8	5/16	35	14
08140050	1434	T50	C 8	5/16	35	15
08140055	1435	T55	C 8	5/16	35	20

1440-1446



Screwdriver bits
— with hollow tip (TORX® Tamper Resistant)
— for recessed TORX® screws
— hex head DIN 3126 / ISO 1173

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08160010	1440	T10	C 6.3	1/4	26	6
08160015	1441	T15	C 6.3	1/4	26	6
08160020	1442	T20	C 6.3	1/4	26	6
08160025	1443	T25	C 6.3	1/4	26	6
08160027	1444	T27	C 6.3	1/4	26	6
08160030	1445	T30	C 6.3	1/4	26	6
08160040	1446	T40	C 6.3	1/4	26	7

1427



Screwdriver bit
— for recessed TORX® screws
— external hex DIN 3126 / ISO 1173

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08131025	1427	T25	C 6.3	1/4	65	18

1440 IP-1446 IP



Screwdriver bits
— for recessed TORX PLUS® screws
— external hex DIN 3126 / ISO 1173

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08162010	1440 IP	10IP	C 6.3	1/4	25	4
08162015	1441 IP	15IP	C 6.3	1/4	25	5
08162020	1442 IP	20IP	C 6.3	1/4	25	5
08162025	1443 IP	25IP	C 6.3	1/4	25	5
08162027	1444 IP	27IP	C 6.3	1/4	25	5
08162030	1445 IP	30IP	C 6.3	1/4	25	6
08162040	1446 IP	40IP	C 6.3	1/4	25	6

1440 TPI-1446 TPI



5-star screwdriver bits
— with hollow tip
— for recessed 5-star screws with centre pins
— external hex DIN 3126 / ISO 1173

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08161010	1440 TPI	TPI10	C 6.3	1/4	26	6
08161015	1441 TPI	TPI15	C 6.3	1/4	26	5
08161020	1442 TPI	TPI20	C 6.3	1/4	26	5
08161025	1443 TPI	TPI25	C 6.3	1/4	26	5
08161027	1444 TPI	TPI27	C 6.3	1/4	26	5
08161030	1445 TPI	TPI30	C 6.3	1/4	26	5
08161040	1446 TPI	TPI40	C 6.3	1/4	26	7

1300-1304



Screwdriver bits
— for hex socket screws
— external hex DIN 3126 / ISO 1173
— DIN ISO 2351-3 / ISO 2936

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08090003	1300	3 mm	C 6.3	1/4	25	4
08090004	1301	4 mm	C 6.3	1/4	25	5
08090005	1302	5 mm	C 6.3	1/4	25	6
08090006	1303	6 mm	C 6.3	1/4	25	6
08090008	1304	8 mm	C 6.3	1/4	30	11

1299



Screwdriver bit
— for hex socket screws
— to operate the adjustment screws on torque wrenches No. 720, 721, 721 Quick, 730, 730 Quick, 730N, 730 Fix
— external hex DIN 3126/ISO 1173

Product no.	Size mm	⬢ mm	⬢ "	L mm	g
08090002	2	C 6.3	1/4	34	4

13008



Screwdriver bits

— for TRI-WING® screws
— external hex DIN 3126 / ISO 1173

Product no.	Size	⬢ mm	⬢ "	L mm	g
08250000	0.0	C 6.3	1/4	25	5
08250001	1	C 6.3	1/4	25	5
08250002	2	C 6.3	1/4	25	5
08250003	3	C 6.3	1/4	25	5
08250004	4	C 6.3	1/4	25	5
08250005	5	C 6.3	1/4	25	5
08250006	6	C 6.3	1/4	25	8

13010



Screwdriver bits

— for TORQ-SET® screws
— external hex DIN 3126 / ISO 1173

Product no.	Size	⬢ mm	⬢ "	L mm	g
08260000	TQ0	C 6,3	1/4	25	5
08260001	TQ1	C 6,3	1/4	25	5
08260002	TQ2	C 6,3	1/4	25	5
08260003	TQ3	C 6,3	1/4	25	5
08260004	TQ4	C 6,3	1/4	25	5
08260005	TQ5	C 6,3	1/4	25	5
08260006	TQ6	C 6,3	1/4	25	5
08260008	TQ8	C 6,3	1/4	25	5
08260010	TQ10	C 6,3	1/4	25	5
08260016	1/4	C 8	5/16	32	9
08260020	5/16	C 8	5/16	32	11
08260024	3/8	C 8	5/16	32	11



1202



Bit box

— storage case with 20 bits for slotted, hex, TORX®, PHILLIPS® and POZIDRIV® screws
— self-locking magnetic bit holder with quick-change function
— in a compact, durable storage box
— transparent lid allows the user to check the contents at a glance
— with hex head for quick use

Contains 21-pieces:

1 bit holder with quick-change chuck and magnet
3 bits PHILLIPS®: PH1; PH2; PH3
3 bits POZIDRIV®: PZ1; PZ2; PZ3
4 bits slotted: 0.6 x 3.5; 0.8 x 4.0; 1.0 x 5.5; 1.2 x 6.5 mm
4 bits TORX®: T15; T20; T25; T30
3 bits TORX® with hole: T20; T25; T30
3 bits INHEX: 4; 5; 6 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96080110	120	60	33	21	222

1203



Bit box

— storage case with 10 bits for hex, PHILLIPS® and POZIDRIV® screws
— compact: many tools - little space required
— including practical stand function

Contains 11-pieces:

1 bit holder with quick-change chuck and magnet
3 bits PHILLIPS®: PH1; PH2; PH3
3 bits POZIDRIV®: PZ1; PZ2; PZ3
4 bits INHEX: 3; 4; 5; 6 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96080115	100	60	12	11	110

1204/8



5-star bit box

— storage case with 7 bits for internal 5-star screws and bit holder

Contains 8-pieces:

1 bit holder **No. 412**: L. 25 mm

7 bits with hollow tip 5-star: TPI10; TPI15; TPI20; TPI25; TPI27; TPI30; TPI40

Product no.	L mm	W mm	H mm	Content pcs.	g
96081113	100	81	31	8	104

1204/21-1



Bit box

— storage case with 20 bits for TORX®, hex, PHILLIPS® and POZIDRIV® screws

Contains 21-pieces:

1 bit holder with quick-change chuck and magnet

4 bits PHILLIPS®: PH1; PH2 (2x); PH3

4 bits POZIDRIV®: PZ1; PZ2 (2x); PZ3

6 bits TORX®: T10; T15; T20 (2x); T25 (2x); T27; T30; T40

3 bits INHEX: 4; 5; 6 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96080121	100	81	31	21	186

1204/21-2



Bit box

— storage container with 20 bits for slotted, TORX®, TORQ-SET®, hex, PHILLIPS® screws

Contains 21-pieces:

1 bit holder with quick-change chuck and magnet

3 bits PHILLIPS®: PH1; PH2; PH3

4 bits slotted: 0.5 x 4.0; 0.6 x 4.5; 0.8 x 5.5; 1.2 x 6.5 mm

6 bits TORX®: T10; T15; T20; T25; T30; T40

3 bits INHEX: 4; 5; 6 mm

4 bits TORQ-SET®: 4; 6; 8; 10

Product no.	L mm	W mm	H mm	Content pcs.	g
96080122	100	82	32	21	181

1206



Bit box

— with colour marking

— robust box with transparent lid with bits for slotted, TORX®, hex, PHILLIPS® and POZIDRIV® screws

— $^1/_4$" external hex drive according to DIN 3126 / ISO 1173

Contains 56-pieces:

1 bit holder with quick-change chuck with magnet

3 bits slotted: 4; 5; 6 mm (2x each), L. 25 mm

3 bits PHILLIPS®: PH1; PH2; PH3 (3x each), L. 25 mm

3 bits POZIDRIV®: PZ1; PZ2; PZ3 (3x each), L. 25 mm

7 bits TORX®: T10; T15; T20; T25; T27; T30; T40 (2x each), L. 25 mm

7 bits TORX® with hole: T10; T15; T20; T25; T27; T30; T40, L. 25 mm

3 bits INHEX: 3; 4; 5 mm, L. 25 mm

1 bit slotted: 6 mm, L. 75 mm


2 bits PHILLIPS®: PH2; PH3, L. 75 mm

2 bits POZIDRIV®: PZ1; PZ2, L. 75 mm

2 bits TORX®: T20; T25, L. 75 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96080156	128	100	37	56	490

TCS 4008/8/52



Bit ratchet screwdriver set
— safely integrated in the modular Tool Control System (TCS)
Contains 60-pieces:
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit holder 1/4" **No. 412/1**: L. 20 mm
1 bit holder 3/8" **No. 442**: L. 32 mm
1 bit holder 1/4" **No. 1200/1**: L. 72 mm
1 bit quick-change holder 1/4" **No. 3825/1:** L. 62 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
10 bits INHEX **No. 1300**: 3 mm (2x); 4 mm (2x); 5 mm (2x); 6 mm (2x); 8 mm (2x)
8 bits PHILLIPS® 1/4" **No. PH 1220-1223**: PH0 (2x); PH1 (2x); PH2 (2x); PH3 (2x)
6 bits POZIDRIV® 1/4" **No. PZ 1221-1223**: PZ1 (2x); PZ2 (2x); PZ3 (2x)
12 bits TORX® 1/4" **No. 1414-1420**: T10 (2x); T15 (2x); T20 (2x); T25 (2x); T30 (2x); T40 (2x)
12 bits TORX® with hole 1/4" **No. 1440-1446**: T10 (2x); T15 (2x); T20 (2x); T25 (2x); T30 (2x); T40 (2x)
4 bits slotted 1/4" **No. 1161-1166/1**: 0.5 x 4.0; 0.6 x 4.5; 0.8 x 5.5; 1.2 x 6.5 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838773	350	175	50	1/3	60	753



TCS 4008/4009/1206/4



Bit set
— safely integrated in the modular Tool Control System (TCS)
Contains 59-pieces:
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830265	350	175	63	1/3	59	1138

4008/27/1R




Bit ratchet screwdriver set
— in a sturdy, stackable ABS plastic box
Contains 29-pieces:
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
3 bits PHILLIPS® 1/4" **No. PH 1221-1223**: PH1; PH2; PH3
3 bits POZIDRIV® 1/4" **No. PZ 1221-1223**: PZ1; PZ2; PZ3
6 bits TORX® with hole 1/4" **No. 1440-1446**: T10; T15; T20; T25; T30; T40
3 bits INHEX 1/4" **No. 1301-1303**: 4; 5; 6 mm
3 bits slotted 1/4" **No. 1163, 1165, 166/1**: 0.6 x 4.5; 0.8 x 5.5; 1.2 x 6.5 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
9 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 10; 11; 13 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96182203	325	135	60	29	955

4000



Bit holder
— for 1/4" screwdriver bits with external hex
— internal hex with collar-thrust spring
— with 3-component handle
— DIN 3126 / ISO 1173 Form C 6.3




Product no.	"	L1 mm	L2 mm	b mm	g
18073026	1/4	75	190	11	119

12503



Bit holder
— extra short version
— for 1/4" screwdriver bits with external hex
— internal hex socket with magnet
— DIN 3126 / ISO 1173 Form C 6.3




Product no.	"	L1 mm	L2 mm	g
18110016	1/4	10	65	50

4009



Bit holder
— for 1/4" screwdriver bits with external hex
— hex socket with magnet
— with 2-component T-handle
— DIN 3126 / ISO 1173 Form C 6.3




Product no.	"	d mm	L1 mm	L2 mm	g
18093016	1/4	10	150	175	108

12504



Bit holder
— with flexible shaft
— for 1/4" screwdriver bits with external hex
— with 3-component handle
— DIN 3126 / ISO 1173 Form C 6.3




Product no.	"	L1 mm	L2 mm	g
18103016	1/4	175	290	168

415B 2K



Bit ratchet
— reversible
— 22 teeth
— with 2-component handle
— internal 1/4" hex drive with collar-thrust spring
— for 1/4" screwdriver bits
— DIN 3126 / ISO 1173 Form D 6.3



Product no.	"	°	Number of teeth	L mm	b mm	a mm	g
11131011	1/4	16 °	22	117	22	12	76

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

STAHLWILLE 1/4" BIT FINE-TOOTH MINI RATCHET – tight spaces need great tools.

418B



Ergonomic.

The bit fine-tooth mini ratchet with steel handle fits securely and comfortably in the hand. For fatigue-free work.



Resilient.

Unlike conventional fine-tooth ratchets, eight pairs of teeth mesh simultaneously. For maximum load-bearing capacity while also ensuring smooth running and durability.



Compact.

With a length of only 9 cm, the bit fine-tooth mini ratchet with steel handle is the perfect companion in particularly tight installation spaces. And our fine-tooth ratchets have 80 teeth and a working angle of only 4.5°.



Reliable.

FOD preventative. Also ideal for safety-critical sectors such as aviation, thanks to the screwless design.

4150B


Spare parts set for bit ratchet
Contains 9-pieces:
1 pinion; 1 pawl; 1 lever with pin; 1 ball; 2 compression springs; 2 screws M 1.7 x 8; 1 cover plate

Product no.	for model	Content pcs.	g
19010011	415B	9	20

415SGB N



Bit fine-tooth ratchet
— reversible
— 80 teeth
— with steel handle
— internal 1/4" hex drive with collar-thrust spring
— for 1/4" screwdriver bits
— for working in tight spaces, with a working angle of just 4.5°
— FOD-preventive due to screwless design
— DIN 3126 / ISO 1173 D 6.3




Product no.	"	°	L mm	b mm	a mm	g
11132020	1/4	4.5 °	117	22.6	10.7	85



418B



Bit fine-tooth mini ratchet
— short version
— reversible
— 80 teeth
— with steel handle
— internal 1/4" hex drive with collar-thrust spring
— for 1/4" screwdriver bits
— for working in tight spaces, with a working angle of just 4.5°
— FOD-preventive due to screwless design
— DIN 3126 / ISO 1173 Form D 6.3




Product no.	"	°	L mm	b mm	a mm	g
11133030	1/4	4.5 °	90	22.5	11	70

419B



Bit fine-tooth ratchet
— reversible, with a push-out function
— 80 teeth
— with 2-component handle
— internal 1/4" hex drive with collar-thrust spring
— for 1/4" screwdriver bits
— for working in tight spaces, with a working angle of just 4.5°
— FOD-preventive due to screwless design
— DIN 3126 / ISO 1173 Form D 6.3



Product no.	"	°	Number of teeth	L mm	b mm	a mm	g
11131010	1/4	4.5 °	80	115	22	16	76

4153B


Spare parts set for bit ratchet
Contains 8-pieces:
1 locking shell; 1 switching lever; 1 cover plate; 1 compression spring; 1 bit rotary part with push-out function; 1 ball; 1 rubber ring; 1 repair and maintenance instruction

Product no.	for model	○ "	Content pcs.	g
19010014	419B	1/4	8	62

25B



Ratcheting bit holder spanner
— reversible
— with magnetic holder for screwdriver bits
— angled
— chrome-plated




Product no.	○ "	d_1 mm	d_2 mm	L mm	a_1 mm	a_2 mm	g
41541620	1/4 x 5/16	20	23	138	15	17	105

4008-1



Bit ratchet screwdriver
— high load mechanism with 48 teeth (7.5° working angle)
— easy bit change with magnetic internal hex
— quick change of direction using the changeover ring (left, right and fixed)
— knurled zone for fast pre-turning of the screws
— 1/4" bits can be used with bit adaptor No. 3116 (external hex and external square 1/4")
— pop-up storage compartment for 6 bits at the end of the handle for easy access
— with 2-component handle
— for bits with external hex 1/4" DIN 3126 / ISO 1173 Form C 6.3




Product no.	Size	○ "	∠	Number of teeth	d mm	L_1 mm	L_2 mm	g
18120001	1	1/4	7.5 °	48	10	127	250	220

4008-2



Bit ratchet screwdriver
— high load mechanism with 48 teeth (7.5° working angle)
— easy bit change with magnetic internal hex
— quick change of direction using the changeover ring (left, right and fixed)
— knurled zone for fast pre-turning of the screws
— 1/4" sockets can be used with bit adaptor No. 3116 (external hex and external square 1/4")
— with 2-component handle
— for bits with external hex 1/4" DIN 3126 / ISO 1173 Form C 6.3



Product no.	Size	○ "	∠	Number of teeth	d mm	L_1 mm	L_2 mm	g
18120002	2	1/4	7.5 °	48	10	25	95	137

3825/1



Bit quick-change holder
— machine-operated bits
— for screwdriver bits with external hex 1/4"
— with quick-change chuck
— external hex drive DIN 3126 / ISO 1173 Form C 6.3


Product no.	○ mm	○ "	L mm	g
38250002	D 6.3	1/4	62	27



3115



Bit adaptor
- for connecting sockets to tools
- for torque screwdrivers No. 760 and No. 775
- for manual sockets with internal square drive 6.3 (1/4")
- square with spring-loaded ball
- steel grey, oiled surface
- external square DIN 3120 / ISO 1174-1
- external hex drive DIN 3126 / ISO 1173



Product no.	■ mm	■ "	⬣ mm	⬣ "	d mm	L mm	h mm	g
31150000	A 6.3	1/4	E 6.3	1/4	8.9	50	8	16

3116



Bit adaptor
- for connecting sockets to tools
- for manual sockets with internal square drive 6.3 (1/4")
- square with spring-loaded ball
- steel grey, oiled surface
- external square DIN 3120 / ISO 1174-1
- external hex drive DIN 3126 / ISO 1173

Product no.	■ mm	■ "	⬣ mm	⬣ "	L mm	h mm	g
31160000	A 6.3	1/4	C 6.3	1/4	25	8	10


MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

3116/1QR-3316/1QR



QuickRelease bit adaptors
- with external hex drive
- for machine-operated IMPACT sockets DIN 3129 / ISO 2725-2 with internal square DIN 3121 / ISO 1174-2
- with a larger diameter for improved contact with the IMPACT sockets
- Chrome Alloy Steel, gunmetal finish




Product no.	Model	■ mm	■ "	⬣ mm	⬣ "	L mm	h mm	g
31161001	3116/1QR	E 6.3	1/4	E 6.3	1/4	50	11.2	18
32161001	3216/1QR	E 10	3/8	E 6.3	1/4	50	14.6	26
33161001	3316/1QR	E 12.5	1/2	E 6.3	1/4	50	19.2	46

3117-3119



Bit adaptors
- for machine-operated sockets with internal square drive 6.3 (1/4")
- steel grey, oiled surface
- external square DIN 3121 / ISO 1174-2 with spring-loaded pin
- external hex drive DIN 3126 / ISO 1173



Product no.	Model	■ mm	■ "	⬣ mm	⬣ "	d mm	L mm	h mm	g
31170000	3117	E 6.3	1/4	E 6.3	1/4	8.9	50	8	16
31180000	3118	E 10	3/8	E 6.3	1/4	15.5	50	13	23
31190000	3119	E 12.5	1/2	E 6.3	1/4	18	50	15	34

412



Bit holder
- internal 1/4" hex drive with collar-thrust spring
- bits are easy to insert, lock securely into place and can be easily pulled out again
- HPQ® heavy duty steel
- DIN 3126 Form D 6.3/ISO 1173 Form D 6.3

Product no.	○ "	○ mm	○ "	d mm	L mm	g
11180010	1/4	D 6,3	1/4	11,6	25	14

412-1



Bit holder
- internal 1/4" hex drive with collar-thrust spring
- 10 mm external hex for use in tools with 10 mm internal hex drive or internal double hex drive (e.g. FLEXI double-ended, flexi-joint spanners, flex handles, box spanner, ratcheting ring spanner, etc.)
- bits are easy to insert, lock securely into place and can be easily pulled out again
- HPQ® heavy duty steel
- DIN 3126 Form D 6.3 / ISO 1173 Form D 6.3

Product no.	○ "	○ mm	○ "	d mm	L mm	g
11180020	1/4	D 6,3	1/4	11,6	20	11

442



Bit holder
- internal 1/4" hex drive with collar-thrust spring
- bits are easy to insert, lock securely into place and can be easily pulled out again
- DIN 3126 Form D 6.3 / ISO 1173 Form D 6.3

Product no.	○ "	○ mm	○ "	d mm	L mm	g
12180026	3/8	D 6,3	1/4	16,5	32	30

443



Bit holder
- internal 5/16" hex drive with collar-thrust spring
- bits are easy to insert, lock securely into place and can be easily pulled out again
- DIN 3126 Form D 8 / ISO 1173 Form D 8

Product no.	○ "	○ mm	○ "	d mm	L mm	g
12180030	3/8	D 8	5/16	16,5	32	39

543



Bit holder
- internal 5/16" hex drive with collar-thrust spring
- bits are easy to insert, lock securely into place and can be easily pulled out again
- DIN 3126 Form D 8 / ISO 1173 Form D 8

Product no.	○ "	○ mm	○ "	d mm	L mm	g
13180010	1/2	D 8	5/16	22	38	65

3100




Bit holder
- with strong magnet
- with bit holder for screwdriver bits
- chrome-plated sleeve, hex shaft in steel grey
- external hex 1/4", DIN 3126 / ISO 1173

Product no.	○ mm	○ "	L mm	g
31000000	D 6.3	1/4	72	37

1242-1250



Screwdriver bits
- machine-operated bits
- for slotted screws
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3
- DIN 3127 / ISO 2351



Product no.	Model	a x b mm	⬢ mm	⬢ "	L mm	g
08300635	1242	0.6 x 3,5	E 6.3	1/4	50	8
08300840	1244	0.8 x 4,0	E 6.3	1/4	50	9
08301055	1246	1.0 x 5,5	E 6.3	1/4	50	10
08301265	1248	1.2 x 6,5	E 6.3	1/4	50	11
08301680	1250	1.6 x 8,0	E 6.3	1/4	50	14

1260-1262



Screwdriver bits
- machine-operated bits
- for PHILLIPS® screws (DIN 5260)
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3
- DIN 3128 / ISO 8764

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08310001	1260	PH1	E 6.3	1/4	50	10
08310002	1261	PH2	E 6.3	1/4	50	11
08310003	1262	PH3	E 6.3	1/4	50	11

1270-1272



Screwdriver bits
- machine-operated bits
- for POZIDRIV® screws
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3
- DIN 3128 / ISO 8764

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08320001	1270	PZ1	E 6.3	1/4	50	10
08320002	1271	PZ2	E 6.3	1/4	50	11
08320003	1272	PZ3	E 6.3	1/4	50	11

1280-1284



Screwdriver bits
- machine-operated bits
- for hex socket screws
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3
- DIN 7426 / ISO 2936

Product no.	Model	⬢ mm	⬢ "	L mm	g
08330003	1280	3	1/4	50	9
08330004	1281	4	1/4	50	10
08330005	1282	5	1/4	50	12
08330006	1283	6	1/4	50	13
08330008	1284	8	1/4	50	18

1290-1296




Screwdriver bits
- machine-operated bits
- for recessed TORX® screws
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3

Product no.	Model	Size	⬢ mm	⬢ "	L mm	g
08340010	1290	T10	E 6.3	1/4	70	14
08340015	1291	T15	E 6.3	1/4	70	14
08340020	1292	T20	E 6.3	1/4	70	14
08340025	1293	T25	E 6.3	1/4	70	15
08340027	1294	T27	E 6.3	1/4	70	16
08340030	1295	T30	E 6.3	1/4	70	16
08340040	1296	T40	E 6.3	1/4	70	18

2801



Socket bits
- machine-operated bits
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3
- hex with strong magnet
- Chrome Alloy Steel, polished, painted with a clear finish



Product no.	⌀ mm	⬢ mm	⬢ "	d mm	L mm	g
28011007	7	E6,3	1/4	12	50	23
28011008	8	E6,3	1/4	13	50	26
28011010	10	E6,3	1/4	15.5	50	31
28011013	13	E6,3	1/4	18.7	50	44

13006



Special socket bit
- machine-operated bits
- for plugs in the Airbus A320-A340 electronic rack
- external hex drive in accordance with DIN 3126 / ISO 1173 Form E 6.3

Product no.	⬢ mm	⬢ "	d mm	L mm	g
08230001	E 6.3	1/4	11	50	32

4060



IMPACT bit and driver set
— for M5-M10 screws
— in a sturdy, stackable ABS plastic box
Contains 15-pieces:
1 IMPACT driver **No. 4030**
1 bit adaptor 3/8" **No. 4035**
1 bit adaptor 1/2" **No. 4036**
5 bits slotted **No. 4040-4044**: 1 x 7; 1.4 x 9; 1.5 x 13; 1.6 x 10; 2 x 12 mm
3 bits PHILLIPS® **No. 4050-4052**: PH2; PH3; PH4
4 bits hex **No. 4055-4058**: 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96323001	230	130	60	15	1264

4030



IMPACT driver
— with bit holder for screwdriver bits No. 4040-4058
— for M5-M10 screws
— torque 120 N·m

Product no.	■ "	○ "	L mm	g
32200005	3/8	3/8	138	604


4035/4036



Bit adaptors
— with external hex drive
— for IMPACT driver No. 4030

Product no.	Model	■ "	⬣ "	L mm	H mm	g
32210001	4035	3/8	3/8	38	12	34
33210001	4036	1/2	3/8	38	17	43

4040-4044



Screwdriver bits
— for slotted screws
— for IMPACT driver No. 4030

Product no.	Model	a x b mm	⬣ "	L mm	g
08400010	4040	1.0 x 7	3/8	40	17
08400014	4041	1.4 x 9	3/8	40	20
08400015	4044	1.5 x 13	3/8	40	24
08400016	4042	1.6 x 10	3/8	40	21
08400020	4043	2.0 x 12	3/8	40	20

4050-4052



Screwdriver bits
— for PHILLIPS® screws
— for IMPACT driver No. 4030
— DIN ISO 8764

Product no.	Model	Size	⬣ "	L mm	g
08410002	4050	PH2	3/8	35	17
08410003	4051	PH3	3/8	35	17
08410004	4052	PH4	3/8	35	17


4055-4058



Screwdriver bits
— for hex socket screws
— for IMPACT driver No. 4030

Product no.	Model	⬣ mm	⬣ "	L mm	g
08420005	4055	5	3/8	35	16
08420006	4056	6	3/8	35	16
08420008	4057	8	3/8	35	19
08420010	4058	10	3/8	35	23


WB 625
STAHLWILLE



6 Factory and workshop equipment

283 **Tool trolleys and workbenches**

288 **Accessories for tool trolleys and workbenches**

292 **Tool storage**

298 **Perforated panels, hooks and holders**

STAHLWILLE WORKSHOP EQUIPMENT –
The right solution for everyone.

STAHLWILLE tool storage systems impress with their modern design, high level of safety and well thought-out details. Whether workbenches, tool trolleys or tool boxes – STAHLWILLE offers a variety of variants, with many options for customisation.

MOBILE



Well thought-out.

Three-stage safety concept: Central locking with recessed cylinder lock located on the side. The individual locking mechanism prevents unintentional opening during transit – the anti-tilt protection makes it impossible to pull out multiple drawers simultaneously.

Clearly arranged.

All drawers are 100% extendable. In combination with the STAHLWILLE TCS inlays, optimal visibility is guaranteed.

More volume.

Space marvel. The 98 PRO tool trolley offers 100% more drawer volume compared to the 93 and 95 PRO models.



Generous.

7 large drawers offer plenty of storage space. The spacious cabinet section features an adjustable-height shelf, two rubberised cable outlets, and a cable duct that can be unscrewed at the back. Includes an adjustable paper roll holder for paper rolls up to 30 cm wide.

Comfortable.

Only at STAHLWILLE: the ergonomic working height of 104 cm enables comfortable work at the workbench.

Agile.

Oil and acid-resistant smooth-running wheels (Ø 125 mm) with thread guards to protect the bearings from dirt and fibres, with 2 locking brakes.



Comparison of models

					
93/6	**95/6 PRO**	**95/7 PRO**	**95/8 PRO**	**98/7 PRO**	**98/8 PRO**
481 x 877 x 1000 mm	496 x 827 x 1020 mm	496 x 827 x 1020 mm	496 x 827 x 1020 mm	651 x 1001 x 1020 mm	651 x 1001 x 1020 mm
RAL 7016; RAL 9005	RAL 7016; RAL 9005	RAL 7016; RAL 9005	RAL 7016; RAL 9005	RAL 7016; RAL 9005	RAL 7016; RAL 9005
6	6	7	8	7	8
351 x 530 x 68 mm (4x) 351 x 530 x 145 mm (1x) 351 x 530 x 198 mm (1x)	346 x 528 x 73 mm (2x) 346 x 528 x 113 mm (2x) 346 x 528 x 153 mm (1x) 346 x 528 x 170 mm (1x)	346 x 528 x 73 mm (4x) 346 x 528 x 113 mm (2x) 346 x 528 x 170 mm (1x)	346 x 528 x 73 mm (7x) 346 x 528 x 170 mm (1x)	695 x 525 x 73 mm (4x) 695 x 525 x 113 mm (2x) 695 x 525 x 170 mm (1x)	695 x 525 x 73 mm (7x) 695 x 525 x 170 mm (1x)
30 kg 30 kg 45 kg	30 kg 30 kg 30 kg 45 kg	30 kg 30 kg 45 kg	30 kg 45 kg	40 kg 40 kg 60 kg	40 kg 60 kg
500 kg	750 kg	750 kg	750 kg	1,400 kg	1,400 kg


additional colours available: body blue, RAL 2703035; drawers black, RAL 9005; body red, RAL 3020; drawers black, RAL 9005

TOOL TROLLEYS AND WORKBENCHES.

612 ST



Service trolley
- 1 drawer
- 2 shelves
- rubber castors with 2 parking brakes



Product no.	Colour samples	Colour	Number of drawers	kg
81300612		green, RAL 6024; anthracite, RAL 7016	1	25.5




Key features of the TTS 93/6 tool trolley
Perfect order for the workshop

- two-stage safety concept:
  - central locking through cylinder lock with folding key
  - tilt protection - it is not possible to pull out several drawers at the same time
- 2 handles
- all-round impact protection
- durable plastic tray made of ABS with compartments for small parts
- oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, and 2 parking brakes
- perforation on both sides for hooks No. 8031-8041, e.g. for larger tools
- with paper roll holder
- can be equipped with STAHLWILLE TCS inlays

93/6



Tool trolley
- 6 easily removable drawers, black, full-extension runners with bearing cage guide



Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200154	93/6 A		anthracite, RAL 7016; black, RAL 9005	6	57

TOOLS THAT ... inspire


Key features of the TTS 95 PRO tool trolleys
Perfect order for the workshop


- three-stage safety concept:
  - central locking with a lateral cylinder lock and folding key
  - individual locks prevent inadvertent opening during transit
  - tilt protection - it is not possible to pull out several drawers at the same time
- steel handle with reinforced body connection
- all-round collision protection with impact damping
- tightly welded, scratch-resistant worktop prevents liquids from penetrating
- oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, and 2 parking brakes
- paper roll holder and spray can holder included
- perforation on both sides for hooks No. 8031-8041, e.g. for larger tools
- can be equipped with STAHLWILLE TCS inlays

95/7 PRO



Tool trolleys
- 7 easily removable drawers, black, full-extension runners with bearing cage guide







Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200163	95/7 A PRO		anthracite, RAL 7016; black, RAL 9005	7	71.5
81200164	95/7 B PRO		blue, RAL 270 30 35; black, RAL 9005	7	71.5
81200165	95/7 R PRO		red, RAL 3020; black, RAL 9005	7	71.5

95/6 PRO



Tool trolleys
- 6 easily removable drawers, black, full-extension runners with bearing cage guide







Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200160	95/6 A PRO		anthracite, RAL 7016; black, RAL 9005	6	71.5
81200161	95/6 B PRO		blue, RAL 270 30 35; black, RAL 9005	6	71.5
81200162	95/6 R PRO		red, RAL 3020; black, RAL 9005	6	71.5

95/8 PRO



Tool trolleys
- 8 easily removable drawers, black, full-extension runners with bearing cage guide





Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200166	95/8 A PRO		anthracite, RAL 7016; black, RAL 9005	8	71.5
81200167	95/8 B PRO		blue, RAL 270 30 35; black, RAL 9005	8	71.5
81200168	95/8 R PRO		red, RAL 3020; black, RAL 9005	8	71.5

Key features of the TTS 98 PRO tool trolleys
Perfect order for the workshop


- three-stage safety concept:
  - central locking with a lateral cylinder lock and folding key
  - individual locks prevent inadvertent opening during transit
  - tilt protection - it is not possible to pull out several drawers at the same time
- 100% increased drawer volume compared to the TTS 93 and TTS 95 PRO tool trolleys
- steel handle with reinforced connection to body
- all-round impact protection
- tightly welded, scratch-resistant worktop prevents liquids from penetrating
- oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, and 2 parking brakes
- paper roll holder and spray can holder included
- perforation on both sides for hooks No. 8031-8041, e.g. for larger tools
- can be equipped with STAHLWILLE TCS inlays

98/8 PRO



Tool trolleys

- 8 easily removable drawers, black, full-extension runners with bearing cage guide




Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200172	98/8 A PRO		anthracite, RAL 7016; black, RAL 9005	8	114
81200173	98/8 B PRO		blue, RAL 270 30 35; black, RAL 9005	8	114
81200174	98/8 R PRO		red, RAL 3020; black, RAL 9005	8	114

98/7 PRO



Tool trolleys

- 7 easily removable drawers, black, full-extension runners with bearing cage guide



Product no.	Model	Colour samples	Colour	Number of drawers	kg
81200169	98/7 A PRO		anthracite, RAL 7016; black, RAL 9005	7	114
81200170	98/7 B PRO		blue, RAL 270 30 35; black, RAL 9005	7	114
81200171	98/7 R PRO		red, RAL 3020; black, RAL 9005	7	114




Key features of the WB 621 and WB 625 workbenches
Perfect order for the workshop

- three-stage safety concept:
  - central locking with a lateral cylinder lock and folding key
  - individual locks prevent inadvertent opening during transit
  - tilt protection - it is not possible to pull out several drawers at the same time
- large work surface with multiplex beechwood worktop, FSC certified, 1150 x 500 x 30 mm
- stainless steel decorative trim
- oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, and 2 parking brakes
- paper roll holder
- perforation on the side for hooks No. 8031-8041, e.g. for larger tools
- can be equipped with STAHLWILLE TCS inlays

WB 621



Mobile workbench
- 7 easily removable drawers, black, full-extension runners with bearing cage guide
- separate lockable cabinet compartment with magnetic bracket and adjustable shelves (70 mm grid)
- drawers and cabinet section close at the same time
- RAL 7016 body, RAL 9005 drawers and cabinet compartment, in durable industrial powder coating
- cabling is possible through 2 rubberised feed throughs and a removable cable channel on the back
- available separately: e-kit consisting of a magnetic multi-plug with 2 USB ports, a magnetic holder (flexible positioning on any metallic part of the workbench), and a cable holder




Product no.	Colour samples	Colour	Number of drawers	kg
85010621		anthracite, RAL 7016; black, RAL 9005	7	97.5

WB 625



Mobile workbench
- 7 easily removable drawers, black, full-extension runners with bearing cage guide
- RAL 7016 body, RAL 9005 drawers and cabinet compartment, in durable industrial powder coating



Product no.	Colour samples	Colour	Number of drawers	kg
85010625		anthracite, RAL 7016; black, RAL 9005	7	97




WB 630





Workbench

— ready-to-install design
— tool chest bracket including fasteners material suitable for No. 93 TOP BOX
— lockable drawer (including 2 keys) with full extension runners with bearing cage guide
— with non-slip drawer mat
— large work surface with rubberwood worktop, 30 mm thick, with FSC certification
— integrated perforated back panel for fitting tools and e.g. hooks, spray can holder, paper roll holder, etc.
— with EU 3-way plug adaptor, 2 USB ports, and 2 rubberised cable grommets
— height-adjustable legs (by 305 mm) with levelling feet (M12)
— body RAL 7016, in durable, industrial powder coating
— dimensions: width 2,000 mm, depth 725 mm, adjustable height with back panel: 1,281-1,586 mm, without back panel: 773-1,078 mm
— internal drawer dimensions: 530 x 350 x 74.5 mm
— can be equipped with STAHLWILLE TCS inlays
— available separately: Tool box TOP BOX 93 (81200157) and tool assortment TCS 821/6 (97830255)






Product no.	Colour samples	Colour	Number of drawers	kg
85010630		anthracite, RAL 7016; black, RAL 9005	1	102.5



ACCESSORIES FOR TOOL TROLLEYS AND WORKBENCHES.

Suitable accessories at a glance

	Product no.	Description	Model	Suitable for
	**90432802**	Protective cover	Cover TTS 93+TTS95PRO	93/6, 95 PRO
	**90432806**	Rubber mat	95 GR	95 PRO
	**83812070**	Empty tray for small components	LE 912	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 612 ST
	**81490001**	Wheel set	R 95	93/6, 95 PRO, WB 621, WB 625
	**81490005**	Wheel set	R 98	93/6, 95 PRO, 98 PRO, WB 621, WB 625
	**89480003**	Wheel set	R 95/98S	93/6, 95 PRO, 98 PRO, WB 621, WB 625
	**81490007**	Wheel set	R 630	WB 630
	**90432736**	Shelf	WB 621 CS	WB 621
	**90432731**	Multiplex beechwood worktop	WB 621/625 WP	WB 621, WB 625
	**81484002**	Drawer divider	VE 50-150 2/3	93/6, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 93 TOP BOX, 612 ST
	**81484001**	Drawer divider	VE 50-150 3/3	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 612 ST
	**81483004**	Paper roll holder	PRH 925	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630
	**89011053**	Waste bin	95/98 AB	95 PRO, 98 PRO, WB 630
	**89010040**	Cable holder	KH 91	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630
	**90432719**	Spray can holder	SDH 922	95 PRO, 98 PRO, WB 630
	**90432727**	Spray can holder	SDH 923	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630
	**89010041**	Laptop holder	LH 928	WB 621, WB 625, WB 630
	**89010042**	Laptop holder adaptor (to be used only in combination with LH 928)	LH 928/A	93/6, 95 PRO, 98 PRO


93/95 CO



Protective cover
- protection against dust, dirt and splashing water
- for tool trolleys 93 PRO and 95 PRO (also suitable for 90, 95, 95VA models)
- front opening with 2 zippers
- drawers can be used without removing the cover
- durable black nylon fabric

Product no.	for model	L mm	W mm	H mm	g
90432802	93/6, 95 PRO	890	480	990	1768

95 GR



Rubber mat
- for the tool trolleys 95 PRO
- protects the stainless steel surface of the tray
- exact fit, 3 mm thick with fine grooves
- groove direction in longitudinal orientation
- styrene-butadiene rubber, oil and skydrol resistant

Product no.	for model	L mm	W mm	H mm	g
90432806	95 PRO	565	414	3	780

LE 912



Empty tray for small components
- with compartments for small parts such as screws, nuts, etc.
- oil and skydrol-resistant
- each has 8 compartments of 60 x 80 mm and 80 x 80 mm
- each has 2 compartments of 100 x 165 mm and 50 x 330 mm

Product no.	for model	g
83812070	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 612 ST	330

PRH 925



Paper roll holder
- universal paper roll holder, suitable for all models with side perforations
- attaches with 2 fixing screws to the perforated panel

Product no.	for model	Roll width max. mm	g
81483004	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	300	730

KH 91



Cable holder
- for storing cables and hoses

Product no.	for model	L mm	W mm	H mm	g
89010040	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	200	153	170	780

LH 928



Laptop holder
- for mounting on the worktops of workbenches No. WB 621, WB 625 and WB 630, 20-60 mm thickness
- suitable for 10-17" laptops
- for monitors up to 32" with VESA hole (75 x 75 mm and 100 x 100 mm)
- adjustment range of laptop holder: 287-430 mm
- height adjustable 30-400 mm, 180° rotatable
- vertical tilt angle: 55-90°
- made of aluminium tube
- max. load: 6.5 kg
- also suitable for tool trolleys 93, 95 PRO, 98 PRO in combination with adaptor 89010042

Product no.	for model	L mm	W mm	H mm	kg
89010041	WB 621, WB 625, WB 630	445	245	150	3.5

LH 928/A



Laptop holder adaptor
— mounting bracket for laptop holders on tool trolleys
— for attachment to the side perforations of the 93, 95 PRO, 98 PRO tool trolleys
— robust industrial powder coating

Product no.	for model	kg
89010042 *	93/6, 95 PRO, 98 PRO	1.33

* only to be used in combination with LH 928


SDH 923



Spray can holder
— small holder for 3 spray cans

Product no.	for model	L mm	W mm	H mm	g
90432727	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	237	81	70	566


SDH 922



Spray can holder
— large holder for 3 spray cans

Product no.	for model	L mm	W mm	H mm	g
90432719	95 PRO, 98 PRO, WB 630	300	84	70	650


WB 621 CS



Shelf
— additional shelf for workbench WB 621

Product no.	for model	L mm	W mm	H mm	kg
90432736	WB 621	440	327	33	1.31


VE 50-150 2/3



Drawer divider
— for variable drawer layouts
— includes 1 galvanised front and rear panel each, plus 3 dividing panels
— on TCS format 2/3 drawer

Product no.	for model	L mm	W mm	H mm	Size	g
81484002	93/6, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 93 TOP BOX, 612 ST	350	75	20	2/3	758

VE 50-150 3/3



Drawer divider
— for variable drawer layouts
— includes 1 galvanised front and rear panel each, plus 3 dividing panels
— on TCS format 3/3 drawer

Product no.	for model	L mm	W mm	H mm	Size	g
81484001	93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 612 ST	510	350	40	3/3	800

WB 621 E-Kit



Electronic kit
— suitable for workbench WB 621
— consisting of a switchable 3-way socket (EU) with 2 USB ports
— including magnetic holder for mounting anywhere on the workbench (RAL 9005) and cable holder

Product no.	L mm	kg
90432728	300	2.02

95/98 AB



Waste bin
— suitable for tool trolleys 95 PRO/98 PRO and workbench WB 630
— powder coated

Product no.	for model	L mm	W mm	H mm	kg
89011053	95 PRO, 98 PRO, WB 630	300	115	310	2.01

WB 621/625 WP



Multiplex beechwood worktop
— suitable for workbenches WB 621/WB 625
— oiled multiplex beechwood worktop

Product no.	for model	kg
90432731	WB 621, WB 625	13

R 95



Wheel set
— 2 fixed and 2 swivelling smooth-running wheels (Ø 125 mm)
— 2 with parking brake

Product no.	for model	kg
81490001	93/6, 95 PRO, WB 621, WB 625	3.9

R 98



Wheel set
— 2 fixed and 2 swivelling smooth-running wheels (Ø 125 mm)
— 2 with parking brake

Product no.	for model	kg
81490005	93/6, 95 PRO, 98 PRO, WB 621, WB 625	4.5

R 95/98S



Wheel set
— 4 swivelling smooth-running wheels (Ø 125 mm)
— 2 with parking brake and 2 with directional lock

Product no.	for model	kg
89480003	93/6, 95 PRO, 98 PRO, WB 621, WB 625	5.4

R 630



Wheel set
— 4 swivelling and movable smooth-running castors, Ø 125 mm
— with locking brakes
— with thread guard to protect the bearings from dirt and threads
— oil and acid resistant
— load capacity when used with workbench WB 630: 600 kg

Product no.	for model	g
81490007	WB 630	4400

TOOL STORAGE.


83/010



Tool box
— 3 trays
— can be locked with a padlock

Product no.	L mm	W mm	H mm	kg
81060000	475	420	150	3.64

83/09



Tool box
— 5 trays
— can be locked with a padlock

Product no.	L mm	W mm	H mm	kg
81050000	458	420	200	4.74

446/08



Tool box
— 5 trays
— can be locked with a padlock

Product no.	L mm	W mm	H mm	kg
81070000	573	530	200	5.59

82/013



Tool box
— with lift out tray
— can be locked with a padlock

Product no.	L mm	W mm	H mm	kg
81080000	252	545	225	6.87

13219



Tool bag
— with 23 compartments and 5 external pockets
— sturdy carrying handle
— removable, padded shoulder strap for comfortable carrying
— lid with hook-and-loop fastener protects the tools from dust, dirt, and moisture
— sturdy, reinforced plastic base
— made of waterproof polyester

Product no.	L mm	W mm	H mm	kg
81620004	520	500	340	2.3

13215



Backpack trolley
- sturdy tool backpack with reinforced bottom
- flexible use as a trolley or a backpack
- large, smooth-running wheels and a practical telescopic handle for convenient transport
- extendable, padded straps convert trolley into a backpack
- 2 easily removable panels for the most important everyday tools
- front pockets for paperwork and accessories
- padded notebook compartment (up to 15")

Product no.	L mm	W mm	H mm	kg
81620007	250	380	520	4.3

136 L-BOXX®



Tool box L-BOXX®
- mobile tool storage solution for trade and industry
- protects tools from damage and water spray
- compatible with the entire L-BOXX® range
- honeycomb function increases the stability of the base
- innovative one-handed click system
- contents are accessible even when the boxes are stacked and connected
- impact-resistant ABS plastic
- load capacity: 12 kg
- weight bearing capacity: 85 kg, can also be used as a step

Product no.	L mm	W mm	H mm	kg
81620136	360	444	152	1.78

136 L-BOXX® WK



Tool card
- suitable for L-BOXX® to be mounted in the lid
- 12 rubber loops and 6 pockets for safe storage of tools
- mounting fixtures included

Product no.	for model	L mm	W mm	H mm	g
81620137	136 L-BOXX®	375	305	25	400

13301



Tool box
- ABS shells
- robust aluminium frame with impact edge protection
- 2 lockable flip-locks
- variable base shell
- cover with 15 compartments, panel with 22 compartments
- separate document compartment in lid
- max. load capacity: 25 kg

Product no.	L mm	W mm	H mm	Filling volume	kg
81620009	365	490	188	27 l	4

13302/TR




Mobile tool box
- ABS shells
- smooth-running castors and integrated telescopic handle for convenient transport
- ergonomically designed carrying handle
- robust aluminium frame with impact edge protection
- 2 lockable flip-locks and a professional combination lock
- variable bottom section (2 aluminium dividers, 4 end caps, 2 centre caps)
- cover with 15 compartments, panel with 22 compartments
- separate document compartment in lid
- max. load capacity: 30 kg

Product no.	L mm	W mm	H mm	Filling volume	kg
81620010	260	515	445	36 l	6

13216/4



Tool box
- with 4 drawers, a compartment under the lid, a safety lock and a sturdy aluminium structural sheet on the lid
- wide, spring-mounted, plastic-covered handles on the sides
- high-quality, fully-extendable, stable sliding rail system
- easy removable drawers
- affix items to the perforated panel with spring clamps No. 8050



Product no.	L mm	W mm	H mm	kg
81091004	510	230	415	14

TBT 13216



Tool box trolley
- for tool box No. 13216/4
- secure locking with a convenient release mechanism
- for ease of transport and increased usability of the tool boxes
- sturdy sheet-steel construction
- 2 fixed castors and 2 swivel castors (Ø 75 mm) with brakes
- practical, fold-away handle with stop
- maximum static load capacity: 150 kg
- colour: black, RAL 9005
- tool boxes to be purchased separately

Product no.	for model	L mm	W mm	H mm	kg
81091009	13216/4	328	570	216	7.5

1500



Roll-up tool pouches


— sturdy tool roll with polyester hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe

Product no.	for model	L mm	W mm	H mm	Number of shelves	g
81231040	10/5; 17F/4; 17F/5; 240/4; 17/5; 17a/5; 25/4	290	80	30	5	138
81231041	12160/6 VDE; 12161/6 VDE; 240/6; 17F/6	300	90	30	6	170
81231042	10/6; 10/8; 13/9; 13/8; 13/6; 25/7; 25a/7	300	110	30	9	274
81231043	10a/7	330	120	45	9	298
81231044	13/11; 17F/12; 17/12	525	230	30	12	296
81231045	10/12; 10/10; 14/11; 10a/11; 17a/12	340	150	40	13	448
81231046	12/15; 12/10; 12a/13	150	90	35	15	112
81231047	13/17; 13/16 CH; 14/17; 17/15; 17F/15	350	140	40	18	547
81231048	13/15; 14/15	500	130	80	18	742
81231060	13/19CH	1000	400	55	20	802



13217





Tool trolleys

— robust and durable tool trolley made from polypropylene for professional use
— 5 easily removable lockable drawers with transparent covers, end-stops for the rails, and in 3 different drawer heights
— drawers can be inserted in any order
— with 1 top cover and 1 removable front cover
— the top lid is lined with dimpled foam to hold the tools securely in place
— 1 removable tray with 2 handles and 2 transparent drawer lids under the top tray
— drawers can be used as a separate toolbox thanks to the transparent lids
— custom label options for the case and the drawers
— 2 smooth-running double castors at the rear
— for upright transport on 4 wheels; can be fitted with wheel set R 13217 (please order separately)
— extendable telescopic handle for easy transport
— 2 side handles
— resistant to skydrol, acetone, petrol and hydraulic oils
— load capacity: 60 kg
— lockable in 3 places with a padlock
— lockable with the integrated lock, 2 keys included (excluding IP67 version)
— also available in IP67 (6 drawers, 4 x 30 mm, 2 x 60 mm)
— additional fasteners and seals protect against water and dust
— with valve for pressure compensation (IP67 version only)
— also available with all-round reflective decals (5 drawers, 2 x 30 mm, 3 x 60 mm), for increased safety when working in dark environments
— individual case configurations on request

Product no.	Model	L mm	W mm	H mm	kg
81091301	13217 LGE	381	581	455	16
81091304	13217 LR	381	581	455	16
81091306	13217 TS	381	581	455	16
81091322	13217 TS IP67	381	581	455	16
96894809	13217 TS RF	381	581	455	16

Configurable tool trolleys without drawers

Product no.	Model	L mm	W mm	H mm	Load capacity	g
81091323	13217 TS IP67/K	381	581	455	60 kg	12000
81091333	13217 LGE K	381	581	455	60 kg	12000
81091334	13217 LR K	381	581	455	60 kg	12000
81091335	13217 TS K	381	581	455	60 kg	12000

TA 13217



Transparent cover

— creates additional storage space in the top lid
— mounting fixtures included

Product no.	for model	L mm	W mm	H mm	g
89010100	13217	500	275	40	630

TR-SCH 13217



Drawers

— robust and durable drawer with polypropylene handle
— for tool trolleys No. 13217
— combines with the cover No. TA 13217 to make a tool box

Product no.	Model	for model	L mm	W mm	H mm	g
81483230	30 SC	13217	467.5	255	30	612
81483260	60 SC	13217	467.5	255	60	778
81483295	95 SC	13217	467.5	255	95	984

12932



Padlock

— for locking tool trolleys No. 13217
— includes 2 keys

Product no.	for model	L mm	W mm	H mm	g
77210002	13217	47	34	15	85

R 13217



Wheel set

— 4 swivel castors, including 2 with parking brake

Product no.	for model	g
96894805	13217	670

DRAWER CONFIGURATION –
Systematic tool storage.

The tool trolley 13217 is also available without drawers and can be equipped on a modular basis with different drawer configurations (C1 – C10) as required. The order of the drawers is also variable. The product codes of the drawers that must be ordered separately for the empty case can be found under TR-SCH 13217 on the adjacent page. The trolley is available in black (also as IP67 version), yellow and red – the drawer colour is always black.



81091333



81091334




81091335





81091323 (IP67)

C1
3 x **H 30 mm**, 81483230
1 x **H 60 mm**, 81483260
1 x **H 95 mm**, 81483295




C2
6 x **H 30 mm**, 81483230
1 x **H 60 mm**, 81483260







C3
4 x **H 30 mm**, 81483230
2 x **H 60 mm**, 81483260




C4
2 x **H 30 mm**, 81483230
3 x **H 60 mm**, 81483260




C5
4 x **H 60 mm**, 81483260




C6
5 x **H 30 mm**, 81483230
1 x **H 95 mm**, 81483295




C7
2 x **H 30 mm**, 81483230
2 x **H 95 mm**, 81483295




C8
1 x **H 60 mm**, 81483260
2 x **H 95 mm**, 81483295



C9
1 x **H 30 mm**, 81483230
2 x **H 60 mm**, 81483260
1 x **H 95 mm**, 81483295




C10
8 x **H 30 mm**, 81483230



PERFORATED PANELS, HOOKS AND HOLDERS.

8002



Perforated panel

— durable perforated panel for affixing tools and objects
— compatible with hooks and brackets No. 8031-8041 (not included)
— square perforation, 9 x 9 mm
— made of sturdy sheet steel
— 2 reinforcing cross ribs on the back
— with holes for easy wall or bench mounting
— high load capacity

Product no.	L mm	W mm	H mm	kg
80020001	1000	500	15	3.8

Tool hooks

with practical clip system

— sturdy plastic clip
— suitable for perforated panels with a 9 x 9 mm perforation
— simple, tool-free attachment
— screwless safety lock prevents scratching of the perforated wall

8031



Single hooks

— heavy-duty tool hook with practical clip-on system
— made of robust steel
— angled hook, 45°

Product no.	for model	L mm	g
80310030	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	30	13
80310060	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	60	17
80310090	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	90	21

8032



Twin hooks

— heavy-duty double hook with practical clip-on system
— made of robust steel
— 2 angled hooks, 45°

Product no.	for model	L mm	g
80320030	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	30	19
80320060	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	60	26

8034



Twin hooks

— heavy-duty double hook with practical clip-on system
— made of robust steel
— 2 angle hooks with vertical holder ends

Product no.	for model	L mm	W mm	g
80340040	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	40	35	30
80340050	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	50	40	30

8035




Rectangular lugs

— heavy-duty bracket for pliers, with practical clip-on system
— made of robust steel

Product no.	for model	L mm	W mm	g
80350017	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	17	35	23
80350020	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	20	55	26

8036



Spring clips

— heavy-duty aluminium tool clamp with practical clip-on system

Product no.	for model	d mm	g
80360012	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	12	9
80360018	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	18	10
80360024	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	24	14

8038



Container

— robust case with practical clip-on system
— for tidy storage of pens, centre punches, etc.

Product no.	for model	d mm	H mm	g
80380030	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	30	72	15

8041



Holder for spanners

— space-saving tool holder with practical clip-on system
— for 8 spanners
— made of robust steel

Product no.	for model	g
80410235	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630	62

8050



Spring clips

— heavy-duty tool clamp with practical clip system
— made of sturdy sheet steel, galvanised

Product no.	for model	d mm	g
81485006	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 13216	6	28
81485012	8002, 93/6, 93 TOP BOX, 95 PRO, 98 PRO, WB 621, WB 625, WB 630, 13216	12	28


STAHLWILLE

7 Tool assortments



304 **Tool assortments in tool trolleys and workbenches**

323 **Tool assortments in TCS inlays**

350 **Tool assortments in TCS inlay**

354 **Large workshop tool sets**

360 **Tool assortments in trolleys**

368 **Tool assortments for trolleys**

378 **Tool assortments in cases**

381 **Tool assortments in L-BOXX®**

383 **Tool assortments in tool boxes**

386 **Other tool assortments**

STAHLWILLE TOOL ASSORTMENTS –
Perfectly sorted. Perfectly protected.

STAHLWILLE offers an enormous variety of pre-configured premium tool sets – either as a stand-alone solution or in combination with a tool storage solution such as a tool trolley or tool box. The Tool Control System (TCS) always ensures order and ensures that no tool is left behind on the job.



Clearly arranged.

The STAHLWILLE Tool Control System (TCS) is functional and promotes efficiency. Every tool has its place – the user immediately knows where it belongs. This saves valuable time in everyday work.

Reliable.

Thanks to the 2-layer/two-colour system, you can see at a glance whether the TCS inlay is fully loaded or if a tool is missing.

Individual.

STAHLWILLE offers many TCS assortments tailored to special areas of application – including customer-specific solutions.



Tailored.

The Tool Control System (TCS) creates order and protects the tools from damage. Thanks to computer-aided production, every tool cutout is precisely tailored.

Durable.

STAHLWILLE tool assortments impress with premium-quality inlays and are therefore ideally suited for professional use.

Comprehensive.

Detailed information on STAHLWILLE's versatile tool storage solutions can be found in the chapter on service and workshop equipment.

TOOL ASSORTMENTS IN TOOL TROLLEYS AND WORKBENCHES.



612/83 ST

98830176 Tool assortment with service trolley


— safely integrated in the modular Tool Control System (TCS)
— 1 service trolley **No. 612 ST**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98830176	410	819	909	83	30




96830277

Contains 83-pieces:
96830277
1 wooden folding ruler **No. 13112**: L. 2 m
1 L-Key hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 bit ratchet screwdriver ¼" **No. 4008**: L. 250 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 side cutters **No. 6720**: L. 160 mm
2 slotted screwdrivers **No. 4620**: 1.2 x 6.5 x 150; 0.6 x 3.5 x 75 mm
2 PH cross-head screwdrivers **No. 4632**: PH1; PH2
1 cable knife **No. 12320:** Blade length: 90 mm
1 mini magnetic lifter **No. 12600**: 270 g
7 double open-ended spanners **No. 10**: 8 x 10; 10 x 13; 13 x 14; 16 x 18; 17 x 19; 19 x 22; 21 x 24 mm
1 engineer's hammer **No. 10961**: 500 g
1 bit box ¼" **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces



Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.



Tool assortment in a modular system with tool inserts, Tool Control System (TCS) - safely integrated
All advantages at a glance:

With the Tool Control System, the tools fit into chemical-resistant safety foam inlays with high-precision, 3D cutouts. Two-tone colour system facilitates quick audits of the contents: Visible colour immediately indicates a missing tool.

Top features tool trolley 93/6
for mobile use in the workshop

— two-stage safety concept:
  — central locking through cylinder lock with folding key
  — tilt protection - it is not possible to pull out several drawers at the same time
— 2 handles, all-round impact protection
— durable plastic tray made of ABS with compartments for small parts
— oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, with two parking brakes
— perforation on both sides for hooks 8031-8041, e.g. for larger tools
— 6 easy-to-remove drawers (black, RAL 9005) with full extension runners (370 mm) and ball bearing cage guide
— with paper roll holder



93/130

98830177 Tool assortment with tool trolley
— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 93/6 A**: 6 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830177	481	877	1000	6	130	78.5



96830244



96830245

Contains 130-pieces:

96830244
10 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 bit ratchet 1/4" **No. 415-2K**: L. 117 mm
1 extension 1/2" **No. 509**: L. 130 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 engineer's hammer **No. 10961**: 500 g
1 cable knife **No. 12320**: Blade length: 90 mm
1 bit box 1/4" **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830245
15 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 22; 24 mm
1 wooden folding ruler **No. 13112**: L. 2 m
1 mini magnetic lifter **No. 12600**: 270 g
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 slotted screwdriver **No. 4620**: 0.8 x 4.0 x 100 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2
3 TORX® screwdrivers **No. 4650**: T15; T20; T25



93/157QR

98830178 Tool assortment with tool trolley

— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 93/6 A**: 6 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830178	481	877	1000	6	157	82



96830264



96830265



96830266



96830267



96830268



96830269

Contains 157-pieces:

96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4.0 x 100; 1.6 x 10.0 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 wooden folding ruler **No. 13112**: L. 2 m
1 torch **No. 13132**: 130 lm
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 21; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm




93/206QR

98830203 Tool assortment with tool trolley

— particularly suitable for the automotive sector
— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 93/6 A**: 6 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830203	481	877	1000	6	207	100



96830283



96830284



96830285



96830286



96830287

Contains 207-pieces:

96830283

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
7 screwdriver sockets TORX®, with hole 1/4" **No. 44KTXB**: T10; T15; T20; T25; T27; T30; T40
3 extensions 1/4" **No. 405**: L. 54; 100; 150 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
12 bits TORX® 1/4" **No. 1410-1421**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30; T40; T45
16 sockets with hex 3/8" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
3 screwdriver sockets INHEX 3/8" **No. 49**: 5; 6; 7 mm
3 screwdriver sockets TORX® 3/8" **No. 49TX**: T30; T40; T45
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
3 extensions 3/8" **No. 427**: L. 76; 160; 240 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
6 sockets TORX® 1/2" **No. 50TX**: E11; E12; E14; E18; E20; E24
2 IMPACT wheel nut sockets with hex 1/2" **No. 2309IMP K**: 17; 19 mm
5 screwdriver sockets INHEX 1/2" **No. 54**: 8; 10; 12; 14; 17 mm
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T45; T50; T55; T60
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR**: L. 265.5 mm

96830284

6 pin punches **No. 108**: Ø 2, 3, 4, 5, 6, 8 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 tape measure **No. 12935**: L. 3 m
1 dead blow hammer **No. 10959**: Ø 40 mm
1 engineer's hammer **No. 10961**: 500g
1 magnetic lifter **No. 12600**: 500 g
1 cable knife **No. 12320** Blade length: 90 mm
1 telescopic mirror **No. 12921**: L. 178-921 mm
1 torch **No. 13132**: 130 lm
2 batteries AAA 1.5 V
1 brake caliper brush, steel wire **No. 12373**: L. 230 mm
1 claw lifter **No. 12922**: Ø 6 mm, L. 540 mm

96830285

8 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13;

Tool assortments

14 x 15; 16 x 17; 18 x 19; 20 x 22 mm
1 slotted screwdriver with impact cap **No. 4622SK**: 1.2 x 10 x 175 mm
1 triangular bearing scraper **No. 10676**: 85 x 12 x 315 mm
1 lever bar **No. 12770**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 PZ cross-head screwdriver **No. 4744**: PZ2
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 4724**: 0.6 x 3.5 x 25 mm

96830286

23 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 23; 24; 27; 29; 30; 32 mm
11 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 10 x 12; 10 x 13; 13 x 14; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24
4 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12; E14 x E18; E20 x E24

96830287

4 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 water pump pliers **No. 6572**: L. 240 mm
4 circlip pliers **No. 6543, 6545**: J1; J2; A1; A2
1 combination pliers **No. 6700**: L. 180 mm
1 heavy-duty side cutters **No. 6721** L. 160 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 telephone pliers **No. 6731**: L. 200 mm



93/250QR

98830180 Tool assortment with tool trolley

— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 93/6 A**: 6 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830180	481	877	1000	6	250	85.5


96830264


96830265


96830266


96830267


96830268


96830269


96830271


96830272


96830273


96830274

Contains 250-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 21; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830271
1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm

96830272
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm



Tool assortments

Top features tool trolley 95 PRO
for mobile use in the workshop

— three-stage safety concept:
  — central locking with a lateral cylinder lock and folding key
  — individual locks prevent inadvertent opening during transit
  — tilt protection - it is not possible to pull out several drawers at the same time
— black lacquered steel handle with reinforced body connection
— all-round impact protection with impact damping
— tightly welded, scratch resistant worktop prevents liquids from penetrating
— oil and acid-resistant wheels (Ø 125 mm) with bearings protected from the ingress of dirt and fibres, and two parking brakes
— paper roll holder and spray can holder included
— 6, 7 or 8 easy-to-remove drawers (black, RAL 9005) with full extension and ball bearing cage guide
— perforation on both sides for hooks 8031-8041, e.g. for larger tools



95/157QR

98830192 Tool assortment with tool trolley
— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 95/7 A PRO**: 7 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830192	497	823	1021	7	157	101


96830264


96830265


96830266


96830267



96830268


96830269

Contains 157-pieces:

96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm

1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm



95/250QR

98830193 Tool assortment with tool trolley
— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley, anthracite **No. 95/7 A PRO**: 7 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830193	497	823	1021	7	250	111


96830264


96830265


96830266


96830267


96830268


96830269


96830271


96830272


96830273


96830274

Contains 250-pieces:
96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

Tool assortments

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830271
1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095:** 0.05-1.00 mm

96830272
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2 A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm



98/250QR

98830234 Tool assortment with tool trolley
— 1 tool trolley, anthracite **No. 98/7 A PRO**: 7 drawers
— Key features of tool trolley (see page 285)
Contains 250-pieces: with the TCS inserts of the 95/250QR tool assortment (98830193), but with a larger tool trolley

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830234	651	1001	1020	7	250	111



Top features workbench WB 621
for mobile use in the workshop

— three-stage safety concept:
  — central locking with a lateral cylinder lock and folding key
  — individual locks prevent inadvertent opening during transit
  — tilt protection - it is not possible to pull out several drawers at the same time
— 7 easy-to-remove drawers with full extension runners and ball bearing cage guide
— 2 drawers in generous XXL format, 880 mm
— lockable cabinet compartment with height-adjustable shelf (70 mm grid)
— cabling through 2 rubberized grommets
— removable cable duct on the back side
— oil and acid-resistant wheels (Ø 125 mm) with thread guards to protect the bearings from dirt and threads, with two locking brakes
— body RAL 7016, drawers RAL 9005 in durable industrial powder coating
— Paper roll holder
— available separately: e-kit consisting of a magnetic multi-plugwith 2 USB ports, a magnetic holder (flexible positioning on anymetallic part of the workbench), and a cable holder



WB 621/161QR

98830194 Tool assortment with workbench
— for service and maintenance work on industrial systems
— metric tools
— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No. WB 621**: 7 drawers and cabinet compartment

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830194	500	1150	1045	7 + 1 cabinet compartment	161	107.5


96830264


96830265


96830266


96830267



96830268


96830269


96830273

Contains 161-pieces:

96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm

Tool assortments

1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3

1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 21; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21



WB 621/238QR

98830204 Tool assortment with workbench
— for service and maintenance work on agricultural, construction and commercial vehicles
— metric tools
— extra-long spanners for hard-to-reach bolted joints and greater force transmission
— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No. WB 621**: 7 drawers and cabinet compartment

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830204	500	1150	1045	7 + 1 Fach	238	135


96830288


96830289



96830291


96830292


96830290

Contains 238-pieces:
96830288
23 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34; 36 mm
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27
6 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T40; T45; T50; T55; T60
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11;12; 13; 14 mm

4 screwdriver sockets INHEX 1/4" **No. 44K**: 4; 5; 6; 8 mm
6 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 telescopic ratchet 1/2" **No. 516**: L. 410-630 mm
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 QuickRelease extensions 3/8" **No. 427QR**: L. 160 mm
1 square drive adaptor **No. 432**: 1/2 to 3/8"
1 square drive adaptor **No. 431**: 1/4 to 3/8"
1 automotive circuit tester **No. 12905**: 6-12 and 24 V
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
2 L-Keys hex **No. 10765**: 12; 14 mm
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830289
7 pin punches **No. 108**: Ø 2; 3; 4; 5; 6; 8; 10 mm
1 centre punch **No. 105**: Ø 12 mm
1 engineer's hammer **No. 10961**: 500 g
1 flat chisel **No. 102**: W. 24; L. 200 mm
1 soft-face hammer **No. 10959**: Ø 50 mm
1 cross-cut chisel **No. 103**: W. 18; L. 200 mm
1 engineer's hammer **No. 10961**: 1500 g

1 gasket scraper **No. 12718**: L. 265 mm
1 lever bar **No. 11007**: L. 400 mm
1 magnetic lifter **No. 12600**: 3000 g
1 tape measure **No. 12935**: L. 5 m
1 flat file **No. 12036**: L. 260 mm
1 half-round file **No. 12030**: L. 260 mm
1 round file **No. 12025**: L. 210 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 adjustable spanner **No. 4025** max. 39 mm
1 wire brush **No. 12374**: L. 290 mm

96830290
22 combination spanners **No. 14**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 36 mm

96830291
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 cable knife **No. 12320**: Blade length: 90 mm
6 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30; T40
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
4 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.2 x 8.0 x 150 mm
1 PH cross-head screwdriver **No. 4632**: PH4
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m

96830292
8 circlip pliers **No. 6543-6546**: J1; J2; J11; J21; A1; A2; A11; A21
1 side cutters **No. 6720**: L. 160 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 telephone pliers **No. 6730**: L. 160 mm
1 combination pliers **No. 6700**: L. 180 mm
1 wire strippers: max. Ø 4 mm²
1 crimping pliers **No. 6638**: L. 220 mm





WB 621/267QR

98830195 Tool assortment with workbench

— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No WB 621**: 7 drawers and cabinet compartment

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830195	500	1150	1045	7 + 1 cabinet compartment	267	137



96830264



96830265



96830266



96830267



96830268



96830269



96830270



96830271



96830272



96830273



96830274



96830275

Contains 267-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265

2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266

1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830270
4 electrician's slotted screwdrivers **No. 4751**: 0.3 x 1.5; 0.4 x 2; 0.4 x 2.5; 0.5 x 3 mm
3 electrician's PH cross-head screwdrivers **No. 4752**: PH00; PH0; PH1
1 electronics needle nose pliers **No. 6711**: L. 130 mm
1 mini electronics side cutters **No. 6708** L. 115 mm

96830271
1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095:** 0.05-1.00 mm

96830272
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

96830275
1 slotted screwdriver **No. 4620**: 1.0 x 5.5 x 125 mm
4 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2; PZ3
2 PH cross-head screwdrivers **No. 4734**: PH1; PH2
1 voltage tester **No. 10554**: 125-250 V

TOOLS THAT
... inspire

Top features workbench WB 625
for mobile use in the workshop

— three-stage safety concept:
  — central locking with a lateral cylinder lock and folding key
  — individual locks prevent inadvertent opening during transit
  — tilt protection - it is not possible to pull out several drawers at the same time
— 7 drawers with full extension runners and ball bearing cage guide
— large work surface with FSC-certified birch multiplex worktop (1150 x 500 x 30 mm)
— working height of 104 cm
— stainless steel decorative trim
— oil and acid-resistant wheels (Ø 125 mm) with thread guard and 2 parking brakes
— body RAL 7016, drawers and cabinet RAL 9005 in durable industrial powder coating
— perforation on the side for hooks 8031-8041, e.g. for larger tools
— Drawer dimensions: 1-4 up to 40 kg, 3-7 up to 60 kg



WB 625/161QR

98830179 Tool assortment with workbench
— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No. WB 625**: 7 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830179	500	1150	1045	7	161	119


96830264


96830265


96830266


96830267



96830268


96830269


96830273

Contains 161-pieces:

96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm

1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm


96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21



WB 625/238QR

98830205 Tool assortment with workbench
— for service and maintenance work on agricultural, construction and commercial vehicles
— metric tools
— extra-long spanners for hard-to-reach bolted joints and greater force transmission
— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No WB 625**: 7 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830205	500	1150	1045	7	238	135



96830288


96830289



96830291


96830292


96830290

Contains 238-pieces:
96830288
23 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34; 36 mm
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27
6 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T40; T45; T50; T55; T60
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7 ;8; 9; 10; 11;12; 13; 14 mm

Tool assortments

4 screwdriver sockets INHEX 1/4" **No. 44K**: 4; 5; 6; 8 mm
6 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 telescopic ratchet 1/2" **No. 516**: L. 410-630 mm
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 QuickRelease extensions 3/8" **No. 427QR**: L. 160 mm
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 automotive circuit tester **No. 12905**: 6-12 and 24 V
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
2 L-Keys hex **No. 10765**: 12; 14 mm
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830289
3 pin punches **No. 108**: Ø 4; 6; 8 mm
1 centre punch **No. 105**: Ø 12 mm
4 pin punches **No. 108**: Ø 2; 3; 5; 10 mm
1 engineer's hammer **No. 10961**: 500 g
1 flat chisel **No. 102**: W. 24; L. 200 mm
1 soft-face hammer **No. 10959**: Ø 50 mm
1 cross-cut chisel **No. 103**: W. 18; L. 200 mm
1 engineer's hammer **No. 10961**: 1500 g
1 gasket scraper **No. 12718**: L. 265 mm
1 lever bar **No. 11007**: L. 400 mm
1 magnetic lifter **No. 12600**: 3000 g
1 tape measure **No. 12935**: L. 5 m
1 flat file **No. 12036**: L. 260 mm
1 half-round file **No. 12030**: L. 260 mm
1 round file **No. 12025**: L. 210 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 adjustable spanner **No. 4025**: max. 39 mm
1 wire brush **No. 12374**: L. 290 mm

96830290
22 combination spanners **No. 14**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 36 mm

96830291
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 cable knife **No. 12320**: Blade length: 90 mm
6 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30; T40
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
4 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.2 x 8.0 x 150 mm
1 PH cross-head screwdriver **No. 4632**: PH4
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m

96830292
8 circlip pliers **No. 6543-6546**: J1; J2; J11; J21; A1; A2; A11; A21
1 side cutters **No. 6720**: L. 160 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 telephone pliers **No. 6730**: L. 160 mm
1 combination pliers **No. 6700**: L. 180 mm
1 wire strippers: max. Ø 4 mm²
1 crimping pliers **No. 6638**: L. 220 mm

TOOLS THAT
... inspire



WB 625/267QR

98830181 Tool assortment with workbench

— safely integrated in the modular Tool Control System (TCS)
— 1 workbench, anthracite **No. WB 625**: 7 drawers

Product no.	L mm	W mm	H mm	Number drawers	Content pcs.	kg
98830181	500	1150	1045	7	267	151



96830264



96830265



96830266



96830267



96830268



96830269



96830270



96830271



96830272



96830273



96830275



96830274

Contains 267-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265

2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266

1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutter **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267

16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025** max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

Tool assortments

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830270
4 electrician's slotted screwdrivers **No. 4751**: 0.3 x 1.5; 0.4 x 2; 0.4 x 2.5; 0.5 x 3 mm
3 electrician's PH cross-head screwdrivers **No. 4752**: PH00; PH0; PH1
1 electronics needle nose pliers **No. 6711**: L. 130 mm
1 mini electronics side cutters **No. 6708** L. 115 mm

96830271
1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces

1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095/20:** 0.05-1.00 mm

96830272
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

96830275
1 slotted screwdriver **No. 4620**: 1.0 x 5.5 x 125 mm
4 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2; PZ3
2 PH cross-head screwdrivers **No. 4734**: PH1; PH2
1 voltage tester **No. 10554**: 125-250 V



TOOL ASSORTMENTS IN TCS INLAYS.

TCS 806/9

98830004 Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
98830004	98	17.95



96838175



96838176



96838177



96838179



96838180




96838181



96838182



96838183



96838278

Contains 98-pieces:

96838175

1 T-handle 1/2" **No. 506**: L. 300 mm
3 extensions 1/2" **No. 509**: L. 52; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

96838176

10 sockets with hex 1/4" **No. 40**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 L-Key hex **No. 10760**: 12 mm
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96838177

17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

96838179

1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96838180

2 circlip pliers **No. 6543, 6545**: J2; A2
1 self-grip wrench **No. 6564**: L. 250 mm

96838181

1 flat chisel **No. 102**: W. 20; L. 175 mm
2 pin punches **No. 108**: Ø 6; L. 150, 175 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 nylon hammer **No. 10956**: Ø 35 mm
1 engineer's hammer **No. 10961**: 500 g

96838182

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm

96838183

18 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24 mm

96838278

4 slotted screwdrivers **No. 4620**: 0.6 x 3,5 x 75: 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3

TCS 820/2

97830254 Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830254	130	9.96



96830244



96830245

Contains 130-pieces:

96830244

10 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 extension 1/2" **No. 509**: L. 130 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 engineer's hammer **No. 10961**: 300 g
1 cable knife **No. 12320**: Blade length: 90 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830245

15 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 15; 15; 16; 17; 18; 19; 22; 24 mm
1 wooden folding ruler **No. 13112**: L. 2 m
1 mini magnetic lifter **No. 12600**: 270 g
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm; 9-piece
1 slotted screwdriver **No. 4620**: 0.8 x 4.0 x 100 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2
3 TORX® screwdrivers **No. 4650**: T15; T20; T25



TCS 821/6

97830255 Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830255	157	14.5



96830264



96830265



96830266



96830267



96830268



96830269

Contains 157-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265

2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266

1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267

16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268

1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269

1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

TOOLS THAT ... inspire

TCS 821/7

97830256 Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830256	161	14.5



96830264



96830265



96830266



96830267



96830268



96830269



96830273

Contains 161-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265

2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266

1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267

16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268

1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269

1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830273

4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

TCS 821/10

97830257 Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830257	250	28



96830264



96830265



96830266



96830267



96830268



96830269



96830271



96830272



96830273



96830274

Contains 250-pieces:

96830264

11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265

2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266

1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267

16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268

1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269

1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830271

1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm

Tool assortments

1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095:** 0.05-1.00 mm

96830272
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

TCS 821/12

97830258 Tool assortment
— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830258	267	29.5


96830264


96830265


96830266


96830267


96830268


96830269


96830270


96830271


96830272


96830273


96830274


96830275

Contains 267-pieces:

96830264
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L 25 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm

1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm

96830265
2 bit ratchet screwdrivers 1/4" **No. 4008**: L. 95; 250 mm
1 bit holder 1/4" **No. 4009**: L. 176 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830266
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

96830267
16 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24 mm
1 adjustable spanner **No. 4025**: max. 34 mm
5 combination ratchet spanners, flat **No. 17F**: 8; 10; 13; 17; 19 mm

96830268
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830269
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

96830270
4 electrician's slotted screwdrivers **No. 4751**: 0.3 x 1.5; 0.4 x 2; 0.4 x 2.5; 0.5 x 3 mm
3 electrician's PH cross-head screwdrivers **No. 4752**: PH00; PH0; PH1
1 electronics needle nose pliers **No. 6711**: L. 130 mm
1 mini electronics side cutters **No. 6708** L. 115 mm

96830271
1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095:** 0.05-1.00 mm

96830272
13 combination spanners **No. 14**: 6; 8; 10; 13; 14; 17; 19; 21; 22; 24; 27; 30; 32 mm
15 double open-ended spanners **No. 12**: 3.2; 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

96830273
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830274
9 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27; T30; T40; T45; T50; T55; T60
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets INHEX 1/2" **No. 1054/2054**: 6; 8 mm
4 screwdriver sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T10; T15; T20; T25; T27; T30; T40
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm

96830275
1 slotted screwdriver **No. 4620**: 1.0 x 5.5 x 125 mm
4 PZ cross-head screwdrivers **No. 4640**: PZ0; PZ1; PZ2; PZ3
2 PH cross-head screwdrivers **No. 4734**: PH1; PH2
1 voltage tester **No. 10554**: 125-250 V


TOOLS THAT
... inspire

TCS 1100 Porsche

97830411 Workshop set for Porsche

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830411	228	24.7



96830192



96830193



96830194



96830195



96830197



96830198



96831196

Contains 228-pieces:

96830192

13 sockets with hex 1/4" **No. 40**: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
4 sockets INHEX 1/4" **No. 44**: 3; 4; 5; 6 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 extension 1/4" **No. 405**: L. 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
12 sockets with bi-hex 3/8" **No. 45**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
1 socket long, with bi-hex 3/8" **No. 46**: 3/8 to 20.8 mm-13/16"
6 screwdriver sockets INHEX 3/8" **No. 49**: 4; 5; 6; 7; 8; 10 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
7 sockets with hex 1/2" **No. 50**: 19; 21; 22; 24; 27; 30; 32 mm
5 sockets TORX® 1/2" **No. 50TX**: E11; E16; E18; E20; E24
9 sockets with hex 1/2" **No. 52**: 16; 17; 18; 19; 22; 24; 27; 30; 32 mm
4 sockets INHEX 1/2" **No. 54**: 6; 7; 8; 10 mm
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T45; T50; T55; T60
4 screwdriver sockets XZN® 1/2" **No. 54X**: M6; M8; M12; M14
1 T-handle 1/2" **No. 506**: L. 300 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 514M**: 1/2 to 3/4"
5 bits TORX® **No. 1410-1427**: T6; T7; T8; T9; T25
7 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40

96830193

3 double open-ended spanners **No. 12**: 5.5; 12; 14 mm
20 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 22; 24; 30; 32; 36 mm
1 combination spanner **No. 14**: 17 mm

96830194

5 double-ended ring spanners **No. 20**: 10 x 11; 12 x 13; 14 x 15; 17 x 19; 19 x 22 mm
3 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12; E14 x E18
11 double-ended ring spanners **No. 23**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 30 x 32 mm
5 double-ended ring spanners **No. 24**: 8 x 10; 11 x 13; 12 x 14; 17 x 19; 22 x 24 mm

96830195

7 double-ended flex spanners **No. 29**: 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm

96830197
1 combination pliers **No. 6700**: L. 180 mm
3 circlip pliers **No. 6543, 6545, 6546**: J2; A2; A21
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96830198
1 ribbed flat chisel **No. 100**: B.20; L. 150 mm
1 centre punch **No. 105**: Ø 12 mm
2 drift punches **No. 104**: Ø 4; 6 mm
1 pin punch **No. 108**: Ø 4 mm
2 engineer's hammers **No. 10961**: 300; 500 g
1 soft face hammer **No. 10940**: Ø 55 mm
1 plastic hammer **No. 10955**: Ø 32 mm
1 triangular special scraper **No. 10670**: L. 265 mm
1 flat file **No. 12036**: L. 260 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 strap wrench **No. 12005**: L. 600 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 automotive circuit tester **No. 12905**: 6-12 and 24 V

96831196
4 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.6 x 10.0 x 175; 2.0 x 12.0 x 200 mm
1 PH cross-head screwdriver **No. 4630**: PH1
1 PH cross-head screwdriver **No. 4632**: PH3
10 TORX® screwdrivers **No. 4650**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set TORX® **No. 10766/9**: T8; T9; T10; T15; T20; T25; T27; T30; T40



TCS 1120 VW/AUDI

97830820 Workshop set for VW/Audi (basic)

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830820	241	30.7



96830166



96830877



96831584



96831585



96831608



96831609




96831610



96831613



96831614



96831615

Contains 241-pieces:

96830166

10 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

96830877

10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm

4 screwdriver sockets INHEX 1/2" **No. 54KK**: 5; 6; 8; 10 mm

96831584

1 combination pliers **No. 6700**: 180 mm

1 flat nose round pliers **No. 6730:** L. 160 mm

4 circlip pliers **No. 6543-6546:** J2, J21; A2; A21

1 water pump pliers **No. 6572**: L. 240 mm

1 heavy-duty side cutters **No. 6721**: 180 mm

96831585

1 self grip wrench **No. 6563**: L. 250 mm

2 flat chisels **No. 102**: W. 17; 23; L. 150; 200 mm

1 centre punch **No. 105**: Ø 10 mm

5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm

1 engineer's hammer **No. 10961**: 500 g

1 nylon hammer **No. 10956N**: Ø 35 mm

1 gasket scraper **No. 12718**: W. 33; L. 265 mm

1 tyre lever **No. 39 PKW:** L. 400 mm

1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm

1 cable knife **No. 12320**: Blade length: 90 mm

1 tape measure **No. 12935**: L. 3 m

1 magnetic lifter **No. 12600**: 500 g

1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm

1 telescopic mirror **No. 12920N**: L. 310-750 mm

1 brake caliper brush, steel wire **No. 12373**: L. 230 mm

1 automotive voltage tester set **No. 7756**: 3-48 V

96831608
12 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
4 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6 mm
4 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E8
1 screwdriver socket slotted 1/4" **No. 41K**: 1.0 x 5.5 mm
2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2
8 screwdriver sockets TORX® 1/4" **No. 44KTX**: T10; T15; T20; T25; T27
12 sockets with bi-hex 1/2" **No. 50**: 8; 9; 10; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
8 screwdriver sockets TORX® 1/2" **No. 54TX**: T25; T27; T30; T40; T45; T50; T55; T60
4 bits TORX® **No. 1410-1413**: T6; T7; T8; T9
3 Wobble-Drive extensions 1/4" **No. 405W**: L. 54; 100; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
3 Wobble-Drive extensions 1/2" **No. 509W**: L. 52; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 IMPACT square drive adaptor **No. 513IMP**: 1/2 to 3/8"
1 IMPACT square drive adaptor **No. 514IMP**: 1/2 to 3/4"
1 T-handle 1/2" **No. 506**: L. 300 mm
1 IMPACT square drive adaptor **No. 568IMP**: 3/4 to 1/2"
1 sliding head for T-handle 3/4" **No. 556**: L. 61.5 mm
1 handle 3/4" **No. 558**: L. 510 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm

96831609
6 combination ratchet spanners **No. 17**: 8; 10; 12; 13; 17; 19 mm

96831610
7 screwdriver sockets XZN® 1/2" **No. 54X**: M5; M6; M8; M10; M12; M14; M16
6 sockets TORX® 1/2" **No. 50TX**: E10; E12; E14; E16; E18; E20
1 screwdriver socket XZN® 1/2" **No. 1054X**: M8
3 screwdriver sockets XZN® 1/2" **No. 3054X**: M10; M12; M14
1 screwdriver socket XZN® 3/4" **No. 59X**: M18
2 IMPACT sockets with bi-hex 1/2" **No. 50D IMP**: 32; 36 mm
2 IMPACT wheel nut sockets with hex 1/2" **No. 2309IMP K**: 17; 19 mm

96831613
7 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8 x 175; 1.6 x 10 x 200; 2 x 12 x 250 mm
3 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4 x 90; 1 x 5.5 x 100; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
2 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2
1 slotted screwdriver **No. 4724**: 0.6 x 3.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2

96831614
10 TORX® screwdrivers **No. 4650**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set TORX® **No. 10771/8**:: T9; T10; T15; T20; T25; T27; T30; T40

96831615
20 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
1 double-ended ring spanner **No. 20**: 10 x 11 mm



TCS 1120/1 VW

97830821 Supplementary set VW

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830821	66	6.6



96831601



96831602



96831607

Contains 66-pieces:

96831601

3 nut spinners **No. 12507**: 8; 10; 13 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 140 mm
1 telephone pliers **No. 6731**: L. 200 mm
1 side cutters **No. 6720**: L. 140 mm
1 heavy-duty side cutters **No. 6721**: L. 200 mm

96831602

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

96831607

1 socket long, with bi-hex 1/4" **No. 40DL**: 8 mm
1 socket long, with bi-hex 3/8" **No. 46:** 12 mm
8 sockets long, with bi-hex 3/8" **No. 51**: 10; 13; 14; 15; 16; 17; 18; 19 mm
5 screwdriver sockets TORX® **No. 54TX**: T30; T40; T45; T50; T55
3 bits PHILLIPS® **No. PH 1221-1223** : PH1; PH2; PH3
3 bits POZIDRIV® **No. PZ 1221-1223**: PZ1; PZ2; PZ3
5 bits slotted **No. 1162**; **1164**; **1168**; **1166; 1166/1**: 0.6 x 3.5; 0.8 x 4; 1.6 x 8; 1 x 5.5; 1.2 x 6.5 mm
1 bit slotted **No. 1299**: 2 mm
5 bits hex **No. 1300-1304**: 3; 4; 5; 6; 8 mm
13 bits TORX® **No. 1410-1421; 1435**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30; T40; T45; T55
1 bit ratchet 1/4" **No. 415B-2K**: L. 117 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm

TOOLS THAT
... inspire

TCS 1120/2 AUDI

97830822 Supplementary set for Audi

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830822	73	8.04



96831601



96831602



96831603



96831695

Contains 73-pieces:

96831601

3 nut spinners **No. 12507**: 8; 10; 13 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 140 mm
1 telephone pliers **No. 6731**: L. 200 mm
1 side cutters **No. 6720**: L. 140 mm
1 heavy-duty side cutters **No. 6721**: L. 200 mm

96831602

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

96831603

5 bits 1/4" **No. 1350, 1356-1359**: M4; M5; M6; M8; M10
1 bit holder 5/16" **No. 543:** L. 38 mm
3 nut spinners **No. 12506-2K**: 6; 7; 8 mm
1 bit holder insert tool 5/16" **No. 736/10**: 9 x 12 mm
1 bit holder insert tool 1/4" **No. 736/10**: 9 x 12 mm

96831695

10 sockets long, with bi-hex 3/8" **No. 46**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
10 uniflex sockets with bi-hex 3/8" **No. 47**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
12 sockets with hex 3/8" **No. 456**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
3 extensions 3/8" **No. 427**: L. 76; 160; 240 mm
3 Wobble-Drive extensions 3/8" **No. 427W**: L. 76; 125; 160 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
4 TORX® screwdrivers long **No. 4650L**: T15; T20; T25; T30
1 ratchet 3/8" **No. 435-2K**: L. 193 mm



TCS 2500 BMW

97830600 Workshop tool set for BMW automotive

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830600	285	27.8



96830602




96830603



96830604



96830605



96830607



96830608



96830609



96830622



96830679



96830706



96838177



96838192

Contains 285-pieces:

96830602

16 sockets with hex $^{3}/_{8}$" **No. 456**: 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
4 sockets long, with bi-hex $^{3}/_{8}$" **No. 46**: 10; 11; 12; 13 mm
7 uniflex sockets with bi-hex $^{3}/_{8}$" **No. 47**: 10; 11; 12; 13; 14; 15; 16 mm
1 screwdriver socket INHEX $^{3}/_{8}$" **No. 1049**: 9 mm
3 screwdriver sockets XZN® $^{3}/_{8}$" **No. 49X**: M6; M8; M10
3 extensions $^{3}/_{8}$" **No. 427**: L. 76; 125; 240 mm
1 universal joint $^{3}/_{8}$" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: $^{3}/_{8}$ to $^{1}/_{4}$"
1 square drive adaptor **No. 432**: $^{3}/_{8}$ to $^{1}/_{2}$"
1 ratchet $^{3}/_{8}$" **No. 435-2K**: L. 193 mm
1 QuickRelease fine-tooth flexible ratchet $^{3}/_{8}$" **No. 452QR**: L. 300 mm

96830603

1 T-handle $^{1}/_{2}$" **No. 506**: L. 300 mm
4 extensions $^{1}/_{2}$" **No. 509**: L. 52; 130; 255 (2 x) mm
1 universal joint $^{1}/_{2}$" **No. 510**: L. 71 mm
1 ratchet $^{1}/_{2}$" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: $^{1}/_{2}$ to $^{3}/_{8}$"
1 square drive adaptor **No. 514**: $^{1}/_{2}$ to $^{3}/_{4}$"

96830604

3 screwdriver sockets INHEX $^{3}/_{8}$" **No. 49**: 5; 6; 7 mm
5 screwdriver sockets INHEX $^{1}/_{2}$" **No. 54**: 8; 10; 12; 14; 17 mm
2 IMPACT wheel nut sockets with hex **No. 2309IMP K**: 17; 19 mm
2 sockets with hex **No. 12506**: 6; 7 mm

96830605
9 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm
20 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
1 double-ended ring spanner **No. 24**: 10 x 11 mm

96830607
4 double-ended ring spanners TORX® **No. 21TX** E6 x E8; E10 x E12; E14 x E18; E20 x E24
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
7 screwdriver sockets TORX®, with hole 1/4" **No. 44KTXB**: T10; T15; T20; T25; T27; T30; T40
1 square drive adaptor **No. 409M**: 1/4 to 3/8
1 bit ratchet 1/4" **No. 415B-2K**: L. 117 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 50 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
2 uniflex sockets TORX® 3/8" **No. 47TX**: E8; E10
1 screwdriver socket TORX® 3/8" **No. 49TX:** T40
5 sockets TORX® 1/2" **No. 50TX**: E11; E16; E18; E20; E24
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T45; T50; T55; T60
4 screwdriver sockets TORX®, with hole 1/2" **No. 54TXB**: T30; T40; T45; T50
3 bits POZIDRIV® **No. PZ 1221-1223**: PZ1; PZ2; PZ3
4 bits TORX® **No. 1410-1413**: T6; T7; T8; T9
1 bit TORX® **No. 1427**: T25
7 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40
10 TORX® screwdrivers **No. 4856**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40

96830608
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830609
1 flat chisel **No. 102**: W. 23; L. 200 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
5 pin punches **No. 108**: Ø 3;4; 5; 6; 8 mm
1 dead blow hammer **No. 10959**: Ø 40 mm
1 engineer's hammer **No. 10961**: 500 g
1 brake caliper brush, steel wire **No. 12373**: L. 230 mm
1 magnetic lifter **No. 12600**: 500 g
1 gasket scraper **No. 12718**: L. 265 mm
1 tape measure **No. 12935**: L. 3 m
1 tyre lever **No. 39 PKW:** L. 400 mm
1 self-grip wrench **No. 6564**: L. 250 mm

96830622
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96830679
10 sockets with hex 1/4" **No. 40**: 3; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 socket long, with hex **No. 40L**: 4.5 mm
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
4 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2; PH3; PH4
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
3 extensions 1/4" **No. 405**: L. 54; 100; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 bit holder insert tool 5/16" **No. 736/40**: 14 x 18 mm
1 bit TORX® **No. 1435**: T55

96830706
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 PZ cross-head screwdriver **No. 4744**: PZ1
5 slotted screwdrivers **No. 4820**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150; 1.6 x 10.0 x 200; 2.0 x 12.0 x 250 mm
3 PH cross-head screwdrivers **No. 4830**: PH1; PH2; PH3
1 PZ cross-head screwdriver **No. 4840**: PZ1
1 automotive voltage tester set **No. 7756**: 3-48 V
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 claw lifter **No. 12922**: Ø 6 mm

96838177
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

96838192
8 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22 mm

TCS 2501 BMW


97830606 Workshop set for BMW motorbikes

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830606	215	27.5



96830622



96832095



96832096



96832097



96832098




96832099



96832100



96832101



96832102

Contains 215-pieces:

96830622

1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96832095

11 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
2 sockets TORX® 1/4" **No. 40TX**: E8; E10
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
8 screwdriver sockets TORX®, with hole 1/4" **No. 44KTXB**: T8; T10; T15; T20; T25; T27; T30; T40
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
2 extensions 1/4" **No. 405**: L. 54; 100 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
4 sockets TORX® 3/8" **No. 45TX**: E8; E10; E12; E14
3 sockets INHEX 3/8" **No. 49**: 5; 6; 8 mm
2 sockets TORX® 3/8" **No. 49TX**: T25; T45
1 T-handle 3/8" **No. 425**: L. 165 mm
2 extensions 3/8" **No. 427**: L. 76; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
15 sockets with hex 3/8" **No. 456**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 34 mm
2 screwdriver sockets INHEX 1/2" **No. 54**: 10; 12 mm
4 screwdriver sockets TORX® 1/2" **No. 54TX**: T40; T50; T55; T60
1 T-handle 1/2" **No. 506**: L. 300 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T50; T55
2 screwdriver sockets TORX® 1/2" **No. 2054TX**: T40; T45

96832096
25 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 27; 29; 30; 32; 34 mm

96832097
10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 18 x 21; 20 x 22
2 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12

96832098
5 slotted screwdrivers **No. 4621**: 0.4 x 2.5 x 80; 0.5 x 3.5 x 90; 0.6 x 4.0 x 100; 1.0 x 6.5 x 140; 1.2 x 8.0 x 160 mm
2 PH cross-head screwdrivers **No. 4631**; PH1; PH2
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 10506**: 0.8 x 4.0 x 300 mm
1 slotted screwdriver **No. 10518**: 1.0 x 5.5 x 410 mm
1 magnetic lifter **No. 12600**: 500 g
1 claw lifter **No. 12922**: Ø 6 mm

96832099
9 TORX® screwdrivers with T-handle **No. 10769**: T9; T10; T15; T20; T25; T30; T40; T45; T50
1 L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40

96832100
1 telephone pliers **No. 6730**: L. 200 mm
1 telephone pliers **No. 6731**: L. 200 mm
4 circlip pliers **No. 6543, 6545**: J1; J2; A1; A2

96832101
1 flat chisel **No. 102**: W. 23; L. 200 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
6 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6; 8 mm
1 glass scraper **No. 10356**: L. 165 mm
1 triangular special scraper **No. 10670**: L. 285 mm
1 flat scraper **No. 10672**: L. 315 mm
1 dead blow hammer **No. 10959**: Ø 40 mm
2 engineer's hammers **No. 10961**: 300; 500 g
1 wire brush **No. 12374**: L. 290 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 safety knife **No. 12965**: L. 174 mm

96832102
1 socket long, with bi-hex $^{3}/_{8}$" **No. 46**: 20.8 mm/$^{13}/_{16}$"
1 spark plug socket long, with rubber insert and bi-hex $^{3}/_{8}$" **No. 4600**: 16 mm/$^{5}/_{8}$"
1 spark plug socket long, with rubber insert and hex $^{3}/_{8}$" **No. 4606**: 18 mm/$^{11}/_{16}$"
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
7 hex screwdrivers with T-handle **No. 10768**: 2.5; 3; 4; 5; 6; 8; 10 mm
2 nut spinners **No. 12507**: 8; 10 mm




TCS 2502 BMW

97830607 Workshop set for BMW motorbikes

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830607	139	12.4




96830180



96830181



96830182



96833414

Contains 139-pieces:

96830180

10 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"
1 bit box **No. 1204/21-1**: 4 x PH; 4 x PZ; 9 x TORX®; 3 x hex
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96830181

5 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 PH cross-head screwdriver **No. 4734**: PH2
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set TORX® **No. 10771/8**:: T9; T10; T15; T20; T25; T27; T30; T40
1 warding file set **No. 12800**: 6-pieces

96830182

15 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 22; 24 mm
5 combination ratchet spanners **No. 17**: 8; 10; 13; 17; 19 mm
1 centre punch and pin punch set, 6-piece **No. 105-108/6**: No. 105/Ø 10 mm; No. 108/Ø 2.5; 3; 4; 5; 6 mm
1 engineer's hammer **No. 10961**: 300 g
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m

96833414

2 screwdriver sockets INHEX, extra long 1/2" **No. 1054**: 8; 10 mm
2 screwdriver sockets INHEX, extra long 1/2" **No. 2054**: 5; 6 mm
2 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T50
2 screwdriver sockets TORX® 1/2" **No. 2054TX**: T40; T45

TCS 3022 Mercedes Benz

97830209 Workshop set for Mercedes-Benz trucks

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830209	264	47.8



96830172



96830174




96830221




96830608



96830622



96833399



96833401



96833402




96833403



96833404



96833413



96833400

Contains 264-pieces:

96830172

2 IMPACT sockets long, with hex 1/2" **No. 51IMP**: 24; 27 mm
9 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
1 IMPACT socket long, with hex 1/2" **No. 2309IMP**: 22 mm
3 IMPACT wheel nut sockets with hex 1/2" **No. 2309IMP K**: 17; 19; 21 mm

96830174

21 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32; 34 mm

96830221

11 sockets with hex 3/4" **No. 55**: 22; 24; 27; 30; 32; 34; 36; 38; 41; 46; 50 mm
1 ratchet 3/4" **No. 552**: L. 165 mm
1 sliding head for T-handle 3/4" **No. 556**: L. 61.5 mm

Tool assortments

1 handle **No. 558**: L. 510 mm
2 extensions 3/4" **No. 559**: L. 200; 400 mm
1 square drive adaptor **No. 568**: 3/4 to 1/2"

96830608
4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96830622
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96833399
3 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150 mm
2 slotted screwdrivers **No. 4621**: 0.5 x 3.5 x 90; 1.2 x 8.0 x 160 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
2 PZ cross-head screwdrivers **No. 4640**: PZ1; PZ2
10 TORX® screwdrivers **No. 4650**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2

96833400
9 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22 mm

96833401
12 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32; 34 x 36; 36 x 41 mm
5 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15 mm
4 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12; E14 x E18; E20 x E24

96833402
2 flat chisels **No. 102**: W. 17; 23; L. 150; 200 mm
1 centre punch **No. 105:** Ø 12 mm
5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm
1 dead blow hammer **No. 10959**: Ø 50 mm
2 engineer's hammers **No. 10961**: 500; 1000 g
1 steel wire brush **No. 12374/2**: L. 290 mm
1 magnetic lifter **No. 12600**: 3000 g

96833403
1 fine scraper **No. 10669** L. 147 mm
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set TORX® **No. 10771/8**:: T9; T10; T15; T20; T25; T27; T30; T40
1 round file **No. 12025**: L. 210 mm
1 half-round file **No. 12030**: L. 260 mm
1 triangular file **No. 12035**: L. 210 mm
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 tape measure **No. 12935**: L. 3 m

96833404
21 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 26; 27; 28; 30; 32; 34 mm
5 sockets TORX® 1/2" **No. 50TX**: E11; E16; E18; E20; E24
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T50; T55; T60
6 screwdriver sockets XZN® 1/2" **No. 54X**: M6; M8; M10; M12; M14; M16
1 flexible handle 1/2" **No. 504**: L. 397 mm
1 T-handle 1/2" **No. 506**: L. 300 mm
3 extensions 1/2" **No. 509**: L. 52; 130; 255 mm
3 Wobble-Drive extensions 1/2" **No. 509W**: L. 52; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"

96833413
12 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2
2 screwdriver sockets POZIDRIV® 1/4" **No. 44PZ**: PZ1; PZ2
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 bit ratchet 1/4" **No. 415B-2K**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
2 screwdriver sockets TORX® 3/8" **No. 49TX**: T40; T45
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
3 extensions 3/8" **No. 427**: L. 76; 160; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 432**: 3/8 to 1/2"
5 bits TORX® **No. 1410-1427**: T6; T7; T8; T9; T25
7 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40

TCS 3026 Mercedes Benz

97830208 Workshop set for Mercedes-Benz cars

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830208	306	43



96830166




96830353




96830608




96831609



96833415



96833416



96833417




96833418



96833419



96833420



96833442



96833460

Contains 306-pieces:

96830166

10 double-ended ring spanners **No. 20**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

96830353

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22; 24 x 27; 30 x 32 mm

96830608

4 circlip pliers **No. 6543-6546**: J2; J21; A2; A21

96831609

6 combination ratchet spanners **No. 17**: 8; 10; 12; 13; 17; 19 mm

96833415

3 nut spinners **No. 12506**: 6; 7; 8 mm
3 nut spinners **No. 12507**: 8; 10; 13 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 160 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 side cutters **No. 6720**: L. 140 mm
2 heavy-duty side cutters **No. 6721**: L. 180; 200 mm

96833416
3 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.2 x 6.5 x 150 mm
2 slotted screwdrivers **No. 4621**: 0.5 x 3.5 x 90; 1.2 x 8.0 x 160 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
9 TORX® screwdrivers **No. 4650**: T6; T7; T8; T10; T15; T20; T25; T27; T30
4 TORX® screwdrivers long **No. 4650L**: T15; T20; T25; T30
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2

96833417
19 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 19; 21; 22; 24; 27; 30; 32 mm
4 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12; E14 x E18; E20 x E24
1 double-ended ring spanner **No. 24**: 10 x 11 mm

96833418
1 tyre lever **No. 39 PKW:** L. 400 mm
2 flat chisels **No. 102**: W. 17; 23; L. 150; 200 mm
1 centre punch **No. 105**: Ø 10 mm
5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm
1 dead blow hammer **No. 10959**: Ø 35 mm
1 engineer's hammer **No. 10961**: 500 g
1 lever bar **No. 11006**: L. 400 mm
1 magnetic lifter **No. 12600**: 3000 g

96833419
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 L-Key hex **No. 10767H/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key TORX® **No. 10769**: T45

96833420
2 IMPACT sockets with bi-hex 1/2" **No. 50D IMP**: 32; 36 mm
2 IMPACT wheel nut sockets with hex 1/2" **No. 2309IMP K**: 17; 19 mm
1 screwdriver socket XZN® 3/4" **No. 59X**: M18
1 sliding head for T-handle 3/4" **No. 556**: L. 61.5 mm
1 handle **No. 558**: L. 510 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 wire brush **No. 12374**: Trim length: 140 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 tape measure **No. 12935**: L. 3 m
1 self-grip wrench **No. 6564**: L. 250 mm

96833442
12 sockets with hex 1/4" **No. 40**: 4; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 screwdriver sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
3 screwdriver sockets slotted 1/4" **No. 41K**: 0.6 x 3.5; 1.0 x 5.5; 1.2 x 8 mm
5 screwdriver sockets INHEX 1/4" **No. 44K**: 3; 4; 5; 6; 8 mm
2 screwdriver sockets PHILLIPS® 1/4" **No. 44PH**: PH1; PH2
2 screwdriver sockets POZIDRIV® 1/4" **No. 44PZ**: PZ1; PZ2
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 bit ratchet 1/4" **No. 415B-2K**: L. 117 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
10 sockets long, with bi-hex 3/8" **No. 46**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
10 uniflex sockets with bi-hex 3/8" **No. 47**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
2 screwdriver sockets TORX® 3/8" **No. 49TX**: T40; T45
3 extensions 3/8" **No. 427**: L. 76; 160; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 ratchet 3/8" **No. 435-2K**: L. 193 mm
1 bit holder 3/8" **No. 442**: L. 32 mm
12 sockets with hex 3/8" **No. 456**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22 mm
1 bit holder insert tool 1/4 " **No. 736/10**: 9 x 12 mm
1 bit holder insert tool 5/16" **No. 736/10**: 9 x 12 mm
2 bits POZIDRIV® 1/4" **No. PZ 1221, PZ 1222**: PZ1; PZ2
5 bits TORX® **No. 1410-1427**: T6; T7; T8; T9; T25
7 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T27; T30; T40
5 bits XZN® **No. 1350-1359**: M4; M5; M6; M8; M10


96833460
21 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 26; 27; 28; 30; 32; 34 mm
5 sockets TORX® 1/2" **No. 50TX**: E11; E16; E18; E20; E24
9 screwdriver sockets INHEX 1/2" **No. 54**: 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
4 screwdriver sockets INHEX 1/2" **No. 54KK**: 6; 7; 8; 10 mm
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T50; T55; T60
5 screwdriver sockets XZN® 1/2" **No. 54X**: M8; M10; M12; M14; M16
1 T-handle 1/2" **No. 506**: L. 300 mm
1 extension 1/2" **No. 509**: L. 130 mm
3 Wobble-Drive extensions 1/2" **No. 509W**: L. 52; 130; 255 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 52; 130 (2 x) mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 square drive adaptor **No. 513**: 1/2 to 3/8"
1 square drive adaptor **No. 514**: 1/2 to 3/4"
2 screwdriver sockets XZN® 1/2" **No. 2054X**: M8; M10
2 screwdriver sockets XZN® 1/2" **No. 3054X**: M12; M14

TCS WB 2700

97830265 Tool assortment

— for service and maintenance work on agricultural, construction and commercial vehicles
— metric tools
— extra long spanner for increased leverage
— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830265	238	35.5



96830288



96830289



96830291



96830292



96830290

Contains 238-pieces:

96830288

23 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32; 34; 36 mm
10 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 7; 8; 10; 12; 14; 17; 19 mm
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T20; T25; T27
6 screwdriver sockets TORX® 1/2" **No. 1054TX**: T30; T40; T45; T50; T55; T60
11 sockets with hex 1/4" **No. 40**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
4 screwdriver sockets INHEX 1/4" **No. 44K**: 4; 5; 6; 8 mm
6 screwdriver sockets TORX® 1/4" **No. 44KTX**: T8; T9; T10; T15; T20; T25
1 square drive adaptor **No. 410**: 1/4 to 1/2"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 25 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 telescopic ratchet 1/2" **No. 516**: L. 410-630 mm
1 QuickRelease T-handle 1/2" **No. 506QR**: L. 300 mm
2 QuickRelease extensions 1/2" **No. 509QR**: L. 130; 255 mm
1 QuickRelease universal joint 1/2" **No. 510QR**: L. 80 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 QuickRelease extension 3/8" **No. 427QR**: L. 160 mm
1 square drive adaptor **No. 432**: 3/8 to 1/2"
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 automotive circuit tester **No. 12905**: 6-12 and 24 V
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
2 L-Keys hex **No. 10765**: 12; 14 mm
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces

96830289

3 pin punches **No. 108**: Ø 4; 6; 8 mm
1 centre punch **No. 105**: Ø 12 mm
4 pin punches **No. 108**: Ø 2; 3; 5; 10 mm
1 engineer's hammer **No. 10961**: 500 g
1 flat chisel **No. 102**: B. 23; L. 200 mm
1 dead blow hammer **No. 10959**: Ø 50 mm
1 cross-cut chisel **No. 103**: W. 18 mm; L. 200 mm
1 engineer's hammer **No. 10961**: 1500 g
1 gasket scraper **No. 12718**: L. 265 mm
1 lever bar **No. 11007**: L. 400 mm
1 magnetic lifter **No. 12600**: 1800 g
1 tape measure **No. 12935**: L. 5 m
1 flat file **No. 12036**: L. 260 mm
1 half-round file **No. 12030**: L. 260 mm
1 round file **No. 12025**: L. 210 mm

Tool assortments

1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 adjustable spanner **No. 4025**: max. 39 mm
1 wire brush **No. 12374**: L. 290 mm

96830290
22 combination spanners **No. 14**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 36 mm

96830291
1 caliper, digital **No. 12900**: Measuring range: 150 mm/6"
1 PH cross-head screwdriver **No. 4734**: PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 cable knife **No. 12320**: Blade length: 90 mm
6 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30; T40
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
4 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.2 x 8.0 x 150 mm
1 PH cross-head screwdriver **No. 4632**: PH4
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m

96830292
8 circlip pliers **No. 6543-6546**: J1; J2; J11; J21; A1; A2; A11; A21
1 side cutters **No. 6720**: L. 160 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm
1 wire strippers: max. Ø 4 mm²
1 crimping pliers **No. 6638**: L. 220 mm

TCS 13214 WW

97830803 Line maintenance set
— for maintenance work on aircraft and helicopters
— 4 x 3/3 inserts for 4 drawers (No. 98 PRO for 2 drawers)
— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830803	167	15.5




96830888



96832206



96832207



96832208

Contains 167-pieces:
96830888
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 brass punch **No. 12495**: L. 200 mm
1 magnet lifter **No. 12601**: 500 g
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 telescopic mirror **No. 12921M**: Ø 57 mm
1 claw lifter **No. 12922**: Ø 6 mm
1 steel ruler **No. 13110**: L. 300 mm

96832206
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 mini electronic's side cutters **No. 6708**: L. 110 mm
1 hook tool **No. 13001:** Angled 45°
1 split pin puller **No. 13009**: L. 265 mm
1 torch **No. 13128**: 320 lm
1 round awl **No. 10758**: L. 280 mm

96832207
2 sockets with hex 1/4" **No. 40**: 4; 4.5 mm
11 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 socket long, with hex 1/4" **No. 40L**: 4.5 mm
11 sockets long, with bi-hex 1/4" **No. 40DL**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 uniflex sockets with bi-hex 1/4" **No. 402**: 6; 7; 8; 9; 10 mm
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 20 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
7 combination ratchet spanners **No. 17**: 8; 9; 10; 12, 13; 17; 19 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm

96832208
18 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 12; 13; 14; 15; 17; 19; 20; 21; 22; 24; 27; 30 mm
5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm




TCS 13214a WW

97830802 Line maintenance set

— for maintenance work on aircraft and helicopters
— 4 x 3/3 inserts for 4 drawers (No. 98 PRO for 2 drawers)
— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830802	163	18.5



96830885



96830886



96830887



96830888

Contains 163-pieces:

96830885

23 combination spanners **No. 13a**: 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8"
1 adjustable spanner **No. 4025**: max. 24 mm

96830886

10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
10 sockets long, with bi-hex 1/4" **No. 40aDL**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
5 uniflex sockets with bi-hex 1/4" **No. 402a**: 1/4; 5/16; 3/8; 7/16; 1/2"
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
8 sockets with bi-hex 3/8" **No. 45a**: 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 15/16; 1"
4 sockets long, with bi-hex 3/8" **No. 46a**: 5/8; 11/16; 3/4; 7/8"
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 3/8" **No. 443**: L. 32 mm
1 bit ratchet screwdriver **No. 4008**: L. 250 mm
6 combination ratchet spanners **No. 17a**: 1/4; 5/16; 3/8; 7/16; 1/2; 9/16"
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces

96830887

2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 electronic's side cutters **No. 6707**: L. 115 mm
1 hook tool **No. 13001:** Angled 45°
1 split pin puller **No. 13009**: L. 265 mm
1 torch **No. 13128**: 320 lm
1 round awl **No. 10758-2K**: L. 175 mm
1 ball-ended L-Key set hex **No. 10767a/13**: 0.050; 1/16; 5/64; 3/32; 7/64; 1/8; 9/64; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8"

96830888

4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm

1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 brass punch **No. 12495**: L. 200 mm
1 magnet lifter **No. 12601**: 500 g
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 telescopic mirror **No. 12921M**: Ø 57 mm
1 claw lifter **No. 12922**: Ø 6 mm
1 steel ruler **No. 13110**: L. 300 mm



TOOL ASSORTMENTS IN TCS INLAY.

TCS 1120/3 VW/AUDI



Tool assortment
— safely integrated in the modular Tool Control System (TCS)
Contains 9-pieces:
1 grooving chisel **No. 112**: W. 26 mm; L. 240 mm
1 triangular special scraper **No. 10670**: L. 260 mm
2 engineer's hammers **No. 10961**: 200; 1000 g
1 sheet metal shears, left-cutting **No. 12752L**: L. 260 mm
1 sheet metal shears, right-cutting **No. 12752R**: L. 260 mm
1 self-grip wrench **No. 6563**: L. 175 mm
2 self-grip wrenches **No. 6564**: L. 145; 250 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96831586	350	530	90	3/3	9	4.4


TCS 102-108/10959/10961/16



Tool assortment
— safely integrated in the modular Tool Control System (TCS)
Contains 16-pieces:
1 flat chisel **No. 102**: W. 23; L. 200 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm
1 dead blow hammer **No. 10959**: Ø 40 mm
1 engineer's hammer **No. 10961**: 500 g
1 brake caliper brush, steel wire **No. 12373**: L. 230 mm
1 magnetic lifter **No. 12600**: 500 g
1 gasket scraper **No. 12718**: L. 265 mm
1 tape measure **No. 12935**: L. 3 m
1 tyre lever **No. 39 PKW:** L. 400 mm
1 self-grip wrench **No. 6564**: L. 250 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830609	350	530	45	3/3	16	4


TCS 1/4 + 10760



Tool assortment
— safely integrated in the modular Tool Control System (TCS)
Contains 27-pieces:
10 sockets with hex 1/4" **No. 40**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 38 mm
1 bit holder 1/4" **No. 412**: L 25 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm
1 L-Key hex **No. 10760**: 12 mm
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96838176	350	175	37	1/3	27	1.08

TCS 1/4 QR + 10760



QuickRelease tool assortment
— safely integrated in the modular Tool Control System (TCS)
Contains 27-pieces:
10 sockets with hex 1/4" **No. 40**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 QuickRelease drive handle 1/4" **No. 400QR**: L. 150 mm
1 QuickRelease T-handle 1/4" **No. 404QR**: L. 116 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 bit holder 1/4" **No. 412**: L 25 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 L-Key hex **No. 10760**: 12 mm
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830364	350	175	37	1/3	27	1.08

TCS 11095-13110/8



Tool assortment


— safely integrated in the modular Tool Control System (TCS)

Contains 8-pieces:

1 thread file **No. 12000/ISO**: L. 230 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 tungsten carbide scriber **No. 12322**: L. 150 mm
1 screw pitch gauges **No. 12665**: 0.25-6 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 steel ruler **No. 13110**: L. 300 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838789	350	175	35	1/3	8	700

TCS 12025-13110/11



Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Contains 11-pieces:

1 gasket scraper **No. 12718**: L. 265 mm
1 engineer's file round, second cut **No. 12025-2K**: L. 210 mm
1 engineer's file half-round **No. 12030**: L. 260 mm
1 engineer's file triangular, second cut **No. 12035-2K**: L. 210 mm
1 engineer's file flat **No.12036-2K:** L. 260 mm
1 hacksaw **No. 12050**: L. 465 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 steel ruler **No. 13110**: L. 300 mm
1 safety knife **No. 12965**: L. 174 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96838759	350	530	35	3/3	11	3.11

TCS 5 821/27



Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Contains 27-pieces:

1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 slotted screwdrivers **No. 4620**: 0.8 x 4 x 100; 1.6 x 10 x 200 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 mini magnetic lifter **No. 12600**: 270 g
1 torch **No. 13132**: 130 lm
1 wooden folding ruler **No. 13112**: L. 2 m
1 ball-ended L-Key set TORX® **No. 10771/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 ball-ended L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830268	350	350	40	2/3	27	2.22

TCS 7 821/9



Tool assortment


— safely integrated in the modular Tool Control System (TCS)


Contains 9-pieces:

4 electrician's slotted screwdrivers **No. 4751**: 0.3 x 1.5; 0.4 x 2; 0.4 x 2.5; 0.5 x 3 mm
3 electrician's PH cross-head screwdrivers **No. 4752**: PH00; PH0; PH1
1 electronics needle nose pliers **No. 6711**: L. 130 mm
1 mini electronics side cutters **No. 6708** L. 115 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830270	350	175	45	1/3	9	418

TCS TORX®/57 MF






Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Contains 53-pieces:

4 double-ended ring spanners TORX® **No. 21TX**: E6 x E8; E10 x E12; E14 x E18; E20 x E24
5 sockets TORX® 1/4" **No. 40TX**: E4; E5; E6; E7; E8
1 bit holder 1/4" **No. 412**: L. 25 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
3 sockets TORX® 3/8" **No. 45TX**: E10; E12; E14
2 screwdriver sockets TORX® 3/8" **No. 49TX**: T40; T45
1 bit holder 3/8" **No. 442**: L. 32 mm
4 sockets TORX® 1/2" **No. 50TX**: E16; E18; E20; E24
3 screwdriver sockets TORX® 1/2" **No. 54TX**: T50; T55; T60
5 bits TORX® **No. 1410-1427**: T6; T7; T8; T9; T25
6 bits TORX® **No. 1440-1446**: T10; T15; T20; T25; T30; T40
10 TORX® screwdrivers **No. 4650**: T6; T7; T8; T9; T10; T15; T20; T25; T27; T30
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830450	350	350	60	2/3	53	2.72




Tool Control System

The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

TCS 8 821/21





Tool assortment

— safely integrated in the modular Tool Control System (TCS)


Contains 21-pieces:

1 screw extractor set **No. 900/6 T**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22
1 warding file set **No. 12800**: 6-pieces
1 flat file **No. 12036**: L. 260 mm
1 gasket scraper **No. 12718**: L. 265 mm
1 safety knife **No. 12965**: L. 165 mm
1 wire brush **No. 12377**: L. 270 mm
1 steel ruler **No. 13110**: L. 300 mm
1 hacksaw **No. 12050**: Blade length: 300 mm
1 tungsten carbide scriber **No. 12322**: Ø 3.15 mm
1 wire cutters **No. 13148**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095:** 0.05-1.00 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830271	350	530	50	3/3	21	3.17

TCS 6 821/7





Tool assortment

— safely integrated in the modular Tool Control System (TCS)

Contains 7-pieces:

1 engineer's hammer **No. 10961**: 500 g
1 dead blow hammer **No. 10959**: Ø 35 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 pin punch **No. 108**: Ø 6 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 drift punch **No. 104**: Ø 4 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830269	350	175	40	1/3	7	1.85

TCS 102-108/10959/10961/12718/13



Punch and chisel set
— safely integrated in the modular Tool Control System (TCS)
Contains 13-pieces:
2 flat chisels **No. 102**: W. 23; 23; L. 200; 300 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm
2 engineer's hammers **No. 10961**: 500; 800 g
1 dead blow hammer **No. 10959**: Ø 40 mm
1 gasket scraper **No. 12718**: L. 265 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830223	350	530	40	3/3	13	5.15

TCS 10956/10961/2



Hammer set
— safely integrated in the modular Tool Control System (TCS)
Contains 2-pieces:
1 engineer's hammer **No. 10961**: 500 g
1 nylon hammer **No. 10956**: Ø 32 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96838194	350	175	45	1/3	2	1.21

TCS 102-108/10956/10960/18



Punch and chisel set
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
1 wire brush **No. 12374**: L. 290 mm
1 safety knife **No. 12965**: L. 174 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
6 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6; 8 mm
1 nylon hammer **No. 10956**: Ø 50 mm
2 engineer's hammers **No. 10961**: 300; 500 g
1 glass scraper **No. 10356**: L. 165 mm
1 triangular special scraper **No. 10670**: L. 285 mm
1 flat scraper **No. 10672**: W. 20; L. 315 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830620	350	530	55	3/3	18	3.94

TCS 102-108/10961/10




Punch and chisel set
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
1 flat chisel **No. 102**: W. 23; L. 200 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 108**: Ø 2 mm
4 pin punches **No. 108**: Ø 3; 4; 5; 6 mm
1 pin punch **No. 108**: Ø 4 mm
1 pin punch **No. 108**: Ø 8 mm
1 engineer's hammer **No. 10961**: 500g

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96830361	350	175	40	1/3	10	1.66

TCS 102-109/10956/10961/6







Punch and chisel set

— safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:

1 flat chisel **No. 102**: B.20; L. 175 mm
2 pin punches **No. 108**: Ø 6 mm, L. 150; 175 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 nylon hammer **No. 10956**: Ø 35 mm
1 engineer's hammer **No. 10961**: 500 g

Product no.	L mm	W mm	H mm	Size	Content pcs.	kg
96838181	350	175	40	1/3	6	1.69

LARGE WORKSHOP TOOL SETS.

801N

Large workshop set

Contains 127-pieces:

1 double open-ended spanner set in roll-up tool pouch **No. 10/12**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm
1 double open-ended spanner set in roll-up tool pouch **No. 12/10**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
1 double-ended ring spanner set **No. 20/12**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm
6 double-ended flex spanner **No. 29**: 10 x 11; 12 x 13; 14 x 15; 16 x 18; 17 x 19; 21 x 23 mm
1 wheel brace $^1/_2$" **No. 35c Pkw**: 17; 19; 22 mm
2 tyre levers **No. 39**: L. 400 mm (2 x)
2 tyre levers **No. 39/1**: L. 600 mm (2 x)
21 sockets with bi-hex $^1/_2$" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32 mm
11 sockets long, with bi-hex $^1/_2$" **No. 51**: 13; 16 mm-$^5/_8$"; 17; 18; 19 mm; 20.8 mm-$^{13}/_{16}$"; 22; 24; 27; 30; 32 mm
7 screwdriver sockets INHEX $^1/_2$" **No. 54**: 4; 5; 6; 8; 10; 12; 14 mm
1 speeder brace $^1/_2$" **No. 501**: L. 433 mm
1 flexible handle $^1/_2$" **No. 504**: L. 397 mm
1 T-handle $^1/_2$" **No. 506**: L. 300 mm
3 extensions $^1/_2$" **No. 509**: L. 52; 130; 255 mm
1 universal joint $^1/_2$" **No. 510**: L. 71 mm
1 ratchet $^1/_2$" **No. 512-2K**: L. 265.5 mm
1 ribbed flat chisel **No. 100**: W. 26; L. 200 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 drift punch **No. 104**: Ø 4 mm
1 centre punch **No. 105**: Ø 10 mm
3 slotted screwdrivers **No. 4622**: 1.2 x 6.5 x 125; 1.2 x 8.0 x 150; 2.0 x 12.0 x 200 mm
2 electrician's slotted screwdrivers **No. 4628**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 125 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 triangular special scraper **No. 10670**: L. 310 mm
1 triangular bearing scraper **No. 10676**: L. 315 mm
1 engineer's hammer **No. 10961**: 500 g
1 precision feeler gauges, 13 blades **No. 11095**: 0.05-1 mm
1 round file **No. 12025**: L. 210 mm
1 half-round file **No. 12030**: L. 260 mm
1 triangular file **No. 12035**: L. 210 mm
1 hacksaw **No. 12050**: L. 300 mm
1 puller, two-armed **No. 12150**: L. 200 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 telephone pliers **No. 6731**: L. 200 mm
2 circlip pliers **No. 6543, No. 6545**: J2; A2
1 water pump pliers **No. 6554**: L. 255 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 oil can **No. 12250**: 0.5 l
1 cable knife **No. 12320**: Blade length: 90 mm
1 spark plug brush **No. 12375**: L. 150 mm
1 tape measure **No. 12935**: L. 3 m

Product no.	Content pcs.	kg
97841210	127	28.65

802N

Large workshop set
Contains 128-pieces:
2 circlip pliers **No. 6545, 6543**: A2; J2
1 water pump pliers **No. 6572**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 oil can **No. 12250**: 0,5 l
1 cable knife **No. 12320**: L. 111 mm
1 spark plug brush **No. 12375:** L. 150 mm
1 double open-ended spanner set in roll-up tool pouch **No. 12/10**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
1 combination spanner set **No. 13/26**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 29; 30; 32 mm
6 double-ended flex spanner **No. 29**: 10 x 11; 12 x 13; 14 x 15; 16 x 18; 17 x 19; 21 x 23 mm
1 wheel brace $^{1}/_{2}$" **No. 35c Pkw**: 17; 19; 22 mm
2 tyre levers **No. 39**: 400 mm (2 x)
2 tyre levers **No. 39/1**: 600 mm (2 x)
21 sockets with bi-hex $^{1}/_{2}$" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 25; 26; 27; 28; 30; 32 mm
11 sockets long, with bi-hex $^{1}/_{2}$" **No. 51**: 13; 16 mm-$^{5}/_{8}$"; 17; 18; 19 mm; 20.8 mm-$^{13}/_{16}$"; 22; 24; 27; 30; 32 mm
7 screwdriver sockets INHEX $^{1}/_{2}$" **No. 54**: 4; 5; 6; 8; 10; 12; 14 mm
1 speeder brace $^{1}/_{2}$" **No. 501**: L. 433 mm
1 flexible handle $^{1}/_{2}$" **No. 504**: L. 397 mm
1 T-handle $^{1}/_{2}$" **No. 506**: L. 300 mm
3 extensions $^{1}/_{2}$" **No. 509**: L. 52; 130; 255 mm
1 universal joint $^{1}/_{2}$" **No. 510**: L. 71 mm
1 ratchet $^{1}/_{2}$" **No. 512-2K**: L. 265.5 mm
1 ribbed flat chisel **No. 100**: W. 26; L. 200 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 drift punch **No. 104**: Ø 4 mm
1 centre punch **No. 105**: Ø 10 mm
3 slotted screwdrivers **No. 4622**: 1.2 x 6.5 x 125; 1.2 x 8.0 x 150; 2.0 x 12.0 x 200 mm
2 electrician's slotted screwdrivers **No. 4628**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 125 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 triangular special scraper **No. 10670**: L. 310 mm
1 triangular bearing scraper **No. 10676**: L. 315 mm
1 engineer's hammer **No. 10961**: 500 g
1 precision feeler gauges, 13 blades **No. 11095**: 0.05-1 mm
1 round file **No. 12025**: L. 210 mm
1 half-round file **No. 12030**: L. 260 mm
1 triangular file **No. 12035**: L. 210 mm
1 hacksaw **No. 12050**: L. 300 mm
1 puller, two-armed **No. 12150**: L. 200 mm
1 tape measure **No. 12935**: L. 3 m
1 combination pliers **No. 6700** L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 telephone pliers **No. 6731**: L. 200 mm

Product no.	Content pcs.	kg
97840312	128	28.9

803N

Large workshop set
Contains 164-pieces:
1 double open-ended spanner set in roll-up tool pouch **No. 10/12**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm
6 double open-ended spanners **No. 10a**: $^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{5}/_{8}$ x $^{11}/_{16}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{15}/_{16}$ x 1"
1 double open-ended spanner set in roll-up tool pouch **No. 12/10**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
1 double open-ended spanner set in roll-up tool pouch **No. 12a/13**: $^{5}/_{32}$; $^{3}/_{16}$; $^{13}/_{64}$; $^{7}/_{32}$; $^{15}/_{64}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"
12 combination spanners **No. 13**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm
7 combination spanners **No. 13a**: $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$"
6 double-ended ring spanners **No. 21**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 17 x 19 mm
5 double-ended ring spanners **No. 20a**: $^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{15}/_{16}$ x 1"
1 double-ended ring spanner set **No. 23/8**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm
6 double-ended ring spanners **No. 230a**: $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{9}/_{16}$ x $^{5}/_{8}$; $^{11}/_{16}$ x $^{3}/_{4}$; $^{13}/_{16}$ x $^{7}/_{8}$; $^{15}/_{16}$ x 1"
18 sockets with bi-hex $^{1}/_{2}$" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 23; 24; 27; 30; 32 mm
15 sockets with bi-hex $^{1}/_{2}$" **No. 50a**: $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1; 1 $^{1}/_{16}$; 1 $^{1}/_{8}$; 1 $^{3}/_{16}$; 1 $^{1}/_{4}$"
1 speeder brace $^{1}/_{2}$" **No. 501**: L. 433 mm
1 flexible handle $^{1}/_{2}$" **No. 504**: L. 397 mm
1 T-handle $^{1}/_{2}$" **No. 506**: L. 300 mm
3 extensions $^{1}/_{2}$" **No. 509**: L. 52; 130; 255 mm
1 universal joint $^{1}/_{2}$" **No. 510**: L. 71 mm
1 ratchet $^{1}/_{2}$" **No. 512-2K**: L. 265.5 mm
1 ribbed flat chisel **No. 100**: W. 20; L. 150 mm
1 centre punch **No. 105**: Ø 12 mm
2 pin punches **No. 108**: Ø 4; 6 mm
4 slotted screwdrivers **No. 4620**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175; 1.6 x 10.0 x 200 mm
1 electrician's slotted screwdriver **No. 4628**: 0.6 x 3.5 x 75 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set hex **No. 10760a/10**: $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{1}/_{8}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"
1 engineer's hammer **No. 10970**: 1 lb.
1 hacksaw **No. 12050**: L. 300 mm
1 combination pliers **No. 6700**: L. 200 mm
1 telephone pliers **No. 6730**: L. 160 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

Product no.	Content pcs.	kg
97842613	164	17.83

804N

Large workshop set
Contains 106-pieces:
1 double open-ended spanner set **No. 12/10**: 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11 mm
19 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
1 socket set 1/4" **No. 40/13/6**: No. 40: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm; No. 400; 404; 405/2; 405/6; 407; 415
15 sockets with bi-hex 1/2" **No. 50**: 10; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm
2 sockets long, with bi-hex 1/2" **No. 51**: 16 mm-5/8"; 20.8 mm-13/16"
1 T-handle 1/2" **No. 506**: L. 300 mm
2 extensions 1/2" **No. 509**: L. 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 ribbed flat chisel **No. 100**: W. 26; L. 200 mm
1 cross-cut chisel **No. 103**: W. 20; L. 200 mm
1 chisel and drift punch set **No. 105-108/6**: No. 105: Ø10 mm; No. 108: Ø 2.5; 3; 4; 5; 6 mm
5 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 plastic hammer **No. 10955**: Ø 35 mm
1 engineer's hammer **No. 10961**: 500 g
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 oil can **No. 12251**: 0,25 l
1 scriber **No. 12321**: L. 250 mm
1 spark plug brush **No. 12375:** L. 150 mm

Product no.	Content pcs.	kg
97842714	106	12.66

811N

Car workshop set
Contains 83-pieces:
1 double open-ended spanner set in roll-up tool pouch **No. 10/12**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm
1 double-ended ring spanner set in roll-up tool pouch **No. 20/12**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 23; 24 x 27; 25 x 28; 30 x 32 mm
1 tyre lever **No. 39**: L. 400 mm
17 sockets with bi-hex 1/2" **No. 50**: 10; 11; 12; 13; 14; 15; 16; 17; 19; 21; 22; 23; 24; 26; 27; 30; 32 mm
2 sockets long, with bi-hex 1/2" **No. 51**: 16 mm-5/8"; 20.8 mm-13/16"
7 screwdriver sockets INHEX 1/2" **No. 54**: 4; 5; 6; 8; 10; 12; 14 mm
1 flexible handle 1/2" **No. 504**: L. 397 mm
1 T-handle 1/2" **No. 506**: L. 300 mm
3 extensions 1/2" **No. 509**: L. 52; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 ribbed flat chisel **No. 100**: W. 26; L. 200 mm
1 cross-cut chisel **No. 103**: W. 16; L. 150 mm
1 drift punch **No. 104**: Ø 4 mm
1 centre punch **No. 105**: Ø 10 mm
3 slotted screwdrivers **No. 4622**: 1.2 x 6.5 x 125; 1.2 x 8.0 x 150; 2.0 x 12.0 x 200 mm
2 electrician's slotted screwdrivers **No. 4628**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 125 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 triangular special scraper **No. 10670:** L. 310 mm
1 triangular bearing scraper **No. 10676**: L. 315 mm
1 engineer's hammer **No. 10961**: 500 g
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 telephone pliers **No. 6731**: L. 200 mm
2 circlip pliers **No. 6543, 6545**: J2; A2
1 water pump pliers **No. 6572**: L. 255 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 spark plug brush **No. 12375:** L. 150 mm

Product no.	Content pcs.	kg
97841311	83	16.3

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

841N

Construction machinery set
Contains 129-pieces:
1 double open-ended spanner set **No. 10/9**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm
23 combination spanners **No. 14**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 34; 36 mm
1 socket set 1/4" **No. 40/13/6**: No. 40: 3.5; 4; 4.5; 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm; No. 400; 404; 405/2; 405/6; 407; 415-2K
1 socket set 1/2" **No. 50/16/6**: No. 50: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 21; 22; 24; 27; 30; 32 mm No. 506, 509/3, 509/5, 509/10, 510, 512-2K
1 flexible handle 1/2" **No. 504**: L. 397 mm
1 square drive adaptor **No. 514**: 3/4 to 1/2"
1 socket set 3/4" **No. 55/9/6N**: No. 55: 32; 34; 36; 38; 41; 46; 50; 55; 60 mm, No. 552, 554, 556, 558, 559/8, 559/16
1 square drive adaptor **No. 568**: 3/4 to 1/2"
1 punch and chisel set **No. 102-108/6**: No. 102: W. 14; L. 125; W. 17; L. 150 mm No. 104: Ø 2; 4 mm; No. 105: Ø 10 mm No. 108: Ø 4 mm
2 PZ cross-head screwdrivers **No. 4840**: PZ1; PZ2
1 screwdriver set **No. 4891**: No. 4820: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm; No. 4830: PH1; PH2
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 self grip wrench **No. 6563** L. 250 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 heavy-duty side cutters **No. 6720**: L. 180 mm
1 nylon hammer **No. 10956**: Ø 35 mm
2 engineer's hammers **No. 10961**: 300; 500 g
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
1 hacksaw **No. 12050**: L. 300 mm
1 metal saw blades **No. 12050R**: 10 blades
1 wire brush **No. 12374**: L. 290 mm
1 magnetic lifter **No. 12600**: 1800 g
1 tape measure **No. 12935**: L. 3 m

Product no.	Content pcs.	kg
97841418	129	35.77



3027

Electrician's set
Contains 85-pieces:
2 combination spanners **No. 13**: 6; 7 mm
1 combination spanner set **No. 13/9**: 9; 10; 11; 12; 13; 14; 17; 19; 22 mm
1 socket set 1/4" **No. 40/23/6** No. 40: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm; No. 41K: 0.6 x 3.5; 1 x 5.5; 1.2 x 8 mm; No. 44K: 3; 4; 5; 6; 8 mm; No. 44PH: PH1; PH2; PH3; PH4; No. 400; 404; 405/2; 405/6; 407; 415-2K
2 sockets long, with bi-hex 3/8" **No. 46**: 12; 20.8 mm
1 spark plug socket long, with bi-hex and rubber insert 3/8" **No. 4600**: 16 mm
1 T-handle 3/8" **No. 425**: L. 165 mm
1 universal joint 3/8" **No. 428**: L. 46 mm
1 extension 3/8" **No. 427**: L. 160 mm
3 electrician's slotted screwdrivers **No. 4628**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 125; 1.0 x 5.5 x 200 mm
2 PH cross-head screwdrivers **No. 4630**: PH1; PH2
1 slotted screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2
1 offset screwdriver slotted **No. 10546**: 1.0 x 5.5 x 125 mm
1 offset screwdriver PH cross-head **No. 10551**: PH1 x PH2
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 160 mm
1 telephone pliers **No. 6731**: L. 160 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 wire cutters **No. 6622**: max. Ø 5 mm²
1 crimping pliers for end sleeves **No. 6638**: L. 220 mm
1 automotive voltage tester set **No. 7756**: 3-48 V
1 nylon hammer **No. 10956**: Ø 35 mm
1 extractor tool **No. 1551**: for flat plug-in sockets with notches, 2.8 mm
1 extractor tool **No. 1552**: for flat plug-in sockets with notches, 5.8 mm
1 tool set KABELEX® **No. 1560**:
1 extractor tool No. 1501: for contact dimension Ø 1.5 mm
1 extractor tool No. 1502: for contact dimension Ø 3.5 mm
1 extractor tool No. 1503: for contact dimension Ø 4.0 mm ABS (truck) or assembly sleeve No. 1523
2 dismantling sleeves No. 1511: Ø 1.5 mm (1 piece mounted)
2 dismantling sleeves No. 1512: Ø 3.5 mm (1 piece mounted)
2 dismantling sleeves No. 1513: Ø 4.0 mm
1 dismantling sleeve No. 1523: ABS

Product no.	Content pcs.	kg
97843101	85	6.29

13200a



Aircraft mechanics basic set

Contains 159-pieces:

1 double open-ended spanner set in roll-up tool pouch **No. 12a/13**: 5/32; 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

21 combination spanners **No. 13a**: 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1"

9 double-ended ring spanners **No. 230a**: 1/4 x 5/16; 5/16 x 11/32; 3/8 x 7/16; 7/16 x 1/2; 1/2 x 9/16; 9/16 x 5/8; 11/16 x 3/4; 13/16 x 7/8; 15/16 x 1"

1 adjustable spanner **No. 4025**: max. 13 mm

1 socket set 1/4" **No. 40aD/30/7QR**: No. 40a: 1/8"; No. 40aD: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 40aDL: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 402a: 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2"; No. 400QR; 405/2QR (2x); 405/6QR; 407QR; 412; 415SG-QR

1 square drive adaptor **No. 409**: 1/4 to 3/8"

1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm

4 sockets long, with bi-hex 3/8" **No. 46a**: 7/16; 1/2; 9/16; 5/8"

1 extension 3/8" **No. 427**: L. 455 mm

1 square drive adaptor **No. 431**: 3/8 to 1/4"

1 socket set 3/8" **No. 45a/22/8QR**: No. 45a: 1/4; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8; 15/16; 1"; No. 47a: 5/16; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4"; No. 427/10QR; 427/6QR; 427/3QR; 428QR; 435SG-QR; 442; 443; 453QR

2 bits PHILLIPS® **No. PH 1220; PH 1222**: PH0; PH2

3 bits TORQ-SET® **No. 13010**: Size 0; 2; 3

1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm

1 bit holder 1/4" **No. 12503**: L. 65 mm

3 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150; 1.6 x 10.0 x 175 mm

3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3

1 L-Key set hex **No. 10760a/9**: 1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 1/4; 5/16; 3/8"

1 pin punch and centre punch set **No. 105-8/6**: No. 105: Ø 10 mm; No. 108: Ø 2.5; 3; 4; 5; 6 mm

1 triangular special scraper **No. 10670**: L. 210 mm

1 plastic hammer **No. 10955**: Ø 27 mm

1 engineer's hammer **No. 10961**: 300 g

1 magnetic lifter **No. 12600**: 500 g

1 telescopic mirror **No. 12921N**: L. 285-725 mm

1 claw lifter **No. 12922**: Ø 6 mm

1 tape measure **No. 12935**: L. 3 m

1 steel ruler **No. 13110**: L. 300 mm

1 combination pliers **No. 6700**: L. 180 mm

1 telephone pliers **No. 6730**: L. 200 mm

1 water pump pliers **No. 6551**: L. 240 mm

1 wire twisting pliers **No. 6575**: L. 280 mm

1 side cutters **No. 6720**: L. 180 mm

1 cable knife **No. 12320**: Blade length: 90 mm

1 scriber **No. 12321**: L. 250 mm

1 caliper **No. 12900**: Measuring range: 150 mm/6"

1 torch **No. 13124**: 165 lm (wide); 122 lm (narrow)

1 wire cutters **No. 13148**: L. 150 mm

1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | IN-HEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces

Product no.	Content pcs.	kg
97846011	159	16

13205a



Aerospace basic set

Contains 131-pieces:

1 double open-ended spanner set in roll-up tool pouch **No. 12a/13**: 5/32; 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

16 combination spanners **No. 13a**: 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4"

6 double-ended ring spanners **No. 230a**: 5/16 x 11/32; 3/8 x 7/16; 7/16 x 1/2; 1/2 x 9/16; 9/16 x 5/8; 11/16 x 3/4"

1 adjustable spanner **No. 4025**: max. 13 mm

1 square drive adaptor 3/8" **No. 409**: 1/4 to 3/8"

1 socket set 1/4" **No. 40aD/30/7QR:** No. 40a: 1/8"; No. 40aD: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 40aDL: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 402a: 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2"; No. 400QR, 405/2QR (2x), 405/6QR, 407QR, 412, 415SG-QR

6 bits slotted 1/4" **No. 1161-1166**: 0.5 x 4; 0.6 x 3.5; 0.6 x 4.5; 0.8 x 4; 0.8 x 5.5; 1 x 5.5 mm

4 bits PHILLIPS® 1/4" **No. PH 1220-1223**: PH0; PH1; PH2; PH3

6 bits TRI-WING® 1/4" **No. 13008**: Size 0; 1; 2; 3; 4; 5

9 bits TORQ-SET® 1/4"**No. 13010:** Size 0; 1; 2; 3; 4; 5; 6; 8; 10

1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm

1 bit holder 1/4" **No. 12503**: L. 65 mm

3 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150; 1.6 x 10.0 x 175 mm

3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3

1 combination pliers **No. 6700**: L. 180 mm

2 telephone pliers **No. 6730**: L. 160; 200 mm

1 water pump pliers **No. 6551**: L. 240 mm

1 wire twisting pliers **No. 6575**: L. 230 mm

1 side cutters **No. 6720**: L. 180 mm

1 pin punch and centre punch **No. 105-8/6**: No. 105: Ø 10 mm; No. 108: Ø 2.5; 3; 4; 5; 6 mm

1 plastic hammer **No. 10955**: Ø 27 mm

1 engineer's hammer **No. 10961**: 300 g

1 round file **No. 12025**: L. 210 mm

1 half-round file **No. 12030**: L. 260 mm

1 triangular file **No. 12035**: L. 210 mm

1 flat file **No. 12036**: L. 250 mm

1 telescopic mirror **No. 12921N**: L. 275-715 mm

1 steel ruler **No. 13110**: L. 300 mm

1 hacksaw **No. 12053**: L. 252 mm

1 scriber **No. 12321**: L. 250 mm

1 caliper **No. 12900**: Measuring range: 150 mm/6"

1 torch **No. 13124**: 165 lm (wide); 122 lm (narrow)

Product no.	Content pcs.	kg
97846012	131	7.79

13211a

Tool assortment
Contains 56-pieces:
3 double open-ended spanners **No. 10a**: 1/4 x 5/16; 3/8 x 7/16; 1/2 x 9/16"
2 combination spanners **No. 13a**: 7/32; 11/32"
3 double-ended ring spanners **No. 230a**: 1/4 x 5/16; 3/8 x 7/16; 1/2 x 9/16"
1 adjustable spanner **No. 4025**: max. 30 mm
1 bit holder 1/4" **No. 442**: L. 32 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 drift punch set **No. 104-105/6**: No. 104: Ø 2; 3; 4; 5; 6 mm; No. 105: Ø 12 mm
1 drift punch **No. 104**: Ø 8 mm
1 pin punch set **No. 108/6**: No. 108: Ø 2.5; 3; 4; 5; 6; 8 mm
4 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150; 1.6 x 10.0 x 175; 2.5 x 14.0 x 250 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 PH cross-head screwdriver **No. 4734**: PH2
1 combination pliers **No. 6700**: L. 180 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 triangular special scraper **No. 10670**: L. 260 mm
1 plastic hammer **No. 10955**: Ø 32 mm
1 engineer's hammer **No. 10970**: 3/4; 1 1/2 lb.
1 round file **No. 12025**: L. 210 mm
1 half-round file **No. 12030**: L. 260 mm
1 triangular file **No. 12035**: L. 210 mm
1 flat file **No. 12036**: L. 260 mm
1 hacksaw **No. 12050**: L. 465 mm
1 tape measure **No. 12935**: L. 3 m
1 steel ruler **No. 13110**: L. 300 mm
1 file brush **No. 12378**: L. 260 mm
1 sheet metal shears, right-cutting **No. 12752R**: L. 260 mm
1 warding file set **No. 12800**: 6-pieces
1 caliper **No. 12900**: Measuring range: 150 mm/6"

Product no.	Content pcs.	kg
97846008	56	9.94

13213a

Tool assortment for engine mechanics
Contains 127-pieces:
4 combination spanners **No. 13a**: 19/32; 5/8; 11/16; 3/4"
8 combination spanners **No. 130a**: 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
5 double-ended ring spanners **No. 24**: 1/4 x 5/16; 5/16 x 3/8; 3/8 x 7/16; 1/2 x 9/16; 5/8 x 3/4"
7 double-ended ring spanners **No. 230a**: 1/4 x 5/16; 5/16 x 3/8; 3/8 x 7/16; 7/16 x 1/2; 9/16 x 5/8; 5/8 x 3/4; 11/16 x 3/4"
2 extensions 1/4" **No. 405**: L. 254; 356 mm
1 QuickRelease speeder brace 1/4" **No. 413QR**: L. 440 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 socket set 1/4" **No. 40aD/30/7QR**: No. 40a: 1/8"; No. 40aD: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 40aDL: 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"; No. 402a: 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2"; No. 400QR; 405/2QR (2x); 405/6QR; 407QR; 412; 415SG-QR
1 socket set 3/8" **No. 45a/22/8QR**: No. 45a: 1/4; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8; 15/16; 1"; No. 47a: 5/16; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4"; No. 427/10QR; 427/6QR; 427/3QR; 428QR; 435SG-QR; 442; 443; 453QR
5 pin punches **No. 109**: Ø 0.9; 1.4; 1.8; 2.4; 2.8 mm
4 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125; 1.6 x 10.0 x 175; 2.0 x 12.0 x 200 mm
2 PH cross-head screwdrivers **No. 4631**: PH1; PH2
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 L-Key set hex **No. 10760a/10T**: 1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8"
1 engineer's hammer **No. 10961**: 300 g
1 precision feeler gauges, 22 blades **No. 11097**: 4-25 mm/1,000"
1 magnetic lifter **No. 12600**: 500 g
1 telescopic mirror **No. 12921N**: L. 285-725 mm
2 telephone pliers **No. 6731**: L. 160; 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 electronic's side cutters **No. 6707**: L. 115 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"

Product no.	Content pcs.	kg
97846010	127	11.5

TOOLS THAT
... inspire

TOOL ASSORTMENTS IN TROLLEYS.

Top features trolley 13217
for professional use

— robust and durable tool trolley made of polypropylene
— easily removable, lockable drawers with pull-out stops in different heights
— 1 removable shelf with 2 handles
— 2 transparent drawer covers beneath the top cover
— 2 smooth-running double castors at the telescopic handle side
— drawers can be used as separate toolboxes thanks to the transparent covers
— with one top cover and one removable cover at the front
— extendable telescopic handle and 2 side carry handles
— resistant to skydrol, acetone, petrol and hydraulic oils
— with integrated lock with 2 keys
— a padlock is optionally available



13214/1 WT/LR

98814930 Line maintenance set (metric) in tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley **No. 13217**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98814930	381	581	455	163	27.5



96831100



96831101




96831102



96831103



96831104



96831105

Contains 163-pieces:

96831100
2 sockets with hex 1/4" **No. 40**: 4; 4.5 mm
11 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
6 sockets with bi-hex 3/8" **No. 45**: 15; 17; 19; 21; 22; 24 mm
4 sockets long, with bi-hex 3/8" **No. 46**: 15; 17; 19; 21 mm
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 QuickRelease universal joint 1/4" **No. 407/1QR**: L. 45 mm

1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428/1QR**: L. 60 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 drive handle 1/4" **No. 400N**: L. 150 mm

96831101
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 claw lifter **No. 12922**: L. 540 mm
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 adjustable spanner **No. 4025**: max. 24 mm
1 combination spanner **No. 13**: 30 mm
1 socket long, with hex **No. 40L**: 4.5 mm
11 sockets long, with bi-hex 1/4" **No. 40DL**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 uniflex sockets with bi-hex 1/4" **No. 402**: 6; 7; 8; 9; 10 mm

96831102
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 telescopic mirror **No. 12921M**: L. 178-921 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 electronics side cutters **No. 6707**: L. 115 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm

96831103
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 soft-faced hammer **No. 10959**: Ø 35 mm
1 steel ruler **No. 13110**: L. 300 mm
1 brass punch **No. 12495**: L. 200 mm
1 scriber **No. 12321**: L. 250 mm
1 pen magnet lifter **No. 12601** : L. 145 mm
1 tape measure **No. 12935**: L. 3 m
1 torch **No. 13128**: 320 lm

96831104
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 round awl **No. 10758**: L. 280 mm
1 hook tool **No. 1300**1: Angled 45°
1 ball-ended L-Key set hex **No. 10767/9:** 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 split pin puller **No. 13009**: L. 265 mm

96831105
17 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 12; 13; 14; 15; 17; 19; 20; 21; 22; 24; 27 mm
5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm
7 combination ratchet spanners **No. 17**: 8; 9; 10; 12; 13; 17; 19 mm





13214a/1 WT/LR


98814935 Line maintenance set (imperial) in tool trolley
No. 13217

— safely integrated in the modular Tool Control System (TCS)
— 1 tool trolley **No. 13217**


Product no.	L mm	W mm	H mm	Content pcs.	kg
98814935	381	581	455	163	28



96831106



96831107



96831108



96831109



96831102



96831103

Contains 163-pieces:

96831106

10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
8 sockets with bi-hex 3/8" **No. 45a**: 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 15/16; 1"
4 sockets long, with bi-hex 3/8" **No. 46a**: 5/8; 11/16; 3/4; 7/8"
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409M** 1/4 to 3/8"
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 60 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 drive handle 1/4" **No. 400N**: L. 150 mm

96831107

1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 claw lifter **No. 12922**: L. 540 mm
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 adjustable spanner **No. 4025**: max. 24 mm
1 combination spanner **No. 13a**: 1 1/8"
10 sockets long, with bi-hex 1/4" **No. 40aDL**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
5 uniflex sockets with bi-hex 1/4" **No. 402a**: 1/4; 5/16; 3/8; 7/16; 1/2"

96831108

4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 round awl **No. 10758**: L. 280 mm
1 hook tool **No. 13001**: Angled 45°
1 L-Key set hex **No. 10767a/13**: 0.05; 1/16; 5/64; 3/32; 7/64; 1/8; 9/64; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8"
1 split pin puller **No. 13009**: L. 265 mm

96831109

22 combination spanners **No. 13a**: 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1 1/16"
6 combination ratchet spanners **No. 17a**: 1/4; 5/16; 3/8; 7/16; 1/2; 9/16"

96831102

1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 telescopic mirror **No. 12921M**: L. 178-921 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 electronics side cutters **No. 6707**: L. 115 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm

96831103

4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 soft-faced hammer **No. 10959**: Ø 35 mm
1 steel ruler **No. 13110**: L. 300 mm
1 brass punch **No. 12495:** L. 200 mm
1 scriber **No. 12321**: L. 250 mm
1 pen magnet lifter **No. 12601** : L. 145 mm
1 tape measure **No. 12935**: L. 3 m
1 torch **No. 13128**: 320 lm






13221 WT/TS

98814915 AOG-set for aircraft in tool trolley No. 13217

— safely integrated in the modular Tool Control System (TCS)

— 1 tool trolley **No. 13217**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98814915	381	581	455	206	29



96830133




96830134



96830135



96830136




96830137



96830138



96830139



96830140

Contains 206-pieces:

96830133

10 sockets with bi-hex 1/4" **No. 40D**: 5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

10 sockets long, with bi-hex 1/4" **No. 40aDL**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"

10 sockets with bi-hex 3/8" **No. 45**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm

8 sockets with bi-hex 3/8" **No. 45a**: 15/16; 1; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4"

1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm

2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 160 mm

2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm

1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm

1 QuickRelease universal joint 3/8" **No. 428QR**: L. 60 mm

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm

1 mini fine-tooth bit ratchet 1/4" **No. 418B**: L. 90 mm

1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm

1 torch **No. 13128**: 320 lm

1 square drive adaptor **No. 431**: 3/8 to 1/4"

1 bit holder 1/4" **No. 412**: L. 25 mm

1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces

96830134

1 water pump pliers **No. 6572**: L. 240 mm

1 telephone pliers **No. 6731**: L. 200 mm

1 connector pliers **No. 6576** L. 230 mm

1 electronics side cutters **No. 6707**: L. 115 mm

1 combination pliers **No. 6700**: L. 160 mm

1 wire twisting pliers **No. 6575**: L. 230 mm

1 telescopic mirror **No. 12921**: Ø 50 mm

1 long nose gripping pliers **No. 6571**: L. 165 mm

1 camloc fastener **No. 4P3**: L. 190 mm

96830135
1 spark plug brush **No. 12375**: L. 150 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
1 claw lifter **No. 12922**: L. 540 mm
1 steel ruler **No. 13110**: L. 300 mm
1 tweezers, straight **No. 13130**: L. 160 mm
1 brass punch **No. 12495**: L. 200 mm
1 pen magnet lifter **No. 12601**: L. 145 mm
1 tire-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 safety knife **No. 12965**: L. 174 mm

96830136
1 drive handle $^{1}/_{4}$" **No. 400N**: L. 150 mm
7 sockets long, with bi-hex $^{1}/_{4}$" **No. 40aDL**: 5; 6; 7; 8; 10; 11; 12; 13 mm
1 square drive adaptor **No. 409**: $^{1}/_{4}$ to $^{3}/_{8}$"
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 soft-face hammer **No. 10959**: Ø 30 mm
1 warding file set **No. 12800**: 6-pieces

96830137
1 double open-ended spanner **No. 10**: 27 x 32 mm
12 combination ratchet spanners **No. 17**: 8; 9; 10; 11; 12, 13; 14; 15; 16; 17; 18; 19 mm

96830138
1 slotted screwdriver with impact cap **No. 4622SK**: 0.8 x 4 x 90 mm
1 PH cross-head screwdriver with impact cap **No. 4632SK**: PH1
1 slotted carburettor screwdriver **No. 4724**: 1.0 x 5.5 x 25 mm
1 PZ cross-head screwdriver **No. 4744**: PZ1
4 electricians slotted screwdrivers **No. 4751**: 0.3 x 1.5 x 40; 0.4 x 2.0 x 60; 0.4 x 2.5 x 75; 0.5 x 3.0 x 75 mm
2 PH electricians cross-head screwdrivers **No. 4752**: PH0; PH1
1 ball-ended L-Key set hex **No. 10767H/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 ball-ended L-Key set hex **No. 10767a/13**: 0.050; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"
1 hook tool **No. 13001**: Angled 45°

96830139
9 double open-ended spanners **No. 10**: 4 x 5; 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 19 x 22
6 combination spanners **No. 13a**: $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{5}/_{8}$; $^{11}/_{16}$"
1 adjustable spanner **No. 4025** max. 24 mm

96830140
8 double-ended ring spanners **No. 23**: 6 x7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22 mm
1 PH cross-head screwdriver with impact cap **No. 4632SK**: PH2
2 TORQ-SET® screwdriver **No. 4636**: 4; 8 mm
1 slotted screwdriver with impact cap **No. 4622SK**: 1.2 x 6.5 x 125 mm
1 split pin puller **No. 13009**: L. 265 mm
1 PH cross-head screwdriver **No. 4632**: PH3
1 round awl **No. 10758**: L. 280 mm

TOOLS THAT
... inspire




13224a WT/TS

98814910 AOG-set for aircraft (imperial) in tool trolley No. 13217

— safely integrated in the modular Tool Control System (TCS)

— 1 tool trolley **No. 13217**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98814910	381	581	455	179	28.4




96830110



96830111



96830112



96830113



96830114



96830115



96830116

Contains 179-pieces:

96830110

1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 Wobble-Drive extension 1/4" **No. 405W**: L. 54 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 45 mm
1 square drive adaptor **No. 409**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L. 25 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
4 sockets long, with bi-hex 3/8" **No. 46a**: 5/8; 11/16; 3/4; 7/8"
8 sockets with bi-hex 3/8" **No. 45a**: 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 15/16; 1"
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 Wobble-Drive extension 3/8" **No. 427W**: L. 76 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 60 mm
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit holder 3/8" **No. 443**: L. 32 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 drive handle 1/4" **No. 400N**: L. 150 mm

96830111

4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 soft-faced hammer **No. 10959N**: Ø 30 mm
1 steel ruler **No. 13110**: L. 300 mm
1 combination spanner **No. 13a**: 1 1/8"
1 scriber **No. 12321**: L. 250 mm

1 pen magnet lifter **No. 12601** : 500 g
1 tape measure **No. 12935**: L. 3 m
1 caliper **No. 12900**: Measuring range: 150 mm/6"

96830112
1 telescopic mirror **No. 12921M**: L. 178-921 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 electronics side cutters **No. 6707**: L. 115 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm
1 connector pliers **No. 6576**: L. 230 mm

96830113
1 QuickRelease speeder brace $^{3}/_{8}$" **No. 453QR**: L. 408 mm
6 uniflex sockets with bi-hex $^{1}/_{4}$" **No. 402a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"
10 sockets long, with bi-hex $^{1}/_{4}$" **No. 40aDL**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"
1 adjustable spanner **No. 4025**: max. 24 mm
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 claw lifter **No. 12922**: L. 540 mm
1 brass punch **No. 12495**: L. 200 mm
1 safety knife **No. 12965**: L. 174 mm

96830114
3 double open-ended spanners **No. 12a**: $^{5}/_{32}$, $^{7}/_{32}$; $^{1}/_{4}$"
17 combination spanners **No. 13a**: $^{3}/_{16}$; $^{13}/_{64}$: $^{7}/_{32}$; $^{15}/_{64}$: $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{19}/_{32}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{25}/_{32}$"
1 hacksaw **No. 12053**: L. 252 mm

96830115
2 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
1 slotted screwdrivers **No. 4724**: 1 x 5.5 x 25 mm
1 PH cross-head screwdriver **No. 4734**: PH2 L. 25 mm
1 L-Key set hex **No. 10767a/13**: 0.050; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
1 split pin puller **No. 13009**: L. 265 mm
1 hook tool **No. 13001**: Angled 45°
1 round awl **No. 10758-2K**: L. 175 mm
1 torch **No. 13128**: 320 lm

96830116
5 combination spanners **No. 13a**: $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1; 1 $^{1}/_{16}$"
1 warding file set **No. 12800**: 6-pieces
6 combination ratchet spanners **No. 17a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"



TOOL ASSORTMENTS FOR TROLLEYS.

805/4 WT TCS

97842803 Tool assortment for trolleys No. 13217

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97842803	89	9.1




96834315



96834316



96834317



96834318


Contains 89-pieces:

96834315 (tray)
10 sockets with hex 1/4" **No. 40:** 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
3 extensions 1/2" **No. 509**: L. 52; 75; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm

96834316 (30 mm)
15 combination spanners **No. 13**: 6; 7; 8; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 22; 24 mm

96834317 (30 mm)
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 L-Key set TORX® **No. 10771/8**:: T9; T10; T15; T20; T25; T27; T30; T40

96834318 (60 mm)
5 combination ratchet spanners **No. 17**: 8; 10; 13; 17; 19 mm
5 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
1 electrician's slotted screwdriver **No. 4628**: 0.4 x 2.5 x 60 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 PH cross-head screwdriver **No. 4734**: PH2



Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

806/6 WT TCS

97830207 Tool assortment for trolleys No. 13217

— safely integrated in the modular Tool Control System (TCS)

Product no.	Content pcs.	kg
97830207	104	14.2



96830094




96830095



96830096



96830097



96830098



96830099

Contains 104-pieces:

96830094 (tray)

10 sockets with hex 1/4" **No. 40**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
17 sockets with hex 1/2" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
2 extensions 1/4" **No. 405**: L. 54; 150 mm
1 universal joint 1/4" **No. 407**: L. 37 mm
1 drive handle 1/4" **No. 400N**: L. 150 mm
1 T-handle 1/4" **No. 404**: L. 116 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
3 extensions 1/2" **No. 509**: L. 75; 130; 255 mm
1 universal joint 1/2" **No. 510**: L. 71 mm
1 T-handle 1/2" **No. 506**: L. 300 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
1 ratchet 1/4" **No. 415-2K**: L. 117 mm

96830095 (30 mm)

10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm

96830096 (30 mm)

5 combination ratchet spanners **No. 17**: 8; 10; 13; 17; 19 mm
1 L-Key hex **No. 10760**: 12 mm
1 flat chisel **No. 102**: W. 20; L. 175 mm
2 pin punches **No. 108**: Ø 6; L. 150; 175 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 engineer's hammer **No. 10961**: 500 g
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96830097 (30 mm)

1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
2 circlip pliers **No. 6543, 6545**: J2; A2
1 water pump pliers **No. 6551**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

96830098 (60 mm)

18 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24 mm

96830099 (60 mm)

5 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150; 1.6 x 8.0 x 175 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 nylon hammer **No. 10956N**: Ø 35 mm

TCS 13214/1 WT/LM 1



Socket set

— for the removable tray of tool trolley No. 13217
— cannot be combined with transparent cover 13217 TA
— safely integrated in the modular Tool Control System (TCS)

Contains 69-pieces:

2 sockets with hex 1/4" **No. 40**: 4; 4.5 mm
11 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
6 sockets with bi-hex 3/8" **No. 45**: 15; 17; 19; 21; 22; 24 mm
4 sockets long, with bi-hex 3/8" **No. 46**: 15; 17; 19; 21 mm
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 QuickRelease universal joint 1/4" **No. 407/1QR**: L. 45 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428/1QR**: L. 60 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 drive handle 1/4" **No. 400N**: L. 150 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831100	245	465	50	69	2.54

TCS 13214a/1 WT/LM 1



Socket set

— for the removable tray of tool trolley No. 13217
— cannot be combined with transparent cover 13217 TA
— safely integrated in the modular Tool Control System (TCS)


Contains 68-pieces:

10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
8 sockets with bi-hex 3/8" **No. 45a**: 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 15/16; 1"
4 sockets long, with bi-hex 3/8" **No. 46a**: 5/8; 11/16; 3/4; 7/8"
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 25 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 60 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 5/16" **No. 443**: L. 32 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 drive handle 1/4" **No. 400N**: L. 150 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831106	245	460	45	68	2.61

TOOLS THAT
... inspire

TCS 13214/1 WT/LM 2




Tool assortment
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)

Contains 24-pieces:
1 QuickRelease speeder brace $^{3}/_{8}$" **No. 453QR**: L. 408 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 claw lifter **No. 12922**: L. 540 mm
1 tire-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 adjustable spanner **No. 4025**: max. 24 mm
1 combination spanner **No. 13**: 30 mm
1 socket long, with hex $^{1}/_{4}$" **No. 40L**: 4.5 mm
11 sockets long, with bi-hex $^{1}/_{4}$" **No. 40DL**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 uniflex sockets with bi-hex $^{1}/_{4}$" **No. 402**: 6; 7; 8; 9; 10 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831101	250	465	30	24	2.02

TCS 13214a/1 WT/LM 2



Tool assortment
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)

Contains 22-pieces:
1 QuickRelease speeder brace $^{3}/_{8}$" **No. 453QR**: L. 408 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1.00 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 claw lifter **No. 12922**: L. 540 mm
1 tyre-tread caliper **No. 12900/3**: Measuring range: 0-30 mm
1 adjustable spanner **No. 4025**: max. 24 mm
1 combination spanner **No. 13a**: 1 $^{1}/_{8}$"
10 sockets long, with bi-hex $^{1}/_{4}$" **No. 40aDL**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"
5 uniflex sockets with bi-hex $^{1}/_{4}$" **No. 402a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$"

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831107	255	460	30	22	1.99

TCS 13214/1 WT/LM 3



Tool assortment
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)

Contains 8-pieces:
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 telescopic mirror **No. 12921M**: L. 178-921 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 electronic's side cutters **No. 6707**: L. 115 mm
1 combination pliers **No. 6700**: L. 160 mm
1 telephone pliers **No. 6731**: L. 200 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831102	250	460	30	8	1.83

TCS 13214/1 WT/LM 4



Tool assortment
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)

Contains 12-pieces
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 engineer's hammer **No. 10961**: 500 g
1 soft-faced hammer **No. 10959**: Ø 35 mm
1 steel ruler **No. 13110**: L. 300 mm
1 brass punch **No. 12495**: L. 200 mm
1 scriber **No. 12321**: L. 250 mm
1 pen magnet lifter **No. 12601**: L. 145 mm
1 tape measure **No. 12935**: L. 3 m
1 torch **No. 13128**: 320 lm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831103	245	460	60	12	2.25

TCS 13214/1 WT/LM 5



Tool assortment
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 13-pieces:
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 round awl **No. 10758**: L. 280 mm
1 hook tool **No. 13001**: Angled 45°
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 split pin puller **No. 13009**: L. 265 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831104	250	455	60	13	1.6


TCS 13214a/1 WT/LM 5



Tool assortment
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 25-pieces:
4 plastic scrapers **No. 10678**: Medium blade, **No. 10679**: Narrow blade, **No. 10680**: Slanted blade, **No. 10681**: Sharp blade
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 round awl **No. 10758**: L. 280 mm
1 hook tool **No. 13001**: Angled 45°
1 L-Key set hex **No. 10767a/13**: 0.05; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"
1 split pin puller **No. 13009**: L. 265 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831108	245	458	60	25	1.64


TCS 13214/1 WT/LM 6



Spanner set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 29-pieces:
17 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 12; 13; 14; 15; 17; 19; 20; 21; 22; 24; 27 mm
5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm
7 combination ratchet spanners **No. 17**: 8; 9; 10; 12; 13; 17; 19 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831105	245	460	60	29	2.81

TCS 13214a/1 WT/LM 6



Spanner set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 28-pieces:
22 combination spanners **No. 13a**: $^{3}/_{16}$; $^{13}/_{64}$; $^{7}/_{32}$; $^{15}/_{64}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{19}/_{32}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{25}/_{32}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1 $^{1}/_{16}$"
6 combination ratchet spanners **No. 17a**: $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$"

Product no.	L mm	W mm	H mm	Content pcs.	kg
96831109	245	458	60	28	2.88

TCS 13217 WT MOTOR 10/10 6-32



Double open-ended spanner set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
10 double open-ended spanners **No. 10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 21; 20 x 22; 24 x 27; 30 x 32 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96830120	250	460	30	10	1545

TCS 13217 WT OPEN BOX 13/18 6-24



Combination spanner set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
18 combination spanners **No. 13**: 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96830121	250	460	60	18	1940

TCS 13217 WT MOTOR 10a/9



Double open-ended spanner set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 9-pieces:
9 double open-ended spanners **No. 10a**: $^{1}/_{4}$ x $^{5}/_{16}$; $^{3}/_{8}$ x $^{7}/_{16}$; $^{1}/_{2}$ x $^{9}/_{16}$; $^{19}/_{32}$ x $^{11}/_{16}$; $^{5}/_{8}$ x $^{3}/_{4}$; $^{3}/_{4}$ x $^{7}/_{8}$; $^{25}/_{32}$ x $^{13}/_{16}$; $^{15}/_{16}$ x 1; 1 $^{1}/_{8}$ x 1 $^{5}/_{16}$"

Product no.	L mm	W mm	H mm	Content pcs.	g
96830124	250	460	30	9	1600

TCS 13217 WT OPEN BOX 13a/22



Combination spanner set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 22-pieces:
22 combination spanners **No. 13a**: $^{3}/_{16}$; $^{13}/_{64}$; $^{7}/_{32}$; $^{15}/_{64}$; $^{1}/_{4}$; $^{9}/_{32}$; $^{5}/_{16}$; $^{11}/_{32}$; $^{3}/_{8}$; $^{7}/_{16}$; $^{1}/_{2}$; $^{9}/_{16}$; $^{19}/_{32}$; $^{5}/_{8}$; $^{11}/_{16}$; $^{3}/_{4}$; $^{25}/_{32}$; $^{13}/_{16}$; $^{7}/_{8}$; $^{15}/_{16}$; 1; 1 $^{1}/_{16}$"

Product no.	L mm	W mm	H mm	Content pcs.	g
96830125	250	460	60	22	2440

TCS 13217 WT OPEN RATCH 17/12



Combination ratchet spanner set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 12-pieces:
12 combination ratchet spanners **No. 17**: 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96830128	250	460	30	12	1485


TCS 13217 WT FastRatch 240/10



Ratchet spanner set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
10 ratchet spanners **No. 240**: 8; 10; 11; 12; 13; 14; 16; 17; 18; 19 mm

Product no.	L mm	W mm	H mm	Content pcs.	g
96830130	250	460	30	10	2005

TCS WT 40/4008/10/9




Socket set
— for the removable tray of tool trolley No. 13217
— cannot be combined with transparent cover 13217 TA
— safely integrated in the modular Tool Control System (TCS)
Contains 39-pieces:
10 sockets with hex 1/4" **No. 40**: 4; 4.5; 5; 6; 7; 8; 10; 11; 12; 13 mm
2 QuickRelease extensions 1/4" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 bit holder 1/4" **No. 412**: L 25 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit box **No. 1204/21-1**: 4 x PH; 4 x PZ; 9 x TORX®; 3 x hex
1 bit adaptor, manual 1/4" **No. 3116**: L. 50 mm
2 bit ratchet screwdriver 1/4" **No. 4008**: L. 95; 250 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830132	250	460	55	39	0.99



TCS WT 40/45/46/37/14




Socket set
— for the removable tray of tool trolley No. 13217
— cannot be combined with transparent cover 13217 TA
— safely integrated in the modular Tool Control System (TCS)

Contains 51-pieces:
10 sockets with bi-hex $^1/_4$" **No. 40aD**: $^3/_{16}$; $^7/_{32}$; $^1/_4$; $^9/_{32}$; $^5/_{16}$; $^{11}/_{32}$; $^3/_8$; $^7/_{16}$; $^1/_2$; $^9/_{16}$"
10 sockets long, with bi-hex $^1/_4$" **No. 40aDL**: $^3/_{16}$; $^7/_{32}$; $^1/_4$; $^9/_{32}$; $^5/_{16}$; $^{11}/_{32}$; $^3/_8$; $^7/_{16}$; $^1/_2$; $^9/_{16}$"
5 uniflex sockets with bi-hex $^1/_4$" **No. 402a**: $^1/_4$; $^5/_{16}$; $^3/_8$; $^7/_{16}$; $^1/_2$"
2 QuickRelease extensions $^1/_4$" **No. 405QR**: L. 54; 150 mm
1 QuickRelease universal joint $^1/_4$" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409M**: $^1/_4$ to $^3/_8$"
1 bit holder $^1/_4$" **No. 412**: L 25 mm
1 QuickRelease fine-tooth ratchet $^1/_4$" **No. 415QR N**: L. 117 mm
1 bit fine-tooth ratchet $^1/_4$" **No. 415SGB N**: L. 117 mm
8 sockets with bi-hex $^3/_8$" **No. 45a**: $^1/_2$; $^9/_{16}$; $^{19}/_{32}$; $^5/_8$; $^{11}/_{16}$; $^3/_4$; $^{15}/_{16}$; 1"
4 sockets long, with bi-hex $^3/_8$" **No. 46a**: $^5/_8$; $^{11}/_{16}$; $^3/_4$; $^7/_8$"
2 QuickRelease extensions $^3/_8$" **No. 427QR**: L. 76; 240 mm
1 QuickRelease universal joint $^3/_8$" **No. 428QR**: L. 46 mm
1 square drive adaptor **No. 431**: $^3/_8$ to $^1/_4$"
1 square drive adaptor **No. 432M**: $^3/_8$ to $^1/_2$"
1 QuickRelease fine-tooth ratchet $^3/_8$" **No. 435QR N**: L. 193 mm
1 bit holder $^3/_8$" **No. 443**: L. 32 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830123	250	460	60	51	2.5

TCS WT 40/52/27/13



Socket set
— for the removable tray of tool trolley No. 13217
— cannot be combined with transparent cover 13217 TA
— safely integrated in the modular Tool Control System (TCS)

Contains 40-pieces:
10 sockets with hex $^1/_4$" **No. 40:** 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 drive handle $^1/_4$" **No. 400N**: L. 150 mm
1 T-handle $^1/_4$" **No. 404**: L. 116 mm
2 extensions $^1/_4$" **No. 405**: L. 54; 150 mm
1 universal joint $^1/_4$" **No. 407**: L. 38 mm
1 bit holder $^1/_4$" **No. 412**: L 25 mm
1 QuickRelease fine-tooth ratchet $^1/_4$" **No. 415QR N**: L. 117 mm
17 sockets with hex $^1/_2$" **No. 52**: 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm
1 T-handle $^1/_2$" **No. 506**: L. 300 mm
3 extensions $^1/_2$" **No. 509**: L. 52; 130; 255 mm
1 universal joint $^1/_2$" **No. 510**: L. 71 mm
1 QuickRelease fine-tooth ratchet $^1/_2$" **No. 512QR N80**: L. 265.5 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830117	350	530	60	40	4

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

TCS WT 4622SK-4650/10767H/20



Screwdriver set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 20-pieces:
3 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
5 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30
1 L-Key set hex **No. 10767H/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830122	220	460	60	20	1.5

TCS WT 4650-4665 VDE/10767a/24



Screwdriver set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 24-pieces:
5 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30
3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75; 0.6 x 3.5 x 100; 1.0 x 5.5 x 125 mm
3 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2; PH3
1 L-Key set hex **No. 10767a/13**: 0.050; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830127	250	460	60	24	1.4

TCS WT 4622SK-4650/10767a/24



Screwdriver set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 24-pieces:
3 slotted screwdrivers with impact cap **No. 4622SK**: 0.8 x 4.0 x 90; 1.0 x 5.5 x 100; 1.2 x 6.5 x 125 mm
3 PH cross-head screwdrivers with impact cap **No. 4632SK**: PH1; PH2; PH3
5 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30
1 L-Key set hex **No. 10767a/13**: 0.050; $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{7}/_{64}$; $^{1}/_{8}$; $^{9}/_{64}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830126	250	460	60	24	1.61

TCS WT 4650-4665 VDE/10767H/20



Screwdriver set
— suitable for the 60 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 20-pieces:
5 TORX® screwdrivers **No. 4650**: T10; T15; T20; T25; T30
3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75; 0.6 x 3.5 x 100; 1.0 x 5.5 x 125 mm
3 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2; PH3
1 L-Key set hex **No. 10767H/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830129	250	460	60	20	1.32

TCS WT 6551-6730/7



Pliers set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
2 circlip pliers **No. 6543, 6545**: J2; A2
1 water pump pliers **No. 6551**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 250 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830118	250	460	30	7	1.88

TCS WT 6543-6730/7



Pliers set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
2 circlip pliers **No. 6543, 6545**: J2; A2
1 water pump pliers **No. 6551**: L. 240 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm


Product no.	L mm	W mm	H mm	Content pcs.	kg
96830131	260	460	30	7	1.66

TCS WT 102-109/16



Hammer and chisel set
— suitable for the 30 mm drawers of tool trolley No. 13217
— safely integrated in the modular Tool Control System (TCS)
Contains 16-pieces:
1 flat chisel **No. 102**: W. 20; L. 175 mm
1 centre punch **No. 105**: Ø 12 mm
6 pin punches **No. 108**: Ø 2; 3; 4; 5; 6; 8 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 nylon hammer **No. 10956**: Ø 27 mm
1 engineer's hammer **No. 10961**: 300 g
1 telescopic stainless steel mirror **No. 12921M**: Ø 32 mm
1 tape measure **No. 12935**: L. 3 m
1 steel ruler **No. 13110**: L. 300 mm
1 cable knife **No. 12320**: L. 111 mm
1 pen light **No. 13126-2**: 35 lm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96830119	250	460	30	16	1.79



Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

TOOL ASSORTMENTS IN CASES.



Top features tool box 13301
robust aluminium frame with impact edge protection

— ABS case shells
— 2 lockable flip-locks
— hinge cover
— variable base shell
— stable feet
— cover plate with 15 compartments, tool board with 22 compartments
— separate document compartment in lid
— max. load capacity: 25 kg

13301/69



Tool assortment in case
1 tool case **No. 13301**: 2 lockable flip-locks; removable inserts
Contains 69-pieces:
1 socket clip rail with sockets 1/4" **No. 40D/10-12916**: 5; 5.5; 6; 7; 8; 9 ;10; 12; 13; 14 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 95 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 50 mm
3 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 1.2 x 6.5 x 150; 1.0 x 5.5 x 125 mm
2 PH cross-head screwdrivers **No. 4632**: PH1; PH2
1 combination pliers **No. 6700**: L. 180 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 safety knife **No. 12965**: L. 174 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 plastic hammer **No. 10955:** Ø 35 mm
1 centre punch **No. 105**: Ø 10 mm
1 drift punch **No. 104**: Ø 2 mm
1 pin punch **No. 108**: Ø 4 mm
1 engineer's hammer **No. 10961**: 500 g
1 voltage tester **No. 10554**: 125-250 V
1 double open-ended spanner set **No. 10/9N**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 wooden folding ruler **No. 13112**: L. 2 m

Product no.	L mm	W mm	H mm	Content pcs.	kg
98830182	500	210	350	69	9.5

13301/87



Tool assortment in case
1 tool case **No. 13301**: 2 lockable flip-locks; removable inserts
Contains 87-pieces:
1 socket clip rail with sockets 1/2" **No. 50/10-12918**: 10, 13, 14, 17, 19, 22, 24, 27, 30, 32 mm
1 QuickRelease extension 1/2" **No. 509QR**: L. 130 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.6 x 3.5 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2; PH3
1 VDE combination pliers **No. 6700 VDE**: L. 180 mm
1 VDE telephone pliers **No. 6730 VDE**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 VDE heavy-duty side cutters **No. 6721 VDE**: L. 160 mm
1 drift punch **No. 104**: Ø 2 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 pin punch **No. 108**: Ø 4 mm
1 centre punch **No. 105:** Ø 10 mm
1 safety knife **No. 12965**: L. 174 mm
1 plastic hammer **No. 10955**: Ø 35 mm
1 voltage tester **No. 10554**: 125-250 V
1 engineer's hammer **No. 10961**: 500 g
1 adjustable spanner **No. 4025** max. 34 mm
3 combination spanners **No. 13**: 21; 22; 24 mm
1 ratchet bit set, in softcase **No. 40/29/4 SCI**: No. 3825/1; 3116; 4008-2; 40: 5.5; 6; 7; 8; 10; 12; 13; 14 mm; 21 bits: SL 1x5.5; PH1 (x2); PH2 (x2); PH3; PZ1 (x2); PZ2 (x2); T10;15;20;25;30;40; INHEX: 3;4;5;6 mm; No. 418B
1 combination spanner set **No. 13/10**: 8; 9; 10; 11; 12; 13; 14; 15; 17; 19 mm
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 wooden folding ruler **No. 13112**: L. 2 m

Product no.	L mm	W mm	H mm	Content pcs.	kg
98830183	500	210	390	87	12.5



Top features tool box 13302/TR
Robust aluminium frame with impact edge protection

— with trolley function
— ABS case shells, ergonomically shaped carrying handle
— with user-friendly telescopic handle and 2 inline castors
— 2 lockable flip-lock and Proficode combination lock
— hinge cover
— variable base tray (2 aluminium dividers)
— stable base feet
— cover plate with 15 insert pockets, tool board with 22 insert pockets
— separate document compartment in the lid
— maximum load capacity: 30 kg

13302/TR/69



Tool assortment in case
1 tool case **No. 13302/TR**: Trolley function; combination lock; removable inserts
Contains 69-pieces:
1 socket clip rail with sockets 1/4" **No. 40D/10-12916**: 5; 5.5; 6; 7; 8; 9 ;10; 12; 13; 14 mm
1 bit ratchet screwdriver 1/4" **No. 4008:** L. 250 mm
1 bit adaptor, manual 1/4" **No. 3116**: L. 50 mm
3 slotted screwdrivers **No. 4620**: 0.6 x 3.5 x 75; 1.2 x 6.5 x 150; 1.0 x 5.5 x 125 mm
2 PH cross-head screwdrivers **No. 4632**: PH1; PH2
1 combination pliers **No. 6700**: L. 180 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm
1 safety knife **No. 12965**: L. 174 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 plastic hammer **No. 10955**: Ø 35 mm
1 centre punch **No. 105**: Ø 10 mm
1 drift punch **No. 104**: Ø 2 mm
1 pin punch **No. 108**: Ø 4 mm
1 engineer's hammer **No. 10961**: 500 g
1 voltage tester **No. 10554:** 125-250 V
1 double open-ended spanner set **No. 10/9N**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 21 x 24 mm
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 wooden folding ruler **No. 13112**: L. 2 m

Product no.	L mm	W mm	H mm	Content pcs.	kg
98830184	525	275	455	69	12

13302/TR/87



Tool assortment in case
1 tool case **No. 13302/TR**: Trolley function; Combination lock; removable inserts
Contains 87-pieces:
1 socket clip rail with sockets 1/2" **No. 50/10-12918**: 10; 13; 14; 17; 19; 22; 24; 27; 30; 32 mm
1 QuickRelease extension 1/2" **No. 509QR**: 130 mm
1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.6 x 3.5 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
3 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2; PH3
1 VDE combination pliers **No. 6700 VDE**: L. 180 mm
1 VDE telephone pliers **No. 6730 VDE**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 VDE heavy-duty side cutters **No. 6721 VDE**: L. 160 mm
1 drift punch **No. 104**: Ø 2 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 pin punch **No. 108**: Ø 4 mm
1 centre punch **No. 105**: Ø 10 mm
1 safety knife **No. 12965**: L. 174 mm
1 plastic hammer **No. 10955**: Ø 35 mm
1 voltage tester **No. 10554**: 125-250 V
1 engineer's hammer **No. 10961**: 500 g
1 adjustable spanner **No. 4025**: max. 34 mm
3 combination spanners **No. 13**: 21; 22; 24 mm
1 ratchet bit set, in soft case 1/4" **No. 40/29/4 SCI**: No. 3825/1; 3116; 4008-2; 40: 5.5; 6; 7; 8; 10; 12; 13; 14 mm; 21 bits: SL 1x5.5; PH1 (x2); PH2 (x2); PH3; PZ1 (x2); PZ2 (x2); T10;15;20;25;30;40; INHEX: 3;4;5;6 mm; No. 418B
1 combination spanner set **No. 13/10**: 8; 9; 10; 11; 12; 13; 14; 15; 17; 19 mm
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 wooden folding ruler **No. 13112**: L. 2 m

Product no.	L mm	W mm	H mm	Content pcs.	kg
98830185	520	280	460	87	15

13302/TR/99



Electronic tool set

1 tool case with trolley function **No. 13302/TR**

Contains 99-pieces:

10 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm

5 combination spanners **No. 13a**: $^{3}/_{16}$; $^{7}/_{32}$; $^{1}/_{4}$; $^{3}/_{8}$; $^{1}/_{2}$"

5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm

1 adjustable spanner **No. 4025**: max. 13 mm

2 nut spinners **No. 12500N**: 6; 7 mm

4 L-Keys hex **No. 10765**: 2; 2.5; 3; 4 mm

1 slotted screwdriver **No. 4621 5**: 1.2 x 8.0 mm

3 PH cross-head screwdrivers **No. 4630**: PH0; PH1; PH2

3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5; 0.8 x 4.0 ;1.2 x 6.5 mm

2 slotted screwdrivers **No. 4724**: 0.6 x 3.5 x 25; 1.0 x 5.5 x 25 mm

3 electronics hex screwdrivers **No. 4753**: 0.7; 0.9; 1.3 mm

1 combination pliers **No. 6700**: L. 160 mm

1 telephone pliers **No. 6730**: L. 160 mm

1 needle nose pliers **No. 6536**: L. 160 mm

1 electronics side cutters **No. 6707**: L. 115 mm

1 mini electronics side cutters **No. 6708**: L. 110 mm

1 wire strippers: max. Ø 4 mm^2

8 pin punches **No. 109**: Ø 0.9; 1.4; 1.8; 2.4; 2.8; 3.4; 3.9; 5.9 mm

2 L-Keys slotted **No. 10546**: 0.8 x 4.0; 1.0 x 5.5 mm

1 wire cutters **No. 13148**: L. 150 mm

1 caliper **No. 12900**: Measuring range: 150 mm/6"

1 telescopic mirror **No. 12921N**: Ø 50 mm

1 voltage tester **No. 10554**: 125-250 V

1 L-Key set hex **No.10760a/9**: $^{1}/_{16}$; $^{5}/_{64}$; $^{3}/_{32}$; $^{1}/_{8}$; $^{5}/_{32}$; $^{3}/_{16}$; $^{1}/_{4}$; $^{5}/_{16}$; $^{3}/_{8}$"

1 electronic screwdriver set **No. 4797:** 4751: 0.3 x 1.5 x 40, 0.4 x 2. 0 x 60; 0.4 x 2.5 x 75; 0.5 x 3.0 x 75 mm; 4752: PH00; PH1

1 needle file set **No. 13100:** 6-pieces

Aerospace tool kit No. 13211:

1 desoldering device: EGB/ESD

1 PCB connector: L. 180 mm: 6-piece

1 magnetic lifter and inspection mirror set: 2-piece

1 assembly tweezers: transverse

1 tweezers, curved: L. 165 mm

1 universal tweezers: L. 140 mm

1 precision knife

1 replacement blade for precision knife

1 test equipment set

1 spring hook set, in bag: 7-piece

1 soldering iron: 40 W

1 oil filler: 5 ccm

1 radio solder pen: 1.0 60% Sn

1 file block: 115 x 8 mm, jaws pointed

1 watchmaker magnifying glass: 7X magnification

1 desoldering wire: 1.4 mm, 1.5 m

1 retaining slotted screwdriver: 0.8 x 5.0 x 150 mm

1 retaining slotted screwdriver: 0.6 x 4.0 x 125 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96221010	520	280	460	99	11.5



TOOL ASSORTMENTS IN L-BOXX®.

Top features of L-BOXX® tool box
mobile tool storage solution for trade and industry

— protects tools from damage and water spray
— compatible with the entire L-BOXX® range
— honeycomb function increases the stability of the base
— innovative one-handed click system
— contents are accessible even when the boxes are stacked and connected
— impact-resistant ABS plastic
— load capacity: 12 kg
— weight bearing capacity: 85 kg, can also be used as a step

136/95 L-BOXX®



Tool assortment basic
1 tool box **L-BOXX®**
Contains 95-pieces:
Tool card in lid:
1 slotted screwdriver **No.: 4621**: 0.5 x 3.5 x 90 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 voltage tester **No. 10554**: 125-250 V
1 magnetic lifter **No. 12600**: 270 g
1 wooden folding ruler **No. 13112**: L. 2 m
1 water pump pliers **No. 6551**: L. 240 mm

96830700 TCS L-BOXX® basic set:
7 combination spanners **No. 13**: 8; 10; 13; 17; 19; 22; 24 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces
1 bit holder 1/2" **No. 543**: L. 38 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 250 mm
1 extension 1/2" **No. 509**: L. 130 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
11 sockets with hex 1/2" **No. 52**: 8; 10; 12; 13; 16; 17; 18; 19; 22; 24, 27 mm
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

Product no.	L mm	W mm	H mm	Filling volume	Content pcs.	kg
97830700	360	444	152	12,2 l	95	7.34

136/96 L-BOXX®



Tool assortment industry
1 tool box **L-BOXX®**
Contains 96-pieces:
Tool card in lid:
4 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH0; PH1; PH2; PH3
3 VDE electrician's slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75;0.6 x 3.5 x 100; 1.0 x 5.5 x 125 mm
1 wire strippers: max. Ø 4 mm^2
1 VDE side cutters **No. 6720 VDE**: L. 160 mm
1 VDE telephone pliers **No. 6730 VDE**: L. 160 mm
1 VDE telephone pliers **No. 6731 VDE**: L. 200 mm
1 wooden folding ruler **No. 13112**: L. 2 m
1 water pump pliers **No. 6551**: L. 240 mm
1 mini magnetic lifter **No. 12600**: 270 g

96830702 TCS L-BOXX® industry set:
1 stripping knife **No. 12967**: Ø 4-28 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces
1 engineer's hammer **No. 10961**: 500 g
1 voltage tester **No. 10554**: 125-250 V
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 95 mm
1 putty knife **No. 12481**: L. 112 mm
1 torch **No. 13132**: 130 lm
1 L-Key set TORX® **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 L-Key set hex**No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 adjustable spanner **No. 4025**: max. 34 mm
1 safety knife **No. 12965**: L. 174 mm

Product no.	L mm	W mm	H mm	Filling volume	Content pcs.	kg
97830701	360	444	152	12,2 l	111	9.5

136/111 L-BOXX®



Tool assortment electrics
1 tool box **L-BOXX®**
Contains 111-pieces:
Tool card in lid:
1 slotted screwdriver **No.: 4621**: 0.5 x 3.5 x 90 mm
3 PH cross-head screwdrivers **No. 4630**: PH1; PH2; PH3
1 voltage tester No. 10554: 125-250 V
1 L-Key set TORX. **No. 10766/8**: T9; T10; T15; T20; T25; T27; T30; T40
1 L-Key set hex **No. 10760/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 side cutters **No. 6720**: L. 180 mm
1 combination pliers **No. 6700**: L. 180 mm
1 safety knife **No. 12965**: L. 174 mm
1 wooden folding ruler **No. 13112**: L. 2 m
1 fl at chisel **No. 102**: W. 18; L. 150 mm
1 torch **No. 13132**: 130 lm

96830701 TCS L-BOXX® electrics set:
7 combination spanners **No. 13**: 8; 10; 13; 17; 19; 22; 24 mm
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | TBO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces
1 bit holder 1/2" **No. 543**: L. 38 mm
1 bit ratchet screwdriver 1/4" **No. 4008**: L. 95 mm
1 extension 1/2" **No. 509**: L. 130 mm
1 ratchet 1/2" **No. 512-2K**: L. 265.5 mm
11 sockets with hex 1/2" **No. 52**: 8; 10; 12; 13; 16; 17; 18; 19; 22; 24, 27 mm
1 engineer's hammer **No. 10961**: 500 g
1 adjustable spanner **No. 4025**: max. 34 mm
1 centre punch **No. 105**: Ø 10 mm
1 mini magnetic lifter **No. 12600**: 270 g

Product no.	L mm	W mm	H mm	Filling volume	Content pcs.	kg
97830702	360	444	152	12,2 l	96	7.5



TOOL ASSORTMENTS IN TOOL BOXES.

Key features of the tool box
for mobile use

— with 4 drawers, a compartment under the lid, a safety lock and a sturdy aluminium structural sheet on the lid
— wide, spring-mounted, plastic-covered handles on the sides
— high-quality, fully-extendable stable sliding rail system
— easy-to-remove drawers
— affix items to the perforated panel with spring clamps No. 8050



13214

98814803 Line maintenance set in carrying case No. 13216N/4
— for maintenance work on aircraft and helicopters
— safely integrated in the modular Tool Control System (TCS)
— 1 carrying case **No. 13216N/4**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98814803	580	300	494	146	27.5



96830795



96830804



96830805



96830806



96831794

Contains 146-pieces:

Lid contents
6 tool spring clamps **No. 8036**: Size 1
4 tool spring clamps **No. 8050**: Size 6
1 claw lifter **No. 12922**: Ø 6 mm L. 540 mm
1 mini magnetic lifter **No. 12600**: 270 g
1 hacksaw **No. 12053**: L. 252 mm
1 bit holder 1/4" **No. 4000**: L. 190 mm
1 QuickRelease speeder brace 3/8" **No. 453QR**: L. 408 mm
1 bit slotted 1/4" **No. 1163**: 0.6 x 4.5 mm

96830795
1 telephone pliers **No. 6731**: L. 200 mm
1 combination pliers **No. 6700**: L. 160 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 electronic's side cutters **No. 6707**: L. 115 mm
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 steel ruler **No. 13310**: L. 300 mm

96830804
2 sockets with hex 1/4" **No. 40**: 4; 4.5 mm
11 sockets with bi-hex 1/4" **No. 40D**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
1 socket long, with hex 1/4" **No. 40L**: 4.5 mm
11 sockets long, with bi-hex 1/4" **No. 40DL**: 5; 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
5 uniflex sockets with bi-hex 1/4" **No. 402**: 6; 7; 8; 9; 10 mm
1 QuickRelease universal joint 1/4" **No. 407/1QR**: L. 38 mm
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
1 bit holder 1/4" **No. 412**: L. 20 mm
6 sockets with bi-hex 3/8" **No. 45**: 15; 17; 19; 21; 22; 24 mm

Tool assortments

4 sockets long, with bi-hex 3/8" **No. 46**: 15; 17; 19; 21 mm
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428/1QR**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 bit holder 3/8" **No. 443**: L. 32 mm
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
4 double-ended ratchet ring spanners **No. 25**: 7 x 8; 9 x 10; 12 x 13; 17 x 19 mm
1 telescopic mirror **No. 12921M**: Ø 57 mm

96830805
18 combination spanners **No. 13**: 5.5; 6; 7; 8; 9; 10; 12; 13; 14; 15; 17; 19; 20; 21; 22; 24; 27; 30 mm
5 combination spanners **No. 16**: 3.2; 3.5; 4; 4.5; 5 mm

96830806
2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
1 cable knife **No. 12320**: Blade length: 90 mm
1 tape measure **No. 12935**: L. 3 m
1 scriber **No. 12321**: L. 250 mm
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 torch **No. 13218**: 320 lm
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm

96831794
1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 engineer's hammer **No. 10961**: 500 g
1 nylon hammer **No. 10956N**: Ø 35 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 hook tool **No. 13001**: Angled 45°



13214a

98814801 Line maintenance set in carrying case No. 13216N/4
— for maintenance work on aircraft and helicopters
— safely integrated in the modular Tool Control System (TCS)
— 1 carrying case **No. 13216N/4**

Product no.	L mm	W mm	H mm	Content pcs.	kg
98814801	580	300	494	147	27.23



96830795



96830796



96831793



96831794



96835692

Contains 147-pieces:

Lid contents
1 QuickRelease speeder brace 3/8" **No. 453QR**: 408 mm
1 bit slotted 1/4" **No. 1163**: 0.6 x 4.5 mm
1 bit holder 1/4" **No. 4000**: L. 190 mm
1 hacksaw **No. 12053**: L. 252 mm
1 mini magnetic lifter **No. 12600**: 270 g
1 claw lifter **No. 12922**: Ø 6 mm; L. 540 mm
2 tool spring clips **No. 8050**: Size 6; 12

96830795
1 telephone pliers **No. 6731**: L. 200 mm
1 combination pliers **No. 6700**: L. 160 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 self-grip wrench **No. 6564**: L. 175 mm
1 wire twisting pliers **No. 6575**: L. 230 mm
1 electronics side cutters **No. 6707**: L. 115 mm
4 pin punches **No. 109**: Ø 1.4; 2.8; 3.4; 3.9 mm
1 steel ruler **No. 13110**: L. 300 mm

96830796

23 combination spanners **No. 13a**: 3/16; 13/64; 7/32; 15/64; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8"

96831793

2 slotted screwdrivers **No. 4622**: 1.0 x 5.5 x 100; 1.2 x 8.0 x 150 mm
1 precision feeler gauges, 20 blades **No. 11095**: 0.05-1 mm
1 tape measure **No. 12935**: L. 3 m
1 caliper **No. 12900**: Measuring range: 150 mm/6"
1 ball-ended L-Key set hex **No. 10767a/13**: 0.050; 1/16; 5/64; 3/32; 7/64; 1/8; 9/64; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8"
1 cable knife **No. 12320**: Blade length: 90 mm
1 scriber **No. 12321**: L. 250 mm
1 torch **No. 13128**: 320 lm

96831794

1 bit fine-tooth ratchet 1/4" **No. 415SGB N**: L. 117 mm
3 PH cross-head screwdrivers **No. 4632**: PH1; PH2; PH3
1 engineer's hammer **No. 10961**: 500 g
1 nylon hammer **No. 10956**: Ø 35 mm
1 bit box **No. 1208**: 1 quick-change holder 1/4" | L. 25 mm: SL4,5;6,5;8 mm | PH1;2;3 (2x) | T6;15;20 | T-SET 4;6;8;10 (2x) | INHEX 5/64;9/64;1/8;3/16;5/32;7/64;3/32;7/32" | Adaptor 1/4" 4KT/6KT | 30-pieces
1 hook tool **No. 13001**: Angled 45°

96835692

4 double-ended ratchet ring spanners **No. 25aN**: 1/4 x 5/16; 5/16 x 11/32; 3/8 x 7/16; 1/2 x 9/16"
10 sockets with bi-hex 1/4" **No. 40aD**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
10 sockets long, with bi-hex 1/4" **No. 40aDL**: 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16
5 uniflex sockets with bi-hex 1/4" **No. 402a**: 1/4; 5/16; 3/8; 7/16; 1/2"
2 QuickRelease extensions 1/4" **No. 408QR**: L. 55; 150 mm
1 QuickRelease universal joint 1/4" **No. 407QR**: L. 38 mm
1 square drive adaptor **No. 409M**: 1/4 to 3/8"
1 bit holder 1/4" **No. 412**: L. 20 mm
1 QuickRelease fine-tooth ratchet 1/4" **No. 415QR N**: L. 117 mm
8 sockets with bi-hex 3/8" **No. 45a**: 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 15/16; 1"
4 sockets with bi-hex 3/8" **No. 46a**: 5/8; 11/16; 3/4; 7/8"
2 QuickRelease extensions 3/8" **No. 426QR**: L. 75; 240 mm
1 QuickRelease universal joint 3/8" **No. 428QR**: L. 46 mm
1 square drive adaptor **No. 431**: 3/8 to 1/4"
1 square drive adaptor **No. 432M**: 3/8 to 1/2"
1 QuickRelease fine-tooth ratchet 3/8" **No. 435QR N**: L. 193 mm
1 bit holder 3/8" **No. 443**: L. 32 mm
1 telescopic mirror **No. 12921N**: Ø 50 mm



OTHER TOOL ASSORTMENTS.

13215/105



Multi-Use Tool Set

A backpack trolley for mobile use, equipped with a comprehensive selection of hand tools for maximum flexibility in changing work situations.

Key features of the backpack trolley

— sturdy tool backpack with reinforced bottom
— flexible use as a trolley or a backpack
— extendable, padded straps convert trolley into a backpack
— large, smooth-running wheels and a practical telescopic handle for convenient transport
— 2 easily removable tool panels for the most important everyday tools
— front pockets for documents and accessories
— padded notebook compartment (up to 15")

Contains 105-pieces:

1 socket set, in soft case ¼" **No. 40/16/3QR SCI**: No. 40: 6; 7; 8; 10; 13 mm; No. 418QR; No. 405QR; No. 412; No. 1300, 1302: 3; 5 mm; No. 1166: 1.0 x 5.5 mm; No. PH 1221-1222: PH1; PH2; No. PZ 1222: PZ2; No. 1415-1419: T15; T20; T25; T27; T30
1 bit box **No. 1206**: 1 bit holder | L. 25 mm: SL4;5;6 mm (2x) | PH1;2;3 (3x) | PZ1;2;3 (3x) | T10;15;20;25;27;30;40 (2x) | T BO10;15;20;25;27;30;40 | INHEX 3;4;5 mm | L. 75 mm: SL6 mm | PH2;3 | PZ1;2 | T20;25 | 56-pieces
1 screwdriver set **No. 4687**: No. 4620: 0.6 x 3.5 mm, 1.0 x 5.5 mm, 1.2 x 6.5 mm; No. 4630: PH1, PH2
1 bit ratchet screwdriver ¼" **No. 4008**: L. 250 mm
1 L-Key set hex **No. 10765/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
10 double open-ended spanners in roll-up pouch **No. 10/10**: 6 x 7; 8 x 9; 10 x 11; 12 x 13; 14 x 15; 16 x 17; 18 x 19; 20 x 22; 24 x 27; 30 x 32 mm
1 engineer's hammer **No. 10961**: 500 g
1 water pump pliers **No. 6551**: L. 240 mm
1 combination pliers **No. 6700**: L. 160 mm
1 side cutters **No. 6720**: L. 180 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
98810302	250	380	520	105	10.04



13253/38



Agrar on-board tool set

— tool set especially for the agricultural industry
— extra long combination spanners for better leverage; particularly effective for loosening tight screws
— available separately, supplementary set 96830278
— perfect size for storing away behind the driver's seat in tractors
— in a fold-out fabric case

Contains 38-pieces:

7 combination spanners **No. 14**: 10; 13; 17; 19; 22; 24; 27 mm (2 each)
1 slotted screwdriver **No. 4622**: 2.5 x 14.0 x 250 mm
1 slotted screwdriver **No. 4620**: 1.2 x 6.5 x 150 mm
2 PH cross-head screwdrivers **No. 4630**: PH1, PH2
1 ball-ended L-Key set hex **No. 10767/9**: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 engineer's hammer **No. 10961**: 800 g
1 flat chisel **No. 102**: W. 18; L. 150 mm
3 pin punches **No. 108**: Ø 2.5; 4; 6 mm
1 cable knife **No. 12320**: L. 111 mm
1 telescopic torch with magnet **No. 13122** L. 170-550 mm
1 magnetic tray **No. 650 MS**: Ø 108 mm
1 wooden folding ruler **No. 13112**: L. 2 m
1 socket clip rail, without sockets **No. 12918/10**: for 1/2" sockets (for 10-pieces)

Product no.	L mm	W mm	H mm	Filling volume	Content pcs.	kg
97830217	445	110	290	0,26 l	38	7.63

13253/1 10



Supplementary tool set AGRAR MOBIL

— tool assortment as a supplementary set for AGRAR MOBIL set 97830217


Contains 10-pieces:

1 QuickRelease fine-tooth ratchet 1/2" **No. 512QR N80**: L. 265.5 mm
1 QuickRelease extension 1/2" **No. 509QR**: L. 255 mm
7 sockets with bi-hex 1/2" **No. 50**: 10; 13; 17; 19; 22; 24; 27 mm
1 water pump pliers **No. 6572**: L. 300 mm

Product no.	Content pcs.	kg
96830278	10	2.06




MADE IN GERMANY



8 Pliers

394 Combination and telephone pliers

395 Side cutters

396 End cutters

397 Wire strippers and crimping pliers

398 Wire twisting pliers

398 Water pump pliers

401 Pipe wrenches

406 Nippers and specialist pliers

408 Circlip pliers

410 Self-grip wrenches

411 Electronics pliers

414 Bolt cutters

418 Structural steel mesh cutters

420 Plier sets in TCS inlays

STAHLWILLE PLIERS –
Precise. Strong. Ergonomic.

For precise work and powerful gripping – STAHLWILLE pliers with multi-component handles. The comfortable handles with textured surface allow safe, low-fatigue work, even with oily hands.

POWERFUL



Precise.

Specially hardened, high-precision cutting edges allow clean and effortless cutting, even of piano wire.

Durable.

Smooth-running lap joints and high-quality materials for a long tool life.

Reliable.

The anti-slip protection prevents hands slipping off towards the jaws.

Patented.

The PowerGRIP pipe wrench from STAHLWILLE impresses with its variable, smooth, quick adjustment and high gear ratio for impressive gripping power.



MADE IN CRONENBERG
MADE IN GERMANY

8

Ergonomic.

Low-fatigue work without pressure points thanks to ergonomically designed handle profile.

Special.

Everything but standard. In addition to universal pliers, STAHLWILLE also offers special tools such as wire twisting pliers.

VBW PLIERS – designed and manufactured in Germany. Professional tools – since 1828.

For generations, VBW has been synonymous with robust tools of the highest quality. Since the tools on construction sites often have to withstand the toughest conditions during demolition or renovation work, our tools are manufactured in Germany with the highest level of manufacturing precision. Numerous unique features also ensure efficient and comfortable work. VBW – a STAHLWILLE Group brand.



LightCUT®

Powerful.

VBW bolt cutters and structural steel mesh cutters are particularly powerful and offer high cutting performance with low effort.

Light.

The LightCUT® series of flat-oval, high-strength aluminium tubes are light in weight at around half the weight of a comparable tool. For fatigue-free work and precise results.

Durable.

All VBW bolt cutters and structural steel mesh cutters are made of high-quality special steel. Drop-forged blade and tube heads guarantee a long service life.



High-quality.

"The red with the yellow dot" stands for the professional quality of VBW water pump pliers. Inductively hardened teeth (including burner hole) offer a long service life.

8

Robust.

Forged professional tip quality for a wide range of applications in trades and industry. The self-clamping teeth ensure a secure grip on the workpiece enabling effortless, non-slip work.

Stable.

Water pump pliers from VBW have push-through sliding joints that are extremely stable due to the double guide.

Reliable.

The pliers are particularly safe as they offer pinch protection against crushing of fingers.

COMBINATION AND TELEPHONE PLIERS.


6700



2K

Combination pliers

— for gripping, holding and cutting cables as well as soft and hard wire
— with fine and coarse serrated gripping surface, with cutters
— hardened and tempered steel, drop-forged
— cutting edges with additional induction hardening to approx. 64 HRC
— chrome-plated
— with 2-component handles
— DIN ISO 5746




Product no.	L mm	L3 mm	T mm	T2 mm	W mm	W3 mm	W4 mm	g
67001160	160	34	21	10.5	57	24	6	210
67001180	180	38	22	11.5	57	26	7	275
67001200	200	42	23	12.5	55	29	8	340

6700



Combination pliers

— for gripping, holding and cutting cables as well as soft and hard wire
— with fine and coarse serrated gripping surface, with cutters
— hardened and tempered steel, drop-forged
— cutting edges with additional induction hardening to approx. 64 HRC
— polished head
— plastic coated handles
— DIN ISO 5746



Product no.	L mm	L3 mm	T2 mm	W3 mm	W4 mm	g
67003160	160	34	10.5	24	6	182
67003180	180	38	11.5	26	7	254
67003200	200	42	12.5	29	8	304


6730



2K


Telephone pliers

— straight with cutters and burner hole
— for precise gripping of nuts, pins and cotter pins
— flat-round, tapered jaws with serrated gripping surface
— hardened and tempered steel, drop-forged
— cutting edges with additional induction hardening to approx. 64 HRC
— chrome-plated
— with 2-component handles
— DIN ISO 5745




Product no.	L mm	L3 mm	T mm	T1 mm	T2 mm	W mm	W3 mm	W4 mm	g
67301160	160	47	21	3.5	9.5	55	18	3.5	155
67301200	200	70	22	4	11	57	20	5	215

6730



Telephone pliers

— straight with cutters and burner hole
— for precise gripping of nuts, pins and cotter pins
— flat-round, tapered jaws with serrated gripping surface
— hardened and tempered steel, drop-forged
— cutting edges with additional induction hardening to approx. 64 HRC
— polished head
— plastic coated handles
— DIN ISO 5745




Product no.	L mm	L3 mm	T1 mm	T2 mm	W3 mm	W4 mm	g
67303160	160	47	3.5	9.5	18	3.5	130
67303200	200	70	4	11	20	5	182

6731



Telephone pliers
- curved (45°) with cutters and burner hole
- for precise gripping of nuts, pins and cotter pins
- flat-round, curved jaws with serrated gripping surface
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- chrome-plated
- with 2-component handles
- DIN ISO 5745




Product no.	L mm	L3 mm	T mm	T1 mm	T2 mm	W mm	W3 mm	W4 mm	∠	g
67311160	160	43	30	3.5	9.5	54	18	3.5	45	155
67311200	200	63	35	4	11	57	20	5	45	215

6731



Telephone pliers
- curved (45°) with cutters and burner hole
- for precise gripping of nuts, pins and cotter pins
- flat-round, curved jaws with serrated gripping surface
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- polished head
- plastic coated handles
- DIN ISO 5745




Product no.	L mm	L3 mm	T1 mm	T2 mm	W3 mm	W4 mm	∠	g
67313160	160	43	3.5	9.5	18	3.5	45	132
67313200	200	63	4	11	20	5	45	192

SIDE CUTTERS.

6720



Side cutters
- with half-round head shape for cutting cables, soft and hard wires, including piano wire
- bevelled cutting edges
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- chrome-plated
- with 2-component handles
- DIN ISO 5749




Product no.	L mm	L4 mm	T mm	T2 mm	W mm	W3 mm	g
67201140	140	19	22	11	59	20	180
67201160	160	19	22	11	58	22	235
67201180	180	21	23	11.5	56	24	265

6720



Side cutters
- with half-round head shape for cutting cables, soft and hard wires, including piano wire
- bevelled cutting edges
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- polished head
- plastic coated handles
- DIN ISO 5749




Product no.	L mm	L4 mm	T2 mm	W3 mm	g
67203140	140	19	11	20	145
67203160	160	19	11	22	208
67203180	180	21	11.5	24	230

6721



Heavy-duty side cutters
- half-round, compact head for flush cutting of all wire types
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- chrome-plated
- with 2-component handles
- DIN ISO 5749




Product no.	L mm	L4 mm	T mm	T2 mm	W mm	W3 mm	g
67211160	160	16	21	11	52	26	210
67211180	180	21	22	12	56	30	300
67211200	200	20	23	12	54	32	300

6721



Heavy-duty side cutters
- half-round, compact head for flush cutting of all wire types
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- polished head
- plastic coated handles
- DIN ISO 5749




Product no.	L mm	L4 mm	T2 mm	W3 mm	g
67213160	160	16	11	26	196
67213180	180	21	12	30	266
67213200	200	20	12	32	270

END CUTTERS.

6770



Heavy-duty end cutters
- for cutting, tying/braiding and twisting wires
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- chrome-plated
- with 2-component handles
- DIN ISO 5748




Product no.	L mm	L4 mm	T mm	T2 mm	W mm	W3 mm	g
67701160	160	8	21	25	56	30	225

6770



Heavy-duty end cutters
- for cutting, tying/braiding and twisting wires
- hardened and tempered steel, drop-forged
- cutting edges with additional induction hardening to approx. 64 HRC
- polished head
- plastic coated handles
- DIN ISO 5748



Product no.	L mm	L4 mm	T2 mm	W3 mm	g
67703160	160	8	25	30	200

6617



Lever action end cutters
- for piano wire
- optimum cutting results thanks to double-lever mechanism
- special steel
- head polished, 80CRV2 (1.2235)
- DIN ISO 5748

Product no.	L mm	T mm	W mm	g
66170180	180	30	50	394
66170215	215	30	63	440
66170235	235	30	47	467


WIRE STRIPPERS AND CRIMPING PLIERS.

6780



2K

Wire strippers
- with adjustment screw and opening spring for setting to the desired wire or cord diameter
- for easy removal of the insulating sheaths from electrical conductors (single-, multi- and fine-wire)
- hardened and tempered steel, drop-forged
- cutting edges also induction hardened to approx. 44 HRC
- chrome-plated
- with 2-component handles




Product no.	L mm	L_3 mm	T mm	T_2 mm	W mm	W_3 mm	Ø max. mm	g
67801160	160	26	21	9.5	58	18	5	185

6780



Wire strippers
- with adjustment screw and opening spring for setting to the desired wire or cord diameter
- for easy removal of the insulating sheaths from electrical conductors (single-, multi- and fine-wire)
- hardened and tempered steel, drop-forged
- cutting edges also induction hardened to approx. 44 HRC
- polished head
- plastic coated handles



Product no.	L mm	L_3 mm	T_2 mm	W_3 mm	Ø max. mm^2	g
67803160	160	26	9.5	18	5	164

6638



Crimping pliers
- for crimping insulated cable lugs, plug, butt and parallel connectors (red/blue/yellow)
- for stripping wires with Ø 0.5 to 6 mm
- with cutting edge for cable separation
- releasable auto lock for high performance precision and easy handling
- non-slip handles with anti-slip protection

Product no.	L mm	Crimping range mm^2	g
66383220	220	red = 0.5-1 (AWG 20-18); blue = 1.5-2,5 (AWG 16-14); yellow = 4-6 (AWG 12-10)	477

TOOLS THAT ... inspire

WIRE TWISTING PLIERS.

6575



Wire twisting pliers
- for twisting wires up to Ø 1.6 mm (0.06")
- with cutters
- secure grip thanks to special serration design
- cutting jaws bevelled by 40°
- for both clockwise and counter-clockwise rotation
- with automatic return
- Chrome Alloy Steel, head and handles burnished

Product no.	L mm	g
65751220	230	330
65751280	280	440

WATER PUMP PLIERS.

6551



Water pump pliers
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976 (No. 207 C)

Product no.	L mm	Jaw opening max. mm	Positions	g
65516175	175	24	6x	173
65516240	240	34	7x	320
65516300	300	45	7x	520

6515



Mini water pump pliers
- compact version with slim head shape for use in confined working areas
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- plastic coated handles
- Chrome Alloy Steel, forged and oil-hardened
- DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
65156125	125	25	4x	118

6572



Water pump pliers FastGRIP
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- quick adjustment of the pliers at the push of a button
- variable and smooth fine adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- Chrome Alloy Steel, forged and oil-hardened
- plastic coated handles
- DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
65726180	180	28	10x	236
65726240	240	37	12x	405
65726300	300	44	15x	530



188



Water pump pliers
- professional version for continuous use
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- induction-hardened serration for impressive dimensional stability and durability
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- with knurled handles
- DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87188005	160	17	4x	106
87188010	250	30	6x	295
87188015	315	40	6x	487

188/3S



Water pump plier set
- professional version for continuous use

Contains 3-pieces:

3 water pump pliers **No. 188**: L. 160; 250; 315 mm

Product no.	Content pcs.	g
87188021	3	970

966



Water pump pliers
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- with knurled handles
- DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87966005	160	26	6x	150
87966010	230	33	7x	310
87966015	300	45	7x	485

966/3S



Water pump plier set
- for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

3 water pump pliers **No. 966**: L. 160; 250; 315 mm

Product no.	Content pcs.	g
87966021	3	940

966



Water pump pliers
- self-clamping on the workpiece, reduces effort and prevents slipping
- sliding slip joint with double support
- easy to adjust thanks to locking hole adjustment
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- plastic coated handles
- DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87966000	125	26	4x	104
87966165	160	26	6x	171
87966166	250	33	7x	320
87966167	315	45	7x	492

966-K/3S



Water pump plier set
- for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

3 water pump pliers **No. 966**: L. 160; 250; 315 mm

Product no.	Content pcs.	g
87966164	3	996

966



Water pump pliers
- — self-clamping on the workpiece, reduces effort and prevents slipping
- — sliding slip joint with double support
- — easy to adjust thanks to locking hole adjustment
- — with built-in protection against crush injuries
- — high-quality, hardened and tempered for excellent wear resistance
- — plastic coated handles
- — DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87966030	160	26	6x	154
87966031	250	33	7x	309
87966032	315	45	7x	485

99/4S



Professional sanitary assortment
- — professional set for plumbing and installation work
- — for all gripping and turning work on pipes, nuts, bolts and similar objects
- — in high-quality fabric bag for flexible transport

Contains 4-pieces:

1 water pump pliers **No. 182**: L. 250 mm
1 pipe wrench **No. 180**: L. 250 mm
1 ABC pipe wrench **No. 115**: 1/2"
1 water pump pliers **No. 188**: L. 250 mm

Product no.	Content pcs.	g
87991500	4	1935

MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

182



Water pump pliers FastGRIP
- — self-clamping on the workpiece, reduces effort and prevents slipping
- — sliding slip joint with double support
- — quick adjustment of the pliers at the push of a button
- — variable and smooth fine adjustment
- — induction-hardened serration for impressive dimensional stability and durability
- — with built-in protection against crush injuries
- — high-quality, hardened and tempered for excellent wear resistance
- — plastic coated handles
- — DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87182005	180	28	10x	221
87182010	250	35	12x	405
87182015	315	44	15x	526

182-K/3S



Water pump plier set FastGRIP

Contains 3-pieces:

3 water pump pliers **No. 182**: L. 180; 250; 315 mm

Product no.	Content pcs.	g
87182900	3	1190

184



Water pump pliers AllGRIP
- — self-clamping on the workpiece, reduces effort and prevents slipping
- — sliding slip joint with double support
- — easy to adjust thanks to locking hole adjustment
- — variable and smooth fine adjustment
- — induction-hardened serration for impressive dimensional stability and durability
- — with built-in protection against crush injuries
- — high-quality, hardened and tempered for excellent wear resistance
- — plastic coated handles
- — DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87184010	250	42	8x	398

186

VBW



S-jaw push-button water pump pliers S-GRIP®

— water pump pliers and pipe wrench in one
— slim, S-shaped jaws for maximum gripping and holding performance
— offset tooth arrangement for optimal firm grip
— self-clamping on the workpiece, reduces effort and prevents slipping
— sliding slip joint with double support
— quick adjustment of the pliers at the push of a button
— variable and smooth fine adjustment
— induction-hardened serration for impressive dimensional stability and durability
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— plastic coated handles
— DIN ISO 8976

Product no.	L mm	Jaw opening max. mm	Positions	g
87186010	250	45	12x	409

6573



Pipe wrenches PowerGRIP

— smooth jaws to protect sensitive surfaces
— secure grip when screwing, holding and bending
— quick adjustment of the pipe wrench at the push of a button
— for workpieces with parallel surfaces (nuts, screws, etc.)
— variable and smooth fine adjustment
— high transmission ratio for noticeable manual force amplification
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— plastic coated handles

Product no.	L mm	Jaw opening max. mm	Positions	g
65735180	180	36	11x	291
65735250	250	46	14x	485
65735300	300	60	18x	661

180

VBW



Pipe wrenches PowerGRIP

— smooth jaws to protect sensitive surfaces
— secure grip when screwing, holding and bending
— quick adjustment of the pipe wrench at the push of a button
— for workpieces with flat surfaces (nuts, screws, etc.)
— variable and smooth fine adjustment
— high transmission ratio for noticeable manual force amplification
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— plastic coated handles

Product no.	L mm	Jaw opening max. mm	Positions	g
87180305	180	36	11x	275
87180310	250	46	14x	490
87180315	315	60	18x	640

180-K/3S

VBW



Pipe wrench set PowerGRIP

— for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

3 pipe wrenches **No. 180**: L. 180; 250; 315 mm

Product no.	Content pcs.	g
87180900	3	1405

PIPE WRENCHES.

6549



Corner pipe wrenches

— Form B, angled 45°
— ideal for concealed and difficult-to-access bolted joints
— DIN 5234

Product no.	max."	L mm	Jaw opening max. mm	g
65490315	1	330	35	780
65490420	1 1/2	445	62	1626
65490555	2	560	78	2780

6556



Swedish pipe wrenches

— Form A, angled 90°
— ideal for concealed and difficult-to-access bolted joints
— DIN 5234

Product no.	max."	L mm	Jaw opening max. mm	g
65560310	1	320	44	780
65560420	1 1/2	420	64	1560
65560560	2	540	83	2676

6557



S-jaw pipe wrenches

— Form C
— ideal for concealed and difficult-to-access bolted joints
— DIN 5234

Product no.	max."	L mm	Jaw opening max. mm	g
65570320	1	330	40	811
65570416	1 1/2	440	60	1595
65570535	2	560	70	2677

6558



HEAVY-DUTY pipe wrenches

— head black lacquered, polished
— US Standard GGG-W-651 Type II, Class A

Product no.	max."	L mm	Jaw opening max. mm	g
65580250	10	250	49	805
65580300	12	300	61	1255
65580350	14	350	61	1665
65580450	18	450	77	2660
65580600	24	600	90	3955

6559



STILLSON pipe wrenches

— head black lacquered, polished
— US Standard GGG-W-651 Type I, Class A

Product no.	max."	L mm	Jaw opening max. mm	g
65590250	10	250	35	550
65590300	12	300	43	750
65590350	14	350	49	1080
65590450	18	450	61	1725
65590600	24	600	77	2745

VBW



Replacement nuts for pipe wrenches

— for pipe wrenches, chrome-plated

87100050	**87100060**	**87100065**	**87100070**	**87110075**	**87110080**
S-JAW PIPE WRENCH RP 1/2 INCH 87952005	ABC-PIPE WRENCH X-GRIP 1 INCH 87115010	ABC-PIPE WRENCH X-GRIP 1 1/2 INCH 87115015	ABC-PIPE WRENCH X-GRIP 2 INCH 87115020	ABC-PIPE WRENCH X-GRIP 3 INCH 87115025	PIPE WRENCH 90° 4 INCH 87110030
CORNER PIPE-WRENCH 45° 1/2 INCH 87111005	S-JAW PIPE WRENCH RP 1 INCH 87100010	S-JAW PIPE WRENCH RP 1 1/2 INCH 87100015	S-JAW PIPE WRENCH RP 2 INCH 87100020	S-JAW PIPE WRENCH RP 3 INCH 87100025	
	S-JAW PIPE WRENCH RP 1 INCH 87952010	S-JAW PIPE WRENCH RP 1 1/2 INCH 87952015	X-GRIP PIPE WRENCH 2 INCH RED EDITION 87115120	S-JAW PIPE WRENCH RP 3 INCH 87952030	
	CORNER PIPE WRENCH 45° 1 INCH 87111010	CORNER PIPE WRENCH 45° R 1 1/2 INCH 87951015	CORNER PIPE WRENCH 45° 2 INCH 87111020	CORNER PIPE WRENCH 45° 3 INCH 87111025	
	CORNER PIPE WRENCH 45° R 1 INCH 87951010	PIPE WRENCH 90° 1 1/2 INCH 87110015	CORNER PIPE WRENCH 45° R 2 INCH 87951020	PIPE WRENCH 90° 3 INCH 87110025	
	PIPE WRENCH 90° 1 INCH 87110010	PIPE WRENCH 90° 1 1/2 INCH 87950015	PIPE WRENCH 90° 2 INCH 87110020		
	PIPE WRENCH 90° 1 INCH 87950010	X-GRIP PIPE WRENCH 1 1/2 INCH RED EDITIO 87115115	PIPE WRENCH 90° 2 INCH 87950020		
		CORNER PIPE WRENCH 45° 1 1/2 INCH 87111015	S-JAW PIPE WRENCH RP 2 INCH 87952020		

100

VBW



S-jaw pipe wrenches
- professional quality for continuous use
- Form C
- special jaw geometry with 3-point support for firm grip and non-slip handle
- with reinforced handle
- self-clamping on the workpiece, prevents loss of secured nuts
- with built-in protection against crush injuries
- induction-hardened serration for impressive dimensional stability and durability
- high-quality, hardened and tempered for excellent wear resistance
- double-T profile handle for safe handling
- DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87100010	1	25.4	320	49	780
87100015	1 1/2	38.1	436	68	1495
87100020	2	50.8	555	85	2530
87100025	3	76.2	673	120	4051

952

VBW



S-jaw pipe wrenches
- Form C
- special jaw geometry with 3-point support for firm grip and non-slip handle
- with reinforced handle
- self-clamping on the workpiece, prevents loss of secured nuts
- with built-in protection against crush injuries
- induction-hardened serration for impressive dimensional stability and durability
- high-quality, hardened and tempered for excellent wear resistance
- double-T profile handle for safe handling
- DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87952005	1/2	12.7	245	39	454
87952010	1	25.4	330	49	780
87952015	1 1/2	38.1	440	68	1570
87952020	2	50.8	560	85	2670
87952030	3	76.2	675	120	4310

952/3S

VBW



S-jaw pipe wrench set
- for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

3 S-jaw pipe wrenches **No. 952**: 1; 1 1/2; 2"

Product no.	Content pcs.	g
87991952	3	5030

952/966/3S

VBW



S-jaw pipe wrench and water pump plier set
- for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

1 water pump pliers **No. 966**: L. 240 mm

2 pipe wrenches **No. 952**: 1; 1 1/2"

Product no.	Content pcs.	g
87991900	3	2685

110

VBW



Pipe wrenches 90°
- professional quality for continuous use
- Form A, angled 90°
- for concealed and hard-to-reach bolted joints
- with reinforced handle
- self-clamping on the workpiece, prevents loss of secured nuts
- with built-in protection against crush injuries
- high-quality, hardened and tempered for excellent wear resistance
- double-T profile handle for safe handling
- DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87110010	1	25.4	305	49	771
87110015	1 1/2	38.1	420	65	1462
87110020	2	50.8	530	84	2520
87110025	3	76.2	682	110	3775
87110030	4	101.6	744	140	5530

950



Pipe wrenches 90°

— Form A, angled 90°
— with reinforced handle
— self-clamping on the workpiece, prevents loss of secured nuts
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— double-T profile handle for safe handling
— DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87950010	1	12.7	306	49	780
87950015	1 1/2	25.4	420	65	1525
87950020	2	38.1	530	84	2530

111



Plumber's pipe wrenches 45°

— professional quality for continuous use
— Form A, angled 45°
— for concealed and hard-to-reach bolted joints
— special jaw geometry with 3-point support for firm grip and non-slip handle
— with reinforced handle
— self-clamping on the workpiece, prevents loss of secured nuts
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— double-T profile handle for safe handling
— DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87111005	1/2	12.7	236	36	464
87111010	1	25.4	316	55	761
87111015	1 1/2	38.1	443	81	1635
87111020	2	50.8	560	94	2790
87111025	3	76.2	710	110	4100

951




Plumber's pipe wrenches 45°

— Form A, angled 45°
— special jaw geometry with 3-point support for firm grip and non-slip handle
— with reinforced handle
— self-clamping on the workpiece, prevents loss of secured nuts
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— double-T profile handle for safe handling
— DIN 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87951010	1	25.4	320	55	815
87951015	1 1/2	38.1	445	81	1635
87951020	2	50.8	560	94	2790

115




ABC pipe wrenches X-GRIP®

— 3 DIN forms in one: Forms A, B and C, angled 45°
— for a secure grip on pipes, flat materials and bolted joints
— special 'Corner-O-Point' jaw shape for round and square workpieces and sheet metal
— with reinforced handle
— self-clamping on the workpiece, prevents loss of secured nuts
— with built-in protection against crush injuries
— high-quality, hardened and tempered for excellent wear resistance
— plastic coated handles
— DIN ISO 5234

Product no.	max."	max. mm	L mm	Jaw opening max. mm	g
87115005	1/2	12.7	238	39	480
87115010	1	25.4	318	55	860
87115015	1 1/2	38.1	427	75	1515
87115020	2	50.8	555	100	3135
87115025	3	76.2	700	120	4180

115-K/3S

VBW



ABC pipe wrench set X-GRIP®

— for universal industrial, trade, workshop and domestic use

Contains 3-pieces:

3 ABC pipe wrenches **No. 115**: 1; 1 1/2; 2"

Product no.	Content pcs.	g
87991115	3	5745

127

VBW



Self-grip pipe wrenches

— for twisting and loosening pipes and nuts with different diameters

— forged jaws

— setting via threaded roller

Product no.	max."	L mm	L "	Jaw opening max. mm	g
87127005	1 1/4	175	7	31.75	278
87127010	1 1/2	225	9	38.1	513
87127015	2	265	10 1/2	50.8	805
87127020	2 1/2	300	12	63.5	968
87127025	3	350	14	76.2	1590

129

VBW



Chain pipe wrench

— ratchet-like operation on the tube, for simple standard applications

— for use in hard-to-reach places

— can be used in 2 directions

— hardened and tempered chain, specially hardened teeth

— drop-forged handle

Product no.	min."	max."	min. mm	max. mm	L mm	Chain length mm	g
87129005	3/4	4	19,5	101,6	300	440	958

129010

VBW



Spare chain

— for chain pipe wrench No. 129

— hardened and tempered chain, specially hardened teeth

Product no.	for model	Chain length mm	g
87129010	129005	440	326

130

VBW



Chain pipe wrenches

— heavy-duty steel chain

— suitable for particularly large diameters

— can be used in 2 directions

— hardened, two-sided serrated, replaceable jaws

— powerful due to maximum leverage

Product no.	min."	max."	min. mm	max. mm	L mm	Chain length mm	g
87130010	1/8	2	3,175	50,8	510	380	2585
87130015	1/4	3	6,35	76,2	710	490	4031
87130020	3/4	4	19,05	101,6	915	610	6669
87130025	1	6	25,4	152,4	1065	850	9500
87130030	1 1/2	8	38,1	203,2	1280	1000	12944

130-1

VBW



Spare chains

— for chain pipe wrenches No. 130

— heavy-duty steel chain

Product no.	for model	Chain length mm	g
87130110	130010	380	530
87130115	130015	490	731
87130120	130020	610	1435
87130125	130025	850	2275
87130130	130030	1000	3153

6576



Connector and siphon pliers
— for loosening or tightening screw connectors, e.g. Cannon connectors
— for work on sensitive light alloy and pipe fittings
— 4-position adjustable sliding joint
— with interchangeable plastic jaws
— Chrome Alloy Steel
— plastic coated handles

Product no.	L mm	g
65765231	230	288

6976



Replacement plastic jaws
— plastic jaws for No. 6576

Product no.	for model	L mm	g
69760001	6576N	25	4

NIPPERS AND SPECIALIST PLIERS.

6661



Pincers
— inductively hardened cutting edges
— drop-forged, oil-hardened
— wear-resistant special steel
— DIN ISO 9243

Product no.	L mm	g
66611180	180	322
66611200	200	350

515

VBW



Pincers
— inductively hardened cutting edges
— drop-forged, oil-hardened
— wear-resistant special steel
— DIN ISO 9243

Product no.	L mm	g
87515005	180	306
87515010	200	342
87515020	250	525

514

VBW



Potter's or brick nippers
— suitable for working with ceramic products in the sanitation sector
— with wire cutter for soft wire before the joint
— inductively hardened cutting edges
— wear-resistant special steel, hardened and tempered

Product no.	L mm	Jaw width mm	g
87514105	200	10	360

6660



Mechanic's nippers
— for twisting and cutting the wire
— limitation of the opening angle for one-handed operation
— optimised cutter geometry reduces the effort required for cutting
— inductively hardened cutting edges
— drop-forged, oil-hardened
— wear-resistant special steel
— DIN ISO 9242

Product no.	L mm	g
66601220	224	318
66601250	250	390
66601280	280	475

6662



Heavy-duty mechanic's nippers
- slim version is suitable for working on low-lying cast iron
- for twisting and cutting the wire
- induction-hardened cutting edges, cutting edge hardness approx. 61 HRC
- extended handles and optimised cutter geometry reduces the effort required for cutting
- significantly dampened cutting impact
- drop-forged, oil-hardened
- wear-resistant special steel
- DIN ISO 9242

Product no.	L mm	g
66624300	300	478

510

VBW



Mechanic's nippers TopCUT®
- for twisting and cutting the wire
- limitation of the opening angle for one-handed operation
- optimised cutter geometry reduces the effort required for cutting
- particularly easy to use
- inductively hardened cutting edges
- drop-forged, oil-hardened
- wear-resistant special steel
- DIN ISO 9242

Product no.	L mm	g
87510005	224	340
87510010	250	410
87510015	280	460
87510020	315	505

510-1

VBW



Mechanic's nippers TopCUT®
- for twisting and cutting the wire
- limitation of the opening angle for one-handed operation
- optimised cutter geometry reduces the effort required for cutting
- particularly easy to use
- inductively hardened cutting edges
- drop-forged, oil-hardened
- wear-resistant special steel
- plastic coated handles
- DIN ISO 9242

Product no.	L mm	g
87510105	224	337
87510110	250	417
87510115	280	468
87510120	315	500

512

VBW



Heavy-duty mechanic's nippers MasterCUT®
- slim version is suitable for working on low-lying cast iron
- for twisting and cutting the wire
- extended handles and optimised cutter geometry reduces the effort required for cutting
- inductively hardened cutting edges
- particularly easy to use
- black lacquered, head polished
- drop-forged, oil-hardened
- wear-resistant special steel
- DIN ISO 9242

Product no.	L mm	g
87512220	300	482

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

512-0



Heavy-duty mechanic's nippers MasterCUT®
- slim version is suitable for working on low-lying cast iron
- for twisting and cutting the wire
- extended handles and optimised cutter geometry reduces the effort required for cutting
- particularly easy to use
- significantly dampened cutting impact
- chrome-plated, head polished
- wear-resistant special steel
- DIN ISO 9242

Product no.	L mm	g
87512000	200	236
87512020	300	475

511-0



Tile hole pliers
- suitable for breaking out and enlarging holes in tiles
- pre-drilled holes can be enlarged by breaking out, and edges can be formed
- special steel

Product no.	L mm	Jaw width mm	g
87511005	200	36	198

511-1



Tile hole pliers
- suitable for breaking out and enlarging holes in tiles
- pre-drilled holes can be enlarged by breaking out, and edges can be formed
- with opening spring
- special steel

Product no.	L mm	Jaw width mm	g
87511105	200	36	205

156



Seaming pliers, straight
- straight version
- suitable for folding sheet metal
- forged

Product no.	L mm	Jaw width mm	g
87156205	260	60	612

156



Seaming pliers, curved 45°
- suitable for folding sheet metal
- forged


Product no.	L mm	Jaw width mm	g
87156210	260	60	632

CIRCLIP PLIERS.

6543



Circlip pliers for internal circlips
- version with straight jaws
- suitable for gripping, inserting and removing internal circlips in drilled holes
- with cylindrical precision tips
- drop-forged
- head and handles chrome-plated, chequered handles
- DIN 5256 C




Product no.	Size	L mm	T1 mm	for circlips mm	g
65434100	J0	140	0.9	8-13	90
65434101	J1	140	1.3	12-25	90
65434102	J2	180	1.8	19-60	135
65434103	J3	225	2.3	40-100	195
65434104	J4	305	3.2	85-140	419

6543



Circlip pliers for internal circlips

— version with straight jaws
— suitable for gripping, inserting and removing internal circlips in drilled holes
— with cylindrical precision tips
— drop-forged
— polished head
— plastic coated handles
— DIN 5256 C




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65436100	J0	140	0.9	8-13	100
65436101	J1	140	1.3	12-25	100
65436102	J2	180	1.8	19-60	150
65436103	J3	228	2.3	40-100	215
65436104	J4	304	3.2	85-140	462

6544



Circlip pliers for internal circlips

— version with 90° angled jaws
— suitable for gripping, inserting and removing internal circlips in drilled holes
— with cylindrical precision tips
— drop-forged
— polished head
— plastic coated handles
— DIN 5256 D




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65446101	J01	130	0.9	8-13	100
65446111	J11	130	1.3	12-25	100
65446121	J21	170	1.8	19-60	150
65446131	J31	215	2.3	40-100	215
65446141	J41	290	3.2	85-140	432

6544



Circlip pliers for internal circlips

— version with 90° angled jaws
— suitable for gripping, inserting and removing internal circlips in drilled holes
— with cylindrical precision tips
— drop-forged
— head and handles chrome-plated, chequered handles
— DIN 5256 D




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65444101	J01	130	0.9	8-13	90
65444111	J11	130	1.3	12-25	90
65444121	J21	170	1.8	19-60	135
65444131	J31	215	2.3	40-100	195
65444141	J41	290	3.2	85-140	416

6545



Circlip pliers for external circlips

— version with straight jaws
— suitable for gripping, inserting and removing external circlips on shafts or axles
— with cylindrical precision tips
— with closing spring
— drop-forged
— head and handles chrome-plated, chequered handles
— DIN 5254 A




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65454100	A0	140	0.9	3-10	95
65454101	A1	140	1.3	10-25	95
65454102	A2	180	1.8	19-60	145
65454103	A3	225	2.3	40-100	205
65454104	A4	300	3.2	85-140	437

6545



Circlip pliers for external circlips
- version with straight jaws
- suitable for gripping, inserting and removing external circlips on shafts or axles
- with cylindrical precision tips
- with closing spring
- drop-forged
- polished head
- plastic coated handles
- DIN 5256 D




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65456100	A0	140	0.9	3-10	105
65456101	A1	140	1.3	10-25	105
65456102	A2	180	1.8	19-60	160
65456103	A3	225	2.3	40-100	232
65456104	A4	300	3.2	85-140	491

6546




Circlip pliers for external circlips
- version with 90° angled jaws
- suitable for gripping, inserting and removing external circlips on shafts or axles
- with cylindrical precision tips
- with closing spring
- drop-forged
- head and handles chrome-plated, chequered handles
- DIN 5254 B




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65464101	A01	125	0.9	3-10	95
65464111	A11	125	1.3	10-25	95
65464121	A21	170	1.8	19-60	145
65464131	A31	210	2.3	40-100	111
65464141	A41	275	3.2	85-140	431

6546



Circlip pliers for external circlips
- version with 90° angled jaws
- suitable for gripping, inserting and removing external circlips on shafts or axles
- with cylindrical precision tips
- with closing spring
- drop-forged
- polished head
- plastic coated handles
- DIN 5254 B




Product no.	Size	L mm	T_1 mm	for circlips mm	g
65466101	A01	125	0.9	3-10	105
65466111	A11	125	1.3	10-25	105
65466121	A21	170	1.8	19-60	160
65466131	A31	210	2.3	40-100	236
65466141	A41	275	3.2	85-140	468

SELF-GRIP WRENCHES.

6562



Parallel jaw self-grip wrench
- with parallel, forged jaws
- with quick-release lever
- head and handles high-gloss nickel-plated
- Chrome Alloy Steel



Product no.	L mm	S mm	g
65622250	250	50	700

6962


Plastic protective jaws for parallel jaw self-grip wrench
— for additional protection of the clamped workpieces
— 1 pair

Product no.	for model	L mm	g
69620001	6562	90	10

6563



Universal self-grip wrenches
— with forged jaws (straight and half-round)
— with quick-release lever
— head and handles high-gloss nickel-plated
— Chrome Alloy Steel




Product no.	L mm	S mm	g
65632175	175	25	365
65632250	250	30	500

6564



Self-grip wrenches
— with forged, half-round jaws
— with quick release levers and wire cutters
— head and handles high-gloss nickel-plated
— Chrome Alloy Steel




Product no.	L mm	S mm	g
65642145	145	14	175
65642175	175	30	323
65642250	250	40	550
65642300	300	65	977

6571



Long-nose self-grip wrench
— particularly suitable in narrow tapered areas
— with quick-release lever
— head and handles high-gloss nickel-plated
— Chrome Alloy Steel



Product no.	L mm	S mm	g
65712165	165	23	190

ELECTRONICS PLIERS.


6707





2K

Electronics side cutters
— for demanding work in electronics/precision mechanics
— slim head design for use in confined work areas
— remarkable cutting performance: Ø 0.6 mm for hard wire and Ø 1.5 mm for soft wire
— long service life, no play, push-through joint
— with double leaf spring for smooth movement
— extended handle cover for better slip protection
— ergonomic thumb rest for optimal handling
— cutting edges induction hardened to approx. 62 HRC
— with 2-component handles
— DIN ISO 9654



Product no.	L mm	a mm	b mm	d mm	W mm	①	②	③	④	g
67076000	115	12	14	8	56	1.5	1	0.8	0.6	72

① Cutting capacity in mm for soft wire
② Cutting capacity in mm for medium-hard wire
③ Cutting capacity in mm for hard wire
④ Cutting capacity in mm for piano wire


6708





Mini electronics side cutters

- for demanding work in electronics/precision mechanics
- compact version with slim head design for use in confined working areas
- long service life, no play, push-through joint
- with double leaf spring for smooth movement
- extended handle cover for better slip protection
- ergonomic thumb rest for optimal handling
- cutting edges induction hardened to approx. 62 HRC
- with 2-component handles
- DIN ISO 9654



Product no.	L mm	a mm	b mm	d mm	W mm	①	②	③	④	g
67086000	110	10	10	7	56	1.0	0.8	0.6	0.4	62

① Cutting capacity in mm for soft wire
② Cutting capacity in mm for medium-hard wire
③ Cutting capacity in mm for hard wire
④ Cutting capacity in mm for piano wire


6709






Electronics end cutters

- for demanding work in electronics/precision mechanics
- 90° rotated and side-angled cutting geometry
- slim head design for use in confined work areas
- long service life, no play, push-through joint
- with double leaf spring for smooth movement
- extended handle cover for better slip protection
- ergonomic thumb rest for optimal handling
- cutting edges induction hardened to approx. 62 HRC
- with 2-component handles
- DIN ISO 9654



Product no.	L mm	a mm	b mm	d mm	W mm	①	②	g
67096000	120	12	6	17	56	0.6	0.3	80

① Cutting capacity in mm for soft wire
② Cutting capacity in mm for medium-hard wire



6710






2K

Electronics diagonal cutters

— for demanding work in electronics/precision mechanics
— 90° rotated and side-angled cutting geometry
— slim head design for use in confined work areas
— long cutting edge, 20° angle
— long service life, no play, push-through joint
— with double leaf spring for smooth movement
— extended handle cover for better slip protection
— ergonomic thumb rest for optimal handling
— cutting edges induction hardened to approx. 62 HRC
— with 2-component handles
— DIN ISO 9654



Product no.	L mm	a mm	b mm	d mm	W mm	①	②	g
67106000	120	13	6	18	56	0.6	0.3	78

① Cutting capacity in mm for soft wire
② Cutting capacity in mm for medium-hard wire

6711






2K

Electronics needle-nose pliers

— for demanding work in electronics/precision mechanics
— for gripping, holding, and bending components
— with half-round jaws
— smooth grip areas
— long service life, no play, push-through joint
— with double leaf spring for smooth movement
— extended handle cover for better slip protection
— ergonomic thumb rest for optimal handling
— with 2-component handles
— DIN ISO 9655



Product no.	L mm	a mm	b mm	f mm	d mm	W mm	g
67116000	130	12	24	1.5	8	56	76

8



BOLT CUTTERS.

The LightCUT® versions (LC)

The flat-oval, high-strength aluminium tubes of the LightCUT® range ensure a low weight, around half that of a comparable tool. For fatigue-free working and precise results.

980LC

VBW



Bolt cutters LightCUT®

- flat-oval, sturdy aluminium tubes ensure low weight
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- precise and simple adjustment of the cutting heads using eccentric screws
- optimised geometry reduces the effort required for cutting
- limit stop with extra-large buffer zone
- high-quality hardened and tempered for excellent wear resistance
- with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87980050	800	32	10	8	7	2650

98013

VBW



Cutter head with screws

- for bolt cutters LightCUT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87980136	980050	147	9	8	7	892

984LC

VBW



Offset bolt cutters LightCUT®

- flat-oval, sturdy aluminium tubes ensure low weight
- allows precise cutting down to the outer corners and close to edges
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- optimised geometry reduces the effort required for cutting
- limit stop with extra-large buffer zone
- high-quality, hardened and tempered for excellent wear resistance
- with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87984050	850	32	11	9	8	2900

434135

VBW



Cutter head with screws

- for bolt cutters/corner deep cutters

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87434135	984050	140	11	9	8	1105

438LC

VBW



Flush cut bolt cutters 30° LightCUT®

- flat-oval, sturdy aluminium tubes ensure low weight
- angled blades, adjustable cutter head for flush cutting of tensioning wires on concrete structures and for gabion wire baskets
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- limit stop with extra-large buffer zone
- high-quality, hardened and tempered for excellent wear resistance
- with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	°	g
87438050	810	32	10	8	7	30	2285

43713

VBW




Cutter head with screws

— for flush cut bolt cutters

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87437133	438050	150	9	8	7	995

430

VBW



Bolt cutters UNIBOLT®

— professional version for continuous use
— for cutting up to 48 HRC
— cutter head made of wear-resistant special steel, drop-forged
— precise and simple adjustment of the cutter head using eccentric screws
— optimised geometry reduces the effort required for cutting
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87430005	460	18	8	6	5	2050
87430010	610	24	9	8	7	2816
87430015	760	30	11	9	8	4328
87430020	910	36	13	11	9	6730
87430025	1070	42	16	11	10	8410

4301

VBW



Cutter heads with screws

— for bolt cutters UNIBOLT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87430136	430005	130	8	6	5	600
87430137	430010	150	9	8	7	910
87430138	430015	170	11	9	8	1425
87430139	430020	190	13	10	9	2025
87430140	430025	240	16	11	10	2835

445

VBW



Bolt end cutters

— the angled cutter head makes it particularly suitable for flush cutting
— for cutting up to 40 HRC
— cutter head made of wear-resistant special steel, drop-forged
— precise and simple adjustment of the cutter head using eccentric screws
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— blade width 28 mm
— for reinforcing steel III + IV in accordance with DIN 488 - strength approx. 550 N/mm²
— for prestressing steel and hardened and tempered steel wire up to 1,226 N/mm² (HRC 40)
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	g
87445010	630	24.8	8	6	2985

445135

VBW



Cutter head with screws

— for bolt end cutters

Product no.	for model	L mm	19 HRC mm	40 HRC mm	g
87445135	445010	150	8	6	1030

980

VBW



Bolt cutters WAGGONIT®

— for cutting up to 48 HRC
— cutter head made of wear-resistant special steel, drop-forged
— precise and simple adjustment of the cutter head using eccentric screws
— optimised geometry reduces the effort required for cutting
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87980005	460	18	8	6	5	2013
87980010	610	24	9	8	7	2800
87980015	760	30	11	9	8	4287
87980020	910	36	13	11	9	6438

98013



Cutter heads with screws

— for bolt cutters WAGGONIT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87980135	980005	129	8	6	5	601
87980136	980050	147	9	8	7	892
87980137	980015	170	11	9	8	1387
87980138	980020	197	13	10	9	1979

437



2K

Flush cut bolt cutters

— angled blades, adjustable cutter head for flush cutting of tensioning wires on concrete structures and for gabion wire baskets
— for cutting up to 48 HRC
— precise and simple adjustment of the cutter head using eccentric screws
— cutter head made of wear-resistant special steel, drop-forged
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	∠°	g
87437002	460	18	8	6	5	40	1905
87437005	610	24	9	8	7	30	2830

43713



Cutter heads with screws

— for flush cut bolt cutters

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87437131	437002	125	8	6	5	500
87437133	437005	150	9	8	7	995

433



Compact bolt cutters CombiCUT®

— compact version for particularly good accessibility
— suitable for cutting applications with low cutting force requirements
— for cutting up to 48 HRC
— cutter head made of wear-resistant special steel, drop-forged
— no blade adjustment required
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 1-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87433020	390	14	7	5	4	1370

433125



Cutter head with pins and circlips

— for bolt cutters CombiCUT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87433125	433020	110	7	5	4	400

433



Bolt end cutters CombiCUT®, compact

— compact version for particularly good accessibility
— angled cutter head makes it particularly suitable for flush cutting
— for cutting up to 48 HRC
— cutter head made of wear-resistant special steel, drop-forged
— no blade adjustment required
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 1-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	g
87433040	365	13	7	5	4	1390

433145



Cutter head with pins and circlips
— for bolt end cutters CombiCUT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87433145	433040	96	7	5	4	410

SolutionCUT

The special geometry of this bolt cutter enables precise and clean cutting not only in the second layer, but also in deeper layers - for effortless and precise working even in hard-to-reach areas.

434



Bolt cutters/corner deep cutters SolutionCUT
— 20° cutting angle facilitates cutting in corners and close to the edge
— for cutting power up to 48 HRC
— cutter head made of wear-resistant special steel, drop-forged
— precise and simple adjustment of the cutter head using eccentric screws
— reduced cutting force required due to optimal geometry enabling precise cutting in the 1st and 2nd layers
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	48 HRC mm	∠	Working length mm	g
87434025	1000	40	11	9	8	20	230	5400

434135



Cutter head with screws
— for bolt cutters/corner deep cutters

Product no.	for model	L mm	19 HRC mm	40 HRC mm	48 HRC mm	g
87434135	434025	140	11	9	8	1105

434 E8

Adjusting screw
— for bolt cutters/corner deep cutters and structural steel mesh cutters

Product no.	for model	g
87434081	434025	69

439



Bolt cutters with interchangeable cutter head
— long service life thanks to two-sided replaceable cutter head
— for cutting up to 40 HRC
— cutter head made of wear-resistant special steel, drop-forged
— with adjustable cutters
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	g
87439005	460	18	7	6	1945
87439010	610	24	9	8	3145
87439015	760	30	11	9	4280
87439020	910	36	13	13	7530

43913



Cutter heads with screws
— for bolt cutters with interchangeable cutter head

Product no.	for model	L mm	19 HRC mm	40 HRC mm	g
87439131	439005	125	7	6	708
87439132	439010	147	9	8	1116
87439133	439015	170	11	9	1814
87439134	439020	190	13	13	2541



STRUCTURAL STEEL MESH CUTTERS.

435LC



Structural steel mesh cutters LightCUT®
- flat-oval, sturdy aluminium tubes ensure low weight
- suitable for easy cutting of flat-lying structural steels
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- with adjustable cutters
- optimised geometry reduces the effort required for cutting
- with small opening angle
- limit stop with extra-large buffer zone
- high-quality, hardened and tempered for excellent wear resistance
- with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87435005	800	32	11	9	8	5	2650
87435010	1000	40	11	9	8	6	2924

435133



Cutter head with screws
- for structural steel mesh cutters LightCUT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87435133	435030; 435005; 435010	122	11	9	8	6	920



985



Structural steel mesh cutters WAGGONIT®
- suitable for easy cutting of flat-lying structural steels
- for cutting up to 48 HRC
- cutter head made of wear-resistant special steel, drop-forged
- with adjustable cutters
- optimised geometry reduces the effort required for cutting
- limit stop with extra-large buffer zone
- high-quality, hardened and tempered for excellent wear resistance
- with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87985010	950	38	11	9	8	6	2650

985135



Cutter head with screws
- for structural steel mesh cutters WAGGONIT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87985135	985010	148	11	9	8	6	1000

980082

Adjusting screw
- including 2 nuts

Product no.	for model	g
87980082	985010	20

700



Floor display for bolt cutters
- presentation stand for showrooms
- with space for 6 bolt cutters and structural steel mesh cutters
- can be displayed in any configuration

Product no.	L mm	H mm	W mm	g
87700050	270	455	500	9500

996

VBW



Structural steel mesh cutters BauCUT®
— suitable for easy cutting of flat-lying structural steels
— for cutting up to 40 HRC
— cutter head made of wear-resistant special steel, drop-forged
— with adjustable cutters
— optimised geometry reduces the effort required for cutting
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 1-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	2 x 40 HRC mm	g
87996010	950	38	11	9	8	3780

996135

VBW




Cutter head with screws
— for structural steel mesh cutters BauCUT®

Product no.	for model	L mm	19 HRC mm	40 HRC mm	2 x 40 HRC mm	g
87996135	996010	150	11	9	8	900

436

VBW



Structural steel mesh cutters, deep cutters SolutionCUT
— optimised geometry reduces the effort required for cutting on the 1st and 2nd layers
— for cutting up to 48 HRC
— cutter head made of special steel, drop-forged
— with adjustable cutters
— limit stop with buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87436010	1000	40	11	9	8	6	5400

436132

VBW



Cutter head with screws
— for structural steel mesh cutters, deep-reach

Product no.	for model	L mm	19 HRC mm	40 HRC mm	2 x 40 HRC mm	48 HRC mm	g
87436132	436010	150	11	9	8	6	950

434 E8


VBW

Adjusting screw
— for bolt cutters/corner deep cutters and structural steel mesh cutters

Product no.	for model	g
87434081	436010	69

480

VBW



Grating and flat material cutters EuroCUT®
— suitable for cutting both flat and round materials
— for cutting up to 30 HRC
— from mesh size 30 x 30 mm
— cutter head made of wear-resistant special steel, drop-forged
— limit stop with extra-large buffer zone
— high-quality, hardened and tempered for excellent wear resistance
— with 2-component handles

Product no.	L mm	L "	30 HRC mm	g
87480010	840	33	4 x 40	3188

480133

VBW



Cutter head with screws
— for grating and flat material cutters No. 480
— made of wear-resistant special steel

Contains 7-pieces:
1 x cutter head
3 x eccentric screws
3 x nuts

Product no.	for model	30 HRC mm	g
87480133	480010	4 x 40	3188

8

980 BO/MA universell

VBW



Cutter head fastener set

— for attaching the cutter head to the frame

Contains 14-pieces:

screws 3 x M8; 1 x M10; eccentric screws 2 x M8; 2 x M10; nuts 3 x M8; 3 x M10

Product no.	for model	Content pcs.	g
87980100	430; 434; 435; 436; 980; 984; 985; 996	14	305

PLIER SETS IN TCS INLAYS.

TCS 6543-6564/3



Plier set

— safely integrated in the modular Tool Control System (TCS)

Contains 3-pieces:


1 circlip pliers for internal circlips **No. 6543**: J2

1 circlip pliers for external circlips **No. 6545**: A2

1 self grip wrench **No. 6564**: L. 250 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838180	350	175	30	1/3	3	975

TCS 6543-6546/4



Circlip plier set

— safely integrated in the modular Tool Control System (TCS)

Contains 4-pieces:

2 circlip pliers for internal circlips **No. 6543, 6544**: J2; J21

2 circlip pliers for external circlips **No. 6545, 6546**: A2; A21

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830608	350	175	30	1/3	4	626

TCS 6534-6545/6



Plier set

— safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:

1 telephone pliers **No. 6730**: L. 200 mm

1 telephone pliers **No. 6731**: L. 200 mm

2 circlip pliers for internal circlips **No. 6543**: J1; J2

2 circlip pliers for external circlips **No. 6545**: A1; A2

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96832100	350	350	30	2/3	6	1070

TCS 10 821/4



Circlip plier set

— safely integrated in the modular Tool Control System (TCS)

Contains 4-pieces:

2 circlip pliers for internal circlips **No. 6543, 6544**: J2; J21

2 circlip pliers for external circlips **No. 6545, 6546**: A2; A21

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830273	350	175	30	1/3	4	790

TCS 6572-6730/4



Plier set
— safely integrated in the modular Tool Control System (TCS)
Contains 4-pieces:
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6572**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830622	350	175	35	1/3	4	1145

TCS 3 821/4



Plier set
— safely integrated in the modular Tool Control System (TCS)
Contains 4-pieces:
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 combination pliers **No. 6700**: L. 180 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830266	350	175	40	1/3	4	1410


TCS 6551-6730/4



Plier set
— safely integrated in the modular Tool Control System (TCS)
Contains 4-pieces:
1 combination pliers **No. 6700**: L. 180 mm
1 telephone pliers **No. 6730**: L. 200 mm
1 water pump pliers **No. 6551**: L. 240 mm
1 heavy-duty side cutters **No. 6721**: L. 160 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838179	350	175	35	1/3	4	1070

TCS 6707-6711



Electronics plier set
— safely integrated in the modular Tool Control System (TCS)
Contains 5-pieces:
1 electronics side cutters **No. 6707**: L. 115 mm
1 mini electronics side cutters **No. 6708**: L. 115 mm
1 electronics end cutters **No. 6709**: L. 120 mm
1 electronics diagonal cutters **No. 6710**: L. 120 mm
1 electronics needle-nose pliers **No. 6711**: L. 130 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838798	350	175	45	1/3	5	480




STAHLWILLE

9 Pullers



426 **Pullers with parallel extractor hooks**

427 **Pullers with swivelling extractor hooks**

429 **Internal pullers, slide hammers and counter stays**


431 **Separation assemblies**

431 **Pullers**

STAHLWILLE PULLERS –
For special requirements.

Well-designed, drop-forged and precisely machined on state-of-the-art machines: The STAHLWILLE puller range includes numerous products for different applications such as external pulling, internal pulling and separating of fixed components of all kinds. The range offers the perfect solution for every challenge and impresses with premium quality.

RESILIENT



Powerful.

Heavy-duty cross members and puller hooks made of oil-hardened Chrome Alloy Steel. Drop-forged.

More stable.

High flexural strength thanks to cross members with precisely calculated profiles and milled, smooth guiderails.

Two- or three-armed.

STAHLWILLE also offers three-armed pullers that allow even more even load distribution in suitable space conditions.



Universal.

Two-arm pullers with parallel puller hooks are ideal for removing bearings, gears and washers that are mounted on a shaft and are freely accessible from an external source.

Precise.

Spindles with freely rotating spindle tips ensure gentle and optimal force transmission to the shafts.

Smooth running.


The special coating on the threaded spindles enables smooth rotation for controlled loosening of the components.

PULLERS WITH PARALLEL EXTRACTOR HOOKS.

11200



Pullers
- two-armed
- with sliding, constantly parallel extractor hooks
- for gears, ball bearings, pulleys and similar parts from a shaft or axle
- for ball bearings, ball bearing outer races and sockets out of drilled holes
- reversible arms for use as external and internal pullers
- adjustment scale for uniform adjustment of the extractor hooks
- nitrided spindle, no lubrication required, maintenance-free
- sturdy design, zinc plated




Product no.	⬢ mm	W1 mm	W2 mm	h mm	a mm	b mm	c mm	Thread	max. t	g
71020001	17	90	140	100	3	22	12	M14 x 1,5 x 140	3	1014
71020002	17	130	180	100	3	22	12	M14 x 1,5 x 140	3	1136
71020003	22	160	220	150	4	30	18	G 1/2 x 210	5	2931
71020004	22	200	260	150	4	30	18	G 1/2 x 210	5	3322
71020005	27	250	330	200	7	36	28	G 3/4 x 280	7.5	6969
71020006	27	350	420	200	7	36	28	G 3/4 x 280	7.5	8042


11300



Pullers
- three-armed
- with sliding, constantly parallel extractor hooks
- for gears, ball bearings, pulleys and similar parts from a shaft or axle
- for ball bearings, ball bearing outer races and sockets out of drilled holes
- reversible arms for use as external and internal pullers
- nitrided spindle, no lubrication required, maintenance-free
- sturdy design, zinc plated



Product no.	⬢ mm	W1 mm	W2 mm	h mm	a mm	b mm	c mm	Thread	max. t	g
71030001	17	90	140	100	3	22	12	M14 x 1,5 x 140	3	1400
71030002	17	130	180	100	3	22	12	M14 x 1,5 x 140	3	1600
71030003	22	160	220	150	4	30	18	G 1/2 x 210	5	3600
71030004	22	200	260	150	4	30	18	G 1/2 x 210	5	4200
71030005	27	250	400	200	7	36	28	G 3/4 x 280	7.5	9300




PULLERS WITH SWIVELLING EXTRACTOR HOOKS.

11251



Pullers
- — two-armed
- — with self-centring puller arms
- — for gears, ball bearings, pulleys and similar parts from a shaft or axle
- — double-sided use of the extractor hooks: narrow arm end (20 mm) for narrow installation spaces, wide arm end (24 mm) with slot (8 mm) for pulling off washers or gear wheels with the aid of 8 mm screws
- — nitrided spindle, no lubrication required, maintenance-free
- — zinc plated




Product no.	⬢ mm	w max. mm	h mm	a mm	b mm	c mm	Thread	max. t	g
71025101	19	160	130	3	24	12	M18 x 1,5 x 170	5	2000
71025102	19	220	170	3	24	12	M18 x 1,5 x 170	5	2300

11351



Pullers
- — three-armed
- — with self-centring puller arms
- — for gears, ball bearings, pulleys and similar parts from a shaft or axle
- — double-sided use of the extractor hooks: narrow arm end (20 mm) for narrow installation spaces, wide arm end (24 mm) with slot (8 mm) for pulling off washers or gear wheels with the aid of 8 mm screws
- — nitrided spindle, no lubrication required, maintenance-free
- — zinc plated




Product no.	⬢ mm	w max. mm	h mm	a mm	b mm	c mm	Thread	max. t	g
71035101	19	160	130	3	24	12	M18 x 1,5 x 170	7.5	2600
71035102	19	220	170	3	24	12	M18 x 1,5 x 170	7.5	3200

TOOLS THAT
... inspire

11250



Pullers
- two-armed
- with swivelling extractor hooks
- extractor hooks and beam are connected by movable tabs
- for V-belt pulleys and flywheels on long shafts
- when the spindle is tightened, the extractor hooks are tensioned and tighten
- variable clamping depth possible by adjusting the extractor hooks
- nitrided spindle, no lubrication required, maintenance-free
- zinc plated




Product no.	⬣ mm	w max. mm	h mm	Thread	max. t	g
71025001	22	280	390	G 1/2 x 250	8	4983
71025002	22	420	480	G 1/2 x 350	8	5894

11210



Pullers
- three-armed
- with swivelling extractor hooks
- extractor hooks and beam are connected by movable tabs
- for V-belt pulleys and flywheels on long shafts
- when the spindle is tightened, the extractor hooks are tensioned and tighten
- variable clamping depth possible by adjusting the extractor hooks
- nitrided spindle, no lubrication required, maintenance-free
- zinc plated



Product no.	⬣ mm	w max. mm	h mm	Thread	max. t	g
71035001	22	280	390	G 1/2 x 250	12	7700
71035002	22	420	480	G 1/2 x 350	12	8900




11040



Battery terminal pullers

— two-armed, with a self-centring quick-action clamp and automatic feed
— for battery terminal clamps, smaller ball bearings, pulleys etc.
— for narrow, hard-to-reach spaces
— as force is applied through the spindle, the extractor hooks automatically apply increasing force to the part being extracted
— particularly suited to car electrics, compressed air system repairs and similar applications due to the compact design and small hooks
— zinc plated



Product no.	⬢ mm	w max. mm	h mm	a mm	b mm	c mm	Thread	max. t	max. torque N·m	g
71120011	12	10-60	45	2,5	11	11	M10 x 110	2,5	25	245
71120012	12	10-70	65	2,5	11	11	M10 x 110	3,0	35	261
71120013	12	10-100	80	2,5	11	11	M10 x 110	3,5	45	315


INTERNAL PULLERS, SLIDE HAMMERS AND COUNTER STAYS.

11400



Internal pullers

— for very tight ball bearings, ball bearing outer races and bushings that are not freely accessible from the outside
— removal is carried out by inserting the internal puller into the bearing and screwing in the spindle
— the expanding jaws spread and the lugs locate under the bearing
— can be used with slide hammers 11402/1-2 or counter stays 11401/1-3




Product no.	Model	Ball bearing ISO	⬢ mm	d_1 mm	b mm	e min./max. mm	L mm	h mm	g
71040001	11400/1	6000	10	M10	26	8-12	105	26	114
71040002	11400/2	6001; 6201; 6202	10	M10	26	12-15	109	26	119
71040003	11400/3	6202; 6203	13	M10	28	15-19	120	28	149
71040004	11400/4	6204; 6205	13	M10	28	19-25	123	28	182
71040005	11400/4a	6205; 6206	13	M10	28	25-30	123	28	297
71040006	11400/5	6206; 6207	13	M10	35	30-35	135	35	384
71040007	11400/6	6207; 6208; 6209	17	M14 x 1,5	42	35-45	170	42	649
71040008	11400/7	6209; 6210; 6211	17	M14 x 1,5	42	45-55	170	42	818
71040009	11400/8	6211; 6212; 6213; 6214	19	M14 x 1,5	55	55-70	205	55	1693
71040014	11400/9	6214	19	M14 x 1,5	55	70-100	205	55	1693

11401



Counter stays

— for internal puller 11400/1-9
— screw the spindle of the counter stay into the internal puller
— insert and spread the internal puller
— pull out the workpiece




Product no.	⬢ mm	for model	d_1 mm	⚖ g
71040101	27	11400/1; /2; /3; /4; /4a; /5	M10	750
71040102	32	11400/6; /7	M14 x 1,5	1650
71040103	32	11400/8; /9	M14 x 1,5	3000

11402



Slide hammers

— for ball bearings, for example, when the counter stay cannot be used for access reasons
— for internal pullers 11400/1-9



Product no.	⬢ mm	for model	d_1 mm	f mm	L mm	⚖ g
71040201	13	11400/1; 11400/2; 11400/3; 11400/4; 11400/4a; 11400/5	M10	200	280	979
71040202	24	11400/6; 11400/7; 11400/8; 11400/9	M14 x 1,5	340	515	2923




SEPARATION ASSEMBLIES.

11500



Separation assemblies

— for pullers 11501/1-4
— for separating and removing ball bearings, roller bearings, bushings, wheels and other tightly fitting parts
— the puller pins of the puller are screwed into the separation assembly
— seperator jaws slide under the component to be removed
— zinc plated



Product no.	Model	Ball bearing ISO	d_1 mm	e min./max. mm	g
71050016	11500/1	6000; 6001; 6201; 6202; 6203; 6204; 6205	M10	5-60	500
71050017	11500/2	6000; 6001; 6201; 6202; 6203; 6204; 6205; 6206; 6207	M10	12-74	900
71050018	11500/3	6000; 6001; 6201; 6202; 6203; 6204; 6205; 6206; 6207; 6208; 6209; 6210; 6211; 6212	M14 x 1,5	22-115	2400
71050019	11500/4	6201; 6202; 6203; 6204; 6205; 6206; 6207; 6208; 6209; 6210; 6211; 6212; 6213; 6214	M18 x 1,5	30-155	4700


PULLERS.

11501



Pullers

— for the separation assemblies 11500/1-4
— for pulling, the puller pins are screwed into the separation assembly
— clamping depth can be increased using extension 11502/1-4
— zinc plated



Product no.	⬢ mm	for model	d_1 mm	w mm	h mm	Thread	g
71050101	17	11500/1	M10	40-120	125	M14 x 120	1000
71050102	19	11500/2	M10	60-165	180	M18 x 170	1100
71050103	22	11500/3	M14 x 1,5	70-215	195	G 1/2 x 210	3400
71050104	27	11500/4	M18 x 1,5	90-300	205	G 3/4 x 280	6500

11502




Extensions

— for use on longer parts for extending the extraction bolts on the puller

Product no.	for model	d_1 mm	L mm	g
71050201	11501/1; /2	M10	100	300
71050202	11501/3	M14 x 1,5	100	300
71050203	11501/4	M18 x 1,5	100	700



10 Special automotive tools



436 **The KABELEX® programme**

441 **Bodywork tools**

446 **Vehicle door tools**

447 **Glass installation and removal tools**

449 **Valve and piston tools**

450 **Ignition and electrical tools**

453 **Brake and wheel tools**

455 **Engine and transmission tools**

457 **Various special automotive tools**

STAHLWILLE SPECIAL AUTOMOTIVE TOOLS –
Always the right solution at hand.

STAHLWILLE's product portfolio also includes special automotive tools to make vehicle repairs easier and safer. With its knowledge of the diverse challenges in daily work life, STAHLWILLE offers various special solutions that facilitate efficient work as well as the damage-free installation and removal of vehicle parts.

EFFICIENT



Resilient.

High-quality sockets manufactured with High Performance Quality (HPQ®) steel are extremely resilient, yet thin-walled and ideal for working in tight spaces.

Versatile.

The vehicle test lamp is an indispensable aid for identifying the causes of faults in the vehicle electrical system, for quickly finding power interruptions, defective fuses, bulbs and much more. With test probe, flexible cable and crocodile clip.

Robust.

The gasket scraper is made with a special steel blade and is ideal for removing gasket and adhesive residues on the cylinder head, cylinder head cover and oil pan.



Individual.

With the KABELEX® programme, STAHLWILLE offers a whole range of different tools for quick and safe release of electrical connectors – without 'snipping off'. This saves time and money. Available individually or in sets.

Efficient.

Tool assortments from STAHLWILLE guarantee optimal and efficient work processes. Whether in the workshop, in production or on the race track – mechanics and technicians appreciate the advantages of STAHLWILLE special automotive tools.

Special.

In cooperation with leading automotive manufacturers, STAHLWILLE also develops tool ranges for workshops and production. These can be found in the catalogue chapter 'Tool assortments'.

THE KABELEX® PROGRAMME.



STAHLWILLE KABELEX® Protect
for workshops and cable assemblers

Over 30 different unlocking tools available. With locking blade guard, to protect the fine blades and prevent injuries. Particularly handy for precision work on delicate connectors. For quick and easy release of cable connections - saving time and money. Blades made from strong and extremely durable Chrome Alloy Steel and special spring steel.

1501-1506



Ejection tools KABELEX®
— for round plug-in sockets with notches
— complete with sleeve

Product no.	Model	for contact size ∅ mm	g
96746230	1501 + 1511	1.5	45
96746231	1502 + 1512	3.5	59
96746232	1503 + 1513	4.0	79
96746233	1504 + 1514	2.5	60
96746234	1505 + 1515	2.3	46
96746235	1506 + 1516	4.0	72

1511-1516



Dismantling sleeves KABELEX®

Product no.	Model	for model	for contact size ∅ mm	Internal ∅ mm	External ∅ mm	L mm	g
78600001	1511	1501	1.5	2.9	3.3	30	1
78600002	1512	1502	3.5	4.4	5.0	30	1
78600003	1513	1503	4.0	6.0	6.5	45	2
78600004	1514	1504	2.5	4.0	4.4	30	1
78600005	1515	1505	2.3	3.0	3.3	35	8
78600006 [1]	1516	1506	4.0	5.6	6.0	35	1

[1] for 4.0 mm MOLEX® contact

1523



Assembly sleeve KABELEX® ABS
— for No. 1503

Product no.	for contact size ∅ mm	Internal ∅ mm	External ∅ mm	L mm	g
78610001	4.0	4.0	6.5	50	5

1551/1552



Cable extractor tools KABELEX®
— for flat plug-in sockets with notches, e.g. in BMW, Ford, Opel, Porsche, Seat, Skoda, VW/Audi

Product no.	Model	for contact dimension □ mm	g
74620001	1551	2.8	19
74640002	1552	5.8	19

1553-1555



Cable extractor tools KABELEX®
— for flat plug-in sockets in plugs with an unlocking channel

Product no.	Model	for contact dimension □ mm	g
74620003	1553	2.8; 5.8	16
74620004	1554	2.8	16
74620005	1555	5.8	16

1556



Cable extractor tool KABELEX®
— for flat plug-in sockets, Micro-Timer II, III contacts, e.g. in Mercedes-Benz, Opel, Porsche, PSA, Renault, Saab, Seat, Skoda, VW/Audi

Product no.	for contact dimension □ mm	g
74620006	1.6	17

1556-1



Cable extractor tool KABELEX®

— for flat plug-in sockets with asymmetrically arranged notches on the contact in plugs with 2 unlocking channels, e.g. in Seat, Skoda, VW/Audi

Product no.	for contact dimension □ mm	g
74612006	0.64	19

1557/1558



Cable extractor tools KABELEX®

— for flat plug-in sockets with asymmetrically arranged notches on the contact in plugs with 2 unlocking channels, e.g. in Seat, Skoda, VW/Audi

Product no.	Model	for contact dimension □ mm	g
74620007	1557	2.8	21
74620008	1558	4.8	22

1559



Cable extractor tool KABELEX®

— for flat plug-in sockets, Maxi Power Timer contacts, e.g. in Mercedes-Benz, VW/Audi

Product no.	for contact dimension □ mm	g
74620009	9.5	39

1562



Cable extractor tool KABELEX®

— for flat plug-in sockets, Pit-Pod contacts

— can be used for all automotive brands

Product no.	for contact dimension □ mm	g
74620012	diverse	25

1574



Cable extractor tool KABELEX®

— for flat plug-in sockets, Micro-Timer I contacts and ABS housings, e.g. in Fiat, Ford, Mazda, Opel, PSA, Renault, Saab, VW/Audi

Product no.	for contact dimension □ mm	g
74620024	1.6	15

1575



Cable extractor tool KABELEX®

— for soldered round plug pin contacts in Ford

— for flat plug-in sockets (retaining by housing safety lock tab), e.g. in Fiat, Mazda, Toyota

Product no.	for contact size ∅ mm	for contact dimension □ mm	g
74620025	1.5	2.8; 5.8	15

1576



Cable extractor tool KABELEX®

— for flat plug-in sockets with single notch (flat plug without box), e.g. MAN

Product no.	for contact dimension □ mm	g
74620026	2.8	18

1577



Cable extractor tool KABELEX®

— for flat plug-in sockets, VKR Box contacts, e.g. in MAN

Product no.		g
74620027		49

1577-1



Cable extractor tool KABELEX®

— for flat plug-in sockets, MKR/MKS contacts, e.g. in MAN/Volvo

Product no.	for contact dimension □ mm	g
74615027	1.5	23

1578K-1



Cable extractor tool KABELEX®

— for flat plug-in sockets and SLK contacts (primary), e.g. in BMW, Mercedes-Benz

Product no.	for contact dimension □ mm	g
74610028	2.8	35

1578K-2



Cable extractor tool KABELEX®

— for flat plug-in sockets and SLK contacts 97 (primary, secondary), e.g. in BMW, Mercedes-Benz

Product no.	for contact dimension □ mm	g
74612028	2.8	35

1584/1585



Cable extractor tools KABELEX®

— for round soldered contacts in Mercedes-Benz

Product no.	Model	for contact size ∅ mm	g
74620034	1584	4.0	13
74620035	1585	2.5	11

1587



Cable extractor tool KABELEX®

— for flat plug-in sockets and E-95 contacts in Mercedes-Benz

Product no.	for contact dimension □ mm	g
74620037	1.65	23

1589K



Cable extractor tool KABELEX®

— for flat plug-in sockets and LSK contacts, e.g. in BMW, Mercedes-Benz

Product no.	for contact dimension □ mm	g
74610039	8	45

1591



Cable extractor tool KABELEX®

— for flat plug-in sockets in terminals with 2 unlocking channels, Junior Power Timer contacts, standard Power Timer Contacts, e.g. in BMW, Mercedes-Benz, Fiat, Ford, MAN, Opel, PSA, Renault, Saab, VW/Audi

Product no.	for contact dimension □ mm	g
74620041	2.8; 5.8	25



STAHLWILLE KABELEX® RANGE.





Plug system	Tools	Cars											Trucks				Contact size mm	Model
		BMW	Fiat	Ford	Mazda	Mercedes-Benz	Opel	PSA	Renault	Volvo	VW/Audi Seat/Skoda Porsche		MAN	Mercedes-Benz	Scania	Volvo		
Round plug systems/ Crimp contacts (The complete tool consists of ejection tool with bush)		○	○			○	○			○	○		○	○		○	∅ 1.5	1501 + 1511
		○	○			○	○			○	○		○	○		○	∅ 3.5	1502 + 1512
													○	○	○	○	∅ 4 ABS	1503 + 1513, 1523
		○				○	○										∅ 2.5	1504 + 1514
			○			○	○	○									∅ 2.3	1505 + 1515
													○	○			∅ 4	1506 + 1516
Round plug systems/ soldered contacts			○	○	○												∅ 1.5 pin contact	1575
						○											∅ 4	1584
			○			○											∅ 2.5	1585
Flat plug systems with 2 or more locking tongues Crimp contacts		○		○		○	○	○	○		○		○				2.8	1551
		○	○	○			○	○	○		○		○				5.8	1552
						○	○	○	○	○	○						1.6	1556
						○					○						9.5 Maxi Power Timer-contacts	1559
							○										2.8 Ducon	1565
							○										1.5 Ducon	1566
													○				VKR box contact	1577
													○			○	MKR/MKS-contacts	1577-1
		○				○											SLK-contacts (primary)	1578K-1
		○				○											SLK-contacts 97 (primary+ secundary)	1578K-2
		○				○											LSK-contacts	1589K
						○											1.65 E 95	1587
		○	○	○		○	○	○	○	○	○		○	○	○	○	2.8/5.8 Junior Power Timer-contacts Standard Power Timer-contacts	1591
Flat plug systems with 2 locking tongues asymmetrical Crimp contacts											○						0.64 MQS asymmetrically	1556-1
											○		○				2.8	1557
											○						4.8	1558
Flat plug systems with 1 locking tongue Crimp contacts		○	○	○	○	○	○	○	○	○	○		○				2.8/5.8	1553
		○						○	○	○							2.8	1554
		○						○	○								5.8	1555
		○	○	○	○	○	○	○	○	○	○		○	○	○	○	Several Pid-Pod	1562
								○									0.8 Ducon	1563
							○										1.5 Ducon	1564
			○	○	○		○	○	○		○						1.6 Without box	1574
													○				2.8	1576

10

1560



Tool set KABELEX®
— for round connectors (including ABS)
Contains 10-pieces:
1 ejection tool **No. 1501**: for contact dimension Ø 1.5 mm
1 ejection tool **No. 1502**: for contact dimension Ø 3.5 mm
1 ejection tool **No. 1503**: for contact dimension Ø 4.0 mm
2 dismantling sleeves **No. 1511**: for contact dimension Ø 1.5 mm (1 piece mounted)
2 dismantling sleeves **No. 1512**: for contact dimension Ø 3.5 mm (1 piece mounted)
2 dismantling sleeves **No. 1513**: for contact dimension Ø 4.0 mm (1 piece mounted)
1 assembly sleeve (ABS) **No. 1523**

Product no.	Content pcs.	g
96747201	10	560

1570/2



Universal set KABELEX®
Contains 12-pieces:
3 ejection tools **No. 1501, 1502, 1505**: for contact dimensions Ø 1.5; 3.5; 2.3 mm
3 dismantling sleeves **No. 1511, 1512, 1515**: for contact dimensions Ø 1.5; 3.5; 2.3 mm
1 cable extractor tool **No. 1553**: for connectors with 1 unlocking channel, flat contacts 2.8 and 5.8 mm
1 cable extractor tool **No. 1556**: for Micro-Timer II, III contacts, flat contacts 1.6 mm
1 cable extractor tool **No. 1559**: for Maxi-Power timer contacts, flat contacts 9.5 mm
1 cable extractor tool **No. 1562**: for Pit Pod contacts
1 cable extractor tool **No. 1574**: for Micro-Timer I contacts and ABS housing, flat contacts 1.6 mm
1 cable extractor tool **No. 1591**: for connectors with 2 unlocking channels, flat contacts 2.8 and 5.8 mm

Product no.	Content pcs.	g
96747304	12	1230

1700 MAN/Volvo




Tool set KABELEX®
— for MAN/Volvo, Mercedes-Benz trucks
Contains 14-pieces:
4 ejection tools **No. 1501, 1502, 1503, 1506**: for contact dimensions Ø 1.5; 3.5; 4.0 (ABS) and 4.0 mm
4 dismantling sleeves **No. 1511, 1512, 1513, 1516**: for contact dimensions Ø 1.5; 3.5; 4.0 (ABS) and 4.0 mm
1 assembly sleeve (ABS) **No. 1523**
2 cable extractor tools **No. 1553, 1591**: for contact dimensions, flat contacts 2.8 and 5.8 mm
1 cable extractor tool **No. 1576**: for flat plugs with single latch, flat contacts 2.8 mm
1 cable extractor tool **No. 1577**: for flat plug-in socjets, VKR box contacts, flat contacts
1 cable extractor tool **No. 1577-1**: for MKR/FMD contacts, flat contacts 1.5 mm

Product no.	Content pcs.	g
96747208	14	1300

TOOLS THAT
... inspire

BODYWORK TOOLS.



Panel beating hammers for bodywork
Explanation of the table headings

L_1 = Overall length
L_2 = Head length
Striking surface (□ mm) = Head size
Striking surface (Ø mm) = Head diameter

10775



Dinging hammer
— 2 round faces with different diameters
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130002	30/40	300	155	516

10780



Planishing hammer
— short version
— square and round face
— with hickory shaft

Product no.	□ mm	∅ mm	L_1 mm	L_2 mm	g
70130003	25x25	32	300	100	346

10785



Planishing hammer
— short version
— smooth square face and round chequered face
— with hickory shaft

Product no.	□ mm	∅ mm	L_1 mm	L_2 mm	g
70130004	35 x 35	40	300	96	484

10790



Pecking hammer
— round face and ball pein
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130005	18/41	300	158	479

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

10795



Pecking hammer
— round face and acorn-shaped pein
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130006	20/41	300	160	461

10800



Pecking hammer
— short version
— round, flat face and pointed tip
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130007	35	300	135	357

10805



Pecking hammer
— round, flat face
— long, thin pein, approx 1 mm thick
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130008	40	300	160	446

10806



Pecking hammer
— extra large thin face and pein
— with hickory shaft

Product no.	∅ mm	L_1 mm	L_2 mm	g
70130011	40	300	135	764

10811



Planishing and grooving hammer
— with hickory shaft

Product no.	□ mm	∅ mm	L_1 mm	L_2 mm	g
70130012	36 x 10	30	320	160	545

10812



Planishing and grooving hammer
— with hickory shaft

Product no.	□ mm	∅ mm	L_1 mm	L_2 mm	g
70130013	25 x 5	30	300	115	344

10880



Bumping spoon
— for body work
— small version
— finely ground work surface

Product no.	L_1 mm	L_2 mm	g
70220001 *	200	460	1866

* L_1 = working length L_2 = total length


10885



Bumping spoon

— for body work
— large version
— finely ground work surface

Product no.	L mm	g
70220002	500	2210



Dollies

Explanation of the table headings

L = Overall length
b = Width
h = Height

10835



Dolly

— comma shape
— dolly for repair, customisation and restoration of motor vehicles

Product no.	L mm	b mm	h mm	g
70210002	130	55	32	958

10855




Universal dolly

— dolly for repair, customisation and restoration of motor vehicles

Product no.	h mm	g
70210010	58	1110

10841



Dolly

— flat shape
— dolly for repair, customisation and restoration of motor vehicles

Product no.	L mm	b mm	h mm	g
70210005	107	66	28	984

10842



Dolly

— diabolo shape
— curved
— dolly for repair, customisation and restoration of motor vehicles

Product no.	L mm	b mm	h mm	d mm	g
70210006	60	55	55	57	658

10845



Dolly
— toe shape
— dolly for repair, customisation and restoration of motor vehicles

Product no.	L mm	b mm	h mm	g
70210008	120	55	22	770

10865



Dolly
— half-round shape
— dolly for repair, customisation and restoration of motor vehicles

Product no.	L mm	b mm	h mm	g
70210012	80	60	35	1070

10890



Body spoon
— for removing dents
— small version
— finely ground work surface

Product no.	L mm	g
70220003	270	550

10905



Body file holder
— with a coarse blade

Product no.	L mm	W mm	H mm	g
72160000	365	35	110	765

10922



Body file holder
— made from wood
— for half-round radius file blades

Product no.	L mm	H mm	g
72200001	530	25	255

10923



Body file holder
— made from wood
— for flat file blades

Product no.	L mm	H mm	g
72200002	530	24	302

10921



File blade for No. 10922
— course, without swarf breaker
— half-round, hollow
— radially milled, toothed on both sides

Product no.	teeth per inch	L mm	g
79060004	9	350	216

10906-10916



File blades for No. 10905 and No. 10923

Product no.	Model	Version	teeth per inch	L mm	g
79060001	10906	fine, radial cut	15	350	321
79060002	10907	medium, radial cut	12	350	286
79060003	10908	coarse, radial cut	9	350	279
79060012	10915	medium, angled cut	12	350	282
79060013	10916	coarse, angled cut	9	350	252

11005



Pry bar

— head and tip polished

Product no.	L mm	W mm	d mm	g
72090000	400	46	14	477

11006



Lever bar

— made of special steel
— bright nickel-plated

Product no.	L mm	W mm	g
72090002	400	14	498

11007



Lever bar

— made of special steel
— bright nickel-plated

Product no.	L mm	W mm	g
72090003	400	17	641

12771



Extractor pliers

— for extracting fixing plugs on door panels, trim, bumper rubber, etc.
— joint and jaws made of hardened steel plate
— handles made of shaped sheet metal

Product no.	L mm	g
76480001	230	205

12752



Sheet metal shears

— lever action
— self-opening by built-in spring
— excellent cutting power
— for sheet steel up to 1.8 mm and stainless steel sheet up to 1.2 mm

Product no.	Version	L "	L mm	g
75230001	left-cutting	10 1/4	260	532
75230002	right-cutting	10 1/4	260	532

12753



Sheet metal shears

— lever action
— self-opening by built-in spring
— excellent cutting power
— for sheet steel up to 1.8 mm and stainless steel sheet up to 1.2 mm

Product no.	Version	L "	L mm	g
75240001	left-cutting	10 1/4	260	473
75240002	right-cutting	10 1/4	260	473

12727




Spot weld milling cutter

— HSS steel
— for spot weld removal on vehicle body or sheet metal construction
— with interchangeable milling tool Ø 10 mm
— adjustable milling depth by setting the adjustment screw
— can be used on both sides
— no pulling and tearing of sheet metal

Product no.	L mm	g
72260001	72	19

12728



Spare milling cutter

— compatible with spot weld milling cutter No. 12727

Product no.	L mm	g
79260001	13	4

12729/12730



Spot weld drills

— for clean, burr-free drilling of spot weld
— no shifting from welding point thanks to self-cutting centre point
— re-grindable

Product no.	Model	d mm	g
72270007	12729	7	18
72270008	12730	8	30



VEHICLE DOOR TOOLS.


12770



3K

Lever bar

— powder coated blade for better sliding effect
— for loosening door panels in cars
— with 3-component handle



Product no.	L mm	a mm	b mm	c mm	g
74593101	260	8	26	21	168

12770/2



3K

Lever bar

— for gently lifting off or unclipping sensitive caps, trim strips, trim rings, switches, rubber and textile coatings
— prevents scratches or damage due to the finely polished, rounded edges
— with 3-component handle

Product no.	L mm	g
74593102	185	20

12770/3



Plastic lever bar

— to remove trim of all types and cover trim on windshields, rear and side windows
— wide contact surface prevents scratches on painted parts, distortion of the trim or damage to windows

Product no.	L mm	W mm	g
74590003	300	50	209

12772



Lever bar
— suitable for bodywork and interior
— closed scoop
— with 3-component handle

Product no.	L mm	g
74593100	380	260

GLASS INSTALLATION AND REMOVAL TOOLS.

10350 N



Windscreen replacement set VERITRAC
Contains 5-pieces:
1 draw handle; 1 guide handle; 1 coil of special cutting wire (50 m); 2 double suction lifters

Product no.	Content pcs.	g
98742711	5	1760

10351 N



Windscreen replacement set VERITRAC
Contains 3-pieces:
1 draw handle; 1 guide handle; 1 coil of special cutting wire (50 m)

Product no.	Content pcs.	g
96742711	3	458



10352



Double suction lifters
— 1 pair
— mechanical action with safety lock
— special ABS-plastic
— oil and acid resistant
— with belt slots in the handle
— load capacity: 60 kg

Product no.	L mm	d mm	g
74280001	530	120	1405

10352/1



Double suction lifters
— mechanical action with safety lock
— special ABS-plastic
— oil and acid resistant
— with belt slots in the handle
— load capacity: 30 kg

Product no.	L mm	d mm	g
74280005	415	120	670

10351/1



Draw handle
— for drawing the cutting wire through the adhesive seal

Product no.	suitable for	g
74270001	SD10351N	90

SD10351N



Cutting wire

— wire removal without uncoiling the entire reel

Product no.	L m	d mm	g
79270011	50	0.6	170

10351/2



Guide handle

— for attaching and clamping the cutting wire inside the vehicle

Product no.	L mm	g
74270002	308	195

10351/3



Guide handle

— for attaching and clamping the cutting wire inside the vehicle
— the extra long length makes it particularly suitable for recessed glass

Product no.	L mm	g
74270006	308	190



1474/2



3K

Wire inserter

— for pulling or pushing the cutting wire through the hardened adhesive
— with 3-component handle

Product no.	L mm	g
78033102	290	69

10355



Wire insert probe

— for threading the cutting wire through the hardened adhesive
— steel tube with brass handle

Product no.	Ø mm	g
74270004	2.5	115

12718



3K

Gasket scraper

— flat forged, sharp and wear-resistant blade
— for removing sealant and adhesive residue
— optimised ergonomics for perfect control when scraping
— with 3-component handle

Product no.	L mm	g
72033101	265	164

12749



3K

Scraper with reversible tungsten steel blade

— to remove glue residue and labels from vehicle glass
— can also be used for scraping metal and seals
— with 3-component handle

Product no.	L mm	b mm	g
72313101	460	25	458

12749R

Spare blade

— for scraper No. 12749

Product no.	for model	g
79310001	12749	19

10354



Ratchet strap

— for tightening and securing freshly fitted vehicle glass
— synthetic webbing

Product no.	L m	W mm	Tension force daN	g
74270003	4.5	25	800	310

VALVE AND PISTON TOOLS.

11063



Valve seating-ring pliers

— for pulling off the valve seal and for removing the valve spring seat
— joint and jaws made of hardened steel plate, gunmetal finish
— handles made of shaped sheet metal, nickel-plated

Product no.	L mm	g
74290001	250	340

11063/1



Valve seating-ring pliers

— for pulling off recessed valve seals, e.g. for four-valve engines
— joint and jaws made of hardened steel plate, gunmetal finish
— handles made of shaped sheet metal, nickel-plated

Product no.	L mm	g
74290002	270	345

12108



Valve spring assembly tool

— with interchangeable hooks and lower bracket
— suitable for almost all passenger car engines, usually without cylinder head detachment

Product no.	Content pcs.	g
74570001	8	780

11068




Piston ring tensioners

— made of special spring-band steel
— with infinitely variable settings
— with hex L-Key for clamping

Product no.	Size	L mm	H mm	g
74140000	0	80	50	106
74140001	1	110	80	230
74140003	2	110	80	270
74140005	3	166	165	603

11069



Piston ring pliers

— for inserting and removing piston rings
— bright nickel-plated

Product no.	Size	for piston rings mm	L mm	H mm	g
74152001	1	55-100	200	18	245
74152002	2	80-120	240	20	279
74152003	3	110-160	240	23	394
74152005 [1]	5	60-160	220	16	194

[1] with V-shaped contact faces, for gentle and safe spreading of piston rings

11095-11097



Precision feeler gauges

— tapered blades made of hardened spring steel
— nickel-plated case with locking screw
— tolerance according to T2

Product no.	Model	Sheet thickness mm	Sheet thickness "	L mm	g
74240001	11095/13	0.05; 0.10; 0.15; 0.20; 0.25; 0.30; 0.40; 0.50; 0.60; 0.70; 0.80; 0.90; 1.00	0,002; 0,004; 0,006; 0,008; 0,010; 0,012; 0,016; 0,020; 0,024; 0,028; 0,032; 0,036; 0,040	100	62
74240002	11095/20	0.05; 0.10; 0.15; 0.20; 0.25; 0.30; 0.35; 0.40; 0.45; 0.50; 0.55; 0.60; 0.65; 0.70; 0.75; 0.80; 0.85; 0.90; 0.95; 1.00	0,002; 0,004; 0,006; 0,008; 0,010; 0,012; 0,014; 0,016; 0,018; 0,020; 0,022; 0,024; 0,026; 0,028; 0,030; 0,032; 0,034; 0,036; 0,038; 0,040	100	96
74240005	11097/26	0.03; 0.04; 0.05; 0.06; 0.07; 0.08; 0.09; 0.10; 0.15; 0.20; 0.25; 0.30; 0.35; 0.40; 0.45; 0.50; 0.55; 0.60; 0.65; 0.70; 0.75; 0.80; 0.85; 0.90; 0.95; 1.00	0,0012; 0,0016; 0,002; 0,0024; 0,0028; 0,003; 0,0035; 0,004; 0,006; 0,008; 0,010; 0,012; 0,014; 0,016; 0,018; 0,020; 0,022; 0,024; 0,026; 0,028; 0,030; 0,032; 0,034; 0,036; 0,038; 0,040	100	80


IGNITION AND ELECTRICAL TOOLS.

3466



Spark plug socket

— long version, with magnet
— hex with AS-Drive profile
— $^3/_8$" internal square drive
— HPQ® high performance steel, chrome-plated




Product no.	mm	"	d_1 mm	d_2 mm	d_3 mm	t_1 mm	t_2 mm	L mm	g
02140036	16	$^5/_8$	21.8	25.5	15	7	72.9	85	180

4600



Spark plug socket

— long version, with rubber insert
— bi-hex with AS-Drive profile
— $^3/_8$" internal square drive
— HPQ® high performance steel, chrome-plated




Product no.	mm	"	d_1 mm	d_2 mm	t_1 mm	t_2 mm	L mm	g
02120036	16	$^5/_8$	21.7	19.5	15	47.8	60	84

4606



Spark plug socket

— long version, with rubber insert
— hex with AS-Drive profile
— $^3/_8$" internal square drive
— HPQ® high performance steel, chrome-plated



Product no.	mm	"	d_1 mm	d_2 mm	t_1 mm	t_2 mm	L mm	g
02130018	18	$^{11}/_{16}$	24.2	22	18	52.8	65	132


MADE IN CRONENBERG
MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

46



Spark plug socket
- long version, with rubber insert
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	"	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	L mm	g
02020208	208	13/16	27.2	25	-	18	-	65	151

51



Spark plug sockets
- long version, with rubber insert
- bi-hex with AS-Drive profile
- 1/2" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709 / ASME B 107.5M




Product no.	mm	"	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	L mm	g
03020216	16	5/8	22.4	23.7	15.4	19	64.5	83	137
03020208	208	13/16	27.7	26	20	22	66.2	83	194

51S



Spark plug socket
- long version, with rubber insert
- for spark plugs and wheel nuts on Japanese cars
- hex with AS-Drive profile
- 1/2" internal square drive
- HPQ® high performance steel, chrome-plated
- DIN 3124 / ISO 2725-1 / DIN EN 3710 / DIN EN 3709



Product no.	mm	"	d1 mm	d2 mm	d3 mm	t1 mm	t2 mm	L mm	g
03240208	208	13/16	27.7	26	20	22	66.2	83	196

5100



Rubber insert
- for 20.8 mm (No. 46; 51; 51S)

Product no.	Internal ∅ mm	External ∅ mm	L mm	g
09010001	11	20	25	6

3047



Uniflex sockets
- extra long design, with flexible joint
- hex
- 3/8" internal square drive
- e. g. for hard-to-reach glow plugs

Product no.	mm	L mm	g
02180010	10	140	138
02180012	12	140	138

12372



Brake caliper brush
- narrow version
- brass wire, thickness 0.25 mm, corrugated
- plastic grip with hanging hole
- extremely strong bristles for very high brushing performance
- universal use
- Made in Germany

Product no.	L mm	g
77440002	225	70

12373



Brake caliper brush
- narrow version
- steel wire, thickness 0.35 mm, smooth
- plastic grip with hanging hole
- extremely strong bristles for very high brushing performance
- universal use
- Made in Germany

Product no.	L mm	g
77440001	230	65

12375



Spark plug brush
- brass wire, thickness 0.3 mm, corrugated
- 3-rows of wire
- wooden handle
- Made in Germany

Product no.	L mm	g
74160001	150	17




BRAKE AND WHEEL TOOLS.

11700



Ball joint separator
- for quick and reliable pressing out of ball joint pins from track rods and stabilisers
- for car and truck ball joints
- compact model
- body and lever made from tempered steel
- drop-forged, hardened and tempered




Product no.	⬣ mm	w mm	Clear height mm (h)	g
71070000	19	23	20-50	730

11701



Ball joint separator
- for quick and reliable pressing out of ball joint pins from track rods and stabilisers
- for car and truck ball joints
- 2-way adjustable
- body and lever made from tempered steel
- drop-forged, hardened and tempered




Product no.	⬣ mm	w mm	Clear height mm (h)	g
71070001	24	20	12-50	1370

11702




Ball joint separator
- for quick and reliable pressing out of ball joint pins from track rods and stabilisers
- for car and truck ball joints
- 2-way adjustable
- body and lever made from tempered steel
- drop-forged, hardened and tempered




Product no.	⬣ mm	w mm	Clear height mm (h)	g
71070002	24	20	50-80	1740

11703



Ball joint separator
- galvanised
- for heavy trucks, buses and construction vehicles




Product no.	w mm	Clear height mm (h)	max. t	max. torque N·m	g
71070003	27-36	90	10	100	2940

11704



Ball joint separator

— galvanised
— for medium and heavy trucks, buses, construction and special vehicles




Product no.	w mm	Clear height mm (h)	max. t	max. torque N·m	g
71070004	35-45	115	20	200	6500

11708



Ball joint extractors

— galvanised
— for pressing out the ball pins of motor vehicles



Product no.	w mm	b mm	Clear height mm (h)	max. torque N·m	g
71080001	18	37	37	50	285
71080002	23	45	45	120	476
71080004	39	70	80	280	2024

10599/2



Balance weight pliers

— with cutters for cutting and positioning lead weights (also with adhesive films)
— Chrome Alloy Steel, chrome-plated

Product no.	L mm	W mm	g
76294003	245	100	380

10613



Brake spring pliers

— for riveted brake pads
— Chrome Alloy Steel, gloss nickel-plated

Product no.	L mm	g
76413001	210	245

10613/1



Brake spring pliers

— with a movable plate, for riveted and glued brake pads

Product no.	L mm	g
76413021	330	461

34c/35c



Wheel braces

— with forged centre piece, pressed arms and extra-deep forged socket heads
— Chrome Alloy Steel, chrome-plated
— DIN 3119 / ISO 6788

Product no.	mm/"	L mm	g
43030005	24; 27; 32 mm; 3/4" square	400	2058
43030006	17; 19; 22 mm; 1/2" square	400	5020

39



Tyre levers

— suitable for fitting and removing vehicle tyres
— easy to use, robust construction with carefully formed profiles
— with sturdy double-T profile
— Chrome Alloy Steel, chrome-plated

Product no.	Model	L mm	g
74010401	39 Pkw	400	358
74010601	39/1 Lkw	600	897
74010604	39/2 Lkw	600	1184
74010605	39/3 Lkw	600	932

ENGINE AND TRANSMISSION TOOLS.

1015



Oil filter claw

— for loosening oil filters on cars

Product no.	"	h mm	Claw length mm	g
74620002	3/8	65	50	530

3045



Oil filter wrench

— for oil filters
— 14 sided
— with an external hex of 22 mm and a 10 mm dia. bore

Product no.	mm	L mm	g
74370001	74	52	131

1058




Oil service spanner

— bent
— 8 and 10 mm external squares
— for drain plugs on sump, transmission, differential

Product no.		g
44730810		315

12007



Oil filter wrenches
— with adjustable steel strap
— for oil filters and round screws from 80 to 110 mm
— hardened anti-slip cams ensure safety during use

Product no.	Model	L mm	g
76521001 [1]	12007/1	150	226
76521002 [2]	12007/2	240	319

[1] with 1/2" internal square
[2] with lever handle

12005



Strap wrench
— for clamping, loosening and tightening oil filters and sensitive screws/bolts up to a diameter of Ø 200 mm
— suitable for working in tight spaces
— low-wear, non-slip rubber fabric belt
— freely adjustable strap for flexible size coverage
— sturdy grip

Product no.	Model	L mm	Strap width	Strap length	g
76500001	12005	236	22	600	264

12005/1

Rubber fabric strap for strap wrench
— low-wear, non-slip rubber fabric strap

Product no.	for model	Strap width	Strap length	g
79150001	12005	22	600	69

1023



Special ring spanner
— single-ended
— angled shaft
— for bolted joints on injection pumps

Product no.	mm	B mm	H mm	g
41110013	13	60	8	67

1068



Air filter claw
— for truck brake systems

Product no.	"	h mm	Claw length mm	g
74620011	1/2	85	60	925

12705



Mechanics stethoscope
— steel probe
— plastic handle and sound tubes

Product no.	L mm	g
74060001	355	137

12717



Pin wrench
— cranked
— pin spacing 18 mm
— pin diameter 2,9 mm
— for tightening timing belts on 1.6-l diesel engines

Product no.	L mm	g
44700018	140	76


12763



Pull hook for rubber exhaust mountings
— for pulling the rubber eyelets on the exhaust mountings on all cars
— with T-handle, black plastic coated
— chrome-plated

Product no.	L mm	g
74200002	220	118

12975



Fuel hose clamp
— clamp area up to Ø 20 mm
— for clamping off hose lines

Product no.	Area of application	g
74340001	0-20 mm	38

VARIOUS SPECIAL AUTOMOTIVE TOOLS.

11085



Jet reamer set
— for cleaning stubborn deposits and machining residues on the carburettor and air filter systems of e.g. motorcycles/scooters
— reamer Ø: 0.33; 0.4; 0.45; 0.5; 0.6; 0.7; 0.75; 0.8; 0.9; 1.0; 1.1; 1.2; 1.4; 1.6; 1.8; 2.0 mm
— with holder

Product no.	Content pcs.	g
74310001	16	25

12915



Ratchet tap holders
— with two-jaw chuck for fixed clamping of square shanks
— switchable for right and left-hand operation as well as "fixed"
— made completely of steel, chrome-plated

Product no.	Size	Span mm	L mm	g
77390001	1	2.0-5,0	85	180
77390002	2	4.6-8	110	305

10614



Hose clip pliers
— for self-tightening hose clamps
— bright nickel-plated

Product no.	L mm	g
76460000	220	293

10615/1



Hose clip pliers CLIC
— for locking and unlocking CLIC hose clamps
— easy work at a variety of angles thanks to variably adjustable jaws

Product no.	L mm	g
76460013	200	189

10623/1



Hose clip pliers
- with rotating jaws and multiple locking positions
- single-handed operation, even with large clamping range thanks to variable joint
- particularly suitable for 12 and 15 mm wide, large spring-belt hose clamps
- DBGM (German Federal Utility Model)

Product no.	L mm	g
76460012	290	414

10623/2



Hose clip pliers
- with Bowden cable and multiple locking positions
- especially suited for 12 and 15 mm wide spring-belt hose clamps, including those in heating and cooling systems up to a diameter of 42 mm
- practical for use in hard-to-reach places thanks to remote control via Bowden cable (length 610 mm)
- DBGM (German Federal Utility Model)

Product no.	L mm	g
76540001	300	565

10623/2EB

Spare bowden cable
- for No. 10623/2

Product no.	L mm	g
79540001	610	120

10625/2



Hose clip pliers
- for the correct closing of infinitely variable tension clamps without lugs on axle boots
- high grade steel, nickel-plated
- gun metal finished jaws

Product no.	L mm	g
76540003	200	173

10625



Ear clamp pincers
- for mounting 1- and 2-ear clamps on axle boots, radiator and fuel lines
- black painted finish

Product no.	L mm	W mm	g
76540002	225	48	340

12495



Brass punch
- for use on bushings, bearing rings, etc.
- steering pivot pin

Product no.	L mm	Ø mm	g
77130000	200	20	533

TOOLS THAT
... inspire

7756



Automotive voltage tester set
— testing device for automotive electrics and electronics
— 3-48 V
— voltage indicator by 2 LEDs - voltage and positive/negative polarity

Contains 3-pieces:
1 base unit with 1.5 m lead, test tip, integrated punch needle with sliding mechanism
1 crocodile clip
1 claw gripper

Product no.	L mm	W mm	Content pcs.	g
77560002	190	140	3	100

12905



Automotive circuit tester
— for checking the lighting and ignition systems of motor vehicles
— for 6-12 and 24 V
— with pointed probe
— protective cap
— cable with crocodile clip

Product no.	L mm	g
77380001	120	73

KM STW



Kneeling mat
— makes it more comfortable to work in a kneeling position
— with a recess for storing small parts, screws, nuts, etc.
— flexible, chemical-resistant foam mat
— anthracite/yellow, lasered STAHLWILLE logo

Product no.	L mm	W mm	H mm	g
83822520	490	245	30	124




STAHLWILLE

11 Miscellaneous tools

464 **Pipe tools**

466 **Striking and lever tools**

474 **Scraping and deburring tools**

476 **Grinding and cutting tools**

479 **Measuring, marking, testing tools**

481 **Reworking tools**

483 **Inspection tools**

485 **Torches and construction tools**

489 **Workshop accessories**

STAHLWILLE MISCELLANEOUS TOOLS – For the daily challenges.

Work processes are becoming increasingly complex, and special tools are increasingly essential for carrying out service and repair work. Pipe cutters, hook and pick tools, hammers, scrapers and screw extractors are just some of the many problem solvers that STAHLWILLE offers.

SPECIAL



Effective.

STAHLWILLE plastic scrapers made of glass-fibre-reinforced plastic: for damage-free removal of gaskets, seals and residues.

Magnetic.

The STAHLWILLE magnetic pen lifter is the perfect tool for recovering metallic objects in difficult-to-reach spaces. The strong neodymium magnet provides a high adhesion force. The built-in scriber is protected by a cap.

Rescue aid.

The STAHLWILLE screw extractor ensures damage-free extraction of broken screws or threaded bolts. Available in a 6-piece set.



Compact.

Handy wire cutters – ideal for clean cutting of cables, brass, copper and aluminium.

11

High-quality.

The shear blades of the wire cutters are made of stainless steel – one of them has a sawing function (serrated cut). The 2-component handles with finger rest ensure fatigue-free working.

Varied.

A wide range of other problem solvers for the daily challenges at work can be found on the following pages. Naturally in proven STAHLWILLE quality.

PIPE TOOLS.

14000/14002



Pipe cutters RAPID
— to cut steel and stainless steel pipes
— forged body with one cutting wheel
— with a spring-loaded system
— cutting wheel can be changed without additional tools
— colour: silver grey (RAL 9006)

Product no.	⌀ "	⌀ mm	⌀ mm	Cutting depth max. mm	L mm	Cutting wheel	g
60030000	1/8-1 1/4	3-32	10-42	5.5	265	1	1113
60030002	1/8-2	3-50	10-63	7	400	1	1975

14001/14003



Pipe cutters RAPID
— to cut steel and stainless steel pipes
— forged body with three cutting wheels
— with a spring-loaded system
— cutting wheel can be changed without additional tools
— colour: silver grey (RAL 9006)

Product no.	⌀ "	⌀ mm	⌀ mm	Cutting depth max. mm	L mm	Cutting wheel	g
60030001	1/8-1 1/4	3-32	6-43	5.5	265	3	1166
60030003	1/8-2	3-50	10-63	7	400	3	2149

14100



Pipe cutter COMPACT
— for cutting aluminium, copper and thin-walled steel pipes
— die-cast body
— with a cutting wheel
— with a spare cutting wheel in the rotary knob
— cutting wheel can be changed without additional tools
— with four guided rollers
— including deburring blades
— colour: silver grey (RAL 9006)

Product no.	⌀ "	⌀ mm	Cutting depth max. mm	L mm	Cutting wheel	g
60031000	1/8-1 3/8	3-35	2.5	160	1	356

14200



Pipe cutter MINI
— for copper, brass, and light metal pipes, as well as for hard plastic and thin-walled steel pipes
— colour: silver grey (RAL 9006)

Product no.	⌀ "	⌀ mm	Cutting depth max. mm	L mm	Cutting wheel	g
60032000	1/8-5/8	3-16	2	55	1	102

14300



Chain pipe cutter
— infinitely adjustable
— with rotary handle
— also suitable for stainless steel pipes up to 1.8 mm wall thickness
— chain length 270 mm

Product no.	⌀ mm	Cutting depth max. mm	⌀ "	L mm	W mm	g
60033000	25-75	2	1/8-1 1/4	240	85	665

14050-14051



Shim rings

— to convert pipe cutters from 1 to 3 cutting wheels, for example, for work on laid pipes
— for pipe cutters No. 14000 ($^1/_8$-1 $^1/_4$"): 2 cutting wheels No. 14010 ($^1/_8$-1 $^1/_4$"), 2 shim rings
— for pipe cutter No. 14002 ($^1/_8$-2"): 2 cutting wheels No. 14011 ($^1/_8$-2"), 2 shim rings

Product no.	for model	Ø mm	g
69135000	14000; 14001	13	8
69135001	14002; 14003	14	4

14060



Spare chain

— for chain pipe cutter

Product no.	for model	g
69136000	14300	188

14020-14021



Guide rollers

— for RAPID pipe cutter

Product no.	for model	W mm	Ø mm	g
69132000	14000; 14001	21	23	38
69132001	14002; 14003	27	28	115

14012



Cutting wheel

— for MINI pipe cutter

Product no.	for model	∅ mm	g
69131002	14200	20	5

14030-14031



Cutting wheel spindles

— for RAPID pipe cutter

Product no.	for model	L mm	g
69133000	14000; 14001	30	10
69133001	14002; 14003	37	20

14032



Cutting wheel spindle

— for MINI and COMPACT pipe cutters

Product no.	for model	L mm	g
69133002	14100; 14200	18	4

14040-14041



Roller spindles

— for RAPID pipe cutter

Product no.	for model	L mm	g
69134000	14000; 14001	39	10
69134001	14002; 14003	48	24

14010-14011




Cutting wheels

— for RAPID pipe cutter

Product no.	for model	∅ mm	Bore (mm)	g
69131000	14000; 14001	25	7.6	15
69131001	14002; 14003	31	9	30

STRIKING AND LEVER TOOLS.

13000-13003 155 mm



Hook tools
— for assembly and removal of small parts
— high hardness values (50-55 HRC)
— with 3-component handle

Product no.	Model	Version	L mm	g
77101000	13000	straight	155	22
77101001	13001	45°	155	22
77101002	13002	90°	155	22
77101003	13003	rounded	155	24

13000-13003 250 mm



Hook tools
— extra long design
— for assembly and removal of small parts
— high hardness values (50-55 HRC)
— with 3-component handle

Product no.	Model	Version	L mm	g
77101100	13000	straight	250	48
77101101	13001	45°	250	48
77101102	13002	90°	250	50
77101103	13003	rounded	250	50

13000-13003/4 155 mm



Hook and pick set
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 4-pieces:
4 hook tools **No. 13000-13003**: straight, 45°; 90°; rounded

Product no.	Content pcs.	g
96722802	4	144

13000-13003/4 250 mm



Hook and pick set
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 4-pieces:
4 hook tools **No. 13000-13003**: straight, 45°; 90°; rounded


Product no.	Content pcs.	g
96722803	4	174

13009



Split-pin puller
— for gentle removal of cotter pins and springs
— high hardness values (50-55 HRC)
— with 3-component handle

Product no.	L mm	g
77101010	265	138



Soft and hard-faced hammers
Explanation of the table headings

L_1 = Overall length
L_2 = Head length
Striking surface (Ø mm) = Head diameter

10955



Plastic hammers
— with interchangeable heads made of impact-resistant cellulose acetate
— with ash shaft

Product no.	Ø mm	Hardness (Shore)	L_1 mm	L_2 mm	g
70160027	27	65	265	90	235
70160032	32	65	280	100	320
70160035	35	65	290	105	376
70160040	40	65	320	110	545
70160050	50	65	340	115	873

10955R



Spare heads for plastic hammers
— made of impact-resistant cellulose acetate
— warm up the head and tap it into position

Product no.	for model	Ø mm	Hardness (Shore)	g
79040027	10955 27	27	65	14
79040032	10955 32	32	65	22
79040035	10955 35	35	65	29
79040040	10955 40	40	65	39
79040050	10955 50	50	65	69

10958



Embossing hammer
— aluminium head
— cylindrical
— with hickory shaft

Product no.	Ø mm	L_1 mm	L_2 mm	g
70240040	40	340	155	648

10940



Rubber composite mallets
— tough rubber head with a hardness of approx. 90 Shore A
— with ash shaft
— according to DIN 5128-90

Product no.	Ø mm	Hardness (Shore)	L_1 mm	L_2 mm	g
70140001	55	90	320	90	317
70140002	65	90	350	115	527
70140003	75	90	350	130	780
70140004	90	90	380	140	1220

10956



Nylon hammers
— with interchangeable heads made of impact-resistant nylon VESTAMID®
— with hickory shaft

Product no.	Ø mm	Hardness (Shore)	L_1 mm	L_2 mm	g
70171027	27	75	265	90	232
70171032	32	75	280	100	336
70171035	35	75	290	105	413
70171040	40	75	320	110	546
70171050	50	75	340	115	865
70171060	60	75	380	135	1339

10956R



Spare heads for nylon hammers

— made of impact-resistant nylon VESTAMID®
— warm up the head and tap it into position

Product no.	for model	Ø mm	Hardness (Shore)	g
79050027	10956 27	27	75	11
79050032	10956 32	32	75	18
79050035	10956 35	35	75	23
79050040	10956 40	40	75	31
79050050	10956 50	50	75	53
79050060	10956 60	60	75	83

10959



Dead blow hammers

— with steel shot in the head to prevent recoil
— with interchangeable heads made of medium-hard polyurethane
— with hickory shaft

Product no.	Ø mm	Hardness (Shore)	L_1 mm	L_2 mm	g
70190130	30	73	330	110	460
70191035	35	73	335	110	580
70190140	40	73	355	115	760
70191050	50	73	365	120	1250
70191060	60	73	360	145	1900

10959R



Spare heads for dead blow hammers

— made of medium-hard polyurethane

Product no.	for model	Ø mm	Hardness (Shore)	g
79091030	10959 30	30	73	19
79091035	10959 35	35	73	26
79091040	10959 40	40	73	38
79091050	10959 50	50	73	72
79091060	10959 60	60	73	118

10961



Engineer's hammers

— steel overstrike sleeve for optimum protection against misses
— ergonomically shaped shaft made of hickory wood
— painted handle end ensures a better grip
— DIN 1041

Product no.	Head weight g	L_1 mm	L_2 mm	g
70110009	200	280	95	254
70110010	300	300	105	400
70110011	500	320	118	600
70110013	800	350	130	951
70110015	1,000	360	135	1132
70110016	1,500	380	145	1617
70110017	2,000	400	155	2285

10970



Engineer's hammers

— with ash shaft

Product no.	Head weight lb.	L_1 mm	L_2 mm	g
70120001	1/4	270	67	176
70120005	1/2	290	82	320
70120006	3/4	310	93	454
70120002	1	320	99	572
70120004	1 1/2	350	118	790
70120003	2	380	126	1045

10962



Lump hammers

— steel overstrike sleeve for optimum protection against misses
— ergonomically shaped shaft made of hickory wood
— painted handle end ensures a better grip
— DIN 6475

Product no.	Head weight g	L_1 mm	L_2 mm	g
70111010	1,000	260	95	1410
70111015	1,250	260	100	1660
70111020	1,500	280	110	1910

100



Ribbed cold chisels

— Chrome Alloy Steel, chrome-plated

Product no.	L mm	W mm	g
70010006	150	20	165
70010008	200	26	305
70010010	250	30	507
70010012	300	35	807

102



Flat chisels

— flat-oval
— Chrome Alloy Steel, painted silver
— DIN 6453

Product no.	L mm	W mm	H mm	g
70020002	125	14	9	96
70020003	150	17	11	172
70020004	175	20	12	269
70020005	200	23	13	379
70020007	250	23	13	521
70020008	300	23	13	591

103



Cross-cut chisels

— flat-oval
— Chrome Alloy Steel, painted silver
— DIN 6451

Product no.	L mm	W mm	H mm	g
70040003	150	17	11	147
70040004	175	17	11	239
70040005	200	20	12	340

110



Grooving chisel

— flat-oval
— Chrome Alloy Steel, painted silver

Product no.	L mm	W mm	g
70080001	240	26	298

112



Grooving chisel

— with hand guard
— flat-oval
— Chrome Alloy Steel, painted silver

Product no.	L mm	W mm	g
70080002	240	26	434

112/1



Hand guard

— robust plastic design

Product no.	▭ mm	g
79160001	26 x 7	101

104



Drift punches

— octagonal
— Chrome Alloy Steel, painted silver
— DIN 6458

Product no.	● mm	● mm	L mm	g
70060007	2	10	120	60
70060010	3	10	120	60
70060002	4	10	120	62
70060008	5	10	120	64
70060003	6	10	120	66
70060009	8	12	120	68

105



Centre punches

— octagonal
— Chrome Alloy Steel, painted silver
— DIN 7250

Product no.	● mm	L mm	g
70050001	10	100	52
70050005	10	120	63
70050002	12	120	90

108



Pin punches
— octagonal
— Chrome Alloy Steel, painted silver
— DIN 6450

Product no.	● mm	● mm	L mm	g
70071152	2	8	115	29
70070013	3	8	125	35
70070001	2.5	10	150	65
70070002	3	10	150	62
70070003	4	10	150	64
70070004	5	10	150	67
70070005	6	10	150	72
70070006	8	10	150	81
70070009	3	10	175	57
70070010	4	10	175	64
70070012	6	10	175	69
70070008	8	12	200	141
70070011	10	12	200	159

108/6T



Pin punch set
— Chrome Alloy Steel, painted silver
— DIN 6450
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
6 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6; 8 mm

Product no.	Content pcs.	g
96700703	6	460

MADE IN GERMANY

For more than 160 years, the STAHLWILLE brand has been synonymous with premium tools. From its foundation by Eduard Wille to the present day, our goal has always been the same: to manufacture tools that set the standard and that are 'Made in Germany'.

108/6



Pin punch set
— Chrome Alloy Steel, painted silver
— DIN 6450
— in a plastic stand
Contains 6-pieces:
6 pin punches **No. 108**: Ø 2.5; 3; 4;5; 6; 8 mm

Product no.	Content pcs.	g
96700701	6	450

109



Pin punches
— with guide sleeve

Product no.	● mm	● mm	L mm	g
70090001	0.9	5	70	7
70090002	1.4	6	81	12
70090003	1.8	6	84	12
70090004	2.4	7	92	18
70090005	2.8	7	95	19
70090006	3.4	8	97	25
70090007	3.9	8	100	27
70090008	5.9	9	102	47

102-108/6



Chisel, drift punch, pin punch and centre punch set
— Chrome Alloy Steel, painted silver
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
2 flat chisels **No. 102**: W. 14; 17; L. 125; 150 mm
2 drift punches **No. 104**: Ø 2; 4 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 108**: Ø 4 mm

Product no.	Content pcs.	g
98812203	6	470

TCS 102-108/11



Chisel and punch set
— Chrome Alloy Steel, painted silver
— safely integrated in the modular Tool Control System (TCS)
Contains 11-pieces:
3 flat chisels **No. 102**: W. 17; 23; 23; L. 150; 200; 250 mm
2 centre punches **No. 105**: Ø 10; 12 mm
6 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6; 8 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838754	350	175	33	1/3	11	1665

104-105/6T



Drift punch and centre punch set
— Chrome Alloy Steel, painted silver
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
5 drift punches **No. 104**: Ø 2; 3; 4; 5; 6 mm
1 centre punch **No. 105:** Ø 10 mm

Product no.	Content pcs.	g
96700600	6	466

TOOLS THAT
... inspire

104-5/6



Drift punch and centre punch set
— Chrome Alloy Steel, painted silver
— in a plastic holder
Contains 6-pieces:
5 drift punches **No. 104**: Ø 2; 3; 4; 5; 6 mm
1 centre punch **No. 105**: Ø 10 mm

Product no.	Content pcs.	g
96700601	6	417

105-108/6



Pin punch and centre punch set
— Chrome Alloy Steel, painted silver
— in a plastic stand
Contains 6-pieces:
5 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6 mm
1 centre punch **No. 105**: Ø 10 mm

Product no.	Content pcs.	g
96700712	6	480

105-108/6T



Pin punch and centre punch set
— Chrome Alloy Steel, painted silver
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
5 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6 mm
1 centre punch **No. 105**: Ø 10 mm

Product no.	Content pcs.	g
96700710	6	476

TCS 102-109/10956/10961/6



Punch, chisel and hammer set
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
1 flat chisel **No. 102**: B.20; L. 175 mm
2 pin punches **No. 108**: Ø 6 mm, L. 150; 175 mm
1 pin punch **No. 109**: Ø 3.4 mm
1 nylon hammer **No. 10956**: Ø 35 mm
1 engineer's hammer **No. 10961**: 500 g

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838181	350	175	40	1/3	6	1605

TCS 102-108/10961/10



Punch, chisel and hammer set
— safely integrated in the modular Tool Control System (TCS)
Contains 10-pieces:
1 flat chisel **No. 102**: W. 23; L. 200 mm
1 centre punch **No. 105**: Ø 10 mm
1 pin punch **No. 108**: Ø2 mm
4 pin punches **No. 108**: Ø 3; 4; 5; 6 mm
1 pin punch **No. 108**: Ø 4 mm
1 pin punch **No. 108**: Ø 8 mm
1 engineer's hammer **No. 10961**: 500g

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830361	350	175	40	1/3	10	1569

TCS 102-108/10956/10960/18



Punch, chisel and hammer set
— safely integrated in the modular Tool Control System (TCS)
Contains 18-pieces:
1 wire brush **No. 12374**: L. 290 mm
1 safety knife (cutter) **No. 12965**: L. 174 mm
1 flat chisel **No. 102**: W. 17; L. 150 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
6 pin punches **No. 108**: Ø 2.5; 3; 4; 5; 6; 8 mm
1 nylon hammer **No. 10956**: Ø 50 mm
2 engineer's hammers **No. 10961**: 300; 500 g
1 glass scraper **No. 10356**: L. 165 mm
1 triangular special scraper **No. 10670**: L. 285 mm
1 flat scraper **No. 10672**: W. 20; L. 315 mm
1 caliper **No. 12900**: measuring range: 150 mm/6"

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830620	350	530	55	3/3	18	3653

TCS 102-108/10959/10961/12718/13



Punch, chisel and hammer set
— safely integrated in the modular Tool Control System (TCS)
Contains 13-pieces:
2 flat chisels **No. 102**: W. 23; 23; L. 200; 300 mm
1 cross-cut chisel **No. 103**: W. 17; L. 150 mm
1 centre punch **No. 105**: Ø 10 mm
5 pin punches **No. 108**: Ø 3; 4; 5; 6; 8 mm
2 engineer's hammers **No. 10961**: 500; 800 g
1 dead blow hammer **No. 10959**: Ø 40 mm
1 gasket scraper **No. 12718**: L. 265 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96830223	350	530	40	3/3	13	4452

TCS 10956/10961/2



Hammer set

— safely integrated in the modular Tool Control System (TCS)

Contains 2-pieces:

1 engineer's hammer **No. 10961**: 500 g

1 nylon hammer **No. 10956**: Ø 32 mm

Product no.	L mm	W mm	H mm	Size	Content pcs.	g
96838194	350	175	45	1/3	2	1130



SCRAPING AND DEBURRING TOOLS.

10757



Four-sided bradawl
— to pre-punch and mill leather, plastic, and other soft materials, such as wood
— for easy starting of wood screws
— with 3-component handle

Product no.	Version	L mm	Blade mm	g
77593000	nickel-plated blade	215	6 x 100	137

10758



Round awls
— to pre-punch leather, plastic, and other soft materials, such as wood
— for easy starting of wood screws
— with 3-component handle

Product no.	Version	L mm	Blade mm	g
77592000	matt chrome-plated blade	215	6 x 100	82
77592001	matt chrome-plated blade	280	6 x 175	104

10669



Fine scraper
— 3-edged hollow profile scraper blades with a black plastic protective cap
— blade made of chromium-alloyed tool steel
— black plastic handle

Product no.	L mm	W mm	H mm	Blade mm	g
72060100	147	20	15	25 x 8	28

10670



Triangular special scrapers
— blade made of chromium-alloyed tool steel
— with 3-component handle

Product no.	L mm	W mm	H mm	g
72063101	210	34	34	106
72063103	260	34	34	124
72063104	285	34	34	140
72063105	310	34	34	152

10672



Flat scrapers
— Chrome Alloy Steel blade
— with 3-component handle

Product no.	Dimensions mm	L mm	W mm	H mm	g
72053104	20 x 315 x 5	315	20	34	227
72053105	25 x 365 x 5	365	25	34	367

10676



Triangular bearing scraper
— Chrome Alloy Steel blade
— with 3-component handle

Product no.	L mm	W mm	H mm	g
72083103	315	12	85	160



10677-10681



Plastic scrapers
— fiberglass reinforced plastic
— for damage-free removal of seals, sealants, and residues (especially in the aerospace sector)
— high visibility bright green

Product no.	Model	L mm	Blade shape	b mm	g
72060200	10677	170	wide	32	28
72060201	10678	170	medium width	22	26
72060202	10679	170	narrow	13	26
72060203	10680	174	slanted	32	24
72060204	10681	175	sharp	6	24

10682/5



Plastic scraper set
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 5-pieces:
5 plastic scrapers **No. 10677-10681**: wide, medium, narrow, angled, pointed blade

Product no.	L mm	W mm	H mm	Content pcs.	g
96722700	205	105	40	5	240

10356



Glass scraper
— for removing residues of adhesive and stickers from glass
— with a 0.3 mm thick interchangeable blade, and a protective cap

Product no.	L mm	W mm	g
74270005	165	40	85

10356R



Spare blades
— 10-pieces in a magazine

Product no.	for model	L mm	W mm	H mm	Content pcs.	g
79270015	10356	61	40	3	10	52

12374



Steel wire brushes
— steel wire bristles, thickness 0.35 mm, smooth
— beechwood brush body
— with 2 hanging holes at end of handle, front, and side
— PEFC standard certified
— Made in Germany

Product no.	Model	Stock mm	L mm	Rows	g
77090001	12374/1	140	290	3	100
77090000	12374/2	140	290	4	129
77090003	12374/3	140	285	5	148

12376



Gas stove brush
— brass bristles, thickness 0.25 mm, corrugated
— 2 rows of bristles
— wooden brush body
— PEFC standard certified
— Made in Germany

Product no.	Stock mm	L mm	Rows	g
77090101	90	200	2	46

12377



Wire brush
— with brass coated steel bristles

Product no.	L mm	g
77090010	270	140

13115



Brass wire brush
— for working on soft, light metal
— brass wire bristles, thickness 0.3 mm, corrugated
— 4 rows of bristles
— wooden brush body
— with hanging hole at the end of the handle
— PEFC standard certified
— Made in Germany

Product no.	L mm	Rows	g
77470001	280	4	134

12378



File brush
— with scratch tape
— wooden brush body
— PEFC standard certified
— Made in Germany

Product no.	L mm	g
77250000	260	74

GRINDING AND CUTTING TOOLS.


12025



3K

Round file
— Cut 2
— with 3-component handle
— DIN 8349

Product no.	L mm	Blade length mm	g
72123100	300	190	118



12030



3K

Half round file
— Cut 2
— with 3-component handle
— DIN 8349

Product no.	L mm	Blade length mm	g
72133100	380	260	339

12035



3K

Triangular file
— Cut 2
— with 3-component handle
— DIN 8349

Product no.	L mm	Blade length mm	g
72143100	310	200	201

12036



3K

Flat file
— Cut 2
— with 3-component handle
— DIN 8349

Product no.	L mm	Blade length mm	g
72173102	380	260	305

12371



3K

Brake caliper file
— to remove brake dust, rust, and dirt from the brake pad (disc brakes)
— with 3-component handle

Product no.	L mm	Blade length mm	g
74543101	270	155	130

12800



Warding file set
— for deburring, finishing, fitting, and repair work
— DIN 7283
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
1 file each: triangular, round, half-round, square, flat blunt, flat pointed: blade length: 100 mm

Product no.	L mm	Content pcs.	g
72230001	100	6	165

13100



Needle file set
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo
Contains 6-pieces:
1 file each: round, half-round, triangular, square, flat blunt, flat pointed

Product no.	L mm	Content pcs.	g
96722801	140	6	50

12050



Hacksaw
— die-cast aluminium body
— grey powder-coated grip with anti-slip protection
— the saw blade is clamped using a wing nut
— 300 mm/12" HSS bi-metal saw blade

Product no.	L mm	Tooth density	g
72211000	450	24 TPI	464

12050 R

Spare hacksaw blades for No. 12050
— 10-pieces
— HSS bi-metal saw blade

Product no.	L mm	Tooth density	g
79180001	300	24 TPI	174

12053



Hacksaw
— chromium-alloyed tool steel
— with fiberglass reinforced plastic handle
— saw blade 150 mm

Product no.	L mm	Tooth density	g
72210002	252	32 TPI	159

12053 R

Spare hacksaw blades for No. 12053
— 6-pieces
— chromium-alloyed tool steel

Product no.	L mm	Tooth density	g
79180002	158	32 TPI	20

12000



Thread restorers
— for restoring internal and external threads
— sand-blasted design

Product no.	Model	L mm	g
72101002	12000/WW	230	122
72101003	12000/SAE	230	118
72101004	12000/ISO	230	115

ISO		Ww		SAE/USS
Pitch mm	metr. thread	threads per inch	Whitworth thread	threads per inch
0,80	5	24	3/16 + 7/32	24
1,00	6 + 7	20	1/4	20
1,25	8 + 9	18	5/16	18
1,50	10 + 11	16	3/8	16
1,75	12	14	7/16	14
2,00	14 + 16	12	1/2 + 9/16	13
2,50	18, 20, 22	11	5/8 + 11/16	12
3,00	24 + 27	10	3/4 + 13/16	11

13155



2K

All-purpose scissors

— scissor blades made from titanium-plated stainless steel
— clamp protection from stop buffers
— ideal for thin sheet metal, plastics, leather, cardboard, etc.
— with 2-component handles

Product no.	L mm	g
75271000	237	180

6630



Cable shears

— for copper and aluminium cables
— simple, clean cut with one-handed operation
— special cutting geometry prevents pressure marks, and frayed ends
— adjustable joint
— with anti-squeeze protection
— not suitable for steel or armoured cables

Product no.	L mm	g
66305220	220	290

13148



2K

Wire cutters

— stainless steel scissor blades, 1 blade with serrated edge
— stop buffers offer clamp protection
— with 2-component handles

Product no.	L mm	g
75270003	150	93

12320



Cable knife

— stainless blade with wire stripper

Product no.	L mm	Blade mm	g
77020000	111	90	78

12965



Safety knife

— suitable for cutting cardboard, rubber, leather, wood, etc.
— adjustable blade length using sliding button
— spare blades can be stored in the handle
— blade change without additional tools
— body made of zinc casting
— with hanging hole

Product no.	L mm	g
77621001	174	200

12965-1



Automatic safety knife

— suitable for cutting cardboard, rubber, leather, wood, etc.
— with automatic blade retraction
— spare blades can be stored in the handle
— blade change without additional tools
— body made of zinc casting
— with hanging hole

Product no.	L mm	g
77621002	174	197

12965R



Spare blades

— for safety and automatic knives
— 5-pieces

Product no.	for model	L mm	g
79250001	12965, 12965-1	61	25

12965-2



Snap-off blade cutter
— suitable for cutting cardboard, rubber, leather, wood, etc.
— with 3 snap-off blades (1 blade mounted, 2 blades in magazine)
— slider with blade lock
— with blade breaker and protective cap
— with stainless steel sliding guide
— body made of zinc casting

Product no.	L mm	b mm	g
77621003	145	9	60

12965-2R



Snap-off blades
— 10-pieces

Product no.	for model	L mm	b mm	g
79251003	12965-2	104	9	26

12965-3



Snap-off blade cutter
— suitable for cutting cardboard, rubber, leather, wood, etc.
— with 3 snap-off blades (1 blade mounted, 2 blades in magazine)
— slider with blade lock
— automatic blade reload
— with a stainless steel blade guide and a hanging hole
— ergonomic design with synthetic rubber insert
— body made of zinc casting

Product no.	L mm	b mm	g
77621004	168	18	249

12965-3R



Snap-off blades
— 10-pieces

Product no.	for model	L mm	b mm	g
79251004	12965-3	117	18	75

12967



Stripping knife with hooked blade
— for round and longitudinal cuts of the outer insulation of the cable
— precise, fast and secure stripping of all common round cables
— infinitely variable cutting depth adjustment prevents damage to the internal wires

Product no.	Ø mm min.	Ø mm max.	g
77620010	4	28	82



12967R

Spare blades
— for stripping knife with hooked blade

Product no.	for model	L mm	g
79250010	12967	112	2

MEASURING, MARKING, TESTING TOOLS.

12321



Scriber
— with a knurled body
— 1 straight and 1 angled blade
— blades with gun metal finish

Product no.	L mm	g
77100000	250	31

12322



Tungsten carbide scriber
— straight
— sturdy shank with carbide tip
— re-grindable
— holder with clip

Product no.	L mm	g
77100001	150	40

10554



EURO voltage tester
— design according to EN standard
— tested in accordance with the current VDE-GS standard
— with plastic handle and clip
— AC 100-250 V

Product no.	L mm	W mm	g
77450001	190	3.5	37

13110



Steel ruler
— metric-inch scales

Product no.	L mm	H mm	Divisions top edge "	Division bottom edge mm	g
77460001	300	1	1/16, 1/32, 1/64	0.5; 1	26

13112 2M



Folding ruler
— accuracy class III
— dual scales
— folding mechanism made of hardened steel
— dirt-resistant spring rod joint for high tension
— 90° angle lock on all links
— dual 180° display on each link
— water-resistant, scratch-resistant
— CE mark
— glass-fibre reinforced special plastic, painted black

Product no.	L m	W mm	H mm	g
77470003	2	36	16	105

12935



Tape measures
— with lock
— metric-inch scales

Product no.	L m	g
77040010	3	92
77040011	5	164

12900/4



Electronic tyre-tread caliper
— large LCD with excellent readability, digit height 9.5 mm
— display accuracy 0.01 mm/0.0005"
— on/off button
— unit of measure can be switched between mm/inch
— zeroing possible in any position
— incl. 1 x 3 V battery (type CR2032) packaged according to UN 3091, class 9

Product no.	Measuring range mm/"	g
77371005	25/1	60

12900/3



Tyre-tread caliper
— vernier 0.1 mm
— brass

Product no.	L mm	Measuring range mm	g
77371004	100	0-30	41

12900/1



Calipers digital
— with metal casing cover and metal push buttons
— mechanical parts in stainless, hardened steel
— including thumb wheel for the user to fit if required
— large LCD with excellent readability, digit height 9 mm
— display accuracy 0.01 mm/0.0005"
— fine-ground and lapped measuring tips
— on/off button
— with depth gauge
— unit of measure in mm or inch, zero position at any position
— incl. 2 x 3 V battery (type CR2032) packaged according to UN 3091, class 9
— in a sturdy plastic case

Product no.	L mm	Measuring range mm/"	g
77371002	250	150/6	312
91050002 *	250	150/6	302

* 91050002 version as 77371002, but without battery **(no hazardous goods)**

12900



Caliper
— metric-inch scales
— made of stainless steel
— vernier $^{1}/_{20}$ mm and $^{1}/_{128}$"
— delivered in a pouch
— DIN 862

Product no.	Measuring range mm/"	g
77371001	150/6	185

12665



Screw pitch gauges
— for 0.25 to 6 mm and 4 to 62 t.p.i (metric/Whitworth threads)

Product no.	Number of blades	g
77270003	52	70

REWORKING TOOLS.

12615



Nut splitters
— galvanised
— mechanical
— for releasing stuck or overtightened nuts up to grade 8
— prevents damage to the thread
— while the spindle is being screwed in, the nut splitter body must be prevented from twisting with a combination wrench
— cutting edge made of high-grade alloy steel

Product no.	Model	for nuts mm	max. torque N·m	g
71250011	12615/1	10-18	40	193
71250012	12615/2	19-27	60	386

900



Screw extractors EXTRACTOR
— extraction tool for removing damaged screws or threaded bolts
— with square drive
— for right-hand threads

Product no.	for screws	L mm	■ mm	■ "	recom-mended drill size	g
71010001	M3-M4 $^{1}/_{8}$-$^{5}/_{32}$"	49	3	$^{1}/_{8}$	2 mm $^{5}/_{64}$"	3
71010002	M5-M7 $^{3}/_{16}$-$^{1}/_{4}$"	54	3.4	$^{9}/_{64}$	3 mm $^{7}/_{64}$"	6
71010003	M8 $^{5}/_{16}$"	59	4.9	$^{3}/_{16}$	5 mm $^{3}/_{16}$"	12
71010004	M10-M12 $^{3}/_{8}$-$^{7}/_{16}$"	65	7	$^{9}/_{32}$	6.4 mm $^{1}/_{4}$"	25
71010005	M14-M16 $^{1}/_{2}$-$^{9}/_{16}$"	88	9	$^{23}/_{64}$	8 mm $^{5}/_{16}$"	50
71010006	M18-M22 $^{5}/_{8}$-$^{3}/_{4}$"	95	12	$^{31}/_{64}$	12 mm $^{15}/_{32}$"	103

900/6T



Screw extractor set EXTRACTOR
— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 6-pieces:
6 screw extractors **No. 900**: M3-M4; M5-M7; M8-M11; M10-M12; M14-M16; M18-M22

Product no.	Content pcs.	g
96710101	6	230

901



Screw extractors
— extraction tool for removing damaged screws or threaded bolts
— with hex drive
— with centre punch and double cutting edge
— suitable for right-hand and left-hand threads

Product no.	for screws	L mm	⬣ mm	⬣ "	recommended drill size	g
71050001	$^{3}/_{16}$-$^{1}/_{4}$" M5-M6	60	6.35	$^{1}/_{4}$	3.2 mm $^{1}/_{8}$"	6
71050002	$^{5}/_{16}$-$^{3}/_{8}$" M8-M10	67	9.5	$^{3}/_{8}$	4.8 mm $^{3}/_{16}$"	16
71050003	$^{7}/_{16}$-$^{1}/_{2}$" M10-M12	75	12.7	$^{1}/_{2}$	6.4 mm $^{1}/_{4}$"	30
71050004	$^{1}/_{2}$-$^{9}/_{16}$" M12-M16	90	15.9	$^{5}/_{8}$	9.5 mm $^{3}/_{8}$"	60
71050005	$^{5}/_{8}$-$^{3}/_{4}$" M16-M20	90	19	$^{3}/_{4}$	11.1 mm $^{7}/_{16}$"	100

901/5T



Screw extractor set

— in a sturdy polyester textile case with hook-and-loop fastener
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 5-pieces:

5 screw extractors **No. 901**: $^{3}/_{16}$-$^{1}/_{4}$" M5-M6; $^{5}/_{16}$-$^{3}/_{8}$" M8-M10; $^{7}/_{16}$-$^{1}/_{2}$" M10-M12; $^{1}/_{2}$-$^{9}/_{16}$" M12-M16; $^{5}/_{8}$-$^{3}/_{4}$" M16-M20

Product no.	Content pcs.	g
96710505	5	248

12915



Ratchet tap holders

— with 2-jaw chuck for fixed clamping of square shanks
— switchable for right and left-hand operation as well as 'fixed'
— made completely of steel, chrome-plate

Product no.	Size	Span mm	for threads	L mm	g
77390001	1	2,0-5,0	M3-M8	85	180
77390002	2	4,6-8	M5-M12	110	305

905/25



Thread extractor set

— M5-M16, $^{3}/_{16}$-$^{5}/_{8}$"
— in a black plastic cassette

Contains 25-pieces:

5 HSS high performance spiral drills (3.2; 4.8; 6.4; 8; 8.7 mm)
5 extraction pins made from special steel size 1-5 for threads M5-M16
5 extraction nuts size 1-5
10 drill bits size 1-10

Product no.	for threads	Content pcs.	g
96713025	M5-M16	25	605



906

Spare parts

— 1 extraction pin and 1 extraction nut each packaged in a plastic bag

Product no.	Model	for model	for threads	g
71310001	906/1	905/25	M5-M6 $^{3}/_{16}$-$^{1}/_{4}$"	5
71310002	906/2	905/25	M7-M8 $^{1}/_{4}$-$^{5}/_{16}$"	10
71310003	906/3	905/25	M10 $^{3}/_{8}$"	33
71310004	906/4	905/25	M12 $^{7}/_{16}$"	46

INSPECTION TOOLS.

12920N



Telescopic mirror
— extendable, non-twisting telescopic pole with folding mirror
— ball joint (swivels 180°), self-clamping
— ergonomically shaped non-slip handle

Product no.	Mirror dimensions mm	L mm	W mm	H mm	g
77401001	65 x 43	310-750	43	35	65

12920N R1



Replacement mirror

Product no.	for model	Mirror dimensions mm	g
79401001	12920N	65 x 43	39

12921M



Telescopic stainless steel mirrors
— unbreakable stainless steel mirrors (FOD-prevention)
— no screw connections (FOD-prevention)
— stainless steel telescopic arm
— ball joint (swivels 180°), self-clamping
— special chemical resistant plastic handle allows for firm grip and safe working

Product no.	Mirror dimensions mm	L mm	g
77401032	Ø 32	171-699	60
77401045	45 x 70	178-927	76
77401057	Ø 57	178-921	70
77402550	25 x 50	178-914	59

12921N



Telescopic mirrors
— extendable, non-twisting telescopic pole with folding mirror
— ball joint (swivels 180°), self-clamping
— ergonomically shaped non-slip handle

Product no.	Mirror dimensions mm	L mm	g
77401030	Ø 30	265-705	108
77401040	Ø 40	275-715	115
77401050	Ø 50	285-725	110
77401060	Ø 60	295-735	130

12921NR



Replacement mirrors

Product no.	for model	Mirror dimensions mm	g
79401030	12921N 30	Ø 30	10
79401040	12921N 40	Ø 40	15
79401050	12921N 50	Ø 50	20
79401060	12921N 60	Ø 60	27

13120N



Telescopic mirror
— with lighting (LED) and batteries (approx. 150 hours of light)
— for inspection of hard to reach joints
— the LED light source is removable and can be used separately as a penlight
— mirror with 5x magnification
— with a non-rotating oval telescopic rod

Product no.	Mirror dimensions mm	L mm	g
77480002	Ø 55	310-750	235

13120R



Replacement concave mirror

Product no.	for model	Mirror dimensions mm	g
79401055	13120N	Ø 55	22

12600



Magnetic lifters

— flexible magnetic lifter with ergonomically shaped handle
— for use in the workshop, industry, and household
— enables the recovery of nuts, bolts, and other small metallic parts from tight spaces

Product no.	Lifting capacity g	L mm	Ø mm	g
77260027 [1]	270	500	5	30
77260025	500	460	8	70
77260060	1800	525	15	230
77260200	3000	535	19	297

[1] Mini magnet lifter with extremely small yet very powerful head

12601

Pen magnet lifter

— enables the recovery of nuts, bolts, and other small metallic parts from tight spaces
— telescopic extension increases the possible applications
— strong neodymium magnet with impressive lifting capacity
— made of high-quality galvanised brass
— the clip allows the magnetic lifter to be attached to shirt pockets, for example
— the built-in scriber is protected by a cap

Product no.	Lifting capacity g	L mm	Ø mm	g
77260026	500	150 - 660	6	26

650 MS



Magnetic tray

— easy attachment with rubberised magnetic base
— for bolts, nails, bits, and other small metallic parts
— chrome-plated steel
— resistant to water as well as weak acids and alkalis

Product no.	H mm	Ø mm	g
90432779	22	108	190

12922



Claw lifters

— flexible body with ergonomically shaped handle
— for use in the workshop, industry, and household
— enables the recovery of nuts, bolts, and other small parts from tight spaces

Product no.	L mm	Ø mm	g
77401103	540	6	113
77407203	540	8	148

13130



Tweezers

— straight
— with rounded tips
— fine-toothed jaws
— special steel, stainless

Product no.	L mm	W mm	g
77500001	160	13	26

13131



Tweezers

— curved
— with rounded tips
— fine-toothed jaws
— special steel, stainless

Product no.	L mm	W mm	g
77510001	155	15	30

TORCHES AND CONSTRUCTION TOOLS.

13124



Torch

— Ex-rated for zone 0, 20
— powerful, extremely durable 2 watt LEDs
— sturdy, electrically non-conductive, corrosion-resistant housing made of ABS/polycarbonate
— high impact resistance and reduced glare due to rubberised light head
— consistently bright beam for more than 80% of the life of the alkaline batteries due to eLED electronics
— adjustable beam (narrow and wide) by turning of the head piece
— rubberised front pressure switch for permanent and temporary light
— waterproof to IP68 in water depths up to 3 m
— hydrogen scrubber catalyst, battery contacts with polarity indicator, and a pressure equalisation valve reduce the risk of explosion
— quick change battery compartment for quick battery replacement
— brightness: 165 lm (wide), 122 lm (narrow)
— lighting range: 232 m (wide), 387 m (narrow)
— lighting duration: 5 hours
— batteries: 4 batteries AA/LR06, alkaline, 1.5 V (not included in delivery)
— certifications: SEV 17 ATEX 0158 X, II 1G Ex ia op is IIC T4 Ga, II 1D Ex ia op is IIIC T75°C Da

Product no.	Brightness lm	L mm	W mm	H mm	g
77490010	165, 122	157.5	35.6	40.6	60

13128



Torch

— high-end power LED
— rapid change of the light beam between spot light and flood light by single-handed slide mechanism
— switch with easy-grip profile for switching between continuous light in 2 brightness levels and flashing
— quick change battery holder for quick replacement of batteries
— brightness: 320 lm
— lighting range: 260 m
— lighting duration: up to 50 hours
— batteries: 4 AAA/LR03 micro-batteries, 1.5 V (not included)
— CE and UKCA certified

Product no.	Brightness lm	L mm	W mm	H mm	g
77490006	320	130	37	37	250

13126-2



Penlight

— Ex-rated for zone 1
— powerful, extremely durable LEDs
— sturdy, electrically non-conductive, corrosion-resistant housing made of ABS/polycarbonate
— high impact resistance and reduced glare due to rubberised light head
— consistently bright beam for more than 80% of the life of the alkaline batteries due to eLED electronics
— rubberised front pressure switch for permanent and temporary light
— easy storage with built-in clip holder close to the lamp head
— waterproof to IP67 in water depths up to 1 m
— brightness: 40 lm
— lighting range: 67 m
— lighting duration: 2.5 hours
— batteries: 2 micro-batteries AAA/LR03, alkaline, 1.5 V (not included)
— certifications: II 2G Ex ib IIB T4 Gb, II 2D Ex ib IIIC T60 °C Db, SEV 11 ATEX 0174 X

Product no.	Brightness lm	L mm	W mm	H mm	g
77490012	40	132	22	24	55

13126-3



Headlamp

— Ex-proof for zones 0, 1, 2, 21, 22
— waterproof design for use in all weather conditions
— 3 selectable beam shapes: spot, scatter light and red scatter light
— 3 switchable power levels
— large switch can also be operated with thick gloves
— the LED lamp module is removable and can be used as a portable work light
— swivel button to adjust beam angle - no flimsy hinge
— with adjustable elastic textile strap
— durable, high-impact ABS/polycarbonate design
— waterproof to IP68 in water depths up to 10 m
— brightness/lighting duration: 250 lm at 3.7 h, 130 lm at 9.3 h, 60 lm at more than 30 h
— lighting range: 71/47/30 m (white), 15/10/6 m (red)
— permissible operating temperature range: -20 °C to +40 °C
— batteries: 3 batteries AAA/LR03, alkaline, 1.5 V (not included)
— certifications: SEV 21 ATEX 0528 X, II 1G Ex ia IIC T4 Ga, II 2D Ex ia IIIC T55°C Db

Product no.	Brightness lm	L mm	W mm	H mm	g
77490013	250, 130, 60	76	38	45	81

13132



Torch

— handy, compact design
— high-performance reflector system
— brightness: 130 lm
— lighting range: 75 m
— lighting duration: up to 4 h
— sturdy aircraft-grade aluminium body
— with practical clip
— protection class: IP54
— incl. 2 AAA 1.5 V batteries

Product no.	Brightness lm	L mm	Ø mm	g
77490014	130	138	15	55.5

13134



Work light

— compact design
— 4.5 W COB-LED
— adjustable brightness with 3 brightness levels: short-term boost (500 lm) / 100% (300 lm) / 30% (100 lm)
— lighting duration/brightness: 1.5 hours (300 lm) / 3 hours (100 lm)
— lighting range: max. 26 m
— rechargeable via USB-C connection
— charging time approx. 2.5 h
— integrated Li-ion battery 3.7 V/600 mah/2.22 Wh
— charging indicator light
— with carabiner for attaching to belts or bags
— for fastening to metal surfaces with holding magnet and magnetic base
— water and impact-proof housing
— protection class: IK07/IPX3
— accessories: USB-C charging cable (100 cm)

Product no.	Brightness lm	L mm	W mm	H mm	g
77490016	500	21	12	89	35

13136 SL



Penlight

— handy, compact version
— adjustable brightness with 3 brightness levels: short-term boost (850 lm) / 100 % (500 lm) / 50 % (250 lm)
— optimal focusing with the rotatable head
— lighting duration/brightness: 1.5 h (500 lm) / 3 h (250 lm)
— lighting range: max. 64 m
— rechargeable via USB-C connection
— charging time: approx. 2 h
— integrated Li-ion battery 3.7 V/720 mAh/2.664 Wh
— with charging indicator light
— with practical clip
— robust aluminium body
— protection class: IK05/IP65
— accessories: USB-C charging cable (100 cm)

Product no.	Brightness lm	L mm	Ø mm	g
77490017	850, 500, 250	148	19,5	72

13137 KL




Headlamp

— adjustable brightness with 3 brightness levels and additional spot: 100 % (450 lm) / 25 % (110 lm) / 8 lm / spot (60 lm)
— lighting duration/brightness: 1.5 h (450 lm) / 4 h (110 lm) / 12 h (8 lm) / 9.5 h (60 lm)
— lighting range: max. 45 m
— lighting duration: up to 9.5 hours
— rechargeable via USB-C connection
— charging time: approx. 2.5 h
— integrated Li-ion battery 3.7 V/1,200 mAH/4.44 Wh
— with charge control, battery status, charging and warning indicator
— with practical sensor control
— protection class: IP20
— accessories: USB-C charging cable (100 cm)

Product no.	Brightness lm	L mm	W mm	H mm	g
77490018	450, 110, 60	320	32	27	99,5

STAHLWILLE CORDLESS SPOTLIGHTS –
For more safety and comfort.

13133






Flexible.

The 180° fully adjustable handle can also be used as a sturdy stand for precise illumination of the work area. The magnetic holder enables secure attachment to metal surfaces. The spotlight can also be hung by a rotatable hook.



Strong.


The powerful LED spotlight achieves a luminosity of up to 2,800 lumens, adjustable in three brightness levels:
100 % / 50 % / 25 %.



Customised.

Our spotlight is suitable for both indoor and outdoor use. Its shock-resistant housing with rubberised edges is dust and water spray resistant (IP64 certified).

13133



Work spotlight

— practical light source for home, hobby, trade, or industry
— 30 W COB-LED
— adjustable lighting modes with 3 brightness levels: 100% (2,800 lm) / 50% (1,400 lm) / 25% (700 lm)
— lighting time/brightness: 3 h (2,800 lm) / 7 h (1,400 lm) / 13 h (700 lm)
— lighting range: max. 61 m
— rechargeable via USB-C connection
— charging time: approx. 8 h
— integrated Li-ion battery 3.7 V/6,600 mAh/24.42 Wh with safety electronics
— with charge control and battery status indicator
— 180° adjustable handle/carry handle
— the magnetic holder enables secure attachment to metal surfaces.
— swivel hook for hanging
— suitable for indoor and outdoor use (IP64 certified)
— compact and flat storage

Product no.	Brightness lm	L mm	W mm	H mm	g
77490015	2800, 1400, 700	129	177	44	700

13138 HL



Hand lamp

— adjustable brightness with 2 brightness levels: 100 % (1,000 lm) / 50 % (380 lm)
— additional top LED with 180 lm
— lighting duration/brightness: 2.5 h (1,000 lm) / 4.5 h (380 lm) / 7 h (180 lm)
— lighting range: max. 60 m
— lighting duration: up to 7 h
— rechargeable via USB-C connection
— charging time: approx. 4 h
— integrated Li-ion battery 3.7 V/2,600 mAh/9.62 Wh
— with charge control and battery status indicator
— for attachment to metal surfaces with integrated magnets
— 2 hooks rotatable through 360° for hanging
— protection class: IK07/IP54
— accessories: USB-C charging cable (100 cm)

Product no.	Brightness lm	L mm	W mm	H mm	g
77490019	1000, 380	266	48	32	340

13139 DL





Duo work spotlight

— 2 fold-out 36 W SMD LED modules (can be swivelled and rotated 180°)
— adjustable brightness with 3 brightness levels: 100% (11,500 lm) / 50% (5,750 lm) / 20% (2,000 lm)
— lighting duration/brightness: 1.5 h (11,500 lm) / 3 h (5,750 lm) / 6 h (2,000 lm)
— lighting range: max. 21 m
— switch for changing light colours: 4,000K (3,500 lm in mains operation), 6,500K (3,700 lm in mains operation)
— lighting duration: up to 6 h
— dual power supply with mains and battery operation
— rechargeable via USB-A connection
— charging time: approx. 3 h
— integrated Li-ion battery pack 14.8 V/4,000 mAh/29.6 Wh with safety electronics
— with power bank function
— charging control, warning and remaining capacity display
— height-adjustable tripod: 1,171–1,980 mm, with handle, cable reel and ground spikes
— removable light head with 2 rotating hooks and 4 holding magnets
— protection class: IK07/IPX4
— accessory: power supply unit with 5 m cable

Product no.	Brightness lm	variable height mm	g
77490020	11.500/ 5.750/ 2.000	max. 1980	5960



245

VBW



Beton hooks
— suitable for fixing plasterboards to wall pillars, etc.
— with fixed strap
— forged, hardened tip
— galvanised
— storage in a bucket

Product no.	L mm	W mm	Content pcs.	g
87245005	150	85	150	170
87245006	150	115	100	210
87245010	210	85	100	210
87245011	210	115	50	250
87245012	340	160	50	540

2450

VBW



Beton hooks
— suitable for fixing plasterboards to wall pillars, etc.
— with moveable strap
— forged, hardened tip
— galvanised
— storage in a bucket

Product no.	L mm	W mm	Content pcs.	g
87245015	150	85	150	170
87245016	150	115	100	210
87245020	210	85	100	210
87245021	210	115	50	250
87245022	340	160	50	540

246

VBW



Cord pins
— suitable for tensioning strings to achieve straight cuts in tiling and paving work
— forged, hardened tip
— galvanised
— storage in a bucket

Product no.	L mm	Content pcs.	kg
87246005	150	300	29
87246010	340	200	34

12481



Putty knife
— beech wood handle

Product no.	L mm	W mm	g
77070000	212	60	65

WORKSHOP ACCESSORIES.

12251



Oil can
— made of plastic

Product no.	Capacity	g
77110002	0.25	60

12250



Oil spray can
— made of metal
— with brass pump

Product no.	Capacity	g
77010001	0.5	275



12 VDE tools



494 **VDE tool assortments and sets**

496 **VDE spanners**

497 **VDE drive parts**

499 **VDE sockets**

500 **VDE screwdrivers**

504 **VDE pliers**

506 **VDE workshop equipment and storage**

STAHLWILLE VDE TOOLS –
Outstanding, even under high voltage.

STAHLWILLE's VDE programme enables safe and efficient work under voltages of up to 1,000 volts. Certified according to strict VDE standard, the tools combine an application-optimised product design, high-quality materials, low tolerances, excellent ergonomics and long service life with durable and long-lasting protective insulation.

SAFE



Reliable.

The insulating plastic sheath of the MANOSKOP® 730 VDE provides reliable protection up to 1,000 volts, and is still non-slip, abrasion-resistant and resistant to diluted alkaline solutions, hydrocarbons, fuels and oils.

Adjustable.

Quick adjustment without disassembly – the adjusting screws are quickly and easily accessible using resealable openings. Once adjusted, the tool does not need to be sent in or checked again.

Quick.

Thanks to QuickSelect, the target torque is set in no time at all. It is also extremely accurate, as it can be read off in very precise increments on the secondary fine scale.



Versatile.

The entire STAHLWILLE VDE programme includes more than 130 products. Spanners, fine-tooth ratchets, torque wrenches, pliers and a variety of sockets – individually or neatly stored in the set box or case.

MADE IN CRONENBERG
MADE IN GERMANY

Flexible.

With the MANOSKOP® 730 VDE, the user can change the ratchet insert adaptor (⅜", 9 x 12 mm) without the need for a new dielectric breakdown test!

Wear-resistant.

The low-wear release system with bending beam works without a spring, and therefore does not require the torque wrench to be reset to '0'. This is the guarantee of consistently reliable measurement results, and saves time.

VDE TOOL ASSORTMENTS AND SETS.

13300 VDE



VDE tool set

— basic tool equipment for all electrical work
(for a detailed description of the case, see 13302/TR VDE)

Contains 48-pieces:

14 VDE sockets with bi-hex 3/8" **No. 12171 VDE**: 7; 8; 9; 10; 11; 12; 13; 14; 16; 17; 18; 19; 20; 22 mm
3 VDE screwdriver sockets TORX® 3/8" **No. 12174 VDE**: T20; T25; T30
2 VDE screwdriver sockets XZN® 3/8" **No. 12175 VDE**: M8; M10
3 VDE extensions 3/8" **No. 12167 VDE**: L. 94; 178; 258 mm
1 VDE QuickRelease fine-tooth ratchet 3/8" **No. 12165 VDE**: L. 205 mm
4 VDE slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75; 0.5 x 3.0 x 100; 0.6 x 3.5 x 100; 0.8 x 4.0 x 100 mm
3 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2; PH3
6 VDE TORX® screwdrivers **No. 4675 VDE**: T8; T10; T15; T20; T25; T30
1 VDE combination pliers **No. 6700 VDE**: L. 200 mm
1 VDE telephone pliers **No. 6730 VDE**: L 160 mm
1 VDE telephone pliers **No. 6731 VDE**: L. 200 mm
1 VDE water pump pliers **No. 6551 VDE**: L 250 mm
1 VDE side cutters **No. 6720 VDE**: L. 180 mm
1 VDE cable shears **No. 6630 VDE**: L. 220 mm
1 VDE cable knife **No. 12188 VDE**: Blade l. 40 mm
1 VDE barrier tape **No. 12191 VDE**: L. 500 m
1 VDE warning sign **No. 12192 VDE**
1 VDE prohibition sign **No. 12193 VDE**
5 VDE grommets with clamping cap **No. 12194 VDE**
5 VDE grommets with clamping cap **No. 12195 VDE**
1 VDE tool box, mobile **No. 13302/TR VDE**

Product no.	L mm	W mm	H mm	Content pcs.	kg
96838193	520	450	285	48	12.68

13302/TR VDE



VDE tool box

— smooth-running castors and integrated telescopic handle for convenient transport
— robust ABS case shells
— ergonomically designed carrying handle
— robust aluminium frame with impact edge protection
— 2 lockable flip-locks and a professional combination lock
— variable bottom section (2 aluminium dividers)
— 2 removable tool cards (with 15 and 22 slots)
— separate document compartment in lid
— max. load capacity: 30 kg

Product no.	L mm	W mm	H mm	kg
81620026	520	280	470	7









13215/19 VDE



VDE MultiUse tool set

Key features of the backpack trolley


— sturdy tool backpack with reinforced base
— flexible use as a trolley or a backpack
— with smooth-running castors and telescopic handle for convenient transport
— padded straps for use as a backpack
— 2 easily removable tool cards for easy access to the most frequently used tools
— front pockets for documents and accessories
— padded notebook compartment (up to 15")

Contains 19-pieces:

1 VDE diagonal cutting pliers **No. 6720 VDE**: L 160 mm
1 VDE telephone pliers with cutting edge **No. 6730 VDE**: L. 200 mm
1 VDE wire strippers **No. 6780 VDE**: L 160 mm
1 engineer's hammer **No. 10961**: 300 g
1 grooving chisel **No. 110**: L. 240 mm
4 VDE slotted screwdrivers **No. 4661 VDE:** 0.6 x 3.5 x 100; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
2 VDE PH cross-head screwdrivers **No. 4666 VDE**: PH1; PH2
2 VDE PZ cross-head screwdrivers **No. 4671 VDE**: PZ1; PZ2
5 VDE TORX® screwdrivers **No. 4676 VDE**: T10; T15; T20; T25; T30
1 wooden folding ruler **No. 13112**: L. 2 m

Product no.	L mm	W mm	H mm	Content pcs.	kg
98810303	250	380	520	19	7.24

12171/19/4 VDE



VDE socket set

— in a sturdy, stackable ABS plastic box

Contains 23-pieces:

14 VDE sockets with bi-hex 3/8" **No. 12171 VDE**: 7; 8; 9; 10; 11; 12; 13; 14; 16; 17; 18; 19; 20; 22 mm
3 VDE screwdriver sockets TORX® 3/8" **No. 12174 VDE**: T20; T25; T30
2 VDE screwdriver sockets XZN® 3/8" **No. 12175 VDE**: M8; M10
3 VDE extensions 3/8" **No. 12167 VDE**: L. 94; 178; 258 mm
1 VDE QuickRelease fine-tooth ratchet 3/8" **No. 12165 VDE:** L. 205 mm

Product no.	L mm	W mm	H mm	Content pcs.	kg
96022020	470	274	80	23	3.06

TCS 12171/19/4 VDE



VDE tool set

— safely integrated in the modular Tool Control System (TCS)

Contains 23-pieces:

14 VDE sockets with bi-hex 3/8" **No. 12171 VDE**: 7; 8; 9; 10; 11; 12; 13; 14; 16; 17; 18; 19; 20; 22 mm
3 VDE screwdriver sockets TORX® 3/8" **No. 12174 VDE**: T20; T25; T30
2 VDE screwdriver sockets XZN® 3/8" **No. 12175 VDE**: M8; M10
3 VDE extensions 3/8" **No. 12167 VDE**: L. 94; 178; 258 mm
1 VDE QuickRelease fine-tooth ratchet 3/8" **No. 12165 VDE**: L. 205 mm


Product no.	L mm	W mm	H mm	Division	Content pcs.	kg
96830041	350	350	45	2/3	23	2.1

VDE SPANNERS.

12160 VDE



VDE open-ended spanners
- — **metric** spanner sizes
- — VDE insulated up to 1,000 V
- — protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- — Chrome Alloy Steel, chrome-plated




Product no.	mm	L mm	a mm	b mm	g
44180010	10	140.7	10.5	26	48
44180013	13	166.4	11.5	32.5	80
44180014	14	181	11.5	34.5	88
44180017	17	200	12.5	40	146
44180019	19	218	13	44.5	184
44180022	22	248	13.5	50	254

12161 VDE



VDE single-ended ring spanners
- — **metric** spanner sizes
- — bi-hex with AS-Drive profile
- — VDE insulated up to 1,000 V
- — protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- — Chrome Alloy Steel, chrome-plated



Product no.	mm	L mm	a mm	d mm	g
44190010	10	147.6	13	19.6	48
44190013	13	171.2	15	23.6	82
44190014	14	184.1	15	25.1	82
44190017	17	208.3	17	29.1	144
44190019	19	227.1	18	32	190
44190022	22	254.2	19	36.3	238

TCS 12160 VDE





VDE open-ended spanner set
- — **metric** spanner sizes
- — safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:

6 VDE open-ended spanners **No. 12160 VDE**: 10; 13; 14; 17; 19; 22 mm

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96830042	350	175	30	1/3	6	900

12160/6 VDE



VDE open-ended spanner set
- — **metric** spanner sizes
- — in rugged polyester roll-up tool pouch with hook-and-loop fastener
- — mesh inserts allow visibility of the tools
- — a compact storage solution to keep your tools safe
- — embroidered STAHLWILLE logo

Contains 6-pieces:

6 VDE open-ended spanners **No. 12160 VDE:** 10; 13; 14; 17; 19; 22 mm

Product no.	Content pcs.	g
96404301	6	950



12161/6 VDE




VDE single-ended ring spanner set
— **metric** spanner sizes
— in rugged polyester roll-up tool pouch with hook-and-loop fastener
— mesh inserts allow visibility of the tools
— a compact storage solution to keep your tools safe
— embroidered STAHLWILLE logo

Contains 6-pieces:
6 VDE single-ended ring spanners **No. 12161 VDE**: 10; 13; 14; 17; 19; 22 mm

Product no.	Content pcs.	g
96404302	6	430

TCS 12161 VDE





VDE single-ended ring spanner set
— **metric** spanner sizes
— safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:
6 VDE single-ended ring spanners **No. 12161 VDE**: 10; 13; 14; 17; 19; 22 mm


Product no.	L mm	W mm	H mm	Content pcs.	g
96830045	350	175	40	6	885

VDE DRIVE PARTS.

12165 VDE



VDE QuickRelease fine-tooth ratchet
— $^{3}/_{8}$" external square output
— reversible
— 80 teeth
— with QuickRelease security lock
— with a double insulated plastic shell for work with voltage
— with a working angle of just 4.5°, for working in tight spaces
— FOD-preventive due to screwless design
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— with 2-component handle



Product no.	■ "	L mm	a mm	b mm	∠	g
12430001	$^{3}/_{8}$	197	61	37	4.5 °	298







80 teeth, capable of withstanding 1,000 V.


The $^{3}/_{8}$" VDE fine-tooth ratchet features the compact shape, perfect functionality and ergonomics of STAHLWILLE fine-tooth ratchets and offers optimum voltage protection in accordance with VDE standards.

730R VDE



VDE torque wrenches MANOSKOP®

— tactile dual stop signal
— with $^{3}/_{8}$" ratchet insert (tool holder 9 x 12 mm)
— replace the ratchet adaptor 725QR VDE without having to check the insulation again
— no reset to '0' required, since measuring element is only loaded during tightening
— with QuickRelease safety lock
— fast, precise adjustment with QuickSelect quick adjustment
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— with insulating sleeve made of glass-fibre reinforced polyamide plastic
— the insulation is resistant to many liquids such as alkalis, fuels or oils
— double scale of N·m/ft·lb resp. N·m/in·lb
— low-wear triggering mechanism
— readjustment without disassembly and without checking the insulation again
— calibration certificate in accordance with DIN EN ISO 6789-2:2017
— **accuracy ± 3%**



Product no.	Size	N·m	ft·lb	in·lb	N·m	ft·lb	in·lb	fine scale	L mm	b_1 mm	b_2 mm	h_1 mm	h_2 mm	L_F mm	S_F mm	Weigth kg
96550125	2.5	4-25	-	40-220	2	-	10	0.2 N·m	337	35	45	30	56	253.5	28	1.19
96550150	5	10-50	7-37	-	5	1	-	0.25 N·m	391.5	35	45	30	56	308.5	28	1.37




VDE SOCKETS.

12171 VDE



VDE sockets
- bi-hex with AS-Drive profile
- 3/8" internal square drive
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- HPQ® high performance steel, chrome-plated




Product no.	mm	L mm	d_1 mm	g
02380007	7	42	15,5	24
02380008	8	43	16,7	26
02380009	9	43	18	28
02380010	10	45	19,3	28
02380011	11	45	20,6	29
02380012	12	46	21,9	36
02380013	13	48	23	36
02380014	14	48	24,4	40
02380016	16	49	26,7	48
02380017	17	49	28	54
02380018	18	50	29,2	58
02380019	19	50	30,2	58
02380020	20	52	31,2	68
02380022	22	53	33,7	78

12175 VDE



VDE screwdriver sockets
- for trisquare screws XZN®
- 3/8" internal square drive
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- Chrome Alloy Steel, gun metal finish




Product no.	Size	L mm	∅ (d) mm	g
02370006	M6	136	23	100
02370008	M8	136	23	98
02370010	M10	136	23	122

12174 VDE



VDE screwdriver sockets
- for recessed TORX® screws
- 3/8" internal square drive
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- Chrome Alloy Steel, gun metal finish




Product no.	Size	L mm	∅ (d) mm	g
02390020	T20	67	22,8	52
02390025	T25	67	22,8	52
02390030	T30	67	22,8	54
02390040	T40	67	22,8	56
02390045	T45	67	22,8	58

12167 VDE



VDE extensions
- 3/8" internal square drive
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- Chrome Alloy Steel, chrome-plated



Product no.	Size	■ "	L mm	∅ (d) mm	g
12420001	3	3/8	94	23	84
12420002	6	3/8	178	23	162
12420003	10	3/8	258	23	224

432 VDE



VDE square drive adaptor
- 3/8 to 1/2"
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- HPQ® high performance steel, chrome-plated


Product no.	■ "	L mm	∅ (d) mm	g
12030005	1/2	68	22,6	84

12179 VDE



VDE sockets

— bi-hex with AS-Drive profile
— 1/2" internal square drive
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— HPQ® high performance steel, chrome-plated




Product no.	mm	L mm	d_1 mm	g
03370010	10	56	19,5	60
03370011	11	56	20,8	64
03370012	12	56	22	64
03370013	13	56	23,3	64
03370014	14	56	24,9	70
03370017	17	56	29	82
03370019	19	56	31,2	94
03370022	22	60	34,7	116
03370024	24	60	37	130

12177 VDE



VDE extensions

— 1/2" square drive
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— Chrome Alloy Steel, chrome-plated



Product no.	Size	■ "	L mm	∅ (d) mm	g
13420001	3	1/2	93	27	130
13420002	5	1/2	148	27	206
13420003	10	1/2	273	27	380


VDE SCREWDRIVERS.

4660 VDE



VDE electrician's slotted screwdrivers DRALL+

— for slotted screws
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— gunmetal finished blade tip
— 3-component handle with laser marking
— Chrome Alloy Steel




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
46603025	1	0.4	2.5	75	160	20
46603030	2	0.5	3	100	185	39
46603035	3	0.6	3.5	100	205	42
46603040	4	0.8	4	100	205	46
46603055	5	1.0	5.5	125	240	93
46603065	6	1.2	6.5	150	265	120
46603080	7	1.2	8	175	300	170

4661 VDE



VDE slotted screwdrivers DRALL+

— for slotted screws
— reduced blade diameter to reach deep joints
— blade with integrated protective insulation
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— gunmetal finished blade tip
— 3-component handle with laser marking
— Chrome Alloy Steel




Product no.	Size	a mm	b mm	L_1 mm	L_2 mm	g
46613035	3	0.6	3.5	100	205	51
46613040	4	0.8	4	100	205	55
46613055	5	1.0	5.5	125	240	103
46613065	6	1.5	6.5	150	265	125

4665 VDE



VDE PH cross-head screwdrivers DRALL+

- for PHILLIPS® screws
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- gunmetal finished blade tip
- 3-component handle with laser marking
- Chrome Alloy Steel




Product no.	Size	L_1 mm	L_2 mm	g
46653000	PH0	60	145	35
46653001	PH1	80	185	47
46653002	PH2	100	215	89
46653003	PH3	150	275	159

4670 VDE



VDE PZ cross-head screwdrivers DRALL+

- for POZIDRIV® screws
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- gunmetal finished blade tip
- 3-component handle with laser marking
- Chrome Alloy Steel




Product no.	Size	L_1 mm	L_2 mm	g
46703000	PZ0	60	145	36
46703001	PZ1	80	185	46
46703002	PZ2	100	215	89

4666 VDE



VDE PH cross-head screwdrivers DRALL+

- for PHILLIPS® screws
- reduced blade diameter to reach deep joints
- blade with integrated protective insulation
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- gunmetal finished blade tip
- 3-component handle with laser marking
- Chrome Alloy Steel




Product no.	Size	L_1 mm	L_2 mm	g
46663001	PH1	80	185	55
46663002	PH2	100	215	105

4671 VDE



VDE PZ cross-head screwdrivers DRALL+

- for POZIDRIV® screws
- reduced blade diameter to reach deep joints
- blade with integrated protective insulation
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- gunmetal finished blade tip
- 3-component handle with laser marking
- Chrome Alloy Steel



Product no.	Size	L_1 mm	L_2 mm	g
46713001	PZ1	80	185	44
46713002	PZ2	100	215	55




4675 VDE



VDE TORX® screwdrivers DRALL+

— for recessed TORX® screws
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— gunmetal finished blade tip
— 3-component handle with laser marking
— Chrome Alloy Steel




Product no.	Size	L_1 mm	L_2 mm	g
46753008	T8	60	145	22
46753010	T10	60	145	22
46753015	T15	75	180	40
46753020	T20	100	205	47
46753025	T25	100	205	51
46753030	T30	100	215	89

4676 VDE




VDE TORX® screwdrivers DRALL+

— for recessed TORX® screws
— reduced blade diameter to reach deep joints
— blade with integrated protective insulation
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— gunmetal finished blade tip
— 3-component handle with laser marking
— Chrome Alloy Steel



Product no.	Size	L_1 mm	L_2 mm	g
46763010	T10	100	215	27
46763015	T15	100	205	55
46763020	T20	100	205	55
46763025	T25	125	240	58
46763030	T30	150	265	106

TCS 4676/5 VDE



VDE TORX® screwdriver set DRALL+


— safely integrated in the modular Tool Control System (TCS)

Contains 5-pieces:

5 VDE TORX® screwdrivers **No. 4676 VDE**: T10; T15; T20; T25; T30

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838815	350	175	45	1/3	5	730

TCS 4675 VDE



VDE TORX® screwdriver set DRALL+

— safely integrated in the modular Tool Control System (TCS)

Contains 6-pieces:

6 VDE TORX® screwdrivers **No. 4675 VDE**: T8; T10; T15; T20; T25; T30

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838793	350	175	40	1/3	6	385

VDE certification mark

In the world of tools, the distinctive triangular VDE certification mark signifies compliance with the highest safety requirements in production. It guarantees that any hand tool bearing this mark meets strict electrical, mechanical, and other safety requirements for safe everyday use.


TCS 4665/4670 VDE



VDE screwdriver set DRALL+
— safely integrated in the modular Tool Control System (TCS)
Contains 7-pieces:
4 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH0; PH1; PH2; PH3
3 VDE PZ cross-head screwdrivers **No. 4670 VDE**: PZ0; PZ1; PZ2

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838785	350	175	40	1/3	7	622


TCS 4660/4665 VDE



VDE screwdriver set DRALL+
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
4 VDE slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75; 0.6 x 3.5 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
2 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838766	350	175	40	1/3	6	391

TCS 4661/4671 VDE



VDE screwdriver set DRALL+
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
2 VDE slotted screwdrivers **No. 4661 VDE**: 0.6 x 3.5 x 100; 1.0 x 5.5 x 125 mm
2 VDE PH cross-head screwdrivers **No. 4666 VDE**: PH1; PH2
2 VDE PZ cross-head screwdrivers **No. 4671 VDE**: PZ1; PZ2

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838814	350	175	72	1/3	6	800

TCS 4661/4666 VDE



VDE screwdriver set DRALL+
— safely integrated in the modular Tool Control System (TCS)
Contains 6-pieces:
4 VDE slotted screwdrivers **No. 4661 VDE**: 0.6 x 3.5 x 100; 0.8 x 4.0 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm
2 VDE PH cross-head screwdrivers **No. 4666 VDE**: PH1; PH2

Product no.	L mm	W mm	H mm	Division	Content pcs.	g
96838816	350	175	45	1/3	6	780



4695 VDE



VDE screwdriver set DRALL+

Contains 6-pieces:

4 VDE slotted screwdrivers **No. 4660 VDE**: 0.4 x 2.5 x 75; 0.6 x 3.5 x 100; 1.0 x 5.5 x 125; 1.2 x 6.5 x 150 mm

2 VDE PH cross-head screwdrivers **No. 4665 VDE**: PH1; PH2

Product no.	L mm	W mm	H mm	Content pcs.	g
96469515	350	175	40	6	595

4798 VDE



Set of interchangeable VDE screwdrivers

— automatic locking to prevent unintentional removal

Contains 14-pieces:

1 VDE 2-component reversible handle

1 VDE rotary cap, attachable

6 VDE interchangeable slotted blades: 2.5 x 0.4; 3.0 x 0.5; 3.5 x 0.6; 4.0 x 0.8; 5.5 x 1.0; 6.5 x 1.2 mm

2 VDE interchangeable PH cross-head blades: PH1; PH2

1 VDE interchangeable PZ cross-head blade: PZ2

3 VDE interchangeable TORX® blades: T10; T15; T20

Product no.	L mm	W mm	H mm	Content pcs.	g
96469511	229	134	54	14	814




VDE PLIERS.

6700 VDE



VDE combination pliers

— with fine and coarse serrated gripping area and cutting function
— for gripping, holding and cutting cables as well as soft and hard wire
— drop-forged from tempered steel
— cutting edges with additional induction hardening to approx. 64 HRC
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— chrome-plated
— with 2-component handle
— DIN ISO 5746




Product no.	L mm	L_3 mm	T mm	T_2 mm	W mm	W_3 mm	W_4 mm	g
67004160	160	34	28	10.5	60	24	6	215
67004180	180	38	30	11.5	60	26	7	280
67004200	200	42	31	12.3	63	29	8	345

6730 VDE



VDE telephone pliers

— straight with cutting edge and burner hole
— for gripping, holding and cutting cables as well as soft and hard wire
— with burner hole for holding nuts and stud bolts
— half round, tapered jaws with serrated gripping surfaces
— drop-forged from tempered steel
— cutting edges with additional induction hardening to approx. 64 HRC
— VDE insulated up to 1,000 V
— protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
— chrome-plated
— with 2-component handle
— DIN ISO 5745




Product no.	L mm	L_3 mm	T mm	T_1 mm	T_2 mm	W mm	W_3 mm	W_4 mm	g
67304160	160	47	28	3.5	9.5	54	20	3.5	160
67304200	200	70	29	4	11	58	20	5	200

6731 VDE



VDE telephone pliers

- curved with cutting edge and burner hole
- for gripping, holding and cutting cables as well as soft and hard wire
- with burner hole for holding nuts and stud bolts
- half round, curved jaws with serrated gripping surfaces
- drop-forged from tempered steel
- cutting edges with additional induction hardening to approx. 64 HRC
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- chrome-plated
- with 2-component handle
- DIN ISO 5745




Product no.	L mm	L_3 mm	T mm	T_1 mm	T_2 mm	W mm	W_3 mm	W_4 mm	∠	g
67314160	160	43	28	3.5	9.5	56	18	3.5	45	160
67314200	200	63	43	4	11	58	20	5	45	220

6720 VDE



VDE side cutters

- side cutters with semicircular head for cutting cables, soft and hard wires, including piano wire
- bevelled cutting edges
- drop-forged from tempered steel
- cutting edges with additional induction hardening to approx. 64 HRC
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- chrome-plated
- with 2-component handle
- DIN ISO 5749




Product no.	L mm	L_4 mm	T mm	T_2 mm	W mm	W_3 mm	g
67204140	140	19	29	11	60	20	185
67204160	160	19	30	11	62	22	240
67204180	180	21	32	11.5	63	24	270

6721 VDE



VDE heavy-duty side cutters

- heavy-duty side cutters with compact head for cutting all types of wire
- drop-forged from tempered steel
- cutting edges with additional induction hardening to approx. 64 HRC
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- chrome-plated
- with 2-component handle
- DIN ISO 5749




Product no.	L mm	L_4 mm	T mm	T_2 mm	W mm	W_3 mm	g
67214160	160	16	28	11	62	26	215
67214180	180	21	30	12	64	30	300
67214200	200	20	30	12	64	32	300

6780 VDE



VDE wire stripper

- mechanical wire stripper with set screw and opening spring for easy removal of the insulation from electrical conductors e.g. conventional or stranded wires
- for single, multi-stranded and finely stranded conductors
- drop-forged from tempered steel
- cutting edges also induction hardened to approx. 44 HRC
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- chrome-plated
- with 2-component handle



Product no.	L mm	L_3 mm	T mm	T_2 mm	W mm	W_3 mm	Ø min. mm^2	Ø max. mm^2	g
67804160	160	26	29	9.5	58	18	5	10	190

6551 VDE



VDE water pump pliers
- with a box joint and a recess
- quick adjustment, 7 positions
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- protection against pinch/crush injuries
- chrome-plated
- DIN ISO 8976 (No. 207 C)

Product no.	L mm	Jaw opening max. mm	Positions	g
65517250	240	35	7x	390

6630 VDE



VDE cable shears
- for copper and aluminium cables
- simple, clean cut with one-handed operation
- special cutting geometry prevents pressure points and splintered ends
- adjustable screw joint
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- protection against pinch/crush injuries
- not suitable for steel wire and steel reinforced cables
- chrome-plated

Product no.	L mm	g
66307220	220	380

VDE WORKSHOP EQUIPMENT AND STORAGE.

12187 VDE



VDE cable knife
- with a straight blade
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- handle made of tough, impact-resistant plastic
- with blade protection

Product no.	L mm	Blade mm	g
77020700	215	50	98

12188 VDE



VDE cable knife
- with a hook blade
- for slicing and stripping moisture proof cables
- VDE insulated up to 1,000 V
- protective insulation according to IEC 60900-AC 1,000 V / DC 1,500 V
- handle made of tough, impact-resistant plastic
- with blade protection

Product no.	L mm	Blade mm	g
77020701	210	40	96

12189 VDE



VDE insulating underlay mat
- protection mat for electrical control rooms
- temperature resistance from -30 °C to +70 °C
- non-slip and stable
- one side smooth, one side ribbed
- tested according to IEC 6111 Class 0 / 1,000 V VDE 0680-1:2010-04, DIN EN 61111:2009

Product no.	L mm	W mm	H mm	g
77030700	1000	1000	3	3040

12190 VDE



VDE bag
- for VDE insulating underlay mat
- high-quality textile bag with carrying handle and adjustable shoulder strap

Product no.	L mm	W mm	H mm	g
77030701	1000	300	65	784

12196 VDE



VDE insulating underlay mat in a bag
— protection mat for electrical control rooms
— temperature resistance from -30 °C to +70 °C
— non-slip and stable
— one side smooth, one side ribbed
— high-quality textile bag with carrying handle and adjustable shoulder strap
— tested according to IEC 6111 Class 0 / 1,000 V VDE 0680-1:2010-04, DIN EN 61111:2009

Product no.	L mm	W mm	H mm	kg
96404303	1000	300	3	3.82

12191 VDE



VDE barrier tape
— red/white blocked
— for the cordoning off of hazardous areas
— full warning effect even with prolonged use (light resistance: 5-6)
— made of polyethylene

Product no.	W mm	L m	kg
77030702	80	500	1.36

12192 VDE



VDE warning sign
— warning of dangerous electrical voltage
— made of plastic
— DIN EN ISO 7010-W012

Product no.	W mm	H mm	g
77030705	200	200	27

12193 VDE



VDE prohibitory sign
— 'Do not switch on' warning sign
— made of plastic
— DIN 4844, BGV A8

Product no.	d mm	g
77030706	200	48

12194/12195 VDE



VDE self clamping cable-end cap
— for insulating cable ends and single wires
— made of a tough insulating material
— with cross-section closure

Product no.	d mm	L mm	g
77030708	10	100	10
77030709	20	100	18

TORX® SCREW SIZES ACCORDING TO DIN.



DIN	931/933	912	963/965	964/966	7984	7985	7991	7981	7982	7983
M 2										
ST 2.2										
M 2.5		T8	T8	T8						
ST 2.9								T8	T8	T8
M 3	E4	T10	T10	T10	T10	T10	T10			
M 3.5			T15	T15		T15				
ST 3.5								T10	T10	T10
ST 3.9								T15	T15	T15
M 4	E5	T20	T20	T20	T20	T20	T20			
ST 4.2								T20	T20	T20
ST 4.8								T25	T25	T25
M 5	E6	T25	T25	T25	T25	T25	T25			
ST 5.5								T25	T25	T25
M 6	E8	T30	T30	T30	T30	T30	T30			
ST 6.3								T30	T30	T30
M 7										
M 8	E10	T45	T40	T45	T45	T45	T40			
M 10	E12	T50	T50	T50	T50	T50	T50			
M 12	E14	T55			T55					
M 14	E18	T60			T60					
M 16	E20	T70			T70					
M 18	E24	T80			T80					
M 20	E24	T90			T90					
M 22		T100*								
Camcar Licence sheet	TMF-16001	TMF-17012	TMF-17065	TMF-17066	TMF-17069	TMF-17085	TMF-17091	TMF-17081	TMF-17082	TMF-17083

*Special screw

Screw correlation for TORX® tools

Size	mm	Screws metric	Screws "
T5	1.4	M1.4 – M2	–
T6	1.6	M2	–
T7	2.0	M2.5	2.2
T8	2.3	M2.5	–
T9	2.5	M3	2.9
T10	2.7	M3 – M3.5	–
T15	3.3	M3.5 – M4	3.5
T20	3.8	M4 – M5	4.2
T25	4.4	M4.5 – M5	4.8
T27	5.0	M4.5 – M5 – M6	–
T30	5.5	M6 – M7	–
T40	6.6	M7 – M8	–
T45	7.8	M8 – M10	–
T50	8.8	M10	–
T55	11.2	M12	–
T60	13.2	M14	–
T70	15.5	M16	–
T80	17.6	M18	–
T90	19.9	M20	–
T100	22.1	M22	–

Screw correlation for TORX® tools

Size	mm	Screws metric	Screws "
E4	3.8	M3	2.2 – 2.9
E5	4.7	M4	–
E6	5.7	M5	–
E7	6.2	M6	–
E8	7.5	M6 – M7	3.5 – 4.2
E10	9.4	M8	–
E11	10.1	–	–
E12	11.1	M10	–
E14	12.9	M12	–
E16	14.7	M12	–
E18	16.6	M14	–
E20	18.4	M16	–
E24	22.1	M18 – M20	–

INCH POUND/FOOT POUND – NEWTON METER.

Inch pound (in·lb) – Newton meter (N·m)

	0	10	20	30	40	50	60	70	80	90
in·lb					N·m					
0	0.0	1.1	2.3	3.4	4.5	5.7	6.8	7.9	9.0	10.2
100	11.3	12.4	13.6	14.7	15.8	17.0	18.1	19.2	20.3	21.5
200	22.6	23.7	24.9	26.0	27.1	28.3	29.4	30.5	31.6	32.8
300	33.9	35.0	36.2	37.3	38.4	39.6	40.7	41.8	42.9	44.1
400	45.2	46.3	47.5	48.6	49.7	50.9	52.0	53.1	54.2	55.4
500	56.5	57.6	58.8	59.9	61.0	62.2	63.3	64.4	65.5	66.7
600	67.8	68.9	70.1	71.2	72.3	73.5	74.6	75.7	76.8	78.0
700	79.1	80.2	81.4	82.5	83.6	84.8	85.9	87.0	88.1	89.3
800	90.4	91.5	92.7	93.8	94.9	96.1	97.2	98.3	99.4	100.6
900	101.7	102.8	104.0	105.1	106.2	107.4	108.5	109.6	110.7	111.9
1000	113.0	114.1	115.3	116.4	117.5	118.7	119.8	120.9	122.0	123.2
1100	124.3	125.4	126.6	127.7	128.8	130.0	131.1	132.2	133.3	134.5
1200	135.6	136.7	137.9	139.0	140.1	141.3	142.4	143.5	144.6	145.8
1300	146.9	148.0	149.2	150.3	151.4	152.6	153.7	154.8	155.9	157.1
1400	158.2	159.3	160.5	161.6	162.7	163.9	165.0	166.1	167.2	168.4
1500	169.5	170.6	171.8	172.9	174.0	175.2	176.3	177.4	178.5	179.7
1600	180.8	181.9	183.1	184.2	185.3	186.5	187.6	188.7	189.8	191.0
1700	192.1	193.2	194.4	195.5	196.6	197.8	198.9	200.0	201.1	202.3
1800	203.4	204.5	205.7	206.8	207.9	209.1	210.2	211.3	212.4	213.6
1900	214.7	215.8	217.0	218.1	219.2	220.4	221.5	222.6	223.7	224.9
2000	226.0	227.1	228.3	229.4	230.5	231.7	232.8	233.9	235.0	236.2
2100	237.3	238.4	239.6	240.7	241.8	243.0	244.1	245.2	246.3	247.5
2200	248.6	249.7	250.9	252.0	253.1	254.3	255.4	256.5	257.6	258.8
2300	259.9	261.0	262.2	263.3	264.4	265.6	266.7	267.8	268.9	270.1
2400	271.2	272.3	273.5	274.6	275.7	276.9	278.0	279.1	280.2	281.4
2500	282.5	283.6	284.8	285.9	287.0	288.2	289.3	290.4	291.5	292.7
2600	293.8	294.9	296.1	297.2	298.3	299.5	300.6	301.7	302.8	304.0
2700	305.1	306.2	307.4	308.5	309.6	310.8	311.9	313.0	314.1	315.3
2800	316.4	317.5	318.7	319.8	320.9	322.1	323.2	324.3	325.4	326.6
2900	327.7	328.8	330.0	331.1	332.2	333.4	334.5	335.6	336.7	337.9
3000	339.0	340.1	341.3	342.4	343.5	344.7	345.8	346.9	348.0	349.2
3100	350.3	351.4	352.6	353.7	354.8	356.0	357.1	358.1	359.3	360.5
3200	361.6	362.7	363.9	365.0	366.1	367.3	368.4	369.5	370.6	371.8
3300	372.9	374.0	375.2	376.3	377.4	378.6	379.7	380.8	381.9	383.1
3400	384.2	385.3	386.5	387.6	388.7	389.9	391.0	392.1	393.2	394.4
3500	395.5	396.6	397.8	398.9	400.0	401.2	402.3	403.4	404.5	405.7
3600	406.8	407.9	409.1	410.2	411.3	412.5	413.6	414.7	415.8	417.0

Foot pound (ft·lb) – Newton meter (N·m)

	0	1	2	3	4	5	6	7	8	9
ft·lb					N·m					
0	0.0	1.4	2.7	4.1	5.4	6.8	8.1	9.5	10.9	12.2
10	13.6	14.9	16.3	17.6	19.0	20.3	21.7	23.1	24.4	25.8
20	27.1	28.5	29.8	31.2	32.5	33.9	35.3	36.6	38.0	39.3
30	40.7	42.0	43.4	44.7	46.1	47.5	48.8	50.2	51.5	52.9
40	54.2	55.6	56.9	58.3	59.7	61.0	62.4	63.7	65.1	66.4
50	67.8	69.2	70.5	71.9	73.2	74.6	75.9	77.3	78.6	80.0
60	81.4	82.7	84.1	85.4	86.8	88.1	89.5	90.8	92.2	93.6
70	94.9	96.3	97.6	99.0	100.3	101.7	103.0	104.4	105.8	107.1
80	108.5	109.8	111.2	112.5	113.9	115.3	116.6	118.0	119.3	120.7
90	122.0	123.4	124.7	126.1	127.5	128.8	130.2	131.5	132.9	134.2
100	135.6	136.9	138.3	139.7	141.0	142.4	143.7	145.1	146.4	147.8
110	149.1	150.5	151.9	153.2	154.6	155.9	157.3	158.6	160.0	161.3
120	162.7	164.1	165.4	166.8	168.1	169.5	170.8	172.2	173.6	174.9
130	176.3	177.6	179.0	180.3	181.7	183.0	184.4	185.8	187.1	188.5
140	189.8	191.2	192.5	193.9	195.2	196.6	198.0	199.3	200.7	202.0
150	203.4	204.7	206.1	207.4	208.8	210.2	211.5	212.9	214.2	215.6
160	216.9	218.3	219.6	221.0	222.4	223.7	225.1	226.4	227.8	229.1
170	230.5	231.9	233.2	234.6	235.9	237.3	238.6	240.0	241.3	242.7
180	244.1	245.4	246.8	248.1	249.5	250.8	252.2	253.5	254.9	256.3
190	257.6	259.0	260.3	261.7	263.0	264.4	265.7	267.1	268.5	269.8
200	271.2	272.5	273.9	275.2	276.6	277.9	279.3	280.7	282.0	283.4
210	284.7	286.1	287.4	288.8	290.2	291.5	292.9	294.2	295.6	296.9
220	298.3	299.6	301.0	302.4	303.7	305.1	306.4	307.8	309.1	310.5
230	311.8	313.2	314.6	315.9	317.3	318.6	320.0	321.3	322.7	324.0
240	325.4	326.8	328.1	329.5	330.8	332.2	333.5	334.9	336.2	337.6
250	339.0	340.3	341.7	343.0	344.4	345.7	347.1	348.5	349.8	351.2
260	352.5	353.9	355.2	356.6	357.9	359.3	360.7	362.0	363.4	364.7
270	366.1	367.4	368.8	370.1	371.5	372.9	374.2	375.6	376.9	378.3
280	379.6	381.0	382.3	383.7	385.1	386.4	387.8	389.1	390.5	391.8
290	393.2	394.5	395.9	397.3	398.6	400.0	401.3	402.7	404.0	405.4
300	406.8									

SPANNER AND FASTENER SPECIFICATIONS.

Spanner opening Nominal width across flats		Metric sizes																American sizes								
			Thread diameters															Thread diameters · American standard ANSI								
			DIN ISO 272				ISO R 272 1968		German standard DIN					French standard	Swedish standard				Nuts				Bolts and screws			
Minimum dimension mm[1]	Maximum dimension mm[1]	Nominal size of wrench, mm	Standard hex	Large hex	Screw with flange	Nut with flange	Normal hex	Small hex	Normal hex[2]	Large hex[3]	Small hex[4]	Screw with flange[5]	Nut with flange[6]	NFE 27-111-1930[9]	Metric, large[8] SMS 1412	Metric, small[8] SMS 1414	Whitworth, large[8] SMS 1413	Whitworth, small[8] SMS 1415	Nominal Size of Wrench	**a** Normal (No)	**b** Square (No)	**c** Heavy (No)	**d** Machine Screw Nuts (No)	**e** Normal (No)	**f** Heavy (No)	**g** Machine Screws (No)	**h** Square Head Set Screws (No)
3.22	3.28	**3.2**	1.6				1.6		1.6																		
3.23	3.35																		**1/8**							1·2·3	
3.52	3.60	**3.5**																									
4.01	4.14													2.5					**5/32**				0·1			
4.02	4.12	**4**	2				2		2							2.3											
4.52	4.62	**4.5**														2.6											
4.83	4.95																		**3/16**				2·3			3·4·5	10
5.02	5.12	**5**	2.5				2.5		2.5					3		3											
5.21	5.33																		**13/64**								
5.52	5.62	**5.5**	3				3		3																		
5.59	5.72																		**7/32**								
6.00	6.13																		**15/64**								
6.03	6.15	**6**							3.5					3.5	3	3.5											
6.40	6.53																		**1/4**				4			6·8	1/4
6.82	6.97																		**17/64**								
7.03	7.15	**7**	4		5		4		4					4·4.5	3.5	4											
7.19	7.32																		**9/32**					10*			
7.62	7.77																		**19/64**								
8.03	8.18																		**5/16**				5·6			10·12	5/16
8.03	8.15	**8**	5		6	5	5		5		6	5	5	5	4	5											
8.41	8.56																		**21/64**								
8.81	8.97																		**11/32**				8				
9.03	9.15	**9**							(5)[7]					5.5	5												
9.60	9.75																		**3/8**				10	1/4*		1/4	3/8
10.04	10.19	**10**	6		8	6	6		6		8	6	6	6		6											
10.39	10.55																		**13/32**								
11.04	11.19	**11**	7				7		7						6	7		1/4									
11.18	11.33																		**7/16**	1/4	1/4		12·1/4	1/4			7/16
11.99	12.14																		**15/32**								
12.04	12.24	**12**						8						7		8											
12.80	12.95																		**1/2**	5/16		1/4		5/16		5/16	1/2
13.04	13.24	**13**	8		10	8	8		8		10	8	8				1/4	5/16									
13.60	13.77																		**17/32**								
14.05	14.27	**14**						10	(8)[7]					8	8												
14.38	14.55																		**9/16**	3/8	5/16	5/16	5/16	3/8		3/8	9/16
15.05	15.27	**15**			12	10						10	10			10	5/16	3/8									
15.18	15.36																		**19/32**								
15.98	16.15																		**5/8**		3/18		3/8	7/16			5/8
16.05	16.27	**16**	10	ZK:M10 M14					10		12	12		9													
16.77	16.95																		**21/32**								
17.05	17.30	**17**					10	12	(10)		(12)			10	10												
17.58	17.75																		**11/16**	7/16		3/8					
18.05	18.30	**18**	12	ZK:M12	14	12			12		16	14	12			12	3/8	7/16									
19.06	19.36	**19**					12	14	(12)		(16)			11													
19.18	19.38																		**3/4**	1/2	7/16	7/16		1/2			3/4
19.97	20.17																		**25/32**								
20.06	20.36	**20**																									
20.78	20.98																		**13/16**	1/2			9/16				
20.86	21.16	**20.8**		ZK:M14 M18																							
21.06	21.36	**21**	14	12	16	14			14	12		16	14	12		14	7/16	1/2									
22.06	22.36	**22**					14	16	(14)	12					12·14												
22.35	22.56																		**7/8**	9/16		1/2			1/2		7/8
23.06	23.36	**23**												14			1/2										
23.98	24.21																		**15/16**	5/8		9/16		5/8			
24.06	24.36	**24**	16	14		16	16	18	16		20		16			16		5/8									
24.76	24.99																		**31/32**								
25.06	25.36	**25**																									
25.55	25.78																		**1**		5/8						1
26.08	26.48	**26**		ZK:M18										16													
27.08	27.48	**27**	18	16	20		18	20	18	16		20			16	18											
27.13	27.36																		**1 1/16**			5/8			5/8		
28.08	28.48	**28**															5/8	3/4									
28.75	29.01																		**1 1/8**	3/4	3/4			3/4			1 1/8
29.08	29.48	**29**												18													
30.08	30.48	**30**	20	18		20	20	22	20		24		20			20											
30.34	30.59																		**1 3/16**								
31.93	32.18																		**1 1/4**			3/4			3/4		1 1/4
32.08	32.48	**32**					22	24	(22)	20				20	18·20	22											
33.08	33.48	**33**															3/4	7/8									
33.53	33.81																		**1 5/16**	7/8	7/8			7/8			
34.08	34.48	**34**	22	20					22	20						24											
35.10	35.60	**35**												22													
35.13	35.41																		**1 3/8**								1 3/8
36.10	36.60	**36**	24	22			24	27	24	22	30				22·24												

Spanner opening SW		Metric sizes																American sizes								
			Thread diameters															Thread diameters · American standard ANSI								
			DIN ISO 272				ISO R 272 1968		German standard DIN					French standard	Swedish standard				Nuts				Bolts and screws			
Minimum dimension mm[1]	Maximum dimension mm[1]	Nominal size of wrench, mm	Standard hex	Large hex	Screw with flange	Nut with flange	Normal hex	Small hex	Normal hex[2]	Large hex[3]	Small hex[4]	Screw with flange[5]	Nut with flange[6]	NFE 27-111-1930[8]	Metric, large[8] SMS 1412	Metric, small[8] SMS 1414	Whitworth, large[8] SMS 1413	Whitworth, small[8] SMS 1415	Nominal Size of Wrench	**a** Normal (No)	**b** Square (No)	**c** Heavy (No)	**d** Machine Screw Nuts (No)	**e** Normal (No)	**f** Heavy (No)	**g** Machine Screws (No)	**h** Square Head Set Screws (No)
36.73	37.01																		1 7/16			7/8			7/8		
37.10	37.60	37															7/8	1"								
38.10	38.60	38												24												
38.30	38.61																		1 1/2	1"	1"			1"			1 1/2
39.89	40.20																		1 9/16								
41.10	41.60	41	27	24			27	30	27	24					27												
41.50	41.81																		1 5/8			1"			1"		
42.10	42.60	42												27			1"	1 1/8								
42.67	42.93																										
43.08	43.38																		1 11/16	1 1/8	1 1/8			1 1/8			
44.70	45.03																		1 3/4								
46.10	46.60	46	30	27			30	33	30	27	36			30	30												
46.28	46.61																		1 13/16			1 1/8			1 1/8		
47.10	47.60	47															1 1/8	1 1/4								
47.88	48.21																		1 7/8	1 1/4	1 1/4			1 1/4			
50.10	50.60	50	33	30			33	36	33	30				33	33												
51.08	51.44																		2"			1 1/4			1 1/4		
52.10	52.60	52															1 1/4	1 3/8								
52.68	53.04																		2 1/16	1 3/8	1 3/8			1 3/8			
54.12	54.72	54												36													
54.25	54.61																		2 1/8								
55.12	55.72	55	36	33			36	39	36		42				36												
55.88	56.26																		2 3/16			1 3/8			1 3/8		
56.12	56.72	56															1 3/8	1 1/2								
57.45	57.84																		2 1/4	1 1/2	1 1/2			1 1/2			
58.12	58.72	58												39													
60.12	60.72	60	39	36			39		39	36					39		1 1/2	1 5/8								
60.66	61.06																		2 3/8			1 1/2			1 1/2		
62.23	62.64																		2 7/16								
63.12	63.72	63												42													
63.83	64.24																		2 1/2								
65.12	65.72	65	42	39			42		42		48				42		1 5/8	1 3/4								
65.43	65.86																		2 9/16			1 5/8					
67.03	67.46																		2 5/8					1 3/4			
67.12	67.72	67												45													
70.12	70.72	70	45				45		45						45		1 3/4	1 7/8								
70.26	70.69																		2 3/4			1 3/4			1 3/4		
71.12	71.72	71												48													
71.81	72.26																		2 13/16								
75.03	75.51																		2 15/16			1 7/8					
75.15	75.85	75	48				48		48		56				48		1 7/8	2"								
76.61	77.09																		3"					2"			
77.15	77.85	77												52													
79.81	80.31																		3 1/8			2"			2"		
80.15	80.85	80	52				52		52						52		2"										
82.15	82.85	82												56													
85.15	85.85	85	56				56		56																		
86.18	86.72																		3 3/8					2 1/4			
88.15	88.85	88												60													
89.36	89.92																		3 1/2			2 1/4			2 1/4		
90.15	90.85	90	60				60		60																		
94.15	94.85	94												64													
95.15	95.85	95	64				64		64																		
95.76	96.34																		3 3/4					2 1/2			
98.93	99.52																		3 7/8			2 1/2			2 1/2		
100.15	100.85	100	68				68		68					68													
105.20	106.00	105	72				72		72					72													
105.33	105.97																		4 1/8					2 3/4			
108.51	109.14																		4 1/4			2 3/4			2 3/4		
110.20	111.00	110	76				76		76					76													
114.91	115.57																		4 1/2					3"			
115.20	116.00	115	80				80		80																		
116.20	117.00	116												80													
118.08	118.77																		4 5/8			3"			3"		
120.20	121.00	120	85				85		85																		

ASME/ANSI B 18.2.2–1987

[1] Maximum and minimum dimensions for metric sizes according to DIN 475/2 series 1 and ISO 691 (machined tolerances), American sizes according to ANSI B 18.2.1 + ASME/ANSI B 18.2.2

[2] DIN ISO 4014, 4016, 4017, 4018, 4032, 4034, 4035, 4036, 8673, 8674, 8675, 8676, 8765, sizes in brackets only DIN 439, 555, 558, 601, 609, 610, 917, 931, 933, 934, 935, 936, 937, 960, 961, 979, 980, 985, 986, 1587, 2510/5, 6330, 6331, 7967, 7968, 79900

[3] DIN 6914, 6915, 7999 (SW 21 + 34)

[4] DIN 561, 564

[5] DIN 6921, 6922

[6] DIN 6923, 6926, 6927

[7] Standards prior to 1963

[8] old standards

[a] Hex Flat and Hex Flat Jam Nuts
Hex Nuts and Hex Jam Nuts
Hex Slotted Nuts
Hex Thick Nuts
Hex Thick Slotted Nuts
Hex Castle Nuts

[b] Square Nuts

[c] Heavy Square Nuts
Heavy Hex Flat Nuts
Heavy Hex Flat Jam Nuts
Heavy Hex Nuts
Heavy Hex Jam Nuts
Heavy Hex Slotted Nuts

ANSI B 18.2.1–1981

[d] ANSI B 18.6.3 – 1972

[e] Square Bolts
Hex Bolts
Hex Cap Screws
Lag Screws

[f] Heavy Hex Bolts
Heavy Hex Structural Bolts
Heavy Hex Screws

[g] ANSI B 18.6.3 – 1972 (R 1983)

[h] ANSI B 18.6.2 – 1972 (R 1983)

* Square Bolt and Lag Screws only

SP = Spark Plug

Alphabetical index

A

ABC pipe wrench set X-GRIP® **405**
ABC pipe wrenches X-GRIP® **404–405**
ABS assembly sleeve KABELEX® **436**
Adaptor laptop holder **290**
Adaptor parts **104, 154–155, 179, 198–199, 215, 218–219, 232, 235, 237, 499**
Adaptors **75, 155, 180, 277**
Adjustable hook spanners **139**
Adjustable open-ended spanner set **135**
Adjustable open-ended spanners **134–135**
Adjustable spanners **134–135**
Adjusting screws **417–418**
Adjusting spanners **134–135**
Aerospace basic set **358**
Air filter claw **456**
All-purpose scissors **478**
Angle gauges **48**
Angle of rotation tester **84**
AOG kit for aircraft (imperial) in toll trolley No. 13217 **366**
AOG kit for aircraft in tool trolley No. 13217 **364**
Audi accessory kit **335**
Automatic calibration and adjustment system **96**
Automatic safety knife **478**
Automotive circuit tester **459**
Automotive voltage tester set **459**
Awl **474**

B

Backpack trolley **293**
Bags **53, 292, 295, 506**
Balance weight pliers **454**
Ball joint extractor **453–454**
Ball joint separator **453–454**
Ball joints **232, 235, 237**
Ball-ended L-Key set **263**
Barrier tape **507**
Basic aircraft mechanics set **358**
Battery **48**
Battery terminal puller **429**
Beton hooks **489**
Bicycle tool kit **55**
Bike tool set **55**
Bit adaptors **237, 274**
Bit boxes **267–268**
Bit connectors **237, 274**
Bit fine-tooth mini ratchet **272**
Bit fine-tooth ratchet **272**
Bit holder insert tools **64, 68**
Bit holders **270, 274–275**
Bit magazines **267–268**
Bit quick-change holder **273**
Bit ratchet insert tool **60**
Bit ratchet screwdriver set **269**
Bit ratchet screwdrivers **273**
Bit ratchet set **269**
Bit ratchet spare part sets **78, 272–273**
Bit ratchets **270, 273**
Bit sets **267–269**
Blades **475, 478–479**
Blank end insert tools **64, 68, 70**
Bluetooth Low Energy module 714 **48**
Body file holder **444**
Body hammers **441–442**
Body spoon **444**
Bolt and mesh cutters **418–419**
Bolt cutters **414–419**
Bolt cutters CombiCUT®, compact **416**
Bolt cutters LightCUT® **414**
Bolt cutters UNIBOLT® **415**
Bolt cutters WAGGONIT® **415**
Bolt cutters with interchangeable blades **417**
Bolt cutters/corner deep cutters SolutionCUT **417**
Bolt end cutters **415**
Bolt end cutters CombiCUT®, small **416**
Bolt offset cutters LightCUT® **414**
Bolt shears **414–417**
Box spanner sets **139**
Box spanners **138–139**
Boxes **53, 292–294**
Bracket for spanner **299**
Brackets **102, 299**
Braiding pliers **406–408**
Brake caliper brush **452**
Brake caliper file **476**
Brake spring pliers **454**
Brass punch **458**
Brass wire brush **476**
Brushes **452, 475–476**
Bumping spoons **442–443**

C

Cable **49, 50**
Cable extractor tools KABELEX® **436–438**
Cable holder **289**
Cable knife **478**
Cable shears **478, 506**
Calibration accessory set **102**
Calibration square drives **105**
Calibration square insert tools **105**
Calibration systems **92–96, 99–100, 102**
Calibration systems, calibration equipments **92–96, 99–100, 102**
Calibrations **81**
Calipers **480–481**
Carpet knives **478–479**
Central gear **77**
Central wheel **77**
Centre cutters **414–417**
Centre punches **469**
Chain pipe cutters **464**
Chain pipe wrenches **405**
Charging dock for batteries **49**
Chassis **294**
Chisel, centre punch and pin punch set **471**
Chisel, drift punch, pin punch and centre punch set **470**
Chisels **469**
Circlip pliers **408–410, 420**
Circlip pliers for external circlips **409–410, 420**
Circlip pliers for internal circlips **408-409, 420**
Circlip pliers set **420**
Circlips **232, 235, 237**
Clamping pliers **410–411**
Claw lifter **484**
CLIC hose clamp pliers **457**
Combination pliers **394, 504**
Combination ratchet spanner sets **127–130, 374**
Combination ratchet spanners **127–130, 374**
Combination spanner sets **115–117, 119–120, 373**
Combination spanners **114–120, 373**
Connection adaptors **277**
Connector pliers (siphon pliers) **406**
Construction machinery set **357**
Container **299**
Control cabinet spanners **221**
Cord pins **489**
Corner pipe wrenches **401, 404**
Corner pipe wrenches 45° **404**
Cotter pin extractor **470**
Counter stays **430**
Cover inlay **293**
Covers **289, 296**
Crimping pliers **397**
Cross-cut chisels **469**
Crowfoot spanners **72–74**
Crowring spanners **72–73**
Cutters **394–397, 411–413, 478–479, 504–505**
Cutter heads complete with screw and eccentric screws **419**
Cutter heads screw set **420**
Cutter heads **414–420**
Cutter heads complete with bolts and retaining rings **416–417**
Cutter heads complete with screws **414–419**
Cutting pliers **394–397, 411–417, 504–505**
Cutting wheel spindles **465**
Cutting wheels **465**
Cutting wire **448**

D

DAkkS calibrations **81**
Dead blow hammers **467–468**
Digital caliper **480**
Digital torque wrenches **26, 42–43, 45– 47**
Dinging hammer **441**
Dismantling sleeves KABELEX® **436**
Display **52, 418**
Display unit for SENSOTORK workshop testing device **52**
Divider plates **290**
Dollies **443–444**
Double open-ended spanner sets **111–113, 373**
Double open-ended spanners **110–113, 373**
Double open-ended spanners, small **113**
Double suction lifters **447**
Double-ended flexi-joint spanners **137–138**
Double-ended flexi-joint spanners sets **137–138**
Double-ended ratchet ring spanner sets **130–131**
Double-ended ratchet ring spanners **130–131**
Double-ended ring spanner sets **122– 123, 125– 126**
Double-ended ring spanners **121–126**
Double-ended ring spanners, open angled **125–126**
Draw handle **447**
Drawer divider **290**
Drawers **296**
Drift punch **469, 471**
Drift punch and centre punch set **471**
Drill bit **446**
Drilling tools **446**
Drive handle **152**
Duo work spotlight **488**

E

Ear clamp pincers **458**
Ejection tools KABELEX® **436**
Electrician's set **357**
Electrician's slotted screwdrivers DRALL+ **243**
Electromechanical angle-controlled torque wrenches MANOSKOP® **46–47**
Electromechanical torque screwdrivers **22**
Electromechanical torque wrenches service/series MANOSKOP® **43**
Electronic diagonal cutters **413**
Electronic hex screwdriver **248**
Electronic kit **290**
Electronic needle-nose pliers **413**
Electronic PH cross-head screwdriver **246**
Electronic screwdriver set **257**
Electronic side cutters **411**
Electronic slotted screwdriver **243**
Electronic angle-controlled torque wrench SENSOTORK® **45**
Electronic torque wrenches SENSOTORK® **42**
Electronic TORX® screwdriver set **257**
Electronic TORX® screwdrivers **247, 257**
Electronic tyre-tread caliper **480**
Electronic workshop testing devices SENSOTORK® **87**
Electronics front end cutters **412**
Electronics pliers set **421**
Electronics tool set assortment **380**
Embossing hammer **467**
Empty tray for small components **289**
Engineer's hammers **468**
EURO voltage tester **480**
Extensions **431**
Extensions for calibration systems **99, 101**
Extraction hammers **430**
Extractor pliers **445**
Extractors, drawers **296**

F

Factory calibrations **81**
Factory certificates **81**
Fastening eyelet **299**
File blades **444 , 445**
File brush **476**
Files **444–445, 476–477**
Fine ratchets **61, 65, 69, 150, 175, 195, 272**
Fine scraper **474**
Fine-tooth ratchet insert tools **61, 65, 69**
Fine-tooth ratchets **61, 65, 69, 150, 175, 195, 272**

Flat chisel **469**
Flat file **476**
Flat scraper **474**
Flexible drive handle **152**
Flexible handle spare part set **196**
Flexible handles **152, 177, 196**
Flexible heads **214, 218**
Flexible socket extensions **154, 178**
Floor display for bolt cutters **418**
Flush cut bolt cutters **414, 416**
Flush cut bolt cutters 30° LightCUT® **414**
Foam inlays **289, 459, 506–507**
Folding rulers **480**
Four-sided bradawl **474**
Friction gauge **27**
Fuel hose clamp **457**

G

Gas stove brush **475**
Gasket scraper **448**
Gauges **450, 481**
Glass scraper **475**
Grating and flat material cutters EuroCUT® **419**
Grid panels **298**
Gripping and cutting pliers **394–395, 504–505**
Gripping pliers **394–395, 410–411, 504–505**
Grooving chisel **469**
Guide handle **448**
Guide rollers **465**

H

Hacksaws **477**
Half-round file **476**
Hammer and chisel set **377**
Hammer heads **467–468**
Hammer set **353**
Hammers **353, 441–442, 467–468**
Hand guard **469**
Hand lamp **488**
Hand wheel attachment for torque screwdrivers **102**
Handles **136, 152, 177, 196, 215, 218**
Headlamps **485–486, 488**
Heads for dead blow hammer **468**
Heads for nylon hammer **468**
Heads for plastic hammer **467**
Heavy-duty Crowfoot spanners **74**
Heavy-duty end cutters **396**
Heavy-duty mechanic's nippers **407–408**
Heavy-duty mechanic's nippers MasterCUT® **407, 408**
Heavy-duty pipe wrenches **402**
Heavy-duty ring spanner **135**
Heavy-duty side cutters **396**
Hex ball-ended L-Keys **262–263**
Hex ball-ended screwdriver DRALL+ **248**
Hex L-Key sets **259–261**
Hex L-Keys **259–261**
Hex screwdriver **249, 254**
Hex screwdriver set **254**
HI-LOK™ fine-tooth ratchet **155**
HI-LOK™ L-Keys **156**
HI-LOK™ ratchet spare part set **155**
HI-LOK™ socket extensions **156**
HI-LOK™ socket set **155**
Holder **65, 69, 71, 289, 299**
Hook tool set **466**
Hook tools **466**
Hooks **298**
Hose clamp pliers **457–458**
Hose clip pliers **458**

I

IMPACT ball joints **232, 235, 237**
IMPACT driver **277**
IMPACT driver set **277**
IMPACT extensions **232, 235, 237**
IMPACT INHEX screwdriver sockets **231, 233**
IMPACT locking pins **232, 235, 237**
IMPACT rubber rings **232, 235, 237**
IMPACT screwdriver socket set **234**
IMPACT sockets **230–231, 233–234, 236**
IMPACT square drive adaptors **232, 235, 237**
IMPACT srewdriver sockets **231–233**
IMPACT tool set **233**
IMPACT wheel nut wrenches **231**
INHEX screwdriver socket sets **205–207**
INHEX screwdriver sockets **148, 174–175, 190–192, 205–207, 213, 217**
INHEX, wheel nut and hex key set **207**
Inlays **53, 289**
Inlays for plastic boxes **53**
Insert tool adaptors **64, 68, 70**
Insert tools **60–71, 105, 276**
Interface adaptor **49**
Interface adaptor set **49**
Internal pullers **429**

J

Jack-push/pull cables **49–50**
Jet reamer **457**
Jet reamer set **457**

K

Kneeling mat **459**
Knives **478–479, 506**

L

Laboratory transducer **98**
Lamps **485–486, 488**
Laptop holder **289**
Large workshop sets **354–359**
Lashing straps **449**
Lever action end cutters **397**
Lever bars **442–443, 445-447**
Levers **446–447, 455**
Lights **485–486, 488**
Line maintenance set (imperial) in tool trolley No. 13217 **362**
Line maintenance set (metric) in tool trolley No. 13217 **360**
Line maintenance sets **346, 348, 360, 362**
Line maintenance sets in tool box No. 13216N/4 **383–384**
Lithium 2 charger **48**
Lithium-ion battery **48**
L-Key bit set **264**
L-Key set **264**
Lock **296**
Locking adaptors **155, 180**
Locking pins **232, 235, 237**
Locking pliers **410–411**
Long-nose self-grip wrench **411**
Lump hammer **468**

M

Magnetic lifter **484**
Magnetic tray **484**
Manual calibration system in sets **93**
Manual calibration systems **92–93, 99–100**
Measuring tapes **480**
Mechanic's nippers **398, 406–408**
Mechanic's nippers TopCUT® **407**
Mechanics stethoscope **456**
Mesh cutters **418–419**
Milling cutters **446**
Mini electronic side cutters **412**
Mini QuickRelease fine-tooth ratchet **151**
Mini water pump pliers **398**
Mirrors **483**
Mobile tool box **294**
Mobile workbench **286**
Motorised calibration and adjustment system **94–95**
Motorised calibration and adjustment system in sets **95**
Mounting bracket set **96**
Multifunctional wrenches **221**
Multiplex beechwood worktop **291**
Multi-use tool set **386**

N

Needle file set **477**
Needle-nose pliers **413**
Notebook holder **289**
Nut spinner **249–250, 254**
Nut spinner DRALL+ **249**
Nut spinner socket set **254**
Nut splitters **481**
Nylon hammers **467**

O

Oil can **489**
Oil filter claw **455**
Oil filter wrenches **172, 455–456**
Oil service spanner **455**
Oil spray can **489**
Oiler **489**
On-board tool set for agriculture **387**
OPEN RING insert tools **63**
Open-ended insert tools **61–62, 66, 69**
Open-ended insert/shell tools **61–62, 66, 69**
Open-ended shell tools **71**
Open-ended spanners **110–113, 134–135, 373, 496**
Open-ended striking spanner **134**

P

Padlock **296**
Paper roll holder **289**
Parallel jaw self-grip wrench **410**
Pecking and driving hammers **441–442**
Pecking hammer **442**
Pen magnet lifter **484**
Penlights **485–486, 488**
Perforated panel **298**
PH cross-head offset screwdriver **258**
PH cross-head screwdriver 3K DRALL® **245**
PH cross-head screwdriver DRALL® **245**
PH cross-head screwdrivers DRALL+ **244, 245**
Pin extractors **430, 470**
Pin punch **470–471**
Pin punch and centre punch set **471**
Pin punch set **470**
Pin wrench **456**
Pincers **406, 408, 458**
Pipe cutters **464**
Pipe cutters KOMPAKT **464**
Pipe cutters MINI **464**
Pipe cutters RAPID **464**
Pipe wrench PowerGRIP **401**
Pipe wrench set PowerGRIP **401**
Pipe wrenches **401–405, 410–411**
Pipe wrenches 90° **403–404**
Piston ring pliers **449**
Piston ring tensioners **449**
Planishing and grooving hammer **442**
Planishing hammer **441**
Plastic boxes, empty **53**
Plastic hammers **467**
Plastic levers **446**
Plastic protective jaws for parallel jaw self-grip wrench **411**
Plastic scraper **475**
Plastic scraper set **475**
Plates **291**
Pliers **377, 399–400, 403, 405–406, 408, 420–421, 458**
Pliers sets **377, 399–400, 403, 405, 420–421**
Plug-in adaptors **71**
Plug-in ratchet tools **60, 65, 69**
Potter's or brick nippers **406**
Power supplies **48–50**
Precision feeler gauges **450**
Product display **418**
Professional sanitary assortment **400**
Profi-Key **221**
Prohibition signs **507**
Protective cover **289**
Protective jaws **406**
Pry bars **442–443, 445**
Pull bar **445**
Pull hammers **430**
Pull hook for exhaust rubber **457**
Pullers **426–429, 431**
Punch and chisel sets **353–354**
Putty knife **489**
PZ cross-head screwdriver 3K DRALL® **246**
PZ cross-head screwdriver DRALL+ **246**
PZ cross-head screwdriver DRALL® **246**

Alphabetical index

Q

Quick-change holder **273**
QuickRelease bit adaptors **237**
QuickRelease drive handle **152**
QuickRelease extensions **153–154, 178, 197**
QuickRelease fine-tooth flexible ratchets **151, 176, 195**
QuickRelease fine-tooth ratchets **150–151, 176, 194**
QuickRelease operating tool sets **210–211**
QuickRelease ratchet insert tools **65, 60**
QuickRelease safety lock **52**
QuickRelease socket sets **158–163, 165–167, 181–182, 185–186, 200–204, 209**
QuickRelease speeder braces **153, 177, 197**
QuickRelease T-handles **153, 177, 196–197**
QuickRelease tool sets with tool trolley **306–308, 310–312**
QuickRelease tool sets with workbench **313–314, 316, 318–319, 321**
QuickRelease universal joints **154, 179, 198**

R

Ratchet heads **70, 176, 195, 214, 218**
Ratchet ring insert tools **65–66**
Ratchet ring spanners **130–131**
Ratchet spanner sets **132, 374**
Ratchet spanners **127–130, 132, 374**
Ratchet spare part sets **78–79, 151–152, 176–177, 196, 214, 218**
Ratchet strap **449**
Ratchet tap holder **457**
Ratcheting bit holder spanners **273**
Ratchets **70, 150–151, 155, 175–176, 194–195, 214, 218, 497**
Reamers **457**
Rectangular lugs **299**
Replacement blades **475, 477, 479**
Replacement blades for handsaw **477**
Replacement chains **405, 465**
Replacement concave mirror **484**
Replacement cutter **446**
Replacement mirror **483**
Replacement plastic jaws **406**
Replacement plate **449**
Replacement saw blade **477**
Replacement wheel sets **291, 296**
Retaining pliers **410–411**
Retaining rings **465**
Reversible screwdriver set **258**
Ribbed cold chisel **469**
Ring insert tools **62–63, 67, 70**
Ring shell tools **71**
Ring spanners **135–136**
Roller spindles **465**
Roll-up tool pouches **295**
Rotary handles **177, 197**
Round awl **474**
Round file **476**
Rubber composite mallets **467**
Rubber fabric tape for strap wrench **456**
Rubber hammers **467–468**
Rubber insert **219**
Rubber mat **289**
Rulers **480**

S

Safety knives **478–479**
Scissors **445, 478, 506**
Scraper with reversible tungsten steel blade **448**
Scrapers **448, 474–475**
Screw extractor **481–482**
Screw extractor set **481–482**
Screw pitch gauges **481**
Screwdriver bits **52, 265–267, 275–277**
Screwdriver ratchet bit set **269**
Screwdriver sets **253, 258, 376**
Screwdriver sets 3K DRALL® **253, 256–257**
Screwdriver sets DRALL+ **251–253, 255**
Screwdriver socket sets **156, 167, 205–208**
Screwdriver sockets **148–149, 156, 167, 174–175, 183, 190–194, 205–206, 213, 217, 231–232, 499**
Screwdrivers **156, 242–264, 269, 273, 376, 455, 500–504**
Scriber **479**
Seaming pliers **406, 408, 458**
Self-grip pipe wrenches **405**
Self-grip wrenches **410–411**
SensoMaster software licence **50**
Sensors **98, 101**
Separation assemblies **431**
Service trolleys **283–285**
Sheet metal pliers **408**
Sheet metal shears **445**
Shelf **290**
Side cutters **395**
Single hooks **298**
Single-ended ring spanners **456, 496–497**
Siphon pliers (connector pliers) **406**
S-jaw pipe wrench and water pump pliers set **403**
S-jaw pipe wrench set **403**
S-jaw pipe wrenches **402–403**
S-jaw push-button water pump pliers S-GRIP® **401**
Sledge hammers **443–444**
Slide hammers **430**
Sliding heads **215, 219**
Slotted offset screwdriver **258**
Slotted screwdrivers 3K DRALL® **243**
Slotted screwdrivers DRALL+ **242, 244**
Slotted screwdrivers DRALL® **243**
Small parts tray **484**
Smoothing and pin hammer **442**
Snap ring pliers **408–410**
Snap-off blade cutters **479**
Snap-off blades **479**
Socket clip rail sets **157**
Socket clip rails **157, 180, 199**
Socket extensions **153–154, 156, 178, 197–198, 214, 218, 232, 235, 237, 431, 499–500**
Socket sets **155–168, 180–186, 199–205, 207–211, 215–216, 219, 370, 374–375, 495**
Socket sets on clip rail **156–157, 180, 199**
Sockets **144–147, 169–174, 187–190, 212–213, 217, 230–231, 233–234, 236, 276, 451, 499–500**
Socket TORX® sets **183, 205**
Spanner holder **139**
Spanner sets **120, 121, 372**
Spanners **120–121, 134–135, 372**
Spare blades **478**
Spare bowden cable **458**
Spare nuts **402**
Spare parts **482**
Spare parts kits **78–79, 151–152, 155, 176–177, 196, 214, 218, 272–273**
Spark plug brush **452**
Spark plug sockets **172–173**
Special ring spanner **456**
Special socket **276**
Special socket extensions **178, 197–198**
Speeder braces **177, 197**
S-pipe wrenches **402–403**
Split-pin puller **466**
Spot weld drill **446**
Spot weld milling cutters **446**
Spotlight **488**
Spray can holder **290**
Spring clips **299**
Square drive adaptor set **219**
Square drive adaptors **104, 154–155, 179, 198–199, 215, 219**
Square drive insert tools **61, 66, 69**
Square drive shell tool **70**
Square drives **80, 105**
Stand alone mechanical loader for torque screwdrivers **102**
Steel ruler **480**
Steel wire brushes **475**
STILLSON pipe wrenches **402**
Strap wrench **456**
Striking ring spanner **136**
Striking tools **353–354, 443–444**
Stripping knife with hooked blade **479**
Structural steel mesh cutters **418**
Structural steel mesh cutters BauCUT® **419**
Structural steel mesh cutters WAGGONIT® **418**
Structural steel mesh cutters/deep cutters SolutionCUT **419**
Suction lifters **447**
Sun gears with overload protection **77**
Swedish pipe wrenches **402**

T

Tape measures **480**
Telephone pliers **394–395**
Telescopic concave mirrors **483**
Telescopic mirrors **483**
Telescopic ratchet **195**
Telescopic stainless steel mirrors **483**
Test lamp **459**
Tester **84–85, 87**
Textile bags for large torque wrenches **53**
T-handles **152–153, 177, 196–197, 218**
Thread extractor set **482**
Thread gauge **481**
Thread restorers **477**
Tile hole pliers **408**
Tommy bars **139**
Tool bag **292**
Tool box L-BOXX® **293**
Tool boxes **292–294, 296, 494**
Tool card **293**
Tool holder **293**
Tool holders **65, 69, 71, 139, 157, 180, 199, 299, 457**
Tool holders/disassembly tools **65, 69, 71**
Tool insert **293**
Tool set **359**
Tool set basic **381**
Tool set electrics **382**
Tool set for engine mechanics **359**
Tool set in service trolley **304**
Tool set industry **381**
Tool set KABELEX® **440**
Tool sets **323–328, 345, 350–352, 371–372**
Tool sets for trolleys **368–369**
Tool sets in cases **378–380**
Tool sets with tool trolley **305–312**
Tool sets with workbench **313–322**
Tool supplementary set AGRAR MOBIL **387**
Tool trolleys **283–285, 296**
Torches **485–486, 488**
TORQ-SET® screwdriver DRALL+ **248**
Torque multipliers MULTIPOWER **76**
Torque ratchets **26–37, 498**
Torque screwdriver sets **54**
Torque screwdriver TORSIOMAX **21**
Torque screwdriver TORSIOMETER **20**
Torque screwdrivers **20–22, 54**
Torque testers **85, 87**
Torque tool sets with SENSOTORK® **54**
Torque tools with digital display **26, 42–43, 45–47**
Torque wrench set **57**
Torque wrenches **26–37, 42–43, 45–47, 57, 498**
Torque wrenches MANOSKOP® **26–36**
Torque wrenches series MANOSKOP® **27**
Torque wrenches service MANOSKOP® **29–30, 33–35**
Torque wrenches service MANOSKOP® (in·lb) **28**
Torque wrenches service MANOSKOP® (N·m) **28**
Torque wrenches service/series MANOSKOP® **35–36**
Torque wrenches standard MANOSKOP® **31–32**
Torque wrenches standard MANOSKOP® with fixed square drive **32**
Torque-limiting screwdrivers **20–22**
TORX® ball-ended L-Key **262**
TORX® ball-ended L-Key set **262**
TORX® insert tools **62, 67**
TORX® L-Key set **261**
TORX® L-Keys **261**
TORX® screwdriver DRALL+ **247, 252, 256**
TORX® screwdriver sets **252–254, 256–257**
TORX® screwdriver sets 3K DRALL® **253, 257**
TORX® screwdriver sets DRALL+ **252, 256**
TORX® screwdriver socket sets **183, 205**
TORX® screwdrivers **247, 250, 252–254, 256–257**
TORX® socket bit sets **207**

TORX® Tamper Resistant screwdriver 3K DRALL® **248**
TORX® Tamper Resistant screwdriver DRALL+ **247**
Transducers **98, 101**
Transparent cover **296**
Tray **484**
Triangular bearing scraper **474**
Triangular file **476**
Triangular special scraper **474**
Trolleys **283–285**
TTS **283–285**
Tungsten carbide scriber **479**
Tweezer **484**
Twin hook **298**
Twisting pliers **398**
Tyre changing kit **56**
Tyre lever **455**
Tyre-tread caliper **480**

U

Uniflex sockets **147, 173–174, 190, 451**
Universal dolly **443**
Universal self-grip wrenches **411**
Universal set KABELEX® **440**
Universals joints **154, 179, 198, 214, 232, 235, 237**
USB adaptor and cable with TorkMaster software **51**
USB adaptor and jack-push/pull cable with SensoMaster 4 software **51**
USB adaptor and jack-push/pull cable with TorkMaster software **51**
USB adaptors **50–51**
USB power supply **50**

V

Valve seating-ring pliers **449**
Valve spring assembly tool **449**
VDE bag **506**
VDE barrier tape **507**
VDE cable knives **506**
VDE cable shears **506**
VDE combination pliers **504**
VDE electrician's slotted screwdriver DRALL+ **500**
VDE heavy-duty side cutters **505**
VDE insulating underlay mat in bag **507**
VDE insulating underlay mats **506–507**
VDE interchangeable screwdriver set **504**
VDE MultiUse tool set **495**
VDE open-ended spanner set **496**
VDE open-ended spanners **496–497**
VDE PH cross-head screwdriver DRALL+ **501**
VDE prohibition sign **507**
VDE PZ cross-head screwdriver DRALL+ **501**
VDE QuickRelease fine-tooth ratchet **497**
VDE screwdriver sets DRALL+ **503–504**
VDE self clamping cable-end cap **507**
VDE side cutters **505**
VDE single-ended ring spanner **496–497**
VDE single-ended ring spanner set **497**
VDE slotted screwdriver DRALL+ **500**
VDE socket extensions **499–500**
VDE socket set **495**
VDE sockets **495, 499–500**
VDE square drive adaptor **499**
VDE telephone pliers **504–505**
VDE tool assortments **494–495**
VDE tool box **494**
VDE torque wrench MANOSKOP® **498**
VDE TORX® screwdriver DRALL+ **502**
VDE TORX® screwdriver sets DRALL+ **502**
VDE warning sign **507**
VDE water pump pliers **506**
VDE wire strippers **505**
Vehicle light tester **459**
Vehicle workshop set **356**
Voltage testers **459, 480**

W

Warding file sets **477**
Warning signs **507**
Waste bin **291**
Water pump pliers **398–401**
Water pump pliers AllGRIP **400**
Water pump pliers FastGRIP **398, 400**
Water pump pliers set **399–400**
Water pump pliers set FastGRIP **400**
Welding pliers **410–411**
Wheel braces **455**
Wheel change set **56**
Wheel sets **291, 296**
Windscreen replacement set VERITRAC **447**
Wire brush **475**
Wire cutters **418–419**
Wire insert probe **448**
Wire strippers **397, 478, 505**
Wire twisting pliers **398**
Wobble-Drive extensions **153, 178, 198**
Work lights **486, 488**
Work spotlight **488**
Workbenches **286– 287**
Workshop set for BMW cars **336**
Workshop set for Mercedes-Benz cars **343**
Workshop set for Mercedes-Benz trucks **341**
Workshop set for Porsche **330**
Workshop set for VW/Audi (basic) **332**
Workshop sets for BMW motorcycles **338, 340**

4–5

4-pin socket **190**
5-star bit box **268**
5-star screwdriver bits **266**

Product number index

Product no.	Page
01010003	144
01010004	144
01010005	144
01010006	144
01010007	144
01010008	144
01010009	144
01010010	144
01010011	144
01010012	144
01010013	144
01010014	144
01010032	144
01010035	144
01010045	144
01010055	144
01011007	146
01011008	146
01011009	146
01011010	146
01011012	146
01011014	146
01020004	146
01020005	146
01020006	146
01020007	146
01020008	146
01020009	146
01020010	146
01020011	146
01020012	146
01020013	146
01020032	146
01020045	146
01020055	146
01021007	146
01021008	146
01021010	146
01030005	144
01030006	144
01030007	144
01030008	144
01030009	144
01030010	144
01030011	144
01030012	144
01030013	144
01030014	144
01030055	144
01050003	148
01050004	148
01050005	148
01050006	148
01050025	148
01120003	148
01120004	148
01120005	148
01120006	148
01120008	148
01140006	147
01140007	147
01140008	147
01140009	147
01140010	147
01190008	72
01190009	72
01190010	72
01190011	72
01190012	72
01190013	72
01190014	72
01200008	73
01200009	73
01200010	73
01211010	73
01211014	73
01240005	145
01240006	145
01240007	145
01240008	145
01240009	145
01240010	145
01240011	145
01240012	145
01240013	145
01240014	145
01240055	145
01270004	146
01270005	146
01270006	146
01270007	146
01270008	146
01270010	146
01280006	148
01280008	148
01280010	148
01280012	148
01290001	149
01290002	149
01290003	149
01290004	149
01300001	149
01300002	149
01350008	149
01350009	149
01350010	149
01350015	149
01350020	149
01350025	149
01350027	149
01350030	149
01350040	149
01351008	149
01351009	149
01351010	149
01351015	149
01351020	149
01351025	149
01351027	149
01351030	149
01351040	149
01410008	144
01410010	144
01410012	144
01410014	144
01410016	144
01410018	144
01410020	144
01410022	144
01410024	144
01410028	144
01410032	144
01410034	144
01450004	148
01450005	148
01450006	148
01450007	148
01450008	148
01450009	148
01450010	148
01450012	148
01450014	148
01450016	148
01490024	72
01490028	72
01490032	72
01490034	72
01500024	74
01530010	145
01530012	145
01530014	145
01530016	145
01530018	145
01530020	145
01530022	145
01530024	145
01530028	145
01530032	145
01530034	145
01540014	147
01540016	147
01540018	147
01540020	147
01540022	147
01540024	147
01540028	147
01540032	147
01541024	147
01541034	147
01542016	147
01542020	147
01640010	145
01640012	145
01640014	145
01640016	145
01640018	145
01640020	145
01640022	145
01640024	145
01640028	145
01640032	145
01640034	145
01650014	145
01650016	145
01650018	145
01650020	145
02010007	169
02010008	169
02010009	169
02010010	169
02010011	169
02010012	169
02010013	169
02010014	169
02010015	169
02010016	169
02010017	169
02010018	169
02010019	169
02010020	169
02010021	169
02010022	169
02010024	169
02011012	170
02011014	170
02011016	170
02020008	171
02020010	171
02020011	171
02020012	171
02020013	171
02020014	171
02020015	171
02020016	171
02020017	171
02020018	171
02020019	171
02020021	171
02020022	171
02020208	171, 451
02021012	171
02021014	171
02040010	173
02040011	173
02040012	173
02040013	173
02040014	173
02040015	173
02040016	173
02040017	173
02040018	173
02040019	173
02050003	174
02050004	174
02050005	174
02050006	174
02050007	174
02050008	174
02050010	174
02060005	175
02060006	175
02060008	175
02060010	175
02070008	174
02070010	174
02070012	174
02070014	174
02100009	175
02100010	175
02100015	175
02100020	175
02100025	175
02100027	175
02100030	175
02100040	175
02100045	175
02110007	172
02110008	172
02110009	172
02110010	172
02110011	172
02110012	172
02110013	172
02110014	172
02110015	172
02110016	172
02110017	172
02110018	172
02110019	172
02110020	172
02110021	172
02110022	172
02111032	172
02111036	172
02120036	173, 450
02130018	173, 450
02140036	172, 450
02151004	175
02151005	175
02151006	175
02151007	174
02151009	174
02151208	175
02151210	175
02152408	174
02180010	451
02180012	451
02181007	75
02181008	75
02181009	75
02181010	75
02181013	75
02190015	72
02190016	72
02190017	72
02190018	72
02190019	72
02190020	72
02190021	72
02190022	72
02190023	72
02190024	72
02190025	72
02190026	72
02190027	72
02200011	73
02200012	73
02200013	73
02200014	73
02200015	73
02200016	73
02200017	73
02200018	73
02200019	73
02200020	73
02200021	73
02200022	73
02200023	73
02200024	73
02200025	73
02200026	73
02200027	73
02200028	73
02200030	73
02200032	73
02200034	73
02200036	73
02200040	73
02200041	73
02200042	73
02200046	73
02200050	73
02211016	73
02211018	73
02211020	73
02211022	73
02211024	73
02211027	73
02211030	73
02261206	175
02261208	175
02261210	175
02270005	170
02270006	170
02270007	170
02270008	170
02270010	170
02270012	170
02270014	170
02370006	499
02370008	499
02370010	499
02380007	499
02380008	499
02380009	499
02380010	499
02380011	499
02380012	499
02380013	499
02380014	499
02380016	499
02380017	499
02380018	499
02380019	499
02380020	499
02380022	499
02390020	499
02390025	499
02390030	499
02390040	499
02390045	499
02410016	169
02410020	169
02410022	169
02410024	169
02410028	169
02410032	169
02410034	169
02410035	169
02410036	169
02410038	169
02410040	169
02410042	169
02410044	169
02410046	169
02410048	169
02420016	171
02420020	171
02420022	171
02420024	171
02420028	171
02420032	171
02420034	171
02420035	171
02420036	171
02420038	171
02420040	171
02420042	171
02420044	171
02420046	171
02420048	171
02430020	169
02440020	173
02440024	173
02440028	173
02440032	173
02440034	173
02440036	173
02440038	173
02440040	173
02450008	174
02450009	174
02450010	174
02450012	174
02450014	174
02450016	174
02450020	174
02450024	174
02470016	75
02470020	75
02470024	75
02470028	75
02470032	75
02470034	75
02470036	75
02480014	75
02480016	75
02480018	75
02480020	75
02480024	75
02480028	75
02480032	75
02480034	75
02480036	75
02490036	72
02490038	72
02490040	72
02490042	72
02490044	72
02490046	72
02490048	72
02490050	72
02500028	74
02500032	74
02500034	74
02500036	74
02500038	74
02500040	74
02500042	74
02500044	74
02500048	74
02500050	74
02500052	74
02500054	74
02500056	74
02500058	74

Product no.	Page
02500060	74
02500062	74
02500064	74
02500065	74
02500066	74
02500067	74
02500068	74
02500070	74
02500072	74
02500074	74
02500076	74
02501024	74
02501028	74
02501032	74
02501034	74
02501036	74
02501038	74
02501040	74
02501042	74
02501044	74
02501046	74
02501048	74
02501050	74
02501052	74
02501054	74
02501056	74
02501058	74
02501060	74
02501062	74
02620016	172
02620020	172
02620024	172
02620028	172
02620032	172
03010008	187
03010009	187
03010010	187
03010011	187
03010012	187
03010013	187
03010014	187
03010015	187
03010016	187
03010017	187
03010018	187
03010019	187
03010020	187
03010021	187
03010022	187
03010023	187
03010024	187
03010025	187
03010026	187
03010027	187
03010028	187
03010030	187
03010031	187
03010032	187
03010034	187
03010036	187
03012024	189
03012028	189
03012034	189
03013028	189
03020010	188
03020013	188
03020014	188
03020015	188
03020016	188
03020017	188
03020018	188
03020019	188
03020021	188
03020022	188
03020024	188

Product no.	Page
03020026	188
03020027	188
03020030	188
03020032	188
03020208	188, 451
03020216	188, 451
03030008	188
03030009	188
03030010	188
03030011	188
03030012	188
03030013	188
03030014	188
03030015	188
03030016	188
03030017	188
03030018	188
03030019	188
03030020	188
03030021	188
03030022	188
03030023	188
03030024	188
03030025	188
03030026	188
03030027	188
03030028	188
03030030	188
03030032	188
03030034	188
03030036	188
03040010	190
03040013	190
03040016	190
03040017	190
03040018	190
03040019	190
03050004	190
03050005	190
03050006	190
03050007	190
03050008	190
03050010	190
03050012	190
03050014	190
03050017	190
03050019	190
03060005	193
03060006	193
03060008	193
03060010	193
03060012	193
03060014	193
03060016	193
03070005	191
03070006	191
03070008	191
03070010	191
03070012	191
03070014	191
03090005	193
03090006	193
03090007	193
03090008	193
03090010	193
03090012	193
03090013	193
03090014	193
03090016	193
03100020	192
03100025	192
03100027	192
03100030	192
03100040	192
03100045	192

Product no.	Page
03100050	192
03100055	192
03100060	192
03100070	192
03110020	192
03110025	192
03110027	192
03110030	192
03110040	192
03110045	192
03110050	192
03110055	192
03110060	192
03131070	194
03131230	194
03131240	194
03131245	194
03131440	194
03131445	194
03131450	194
03131455	194
03131460	194
03150706	192
03150713	192
03150808	192
03151006	192
03151007	192
03151205	191
03151206	191
03151207	191
03151208	191
03151408	192
03151410	191
03151412	191
03151414	191
03151805	192
03152206	192
03160808	193
03161110	193
03161112	193
03161208	193
03190028	72
03190030	72
03190032	72
03190034	72
03190036	72
03190038	72
03190040	72
03190041	72
03190042	72
03190046	72
03190050	72
03230012	194
03240017	189
03240019	189
03240022	189
03240208	189, 451
03261408	193
03261410	193
03261412	193
03261414	193
03270010	190
03270011	190
03270012	190
03270014	190
03270016	190
03270018	190
03270020	190
03270024	190
03280005	191
03280006	191
03280007	191
03280008	191
03280010	191
03310005	192

Product no.	Page
03310008	192
03370010	500
03370011	500
03370012	500
03370013	500
03370014	500
03370017	500
03370019	500
03370022	500
03370024	500
03410024	187
03410028	187
03410032	187
03410034	187
03410035	187
03410036	187
03410038	187
03410040	187
03410041	187
03410042	187
03410044	187
03410046	187
03410048	187
03410050	187
03410052	187
03410054	187
03410056	187
03410058	187
03410060	187
03410062	187
03410064	187
03420024	189
03420028	189
03420032	189
03420034	189
03420036	189
03420038	189
03420040	189
03420042	189
03420044	189
03420046	189
03420048	189
03420050	189
03420052	189
03420054	189
03420056	189
03420058	189
03420060	189
03420062	189
03420064	189
03450014	191
03450016	191
03450020	191
03450024	191
03450028	191
03450032	191
03450034	191
03450036	191
03450040	191
03490052	72
03490056	72
03490058	72
03490060	72
03490062	72
03490064	72
03490065	72
03490066	72
03490068	72
03490069	72
03490072	72
03490076	72
03490077	72
03490078	72
03500078	74
03501064	74

Product no.	Page
03501069	74
03501072	74
03501074	74
03501075	74
03501076	74
03810001	190
03830027	190
05010019	212
05010021	212
05010022	212
05010024	212
05010027	212
05010030	212
05010032	212
05010033	212
05010034	212
05010036	212
05010038	212
05010041	212
05010046	212
05010050	212
05010055	212
05010060	212
05020022	213
05020024	213
05020027	213
05020030	213
05020032	213
05020034	213
05020036	213
05020041	213
05050014	213
05050017	213
05050019	213
05050022	213
05060014	213
05060016	213
05060018	213
05100060	213
05100070	213
05100080	213
05100090	213
05100100	213
05410040	212
05410042	212
05410044	212
05410046	212
05410048	212
05410050	212
05410052	212
05410056	212
05410058	212
05410060	212
05410062	212
05410064	212
05410066	212
05410067	212
05410068	212
05410069	212
05410070	212
05410072	212
06010030	217
06010032	217
06010034	217
06010036	217
06010041	217
06010046	217
06010050	217
06010055	217
06010060	217
06010065	217
06010070	217
06010075	217
06010080	217
06050014	217

Product no.	Page
06050017	217
06050019	217
06050022	217
06050024	217
06050027	217
08010000	265
08010001	265
08010002	265
08010003	265
08030001	265
08030002	265
08030003	265
08030004	265
08050001	265
08050002	265
08050003	265
08070120	265
08070121	265
08070122	265
08070123	265
08070124	265
08070125	265
08070126	265
08070127	265
08070128	265
08070129	265
08070130	265
08090002	52, 266
08090003	266
08090004	266
08090005	266
08090006	266
08090008	266
08130006	265
08130007	265
08130008	265
08130009	265
08130010	265
08130015	265
08130020	265
08130025	265
08130027	265
08130030	265
08130040	265
08130045	265
08131025	266
08140027	265
08140030	265
08140040	265
08140045	265
08140050	265
08140055	265
08160010	266
08160015	266
08160020	266
08160025	266
08160027	266
08160030	266
08160040	266
08161010	266
08161015	266
08161020	266
08161025	266
08161027	266
08161030	266
08161040	266
08162010	266
08162015	266
08162020	266
08162025	266
08162027	266
08162030	266
08162040	266
08200004	265
08200010	265

Product number index

Product no.	Page
08200011	265
08200012	265
08200013	265
08200014	265
08230001	276
08250000	267
08250001	267
08250002	267
08250003	267
08250004	267
08250005	267
08250006	267
08260000	267
08260001	267
08260002	267
08260003	267
08260004	267
08260005	267
08260006	267
08260008	267
08260010	267
08260016	267
08260020	267
08260024	267
08300635	275
08300840	275
08301055	275
08301265	275
08301680	275
08310001	276
08310002	276
08310003	276
08320001	276
08320002	276
08320003	276
08330003	276
08330004	276
08330005	276
08330006	276
08330008	276
08340010	276
08340015	276
08340020	276
08340025	276
08340027	276
08340030	276
08340040	276
08400010	277
08400014	277
08400015	277
08400016	277
08400020	277
08410002	277
08410003	277
08410004	277
08420005	277
08420006	277
08420008	277
08420010	277
09010001	219, 451
11010001	153
11010002	153
11010006	153
11010010	153
11010011	153
11010012	153
11010014	153
11010016	153
11010020	153
11010024	153
11011001	153
11011002	153
11011005	153
11011006	153
11011013	153
11011502	154

Product no.	Page
11011504	154
11011506	154
11011513	154
11011514	154
11020000	154
11021000	154
11021500	154
11030002	154
11030003	155
11030010	104, 155
11040000	154
11050010	152
11050011	152
11051010	152
11053002	152
11061010	152
11070000	152
11071000	153
11071500	153
11100005	153
11110010	155
11111010	150
11111020	150
11111030	150
11111040	151
11111050	151
11131010	272
11131011	270
11132020	272
11133030	272
11180010	274
11180020	275
11231011	150
11240011	156
11240012	156
11240013	156
11261010	151
12010001	178
12010002	178
12010003	178
12010004	178
12010005	178
12010006	178
12010007	178
12010008	178
12010009	178
12011001	178
12011002	178
12011003	178
12011503	178
12011506	178
12011510	178
12011514	178
12020000	179
12021000	179
12021500	179
12030001	179
12030003	179
12030005	499
12030010	179
12040000	178
12061010	177
12070000	177
12071000	177
12071500	177
12100005	177
12100010	177
12111010	176
12111020	176
12111030	176
12140000	176
12180026	275
12180030	275
12231011	175
12250001	178
12261010	176

Product no.	Page
12270020	178
12420001	499
12420002	499
12420003	499
12430001	497
13010001	197
13010002	197
13010003	197
13010004	197
13010005	198
13010006	198
13010007	198
13010008	198
13011001	197
13011002	197
13011003	197
13011004	197
13011502	197
13011503	197
13011505	197
13011510	197
13020000	198
13021000	198
13021500	198
13030002	198
13030005	199
13030010	199
13061015	196
13061018	196
13061024	196
13070000	196
13071000	196
13071500	197
13100005	197
13100010	197
13111010	194
13111030	194
13111120	194
13121010	195
13121020	195
13121030	195
13140000	195
13160000	195
13180010	275
13210001	198
13231011	195
13261010	195
13420001	500
13420002	500
13420003	500
15010001	214
15010002	214
15010003	214
15020000	214
15030003	215
15030006	215
15060000	214
15070000	215
15110000	214
15140000	214
15170000	215
16010001	218
16010002	218
16030005	218
16060000	218
16070000	219
16110000	218
16170000	218
18073026	270
18093016	270
18103016	270
18110016	270
18120001	273
18120002	273
18200001	65
18210001	69

Product no.	Page
18220003	71
19010000	151
19010011	272
19010012	152
19010013	155
19010014	273
19011020	78, 151
19012020	152
19012021	78
19012022	78
19012023	78
19020000	176
19020003	78
19020020	78, 176
19021000	78
19021020	177
19040000	79
19040002	79
19040020	78, 196
19040030	196
19040040	196
19041020	79
19042020	196
19050000	214
19070000	218
19200001	151
22410028	170
23010008	230
23010010	230
23010011	230
23010012	230
23010013	230
23010014	230
23010015	230
23010016	230
23010017	230
23010018	230
23010019	230
23010021	230
23010022	230
23010023	230
23010024	230
23010025	230
23010027	230
23010030	230
23010032	230
23011032	230
23011036	230
23020013	230
23020015	230
23020016	230
23020017	230
23020018	230
23020019	230
23020021	230
23020022	230
23020024	230
23020027	230
23050005	231
23050006	231
23050007	231
23050008	231
23050010	231
23050012	231
23050014	231
23050017	231
23050019	231
23070030	232
23070040	232
23070045	232
23070050	232
23070055	232
23070060	232
23080010	231
23080012	231
23080014	231

Product no.	Page
23080016	231
23080018	231
23080020	231
23080024	231
23090017	231
23090019	231
23090022	231
23090221	231
23091017	231
23091019	231
23091221	231
25010017	234
25010018	234
25010019	234
25010021	234
25010022	234
25010024	234
25010027	234
25010028	234
25010029	234
25010030	234
25010032	234
25010033	234
25010034	234
25010036	234
25010038	234
25010041	234
25010046	234
25020017	234
25020019	234
25020021	234
25020022	234
25020024	234
25020027	234
25020030	234
25020032	234
25020034	234
25020036	234
25020041	234
25020046	234
25090027	234
25090030	234
25090032	234
25090033	234
26010024	236
26010027	236
26010030	236
26010032	236
26010033	236
26010036	236
26010038	236
26010041	236
26010042	236
26010046	236
26010050	236
26010055	236
26010060	236
26010065	236
26010070	236
26010075	236
26010080	236
26020024	236
26020027	236
26020030	236
26020032	236
26020033	236
26020036	236
26020038	236
26020041	236
26020046	236
26090027	236
26090030	236
26090032	236
26090033	236
28011007	276
28011008	276

Product no.	Page
28011010	276
28011013	276
31000000	275
31150000	274
31160000	274
31161001	237, 274
31170000	274
31180000	274
31190000	274
32161001	237, 274
32200005	277
32210001	277
33010001	232
33010002	232
33010003	232
33020000	232
33030002	232
33030005	232
33161001	237, 274
33210001	277
35010001	235
35010002	235
35010003	235
35020000	235
35030003	235
35030006	235
36010001	237
36010002	237
36020000	237
36030005	237
38250002	273
39011940	232
39012440	232
39013650	235
39014850	237
39022030	232
39022530	232
39023540	235
39025050	237
40030405	110
40030607	110
40030708	110
40030809	110
40030810	110
40031011	110
40031012	110
40031013	110
40031113	110
40031213	110
40031214	110
40031314	110
40031315	110
40031317	110
40031415	110
40031417	110
40031617	110
40031618	110
40031719	110
40031819	110
40031821	110
40031922	110
40032022	110
40032123	110
40032124	110
40032224	110
40032426	110
40032427	110
40032528	110
40032730	110
40032732	110
40033032	110
40033034	110
40033236	110
40033436	110
40033641	110
40034146	110

Product no.	Page
40035507	110
40040240	134
40040270	134
40040300	134
40040320	134
40040360	134
40040410	134
40040460	134
40040500	134
40040550	134
40040600	134
40040650	134
40040700	134
40040750	134
40040800	134
40040850	134
40040900	134
40040950	134
40041000	134
40060404	113
40060505	113
40060606	113
40060707	113
40060808	113
40060909	113
40061010	113
40061111	113
40061212	113
40061313	113
40061414	113
40063232	113
40063535	113
40064545	113
40065555	113
40080606	114
40080707	114
40080808	114
40080909	114
40081010	114
40081111	114
40081212	114
40081313	114
40081414	114
40081515	114
40081616	114
40081717	114
40081818	114
40081919	114
40082020	114
40082121	114
40082222	114
40082323	114
40082424	114
40082525	114
40082626	114
40082727	114
40082828	114
40082929	114
40083030	114
40083232	114
40083434	114
40083636	114
40083838	114
40084141	114
40084646	114
40085050	114
40085500	114
40085555	114
40086060	114
40093232	120
40093535	120
40094040	120
40094545	120
40095050	120
40100606	118

Product no.	Page
40100707	118
40100808	118
40100909	118
40101010	118
40101111	118
40101212	118
40101313	118
40101414	118
40101515	118
40101616	118
40101717	118
40101818	118
40101919	118
40102020	118
40102121	118
40102222	118
40102424	118
40102727	118
40103030	118
40103232	118
40103434	118
40103636	118
40104141	118
40146565	119
40147070	119
40147575	119
40148080	119
40170808	129
40170909	129
40171010	129
40171111	129
40171212	129
40171313	129
40171414	129
40171515	129
40171616	129
40171717	129
40171818	129
40171919	129
40172121	129
40172222	129
40172424	129
40250104	134
40250106	134
40250108	134
40250110	134
40250112	134
40250115	134
40250118	134
40260104	135
40260106	135
40260108	135
40260110	135
40260112	135
40260115	135
40260118	135
40431620	110
40432024	110
40432428	110
40432832	110
40433234	110
40433436	110
40433538	110
40433638	110
40433640	110
40433840	110
40433842	110
40434044	110
40434142	110
40434446	110
40434648	110
40435258	110
40461010	113
40461212	113
40461313	113

Product no.	Page
40461414	113
40461515	113
40461616	113
40461818	113
40462020	113
40462222	113
40462424	113
40462828	113
40463232	113
40463434	113
40481212	114
40481313	114
40481414	114
40481515	114
40481616	114
40481818	114
40482020	114
40482222	114
40482424	114
40482828	114
40483232	114
40483434	114
40483535	114
40483636	114
40483838	114
40484040	114
40484141	114
40484242	114
40484444	114
40484646	114
40484848	114
40485050	114
40485252	114
40485454	114
40485656	114
40485858	114
40486060	114
40486262	114
40486464	114
40486666	114
40486969	114
40487070	114
40487272	114
40571616	118
40571818	118
40572020	118
40572222	118
40572424	118
40572828	118
40573232	118
40573434	118
40581616	118
40582020	118
40582424	118
40582828	118
40583232	118
40583434	118
41030608	124
41030911	124
41031011	124
41031214	124
41031314	124
41031719	124
41031819	124
41031922	124
41032022	124
41035507	124
41040607	121
41040809	121
41040810	121
41041011	121
41041013	121
41041213	121
41041317	121
41041415	121

Product no.	Page
41041617	121
41041719	121
41041819	121
41041821	121
41041922	121
41042022	121
41042123	121
41042124	121
41042224	121
41042426	121
41042427	121
41042528	121
41042730	121
41042732	121
41043032	121
41043034	121
41043641	121
41044650	121
41050607	125
41050809	125
41050810	125
41051011	125
41051213	125
41051317	125
41051415	125
41051617	125
41051719	125
41051819	125
41051821	125
41051922	125
41052022	125
41052124	125
41052427	125
41052732	125
41053032	125
41053034	125
41070607	123
41070809	123
41071011	123
41071213	123
41071415	123
41071617	123
41071719	123
41071819	123
41072022	123
41072123	123
41072427	123
41073032	123
41080810	125
41080911	125
41081011	125
41081012	125
41081113	125
41081214	125
41081417	126
41081719	126
41081922	126
41082224	126
41082427	126
41082736	126
41083032	126
41091012	123
41091113	123
41091416	123
41091417	123
41091517	123
41091618	123
41091922	123
41100808	132
41101010	132
41101111	132
41101212	132
41101313	132
41101414	132
41101616	132

Product no.	Page
41101717	132
41101818	132
41101919	132
41110013	456
41130708	130
41130910	130
41131011	130
41131213	130
41131415	130
41131618	130
41131719	130
41160709	124
41160810	124
41161214	124
41161618	124
41161820	124
41162224	124
41162630	124
41162832	124
41170808	127
41170909	127
41171010	127
41171111	127
41171212	127
41171313	127
41171414	127
41171515	127
41171616	127
41171717	127
41171818	127
41171919	127
41172121	127
41172222	127
41172424	127
41250608	125
41251012	125
41251418	125
41252024	125
41431416	124
41431620	124
41432428	124
41433234	124
41433640	124
41433840	124
41441620	122
41442428	122
41443234	122
41443436	122
41443538	122
41443640	122
41443842	122
41444044	122
41444142	122
41444446	122
41444648	122
41445258	122
41471616	128
41472020	128
41472424	128
41472828	128
41473232	128
41473434	128
41473636	128
41473838	128
41474040	128
41474242	128
41474444	128
41474848	128
41481620	126
41482024	126
41482428	126
41483234	126
41483640	126
41484048	126
41541620	273

Product no.	Page
41551620	131
41552428	131
41553234	131
41561620	130
41562022	130
41562428	130
41563234	130
41563638	130
41564044	130
41564246	130
41570810	131
41571214	131
41571618	131
41572022	131
41572428	131
41601620	123
41602428	123
41603234	123
41603436	123
41611620	124
41612022	124
41612024	124
41612428	124
41612832	124
41613234	124
41613436	124
41613640	124
41613840	124
41614244	124
41614648	124
41614850	124
41615256	124
42010032	136
42010036	136
42010041	136
42010046	136
42010050	136
42010055	136
42010060	136
42010065	136
42010070	136
42010075	136
42010080	136
42010085	136
42010090	136
42010095	136
42010100	136
42020024	135
42020027	135
42020030	135
42020032	135
42020036	135
42020038	135
42020041	135
42020042	135
42020046	135
42020050	135
42020055	135
42020060	135
42020065	135
42020070	135
42020075	135
42020080	135
42020085	135
42020090	135
42020095	135
42020100	135
42040027	134
42040030	134
42040032	134
42040036	134
42040041	134
42040046	134
42040050	134
42040055	134

Product number index

Product no.	Page
42040060	134
42040065	134
42040070	134
42040075	134
42040080	134
42040085	134
42040090	134
42040095	134
42040100	134
42050024	136
42050026	136
42050027	136
42050030	136
42050032	136
42050036	136
42050038	136
42050041	136
42050042	136
42050046	136
42050048	136
42050050	136
42050055	136
42050060	136
42050065	136
42050070	136
42050075	136
42050080	136
42050085	136
42050090	136
42050095	136
42050100	136
43010607	137
43010809	137
43011011	137
43011013	137
43011213	137
43011415	137
43011617	137
43011618	137
43011719	137
43011819	137
43012022	137
43012123	137
43012427	137
43030005	455
43030006	455
43062002	156, 259
43064002	156, 259
43093004	249
43093005	249
43093006	249
43093007	249
43093008	249
43093009	249
43093010	249
43093011	249
43093012	249
43093013	249
43093045	249
43093055	249
43103206	249
43103207	249
43103208	249
43153002	259
43153003	259
43153004	259
43153005	259
43153006	259
43153007	259
43153008	259
43153010	259
43153012	259
43153014	259
43153017	259
43153019	259
43153022	259
43153024	259
43153027	259
43153090	259
43153130	259
43153150	259
43153250	259
43213002	261
43213003	261
43213004	261
43213005	261
43213006	261
43213007	261
43213008	261
43213010	261
43213012	261
43213014	261
43213015	261
43213017	261
43213019	261
43213025	261
43223009	261
43223010	261
43223015	261
43223020	261
43223025	261
43223027	261
43223030	261
43223040	261
43233060	250
43233070	250
43233080	250
43233090	250
43233100	250
43233110	250
43233120	250
43233130	250
43253020	249
43253025	249
43253030	249
43253040	249
43253050	249
43253060	249
43253080	249
43253100	249
43263002	262
43263003	262
43263004	262
43263005	262
43263006	262
43263008	262
43263010	262
43263012	262
43263015	262
43263025	262
43263130	262
43273009	262
43273010	262
43273015	262
43273020	262
43273025	262
43273027	262
43273030	262
43273040	262
43293008	250
43293009	250
43293010	250
43293015	250
43293020	250
43293025	250
43293027	250
43293030	250
43293040	250
43293045	250
43293050	250
43330607	138
43330809	138
43331011	138
43331213	138
43331415	138
43331617	138
43331719	138
43331819	138
43332022	138
43332123	138
43332426	138
43332427	138
43332428	138
43333032	138
43333236	138
43333641	138
43334146	138
43334650	138
43335560	138
43412428	137
43413234	137
43413638	137
43553003	260
43553004	260
43553005	260
43553006	260
43553008	260
43553009	260
43553010	260
43553012	260
43553014	260
43553016	260
43553020	260
43553024	260
43553032	260
43553036	260
43560004	156, 259
43560005	156, 259
43560006	156, 259
43564004	156, 259
43564005	156, 259
43564006	156, 259
43573004	262
43573005	262
43573006	262
43573007	262
43573008	262
43573009	262
43573010	262
43573012	262
43573014	262
43573016	262
43573020	262
43573024	262
44010001	139
44010002	139
44010003	139
44180010	496
44180013	496
44180014	496
44180017	496
44180019	496
44180022	496
44190010	496
44190013	496
44190014	496
44190017	496
44190019	496
44190022	496
44700018	456
44730810	455
46203035	242
46203040	242
46203055	242
46203065	242
46203080	242
46203100	242
46203120	242
46213025	242
46213035	242
46213040	242
46213055	242
46213065	242
46213080	242
46223208	242
46223210	242
46223212	242
46223314	242
46223355	242
46223365	242
46223440	242
46223500	242
46223520	242
46223540	242
46223555	242
46223565	242
46223580	242
46233003	263
46233004	263
46233005	263
46233006	263
46233008	263
46233010	263
46283025	243
46283035	243
46283040	243
46283055	243
46283135	243
46283155	243
46303000	244
46303001	244
46303002	244
46303003	244
46313001	244
46313002	244
46323201	245
46323202	245
46323203	245
46323301	245
46323302	245
46323303	245
46323304	245
46363002	248
46363004	248
46363006	248
46363008	248
46363010	248
46363016	248
46403000	246
46403001	246
46403002	246
46403003	246
46503005	247
46503006	247
46503007	247
46503008	247
46503009	247
46503010	247
46503015	247
46503020	247
46503025	247
46503027	247
46503030	247
46503040	247
46503045	247
46503115	247
46503120	247
46503125	247
46503130	247
46563008	247
46563009	247
46563010	247
46563015	247
46563020	247
46563025	247
46563027	247
46563030	247
46563040	247
46563045	247
46603025	500
46603030	500
46603035	500
46603040	500
46603055	500
46603065	500
46603080	500
46613035	500
46613040	500
46613055	500
46613065	500
46653000	501
46653001	501
46653002	501
46653003	501
46663001	501
46663002	501
46703000	501
46703001	501
46703002	501
46713001	501
46713002	501
46753008	502
46753010	502
46753015	502
46753020	502
46753025	502
46753030	502
46763010	502
46763015	502
46763020	502
46763025	502
46763030	502
47241045	243
47241060	243
47241080	243
47341001	245
47341002	245
47441001	246
47441002	246
47513001	243
47513002	243
47513003	243
47513004	243
47513005	243
47513006	243
47513007	243
47513008	243
47523001	246
47523010	246
47523020	246
47533007	248
47533009	248
47533013	248
47533015	248
47540004	247
47540005	247
47540006	247
47540007	247
47540008	247
47540009	247
47540010	247
47540015	247
48010006	139
48010007	139
48010008	139
48030001	136
48030002	136
48030003	136
48030004	136
48201035	243
48201040	243
48201065	243
48201080	243
48201100	243
48202055	243
48202100	243
48301000	245
48301001	245
48301002	245
48301003	245
48301004	245
48401001	246
48401002	246
48560006	248
48560007	248
48560008	248
48560009	248
48560010	248
48560015	248
48560020	248
48560025	248
48560027	248
48560030	248
48560040	248
50010004	27
50010010	27
50010020	27
50010030	27
50021003	37
50021004	37
50021006	37
50030080	26
50100001	27
50180080	30
50181005	33
50181010	33
50181012	33
50181020	33
50181040	33
50181065	33
50181080	33
50181100	33
50181102	33
50181365	33
50184001	28
50184002	28
50184004	28
50184005	29
50184010	29
50184012	29
50184020	29
50184030	29
50184040	29
50184065	29
50184565	29
50190081	32
50200081	32
50204005	31
50204015	31
50204020	31
50204030	31
50204115	31
50204120	31
50240015	27
50450080	26
50581005	34
50581010	34
50581020	34
50581040	34
50581102	34
50584001	28
50584002	28
50584004	28
50584005	29
50584010	29
50584012	29

Product no.	Page
50584020	29
51040007	20
51040015	20
51040030	20
51040060	20
51060003	21
51060012	21
51060030	21
51060050	21
51060100	21
51460003	21
51460012	21
51460050	21
52100050	52
52101050	102
52110051	49
52110052	50
52110054	49
52110056	50
52110058	49
52110061	49
52110063	50
52110091	99
52110092	100
52110191	99
52110192	101
52110220	48
52110291	102
52110491	96
52111057	50
53030800	76
53031350	76
53032000	76
53033000	76
53035000	76
54010001	48
54010002	48
54100060	49
54100062	48
54100070	52
54100071	52
54100072	52
54100073	52
54100074	52
54101195	48
58170108	65
58170110	65
58170112	65
58170113	65
58170117	65
58170119	65
58170122	65
58170217	66
58170219	66
58170221	66
58170222	66
58170224	66
58170227	66
58211007	61
58211008	61
58211009	61
58211010	61
58211011	61
58211012	61
58211013	61
58211014	61
58211015	61
58211016	61
58211017	61
58211018	61
58211019	61
58211024	69
58211027	69
58211030	69
58211032	69
58211034	69
58211036	69
58211041	69
58211046	69
58211050	69
58211055	69
58211060	69
58214013	66
58214014	66
58214015	66
58214016	66
58214017	66
58214018	66
58214019	66
58214021	66
58214022	66
58214024	66
58214025	66
58214027	66
58214030	66
58214032	66
58214034	66
58214036	66
58214038	66
58214041	66
58218024	71
58218027	71
58218030	71
58218032	71
58218034	71
58218036	71
58218041	71
58218046	71
58218050	71
58218055	71
58218060	71
58221007	62
58221008	62
58221010	62
58221011	62
58221012	62
58221013	62
58221014	62
58221015	62
58221016	62
58221017	62
58221018	62
58221019	62
58221021	62
58221022	62
58221024	70
58221027	70
58221030	70
58221032	70
58221034	70
58221036	70
58221041	70
58221046	70
58221050	70
58221055	70
58221060	70
58224013	67
58224014	67
58224015	67
58224016	67
58224017	67
58224018	67
58224019	67
58224021	67
58224022	67
58224024	67
58224027	67
58224028	67
58224030	67
58224032	67
58224034	67
58224036	67
58224041	67
58228024	71
58228027	71
58228030	71
58228032	71
58228034	71
58228036	71
58228041	71
58228046	71
58228050	71
58228055	71
58228060	71
58231010	63
58231011	63
58231012	63
58231013	63
58231014	63
58231016	63
58231017	63
58231018	63
58231019	63
58231021	63
58231022	63
58231024	63
58240004	61
58240005	61
58240010	61
58240020	66
58240040	66
58240080	70
58240100	69
58241004	61
58241005	61
58241100	105
58243004	105
58243005	105
58243012	105
58243020	105
58243040	105
58250004	61
58250005	61
58250010	61
58250020	65
58250040	65
58250065	65
58250080	70
58250100	69
58251065	69
58253004	60
58253005	60
58253010	60
58253020	65
58254004	60
58255004	60
58255005	60
58261010	64
58261040	68
58262610	64
58270010	64
58270040	68
58270100	70
58290010	64
58290012	64
58290040	68
58290041	68
58290042	68
58290080	71
58291006	62
58291008	62
58291010	62
58291012	62
58291014	62
58291100	70
58294014	67
58294018	67
58294020	67
58294024	67
58521087	104
58521088	104
58521089	104
58521090	102
58522089	199
58523089	104
58524089	104
58524090	104
58524091	104
58611016	62
58611020	62
58611024	62
58611028	62
58611032	62
58611034	62
58611036	62
58611038	62
58611040	62
58614028	66
58614032	66
58614034	66
58614036	66
58614038	66
58614040	66
58614042	66
58614044	66
58614046	66
58614048	66
58614052	66
58620007	63
58620008	63
58620009	63
58620010	63
58620013	63
58621016	62
58621020	62
58621024	62
58621028	62
58621032	62
58621034	62
58621036	62
58621038	62
58621040	62
58621042	62
58621044	62
58621216	63
58621220	63
58621224	63
58621228	63
58621232	63
58621234	63
58621236	63
58624032	67
58624034	67
58624036	67
58624038	67
58624040	67
58624042	67
58624044	67
58624046	67
58624048	67
58628046	71
58628050	71
58631024	63
58631028	63
58631032	63
58631034	63
58631036	63
58631038	63
58631040	63
58950001	81
58950002	81
58950003	81
58950004	81
58950005	81
58950006	81
58950007	81
58950008	81
58950009	81
58950010	81
58950011	81
58950012	81
58950013	81
58950014	81
58950015	81
58950016	81
58950017	81
58950018	81
58950019	81
58950020	81
58950021	81
58950022	81
58950025	81
58950026	81
59010001	80
59010003	80
59010005	80
59010007	80
59010008	80
59010011	80
59010014	80
59010015	80
59010016	80
59011003	105
59011008	105
59011011	105
59011012	105
59011014	105
59030800	77
59031350	77
59032000	77
59033000	77
59035000	77
59191005	78
59191030	79
59191080	79
59220007	48
59251005	78
59251010	79
59251020	79
59251040	79
59251065	79
59300039	77
59300067	77
59300068	77
59300069	77
59300070	77
60030000	464
60030001	464
60030002	464
60030003	464
60031000	464
60032000	464
60033000	464
65156125	398
65434100	408
65434101	408
65434102	408
65434103	408
65434104	408
65436100	409
65436101	409
65436102	409
65436103	409
65436104	409
65444101	409
65444111	409
65444121	409
65444131	409
65444141	409
65446101	409
65446111	409
65446121	409
65446131	409
65446141	409
65454100	409
65454101	409
65454102	409
65454103	409
65454104	409
65456100	410
65456101	410
65456102	410
65456103	410
65456104	410
65464101	410
65464111	410
65464121	410
65464131	410
65464141	410
65466101	410
65466111	410
65466121	410
65466131	410
65466141	410
65490315	401
65490420	401
65490555	401
65516175	398
65516240	398
65516300	398
65517250	506
65560310	402
65560420	402
65560560	402
65570320	402
65570416	402
65570535	402
65580250	402
65580300	402
65580350	402
65580450	402
65580600	402
65590250	402
65590300	402
65590350	402
65590450	402
65590600	402
65622250	410
65632175	411
65632250	411
65642145	411
65642175	411
65642250	411
65642300	411
65712165	411
65726180	398
65726240	398
65726300	398
65735180	401
65735250	401
65735300	401
65751220	398
65751280	398
65765231	406
66170180	397
66170215	397
66170235	397
66305220	478
66307220	506
66383220	397

Product number index

Product no.	Page
66601220	406
66601250	406
66601280	406
66611180	406
66611200	406
66624300	407
67001160	394
67001180	394
67001200	394
67003160	394
67003180	394
67003200	394
67004160	504
67004180	504
67004200	504
67076000	411
67086000	412
67096000	412
67106000	413
67116000	413
67201140	395
67201160	395
67201180	395
67203140	395
67203160	395
67203180	395
67204140	505
67204160	505
67204180	505
67211160	396
67211180	396
67211200	396
67213160	396
67213180	396
67213200	396
67214160	505
67214180	505
67214200	505
67301160	394
67301200	394
67303160	394
67303200	394
67304160	504
67304200	504
67311160	395
67311200	395
67313160	395
67313200	395
67314160	505
67314200	505
67701160	396
67703160	396
67801160	397
67803160	397
67804160	505
69131000	465
69131001	465
69131002	465
69132000	465
69132001	465
69133000	465
69133001	465
69133002	465
69134000	465
69134001	465
69135000	465
69135001	465
69136000	465
69620001	411
69760001	406
70010006	469
70010008	469
70010010	469
70010012	469
70020002	469
70020003	469
70020004	469
70020005	469
70020007	469
70020008	469
70040003	469
70040004	469
70040005	469
70050001	469
70050002	469
70050005	469
70060002	469
70060003	469
70060007	469
70060008	469
70060009	469
70060010	469
70070001	470
70070002	470
70070003	470
70070004	470
70070005	470
70070006	470
70070008	470
70070009	470
70070010	470
70070011	470
70070012	470
70070013	470
70071152	470
70080001	469
70080002	469
70090001	470
70090002	470
70090003	470
70090004	470
70090005	470
70090006	470
70090007	470
70090008	470
70110009	468
70110010	468
70110011	468
70110013	468
70110015	468
70110016	468
70110017	468
70111010	468
70111015	468
70111020	468
70120001	468
70120002	468
70120003	468
70120004	468
70120005	468
70120006	468
70130002	441
70130003	441
70130004	441
70130005	441
70130006	442
70130007	442
70130008	442
70130011	442
70130012	442
70130013	442
70140001	467
70140002	467
70140003	467
70140004	467
70160027	467
70160032	467
70160035	467
70160040	467
70160050	467
70171027	467
70171032	467
70171035	467
70171040	467
70171050	467
70171060	467
70190130	468
70190140	468
70191035	468
70191050	468
70191060	468
70210002	443
70210005	443
70210006	443
70210008	444
70210010	443
70210012	444
70220001	442
70220002	443
70220003	444
70240040	467
71010001	481
71010002	481
71010003	481
71010004	481
71010005	481
71010006	481
71020001	426
71020002	426
71020003	426
71020004	426
71020005	426
71020006	426
71025001	428
71025002	428
71025101	427
71025102	427
71030001	426
71030002	426
71030003	426
71030004	426
71030005	426
71035001	428
71035002	428
71035101	427
71035102	427
71040001	429
71040002	429
71040003	429
71040004	429
71040005	429
71040006	429
71040007	429
71040008	429
71040009	429
71040014	429
71040101	430
71040102	430
71040103	430
71040201	430
71040202	430
71050001	481
71050002	481
71050003	481
71050004	481
71050005	481
71050016	431
71050017	431
71050018	431
71050019	431
71050101	431
71050102	431
71050103	431
71050104	431
71050201	431
71050202	431
71050203	431
71070000	453
71070001	453
71070002	453
71070003	453
71070004	454
71080001	454
71080002	454
71080004	454
71120011	429
71120012	429
71120013	429
71250011	481
71250012	481
71310001	482
71310002	482
71310003	482
71310004	482
72033101	448
72053104	474
72053105	474
72060100	474
72060200	475
72060201	475
72060202	475
72060203	475
72060204	475
72063101	474
72063103	474
72063104	474
72063105	474
72083103	474
72090000	445
72090002	445
72090003	445
72101002	477
72101003	477
72101004	477
72123100	476
72133100	476
72143100	476
72160000	444
72173102	476
72200001	444
72200002	444
72210002	477
72211000	477
72230001	477
72260001	446
72270007	446
72270008	446
72313101	448
73013001	244
73103003	248
73103005	248
73213101	244
73213102	244
73273001	258
73273002	258
73273003	258
73273004	258
73282001	258
73282002	258
74010401	455
74010601	455
74010604	455
74010605	455
74060001	456
74140000	449
74140001	449
74140003	449
74140005	449
74152001	449
74152002	449
74152003	449
74152005	449
74160001	452
74200002	457
74240001	450
74240002	450
74240005	450
74270001	447
74270002	448
74270003	449
74270004	448
74270005	475
74270006	448
74280001	447
74280005	447
74290001	449
74290002	449
74310001	457
74340001	457
74370001	455
74543101	476
74570001	449
74590003	446
74593100	447
74593101	446
74593102	446
74610028	438
74610039	438
74612006	437
74612028	438
74615027	438
74620001	436
74620002	455
74620003	436
74620004	436
74620005	436
74620006	436
74620007	437
74620008	437
74620009	437
74620011	456
74620012	437
74620024	437
74620025	437
74620026	437
74620027	437
74620034	438
74620035	438
74620037	438
74620041	438
74640002	436
75230001	445
75230002	445
75240001	445
75240002	445
75270003	478
75271000	478
76294003	454
76413001	454
76413021	454
76460000	457
76460012	458
76460013	457
76480001	445
76500001	456
76521001	456
76521002	456
76540001	458
76540002	458
76540003	458
77010001	489
77020000	478
77020700	506
77020701	506
77030700	506
77030701	506
77030702	507
77030705	507
77030706	507
77030708	507
77030709	507
77040010	480
77040011	480
77070000	489
77090000	475
77090001	475
77090003	475
77090010	475
77090101	475
77100000	479
77100001	479
77101000	466
77101001	466
77101002	466
77101003	466
77101010	466
77101100	466
77101101	466
77101102	466
77101103	466
77110002	489
77130000	458
77210002	296
77250000	476
77260025	484
77260026	484
77260027	484
77260060	484
77260200	484
77270003	481
77371001	481
77371002	480
77371004	480
77371005	480
77380001	459
77390001	457, 482
77390002	457, 482
77401001	483
77401030	483
77401032	483
77401040	483
77401045	483
77401050	483
77401057	483
77401060	483
77401103	484
77402550	483
77407203	484
77440001	452
77440002	452
77450001	480
77460001	480
77470001	476
77470003	480
77480002	483
77490006	485
77490010	485
77490012	485
77490013	485
77490014	486
77490015	488
77490016	486
77490017	486
77490018	486
77490019	488
77490020	488
77500001	484
77510001	484
77560002	459
77592000	474
77592001	474
77593000	474
77620010	479
77621001	478
77621002	478
77621003	479

Product no.	Page
77621004	479
78033102	448
78600001	436
78600002	436
78600003	436
78600004	436
78600005	436
78600006	436
78610001	436
79040027	467
79040032	467
79040035	467
79040040	467
79040050	467
79050027	468
79050032	468
79050035	468
79050040	468
79050050	468
79050060	468
79060001	445
79060002	445
79060003	445
79060004	444
79060012	445
79060013	445
79091030	468
79091035	468
79091040	468
79091050	468
79091060	468
79150001	456
79160001	469
79180001	477
79180002	477
79250001	478
79250010	479
79251003	479
79251004	479
79260001	446
79270011	448
79270015	475
79310001	449
79401001	483
79401030	483
79401040	483
79401050	483
79401055	484
79401060	483
79540001	458
80020001	298
80310030	298
80310060	298
80310090	298
80320030	298
80320060	298
80340040	298
80340050	298
80350017	299
80350020	299
80360012	299
80360018	299
80360024	299
80380030	299
80400003	157, 220
80410235	299
80450003	180, 220
80500005	199, 220
81050000	292
81060000	292
81070000	292
81080000	292
81091004	294
81091009	294
81091301	296

Product no.	Page
81091304	296
81091306	296
81091322	296
81091323	296
81091333	296
81091334	296
81091335	296
81200154	283
81200160	284
81200161	284
81200162	284
81200163	284
81200164	284
81200165	284
81200166	284
81200167	284
81200168	284
81200169	285
81200170	285
81200171	285
81200172	285
81200173	285
81200174	285
81231040	295
81231041	295
81231042	295
81231043	295
81231044	295
81231045	295
81231046	295
81231047	295
81231048	295
81231060	295
81231100	53
81231101	53
81231102	53
81231103	53
81300612	283
81370002	53
81370003	53
81483004	289
81483230	296
81483260	296
81483295	296
81484001	290
81484002	290
81485006	299
81485012	299
81490001	291
81490005	291
81490007	291
81500003	53
81500004	53
81620004	292
81620007	293
81620009	293
81620010	294
81620026	494
81620136	293
81620137	293
83071002	53
83071004	53
83071030	53
83071031	53
83812070	289
83822520	459
85010621	286
85010625	286
85010630	287
87100010	403
87100015	403
87100020	403
87100025	403
87100050	402
87100060	402

Product no.	Page
87100065	402
87100070	402
87110010	403
87110015	403
87110020	403
87110025	403
87110030	403
87110075	402
87110080	402
87111005	404
87111010	404
87111015	404
87111020	404
87111025	404
87115005	404
87115010	404
87115015	404
87115020	404
87115025	404
87127005	405
87127010	405
87127015	405
87127020	405
87127025	405
87129005	405
87129010	405
87130010	405
87130015	405
87130020	405
87130025	405
87130030	405
87130110	405
87130115	405
87130120	405
87130125	405
87130130	405
87156205	408
87156210	408
87172100	221
87172190	221
87173071	221
87180305	401
87180310	401
87180315	401
87180900	401
87182005	400
87182010	400
87182015	400
87182900	400
87184010	400
87186010	401
87188005	399
87188010	399
87188015	399
87188021	399
87245005	489
87245006	489
87245010	489
87245011	489
87245012	489
87245015	489
87245016	489
87245020	489
87245021	489
87245022	489
87246005	489
87246010	489
87430005	415
87430010	415
87430015	415
87430020	415
87430025	415
87430136	415
87430137	415
87430138	415

Product no.	Page
87430139	415
87430140	415
87433020	416
87433040	416
87433125	416
87433145	417
87434025	417
87434081	417, 419
87434135	414, 417
87435005	418
87435010	418
87435133	418
87436010	419
87436132	419
87437002	416
87437005	416
87437131	416
87437133	415, 416
87438050	414
87439005	417
87439010	417
87439015	417
87439020	417
87439131	417
87439132	417
87439133	417
87439134	417
87445010	415
87445135	415
87480010	419
87480133	419
87510005	407
87510010	407
87510015	407
87510020	407
87510105	407
87510110	407
87510115	407
87510120	407
87511005	408
87511105	408
87512000	408
87512020	408
87512220	407
87514105	406
87515005	406
87515010	406
87515020	406
87700050	418
87950010	404
87950015	404
87950020	404
87951010	404
87951015	404
87951020	404
87952005	403
87952010	403
87952015	403
87952020	403
87952030	403
87966000	399
87966005	399
87966010	399
87966015	399
87966021	399
87966030	400
87966031	400
87966032	400
87966164	399
87966165	399
87966166	399
87966167	399
87980005	415
87980010	415
87980015	415

Product no.	Page
87980020	415
87980050	414
87980082	418
87980100	420
87980135	416
87980136	414, 416
87980137	416
87980138	416
87984050	414
87985010	418
87985135	418
87991115	405
87991500	400
87991900	403
87991952	403
87996010	419
87996135	419
89010040	289
89010041	289
89010042	290
89010100	296
89011053	291
89480003	291
89932000	139
90432719	290
90432727	290
90432728	290
90432731	291
90432736	290
90432779	484
90432802	289
90432806	289
91050002	480
91222607	166, 223
96003010	157, 180, 199, 220
96010107	161, 222
96010120	163, 222
96010127	159
96011113	165, 222
96011119	157, 223
96011124	158, 222
96011134	160, 222
96011136	159, 222
96011137	159, 222
96011138	160, 222
96011160	166, 223
96011162	161, 222
96011180	159, 222
96011181	165, 222
96011182	160, 222
96012047	165, 223
96013702	164, 222
96015107	158, 222
96015205	161, 222
96015208	158, 222
96015310	157
96016302	158, 222
96016304	155, 223
96016410	157
96017709	156
96020107	182, 223
96021001	183
96021109	180, 223
96021122	182, 223
96021180	181, 223
96021223	182, 223
96021236	184, 223
96022020	495
96022119	182, 223
96022133	183, 223
96022702	183
96023132	184, 223
96024132	181, 223
96025204	181, 223

Product no.	Page
96025207	181, 223
96030107	201, 224
96030140	201, 224
96030212	205
96031004	205
96031136	201, 224
96031236	202, 224
96031239	203, 224
96031240	204, 224
96031407	201, 224
96031409	203, 224
96031435	200, 225
96031436	202, 224
96031439	202, 224
96031440	202, 224
96031446	200, 225
96031447	200, 225
96031448	203, 224
96031480	203, 224
96031501	204, 224
96031503	206, 224
96031508	205, 223
96032005	205, 224
96032301	204, 224
96032703	205
96033606	206, 224
96033704	205, 225
96035125	200, 224
96050103	215, 225
96050104	215, 225
96051010	156
96052010	180
96053010	199
96054101	216, 225
96054103	216, 225
96060101	219, 225
96060103	219, 225
96080110	267
96080115	267
96080121	268
96080122	268
96080156	268
96081113	268
96090005	54
96090006	54
96112701	155
96121002	219
96121003	219
96122701	180
96182203	269
96190800	196
96190801	196
96221010	380
96231101	233
96231501	233
96323001	277
96400304	111
96400305	111
96400306	111
96400307	111
96400314	111
96400651	113
96400653	113
96400801	115
96400802	115
96400803	115
96400804	115
96400805	115
96400808	115
96400813	115
96400816	115
96400902	120
96401004	119
96401005	119
96401006	119

Product number index

Product no.	Page
96401007	119
96401705	129
96401712	129
96401715	129
96404301	496
96404302	497
96404303	507
96404306	111
96404307	111
96404654	113
96404803	116
96404804	116
96404812	116
96410405	122
96410406	122
96410407	122
96410408	122
96410409	122
96410501	125
96410503	125
96410704	123
96411003	132
96411005	132
96411006	132
96411301	130
96411302	130
96411705	127
96411708	129
96411709	128
96411712	127
96411713	128
96411715	127
96414402	122
96414405	122
96415601	131
96430101	137
96431202	139
96431205	139
96431500	260
96432100	261
96432200	261
96432600	263
96432603	263
96432700	262
96435500	260
96435505	259
96435506	260
96435700	263
96469115	255
96469215	255
96469316	255
96469415	256
96469511	504
96469515	504
96469625	255
96469915	256
96479715	257
96479716	257
96479803	258
96489110	256
96489210	257
96489910	257
96500001	55
96500002	55
96500100	46
96500901	46
96500902	46
96500904	46
96500906	46
96500910	46
96500920	46
96500940	46
96500965	46
96500980	46
96501001	47
96501002	47
96501004	47
96501006	47
96501010	47
96501020	47
96501040	47
96501054	30
96501065	47
96501080	47
96501100	47
96501606	45
96501620	45
96501640	45
96501710	43
96501720	43
96501740	43
96501765	43
96501800	43
96501810	43
96501820	43
96501840	43
96501865	43
96501880	43
96501965	43
96502001	32
96502053	57
96502065	43
96502080	43
96502100	43
96502105	35
96502110	35
96502120	35
96502140	34
96502265	34
96503005	35
96503010	35
96503012	35
96503020	35
96503040	35
96503065	35
96503080	35
96503100	35
96503105	34
96503110	34
96503120	34
96503465	35
96504002	30
96504004	30
96504005	30
96504010	30
96504012	30
96504020	30
96504030	30
96504040	30
96504502	42
96504602	42
96507214	56
96507216	56
96510000	54
96510001	54
96510700	22
96510712	22
96510730	22
96510760	22
96511700	22
96511712	22
96511730	22
96511760	22
96521000	101
96521021	101
96521022	101
96521023	101
96521026	101
96521028	101
96521029	101
96521068	100
96521069	100
96521070	100
96521072	87
96521074	100
96521076	93
96521077	93
96521078	95
96521079	95
96521080	87
96521082	87
96521083	87
96521084	87
96521085	87
96521086	87
96521092	92
96521093	94
96521094	96
96521161	49
96521206	85
96521207	85
96521208	85
96521209	85
96521210	85
96521211	85
96521400	84
96522023	101
96524001	98
96524002	98
96524004	98
96524006	98
96524010	98
96524011	98
96524020	98
96524040	98
96524065	98
96524080	98
96524100	98
96524300	98
96531500	76
96550125	498
96550150	498
96583005	36
96583010	36
96583020	36
96583040	36
96583629	51
96583630	51
96583631	51
96585224	102
96585235	50
96700600	471
96700601	471
96700701	470
96700703	470
96700710	471
96700712	471
96710101	481
96710505	482
96713025	482
96722700	475
96722801	477
96722802	466
96722803	466
96742711	447
96746230	436
96746231	436
96746232	436
96746233	436
96746234	436
96746235	436
96747201	440
96747208	440
96747304	440
96830041	495
96830042	496
96830045	497
96830117	375
96830118	377
96830119	377
96830120	373
96830121	373
96830122	376
96830123	375
96830124	373
96830125	373
96830126	376
96830127	376
96830128	374
96830129	376
96830130	374
96830131	377
96830132	374
96830163	207
96830164	116
96830166	122
96830167	112
96830174	117
96830192	168
96830193	121
96830195	138
96830217	163
96830218	185
96830221	216
96830223	353, 472
96830264	167, 211
96830265	269
96830266	421
96830267	120
96830268	351
96830269	352
96830270	351
96830271	352
96830272	120
96830273	420
96830274	167, 211
96830275	258
96830278	387
96830351	116
96830352	209
96830353	112
96830354	209
96830356	122
96830357	185
96830360	209
96830361	353, 472
96830362	210
96830363	211
96830364	350
96830365	167
96830366	162
96830367	185
96830370	185
96830371	186
96830450	352
96830601	162
96830602	184
96830603	210
96830605	121
96830608	420
96830609	350
96830620	353, 472
96830622	421
96830649	128
96830650	127
96830651	130
96830652	129
96830653	128
96830654	129
96830706	253
96830877	207
96830885	117
96831100	370
96831101	371
96831102	371
96831103	371
96831104	372
96831105	372
96831106	370
96831107	371
96831108	372
96831109	372
96831168	251
96831179	252
96831196	252
96831586	350
96832095	168
96832096	117
96832098	252
96832099	254
96832100	420
96838116	206
96838117	206
96838175	210
96838176	350
96838177	208
96838179	421
96838180	420
96838181	354, 472
96838182	112
96838183	116
96838184	253
96838187	111
96838191	209
96838193	494
96838194	353, 473
96838278	251
96838751	131
96838752	184
96838753	254
96838754	471
96838755	253
96838757	253
96838758	126
96838759	351
96838760	208
96838761	254
96838762	207
96838763	207
96838764	138
96838766	503
96838767	252
96838768	264
96838769	251
96838771	119
96838772	183
96838773	269
96838774	132
96838776	208
96838777	233
96838778	117
96838779	112
96838780	208
96838781	210
96838782	208
96838784	251
96838785	503
96838786	254
96838788	264
96838789	351
96838791	233
96838792	234
96838793	502
96838796	135
96838797	135
96838798	421
96838814	503
96838815	502
96838816	503
96894805	296
96894809	296
97830207	369
97830208	343
97830209	341
97830217	387
97830254	324
97830255	325
97830256	326
97830257	327
97830258	328
97830265	345
97830411	330
97830600	336
97830606	338
97830607	340
97830700	381
97830701	381
97830702	382
97830802	348
97830803	346
97830820	332
97830821	334
97830822	335
97840312	355
97841210	354
97841311	356
97841418	357
97842613	355
97842714	356
97842803	368
97843101	357
97846008	359
97846010	359
97846011	358
97846012	358
98742711	447
98810302	386
98810303	495
98811908	164, 222
98811909	204, 224
98812203	470
98814801	384
98814803	383
98814910	366
98814915	364
98814930	360
98814935	362
98819801	164, 222
98830004	323
98830176	304
98830177	305
98830178	306
98830179	318
98830180	308
98830181	321
98830182	378
98830183	378
98830184	379
98830185	379
98830192	310
98830193	311
98830194	313
98830195	316
98830203	307
98830204	314
98830205	319
98830234	312

Model number index

Model	Page
BLE-MODUL 714	48
CORONA 23	123
CORONA 23/8	123
DAkkS	81
ELECTRIC 12	113
ELECTRIC 12a	113
FastRatch 240	132
FLEXI 29	137
FLEXI 29/7	137
FLEXI 29a	137
KH 91	289
KM STW	459
LE 912	289
LH 928	289
LH 928/A	290
Li-Ion AA 3,7V / 800mAh	48
MANUTORK® 7791	99
MANUTORK® 7792	100
MOTOR 10	110, 111
MOTOR 10a	110, 111
MP100-1500	76
MP300	76
OPEN BOX 13	114, 115
OPEN BOX 13a	114, 116
OPEN BOX 14	118, 119
OPEN BOX 16	120
OPEN BOX 16/5	120
OPEN RATCH 17	127
OPEN RATCH 17a	128
OPEN RATCH 17F	129
OPEN RING 24	125, 126
OPEN RING 24a	126
PH 1220-1223 PH 1231-1234	265
PRH 925	289
PZ 1221-1223	265
R 95	291
R 95/98S	291
R 98	291
R 630	291
R 13217	296
Rad-Set 701	55
Rad-Set 730/2	55
SD10351N	448
SDH 922	290
SDH 923	290
SmartCheck Angle	84
SmartCheck USB	85
SR290-393	77
StahlwilleSTABIL® 8	136
StahlwilleSTABIL® 20	121, 122
StahlwilleSTABIL® 20a	122
StahlwilleSTABIL® 21	125
STARTER 27	123
TA 13217	296
TBT 13216	294
TCS 1/4 + 10760	350
TCS 1/4 QR + 10760	350
TCS 3 821/4	421
TCS 4 821/22	120
TCS 5 821/27	351
TCS 6 821/7	352
TCS 7 821/9	351
TCS 8 821/21	352
TCS 9 821/28	120
TCS 10/13/24/30	121
TCS 10 821/4	420
TCS 12/13/14/29	121
TCS 25/7	131
TCS 40/35/9	162
TCS 40/35/9QR	162
TCS 40/41/44/8	163
TCS 40/41/44/8QR	167
TCS 40/45/50/89/19	168
TCS 40/52/6QR	167, 211
TCS 40/456/52/78/19	168
TCS 49/1049/2049/45TX/49TX	183
TCS 50/51/52/32	209
TCS 50/52/30/6 MF	209
TCS 50/52/30/6QR	209
TCS 50a/17	208
TCS 50IMP/19/2	233
TCS 50IMP/51IMP/19	233
TCS 50TX/54TX/17	207
TCS 51/11	208
TCS 52/14/4	210
TCS 52/14/4QR	209
TCS 52/17	208
TCS 54/54KK/14	207
TCS 54/54TX/18	208
TCS 54/54TX/44/44K/44KTX/40	167, 211
TCS 54/54X/16	207
TCS 54/2309K/12506	207
TCS 54IMP/2307TX/15	234
TCS 54KK/5	206
TCS 55/11/6	216
TCS 102-108/11	471
TCS 102-108/10956/10960/18	353, 472
TCS 102-108/10959/10961/16	350
TCS 102-108/10959/10961/12718/13	353, 472
TCS 102-108/10961/10	353, 472
TCS 102-109/10956/10961/6	354, 472
TCS 456/16/4 MF	185
TCS 456/16/4QR MF	186
TCS 456/16/6	184
TCS 456/16/6QR	185
TCS 456/16/7	185
TCS 456/16/7QR	185
TCS 456/31/8	184
TCS 512/6	210
TCS 512/6QR	210
TCS 512/9	210
TCS 512/9QR	211
TCS 806/9	323
TCS 820/2	324
TCS 821/6	325
TCS 821/7	326
TCS 821/10	327
TCS 821/12	328
TCS 1054/2054	206
TCS 1054/2054/10	208
TCS 1100 Porsche	330
TCS 1120/1 VW	334
TCS 1120/2 AUDI	335
TCS 1120/3 VW/AUDI	350
TCS 1120 VW/AUDI	332
TCS 1202/4000/10766/39	264
TCS 2500 BMW	336
TCS 2501 BMW	338
TCS 2502 BMW	340
TCS 3022 Mercedes Benz	341
TCS 3026 Mercedes Benz	343
TCS 4008/8/52	269
TCS 4008/4009/1206/4	269
TCS 4025/3	135
TCS 4026/3	135
TCS 4620/4630/7	251
TCS 4620/4640	251
TCS 4620/4640/4734/10554/8	258
TCS 4620/4660 VDE	252
TCS 4620/4660 VDE/10767	251
TCS 4620-4734/8	251
TCS 4621/4734/16	252
TCS 4622-4632/4650/10760/10766/20	252
TCS 4650	252
TCS 4660/4665 VDE	503
TCS 4661/4666 VDE	503
TCS 4661/4671 VDE	503
TCS 4665/4670 VDE	503
TCS 4675 VDE	502
TCS 4676/5 VDE	502
TCS 4724/4840/10767	253
TCS 4820/4830	253
TCS 4856	253
TCS 6534-6545/6	420
TCS 6543-6546/4	420
TCS 6543-6564/3	420
TCS 6551-6730/4	421
TCS 6572-6730/4	421
TCS 6707-6711	421
TCS 10760-10771/26	264
TCS 10768/6	254
TCS 10768/8	254
TCS 10769/10771/10	254
TCS 10956/10961/2	353, 473
TCS 11095-13110/8	351
TCS 12025-13110/11	351
TCS 12160 VDE	496
TCS 12161 VDE	497
TCS 12171/19/4 VDE	495
TCS 12500N/5	253
TCS 12507/5	254
TCS 13214/1 WT/LM 1	370
TCS 13214/1 WT/LM 2	371
TCS 13214/1 WT/LM 3	371
TCS 13214/1 WT/LM 4	371
TCS 13214/1 WT/LM 5	372
TCS 13214/1 WT/LM 6	372
TCS 13214a/1 WT/LM 1	370
TCS 13214a/1 WT/LM 2	371
TCS 13214a/1 WT/LM 5	372
TCS 13214a/1 WT/LM 6	372
TCS 13214a WW	348
TCS 13214 WW	346
TCS 13217 WT FastRatch 240/10	374
TCS 13217 WT MOTOR 10/10 6-32	373
TCS 13217 WT MOTOR 10a/9	373
TCS 13217 WT OPEN BOX 13/18 6-24	373
TCS 13217 WT OPEN BOX 13a/22	373
TCS 13217 WT OPEN RATCH 17/12	374
TCS FastRatch 240/6	132
TCS FLEXI 29/6 8x9-18x19	138
TCS FLEXI 29/7 8x9-20x22	138
TCS MOTOR 10/10 6x7-24x27	111
TCS MOTOR 10/10 6x7-30x32	112
TCS MOTOR 10/10 6x7-30x32MF	112
TCS MOTOR 10/11 6x7-34x36	112
TCS MOTOR 10a/9	112
TCS OPEN BOX 13/17 6-24	116
TCS OPEN BOX 13/17 6-24MF	116
TCS OPEN BOX 13/18 6-24	116
TCS OPEN BOX 13/21 6-34	117
TCS OPEN BOX 13/25 5.5-34	117
TCS OPEN BOX 13a/19	117
TCS OPEN BOX 13a/23 3/16-1 1/8	117
TCS OPEN BOX 14/21 6-36	119
TCS OPEN RATCH 17/5	127
TCS OPEN RATCH 17/12	128
TCS OPEN RATCH 17a/5	128
TCS OPEN RATCH 17a/12	129
TCS OPEN RATCH 17F/5	129
TCS OPEN RATCH 17F/12	130
TCS OPEN RING 24/7 8x10-19x22	126
TCS StahlwilleSTABIL® 20/8 6x7-19x22MF	122
TCS StahlwilleSTABIL® 20/10 6x7-30x32	122
TCS TORX®/57 MF	352
TCS WB 2700	345
TCS WT 40/45/46/37/14	375
TCS WT 40/52/27/13	375
TCS WT 40/4008/10/9	374
TCS WT 102-109/16	377
TCS WT 4622SK-4650/10767a/24	376
TCS WT 4622SK-4650/10767H/20	376
TCS WT 4650-4665 VDE/10767a/24	376
TCS WT 4650-4665 VDE/10767H/20	376
TCS WT 6543-6730/7	377
TCS WT 6551-6730/7	377
TORSIOMAX 775	21
TORSIOMETER 760	20

Model number index

Model	Page
TORSIOTRONIC®	22
TORSIOTRONIC® 10/29	54
TR-SCH 13217	296
TWBE	53
VE 50-150 2/3	290
VE 50-150 3/3	290
WB 621	286
WB 621/161QR	313
WB 621/238QR	314
WB 621/267QR	316
WB 621/625 WP	291
WB 621 CS	290
WB 621 E-Kit	290
WB 625	286
WB 625/161QR	318
WB 625/238QR	319
WB 625/267QR	321
WB 630	287
WBS	81
WBS 7395-1	81
WKS	81
5	135
5 1/2	136
21TX	125
25	130
25a	130, 131
25aSP	131
25B	273
26a	131
34c/35c	455
39	455
40	144
40/9/4	157
40/13/6	158
40/13/6QR	159
40/20/4QR SCI	159
40/23/6	159
40/23/6QR	159
40/23/7	160
40/24/6	160
40/24/6QR	160
40/44/17/5	165
40/44/17/5QR	165
40/45/36/12	165
40/52/27/11	166
40/52/45/12QR	166
40a	144
40a/9/4	158
40a/40aD/16/2	155
40aD	145
40aD/9/4	158
40aD/10-12916	157
40aD/12/7QR	158
40aD/30/7QR	161
40aDL	145
40aDL/10-12916	157
40aDV	145
40aLSP	146
40aSP	146
40D	144
40D/10-12916	156
40D/40TX/44KTX/32/6QR	163
40DL	145
40L	146
40ma/25/8	161
40ma/25/8QR	161
40TX	146
41K	148
44	148
44a	148
44K	148
44KTX	149
44KTX/9	156
44KTXB	149
44PH	149
44PZ	149
45	169
45/10-12917	180
45/11/4	180
45/14/5I	181
45/14/5I QR	181
45/49/19/5	182
45/49/32/5TX	182
45a	169
45a/12/5	181
45a/22/8QR	181
45aP	169
45aPSP	170
45aSP	170
45ma/28/5	182
45ma/28/5QR	182
45TX	170
45TX/7	183
46	171, 451
46a	171
46aSP	171
47	173
47a	173
47TX	174
49	174
49a	174
49TX	175
49TX/8	183
49X	175
50	187
50/10-12918	199
50/12/3	200
50/16/6	200
50/16/6QR	200
50/22/6	201
50/43/7N	201
50/43/7QR	202
50/54/25/6	202
50/54/25/6QR	202
50a	187
50a/17/6	200
50aPLSP	189
50aPSP	189
50D IMP	230
50IMP	230
50IMP/6/2	233
50ma/39/6N	201
50ma/39/6QR	201
50TX	190
50TX/7	205
50TX/8	205
51	188, 451
51/8	205
51a	189
51IMP	230
51S	189, 451
52	188
52/12/3	202
52/16/6	203
52/16/6QR	203
52/22/6	203
52/54/25/6	203
52/54/25/6QR	204
53	190
54	190
54/8/4	204
54/10	205
54/12	206
54a	191
54CV	193
54IC	191
54IMP	231
54IMP/9	233
54KK	191
54TX	192
54TX/9	205
54TX/10	205
54TXB	192
54X	193
55	212
55/9/6N	215
55/10/6	215
55a	212
55a/10/5	216
55a/16/6	216
55IMP	234
56	213
56IMP	234
59	213
59TX	213
59X	213
60	217
60/6/6/882	219
60/8/6/882	219
60IMP	236
64	217
66IMP	236
70V	80
70VK	105
71/80	26
71aR/80	26
73Nm/15	27
82/013	292
83/09	292
83/010	292
86TX	164
88TX	164
89TX	164
93/6	283
93/95 CO	289
93/130	305
93/157QR	306
93/206QR	307
93/250QR	308
95/6 PRO	284
95/7 PRO	284
95/8 PRO	284
95/98 AB	291
95/157QR	310
95/250QR	311
95 GR	289
98/7 PRO	285
98/8 PRO	285
98/250QR	312
99/4S	400
100	403, 469
102	469
102-108/6	470
103	469
104	469
104-5/6	471
104-105/6T	471
105	469
105-108/6	471
105-108/6T	471
108	470
108/6	470
108/6T	470
109	470
110	403, 469
111	404
112	469
112/1	469
115	404
115-K/3S	405
127	405
129	405
130	405
130-1	405
130a	118

Model	Page
130aSP	118
136/95 L-BOXX®	381
136/96 L-BOXX®	381
136/111 L-BOXX®	382
136 L-BOXX®	293
136 L-BOXX® WK	293
156	408
172	221
173	221
180	401
180a	123
180-K/3S	401
182	400
182-K/3S	400
184	400
186	401
188	399
188/3S	399
220	124
220a	124
220aSP	124
230a	124
245	489
246	489
400 DRALL®	152
400N	152
400QR	152
401	152
402	147
402a	147
402aK	147
402aSP	147
403	152
404	152
404/1QR	153
404QR	153
405	153
405QR	153
405W	153
406	154
407	154
407/1QR	154
407QR	154
408QR	154
409	154
409M	104, 155
409M/432M/514M/3	219
410	155
411	150
412	274
412-1	275
413QR	153
414H	156
415-2K	150
415B 2K	270
415QRL N	151
415QR N	150
415SGB N	272
415SGH N	155
415SG-QR N	150
416QR	151
417/1	155
418B	272
418QR	151
419B	272
421	177
422	175
424	177
425	177
425/1QR	177
425QR	177
426QR	178
427	178
427QR	178
427W	178
428	179

Model	Page
428/1QR	179
428QR	179
430	415
431	179
432	179
432M	179
432 VDE	499
433	416
433/1	180
434	178, 417
434 E8	417, 419
435-2K	176
435LC	418
435QR N	176
435SG-QR N	176
436	419
437	416
438LC	414
439	417
440	72
440a	72
440S MJ	73
442	275
443	275
445	176, 415
446/08	292
447	75
447a	75
447aSP	75
452QR	176
453QR	177
456	172
456/11/4	183
456/14/5I	184
456/49/19/5	184
460a	172
480	419
501	197
501QR	197
503QR	197
504	196
506	196
506/1QR	197
506QR	196
509	197
509IMP	232
509QR	197
509W	198
510	198, 407
510-1	407
510/1QR	198
510IMP	232
510QR	198
511-0	408
511-1	408
512	407
512-0	408
512-2K	194
512QR N80	194
512SG-QR N	194
513	198
513IMP	232
514	199, 406
514IMP	232
514M	199
515	406
515-2K	195
516	195
517QR	195
522	195
532-2K	195
540	73
540a	74
540a HD	74
543	275
552	214

Model	Page
554	214
556	215
558	215
559	214
560IMP	235
561	214
561IMP	235
563	214
568	215
568IMP	235
569	215
569IMP	235
612/83 ST	304
612 ST	283
650 MS	484
700	418
701/2	42
701/32/1	54
713R	45
714	46
714R	47
717	65
718	66
720Nf/80	32
721Nf	32
721QR/20/3/1 Quick	56
721QR Quick	31
721 Quick	31
725/4	60
725B	60
725QR	60
725QR/20	65
730/80	30
730a Fix	36
730a Quick	28, 29
730D	43
730DR	43
730 Fix	35
730N	33
730Na	34
730NR	34
730NR QR	35
730 Quick	28, 29
730R/40/32 Quick	57
730R Quick	30
730R VDE	498
731/10	61
731/40	66
731/80	71
731/100	69
731a/10	62
731a/40	66
732/10	62
732/40	67
732/80	71
732/100	70
732a/10	62
732a/40	67
732a/80	71
732aG/10	63
732G/10	63
732TX/10	62
732TX/40	67
733/10	63
733a/10	63
734	61, 66
734/80	70
734/100	69
734F	61
734K	105
735	61, 65
735/65	69
735/80	70
735/100	69
736	64
736/40	68

Model number index

Model	Page
737/10	64
737/40	68
737/100	70
750NR	37
750NR/200/3/1	56
755	27
755R/1	27
760	20
775	21
801N	354
802N	355
803N	355
804N	356
805/4 WT TCS	368
806/6 WT TCS	369
811N	356
841N	357
859	218
859IMP	237
866	218
866IMP	237
871IMP	237
876	204
876TX	204
882	218
884	218
886	219
888	218
900	481
900/6T	481
901	481
901/5T	482
905/25	482
906	482
950	404
951	404
952	403
952/3S	403
952/966/3S	403
966	399, 400
966/3S	399
966-K/3S	399
980	415
980 BO/MA universell	420
980LC	414
984LC	414
985	418
996	419
1015	455
1023	456
1049/3049	174
1054/2054	191
1054/3054	192
1054KK	192
1054TX/2054TX	194
1054X/2054X	193
1058	455
1062	190
1068	456
1160-1169	265
1202	267
1203	267
1204/8	268
1204/21-1	268
1204/21-2	268
1206	268
1225	178
1242-1250	275
1260-1262	276
1270-1272	276
1280-1284	276
1290-1296	276
1299	52, 266
1300-1304	266
1350-1360	265
1410-1421 1430-1435	265
1427	266
1440-1446	266
1440 IP-1446 IP	266
1440 TPI-1446 TPI	266
1474/2	448
1500	295
1501-1506	436
1511-1516	436
1523	436
1551/1552	436
1553-1555	436
1556	436
1556-1	437
1557/1558	437
1559	437
1560	440
1562	437
1570/2	440
1574	437
1575	437
1576	437
1577	437
1577-1	438
1578K-1	438
1578K-2	438
1584/1585	438
1587	438
1589K	438
1591	438
1700 MAN/Volvo	440
1820	65
1821	69
1822	71
2049	175
2307TX	232
2308TX	231
2309	231
2309IMP K	231
2450	489
2509	234
2609	236
2801	276
3004	194
3027	357
3045	455
3046	172
3047	451
3049X	175
3054X	193
3054X/54X/8	206
3100	275
3115	274
3116	274
3116/1QR-3316/1QR	237, 274
3117-3119	274
3466	172, 450
3505	198
3678	190
3825/1	273
4000	270
4004	134
4008-1	273
4008-2	273
4008/27/1R	269
4009	270
4014	119
4025	134
4026	135
4030	277
4035/4036	277
4040-4044	277
4050-4052	277
4055-4058	277
4060	277
4110	151
4150	151
4150B	272
4150QR	78, 151
4150QR N	152
4151B	152
4152	155
4153B	273
4204	134
4205	136
4220	78
4301	415
4350	176
4350QR	78, 176
4350QR N	177
4600	173, 450
4606	173, 450
4620	242
4621	242
4622	242
4622SK	242
4628	243
4630	244
4631	244
4632	245
4632SK	245
4636	248
4640	246
4650	247
4650L	247
4656	247
4660 VDE	500
4661 VDE	500
4665 VDE	501
4666 VDE	501
4670 VDE	501
4671 VDE	501
4675 VDE	502
4676 VDE	502
4691/7	255
4692/8	255
4693/9	255
4694/9	256
4695 VDE	504
4696SK/6	255
4699/9	256
4724	243
4734	245
4744	246
4751	243
4752	246
4753	248
4754	247
4754/7	257
4797	257
4798	258
4798 VDE	504
4820	243
4830	245
4840	246
4856	248
4891	256
4892	257
4899	257
5040	196
5040N	196
5091IMP	232
5092IMP	232
5100	219, 451
5120	79
5120G	196
5120QR	78, 196
5120QR N	196
5120QR N80	196
5150	79

Model	Page
5513	219
5520	214
5591IMP	235
5592IMP	235
6091IMP	237
6092IMP	237
6515	398
6543	408, 409
6544	409
6545	409, 410
6546	410
6549	401
6551	398
6551 VDE	506
6556	402
6557	402
6558	402
6559	402
6562	410
6563	411
6564	411
6571	411
6572	398
6573	401
6575	398
6576	406
6617	397
6630	478
6630 VDE	506
6638	397
6660	406
6661	406
6662	407
6700	394
6700 VDE	504
6707	411
6708	412
6709	412
6710	413
6711	413
6720	395
6720 VDE	505
6721	396
6721 VDE	505
6730	394
6730 VDE	504
6731	395
6731 VDE	505
6770	396
6780	397
6780 VDE	505
6962	411
6976	406
7160	49
7161	52
7162	48
7195-2	48
7210/5	78
7210/30	79
7210/80	79
7250/4	78
7250B/4	78
7250B/5	78
7250L/5	78
7250QR/10	79
7301/7302	53
7303/7304	53
7311/7312	53
7313/7314	53
7350/5	78
7350/10	79
7350/20	79
7350/40	79
7350/40HD-65	79
7370/10	64
7370/10-2	64

Model	Page
7370/40	68
7370/40-1	68
7370/40-2	68
7370/80	71
7370/100	70
7380N/7385N	48
7706	100
7707 W	87
7721-7724	101
7728	98
7732-2	50
7750	52
7750-1	102
7751	49
7751-1	49
7751-3	49
7752	50
7756	459
7757-1	50
7759-4	51
7759-5	51
7759-6	51
7760	50
7761	49
7761/3	49
7763	50
7787	104
7788	104
7789	104
7789-1	199
7789-2	104
7789-3	104
7789-4	104
7789-5	104
7789-734K	102
7790	102
7791-1	99
7791-2	102
7791-4	96
7792-1	101
7794-1	92
7794-1 Sets	93
7794-2	94
7794-2 Sets	95
7794-3	96
8002	298
8031	298
8032	298
8034	298
8035	299
8036	299
8038	299
8041	299
8050	299
8820	218
10350 N	447
10351/1	447
10351/2	448
10351/3	448
10351 N	447
10352	447
10352/1	447
10354	449
10355	448
10356	475
10356R	475
10503	244
10506	244
10507N KK	248
10518	244
10546	258
10551	258
10554	480
10599/2	454
10613	454
10613/1	454

Model	Page
10614	457
10615/1	457
10623/1	458
10623/2	458
10623/2EB	458
10625	458
10625/2	458
10669	474
10670	474
10672	474
10676	474
10677-10681	475
10682/5	475
10750	138, 139
10750 1/2	139
10757	474
10758	474
10759	156, 259
10759a	156, 259
10760	259
10760/8	259
10760/9	260
10760a	260
10760a/8	260
10760a/9	260
10765	261
10765/9	261
10766	261
10766/8	261
10767	262
10767/9	263
10767a	262
10767a/13	263
10767H	263
10767H/9	263
10768	249
10769	250
10771	262
10771/8	262
10775	441
10780	441
10785	441
10790	441
10795	442
10800	442
10805	442
10806	442
10811	442
10812	442
10835	443
10841	443
10842	443
10845	444
10855	443
10865	444
10880	442
10885	443
10890	444
10905	444
10906-10916	445
10921	444
10922	444
10923	444
10940	467
10955	467
10955R	467
10956	467
10956R	468
10958	467
10959	468
10959R	468
10961	468
10962	468
10970	468
11005	445
11006	445

Model number index

Model	Page
11007	445
11040	429
11063	449
11063/1	449
11068	449
11069	449
11085	457
11095-11097	450
11200	426
11210	428
11250	428
11251	427
11300	426
11351	427
11400	429
11401	430
11402	430
11500	431
11501	431
11502	431
11700	453
11701	453
11702	453
11703	453
11704	454
11708	454
12000	477
12005	456
12005/1	456
12007	456
12025	476
12030	476
12035	476
12036	476
12050	477
12050 R	477
12053	477
12053 R	477
12108	449
12160/6 VDE	496
12160 VDE	496
12161/6 VDE	497
12161 VDE	496
12165 VDE	497
12167 VDE	499
12171/19/4 VDE	495
12171 VDE	499
12174 VDE	499
12175 VDE	499
12177 VDE	500
12179 VDE	500
12187 VDE	506
12188 VDE	506
12189 VDE	506
12190 VDE	506
12191 VDE	507
12192 VDE	507
12193 VDE	507
12194/12195 VDE	507
12196 VDE	507
12250	489
12251	489
12320	478
12321	479
12322	479
12371	476
12372	452
12373	452
12374	475
12375	452
12376	475
12377	475
12378	476
12481	489
12495	458
12500N	249
12503	270
12504	270
12506	249
12507	250
12600	484
12601	484
12615	481
12665	481
12705	456
12717	456
12718	448
12727	446
12728	446
12729/12730	446
12749	448
12749R	449
12752	445
12753	445
12763	457
12770	446
12770/2	446
12770/3	446
12771	445
12772	447
12800	477
12900	481
12900/1	480
12900/3	480
12900/4	480
12905	459
12910	139
12915	457, 482
12916/10	157
12916/10, 12917/10, 12918/10	220
12916/12917/12918	157, 180, 199, 220
12917/10	180
12918/10	199
12920N	483
12920N R1	483
12921M	483
12921N	483
12921NR	483
12922	484
12932	296
12935	480
12950/11	139
12965	478
12965-1	478
12965-2	479
12965-2R	479
12965-3	479
12965-3R	479
12965R	478
12967	479
12967R	479
12975	457
13000-13003/4 155 mm	466
13000-13003/4 250 mm	466
13000-13003 155 mm	466
13000-13003 250 mm	466
13006	276
13008	267
13009	466
13010	267
13100	477
13110	480
13112 2M	480
13115	476
13120N	483
13120R	484
13124	485
13126-2	485
13126-3	485
13128	485
13130	484
13131	484
13132	486
13133	488
13134	486
13136 SL	486
13137 KL	486
13138 HL	488
13139 DL	488
13148	478
13155	478
13200a	358
13205a	358
13211a	359
13213a	359
13214	383
13214/1 WT/LR	360
13214a	384
13214a/1 WT/LR	362
13215	293
13215/19 VDE	495
13215/105	386
13216/4	294
13217	296
13219	292
13220	178
13221 WT/TS	364
13224a WT/TS	366
13253/1 10	387
13253/38	387
13300 VDE	494
13301	293
13301/69	378
13301/87	378
13302/TR	294
13302/TR/69	379
13302/TR/87	379
13302/TR/99	380
13302/TR VDE	494
14000/14002	464
14001/14003	464
14010-14011	465
14012	465
14020-14021	465
14030-14031	465
14032	465
14040-14041	465
14050-14051	465
14060	465
14100	464
14200	464
14300	464
43713	415, 416
43913	417
98013	414, 416
129010	405
433125	416
433145	417
434135	414, 417
435133	418
436132	419
445135	415
480133	419
980082	418
985135	418
996135	419

Technologies and features

2-component handle
Our 2-component handle is non-slip and ergonomically designed. It is resistant to the most common oils, greases, fuels, brake fluids, and Skydrol. The arrow markings on the handle indicate the direction of operation.

3K DRALL®
The STAHLWILLE 3K DRALL® handle with non-slip, special fibre-coated surface enables fatigue-free working and maximum power transmission. An ingenious opening serves both as a hanging hole and as a lever hole for additional force and high torque.

3-component handle
Our 3-component handle combines hard and soft components, which give it its optimised ergonomics, maximum power transmission, and increased safety during daily use.

Anti-Slip-Drive
The special AS-Drive profile makes high force transmission to the flats of bolts and nuts possible without damaging them. This also prevents stripping of the screw head.

DKD-R 10-8 / DIN 51309
Our transducers for torque wrenches and torque testers are professionally calibrated in our DAkkS-accredited calibration laboratory. Depending on requirements, this is done either with a calibration certificate within the scope of our accreditation (according to DKD-R 10 8 or DIN 51309) or with a factory calibration certificate based on these guidelines.

Double-T profile
Our ring, open-ended and combination spanners have an additional recess in the middle of the tool. Similar to the principle of a double-T beam, this provides a tremendous load capacity and maximum strength whilst reducing weight.

DRALL+
Our DRALL+ handle is non-slip and ergonomic. An extended grip zone protects the fingers and a hand stop prevents the tool from accidentally slipping or rolling away.

Thin-walled rings
The thin-walled diameter of our rings makes it easier to work in confined spaces. The ring wall is deeper than standard nuts, which prevents jamming.

Spring mechanism with the 'click'
Our torque wrench uses a toggle lever as the switching mechanism. When the set torque is reached (click-type), the spring force is exceeded, causing the mechanism to slip and strike. This produces a clearly audible and perceptible 'click'.

Fine-tooth ratchet mechanism
Our fine-tooth ratchets with 80 teeth re-engage after just 4.5° for maximum precision in confined spaces. 8 pairs of parallel teeth simultaneously ensure maximum load-bearing capacity and particularly smooth running, even at high torques.

Foreign Object Damage
STAHLWILLE protects against FOD (Foreign Object Damage). Our tool is ideal for safety-relevant sectors such as aviation, thanks to the screwless design.

High Performance Quality (HPQ®)
Our HPQ® tool is made of wear-resistant high-performance steel, yet is thin-walled and lightweight. It withstands high torques and is ideal for work in confined spaces such as turbines.

HI-LOK™
HI-LOK™ fasteners are widely used in the aerospace industry. Our HI-LOK™ ratchet with centered channel guide for hex L-Keys is designed for safety-critical applications. The boltless design minimises the risk of FOD and ensures robust, vibration-resistant connections with high tensile strength.

Modular Inlay System
This flexible solution for tool storage makes it possible to customise your tool trolleys and workbenches with 1/6, 1/3, 2/3 or 3/3 foam inlays.

LightCUT®
The flat-oval, high-strength aluminium tubes of the LightCUT® range ensure a low weight, approximately half that of a comparable tool. For fatigue-free working and precise results.

Offset Shaft Design
Our spanners are specially designed with additional reinforcement in the load zones where the greatest amount of force is transmitted - namely where the jaw meets the shank - in order to prevent deformation.

QuickRelease
In torque wrenches, ratchets, and sockets:
The QuickRelease safety lock prevents unintentional loss of insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change.
In transducers: The QuickRelease safety lock helps you to quickly mount and change transducers. The sensors lock into the calibration system adaptor and only unlock again at the push of a button.

QuickSelect
Lightning-fast target value setting: Unlock the adjustment knob, set the value, and lock the knob again.

Impact cap
Our DRALL+ screwdriver is equipped with a metal impact cap for use in extreme conditions, enabling the screwdriver to be impacted with a mallet or hammer.

Hex shank profile
Some of our DRALL+ screwdrivers have a hex shank profile at the base of the handle which can be used in conjunction with a spanner to apply more force when loosening tight screws.

SolutionCUT
The special pipe head geometry of this bolt cutter enables precise and clean cutting not only in the second layer, but also in deeper layers - for effortless and precise working even in hard-to-reach areas.

Tool Control System
The intelligent modular inlay system protects and organises the tools in tool boxes, tool trolleys and workbenches. Two-colour foam inlays make checking the completeness of the tools quick and easy.

Adjustment Lock
The target torque can be quickly adjusted using the adjustment knob. The knob can then be removed to prevent subsequent adjustment. The supplied locking screw (TORX® Tamper Resistant) and an adhesive seal provide additional protection against tampering.

VDE-DRALL+
Our VDE-DRALL+ handle is insulated to 1,000 V according to DIN EN 60900. It is non-slip and ergonomically shaped. An extended grip zone protects the fingers and a hand stop prevents the tool from accidentally slipping or rolling away.

Low-wear bending beam system
Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that the spring does not need to be reset to '0' after use.

DIN EN ISO 6789-2
Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

EVERYTHING IN ONE PLACE. ALWAYS AVAILABLE.

The new service portal MySTAHLWILLE offers customers a wealth of options.

The MySTAHLWILLE service portal enables round-the-clock access to a variety of product and service related functions, such as product registration, software downloads, warranty and quotation requests, repair or calibration orders and much more. Everything in one place and available at any time.



Simple.

Setting up an individual customer account and registering tools in MySTAHLWILLE is quick and easy – in just a few steps. Once complete, users have access to all services in the portal.

Current.

The service portal always has the latest information on pending repair and calibration orders. Shipment and order status can be viewed here at any time.

Central.

Important information and resources can be accessed via the customer account: Delivery notes, repair reports, calibration documents as well as downloads of software, drivers and 3D product data.

SERVICE

Accredited.

We can also offer calibrations in our own DAkkS accredited laboratory, and not just for torque wrenches manufactured by STAHLWILLE.

Direct.

For each calibration or repair of a tool, a customer order can be created easily via the direct service option. The firm price for the respective services are visible immediately. Direct service is the quickest way to get your tool back in your possession.

Here's how it works:

1. Product selection and registration
2. Description of the fault
3. Service selection
4. Creation of confirmation and delivery note
5. Product shipment
6. Calibration, service and/or repair, with tracking
7. Return of serviced product




Discover the MySTAHLWILLE service portal.

Technical support can be reached quickly via MySTAHLWILLE. Experienced experts support you with all technical questions relating to your products.
service.stahlwille.com

FOLLOW US TO KNOW MORE –
We're on all major networks.

Whether it's a Facebook post, Insta story or LinkedIn event: We share our content on the major platforms and are happy to network with our partners. It's best to drop by, connect and keep updated!



Facebook
stahlwilletoolexperts | DE, EN
stahlwillepolska | PL
StahlwilleNordic | DK
stahlwillees | ES
utensili.stahlwille | IT

Instagram
stahlwilletoolexperts | DE, EN
stahlwilleteam | DE
stahlwille_polska | PL
stahlwilleuk | EN
stahlwille.nordic | DK
stahlwille_es | ES
stahlwilleutensili | IT

LinkedIn
stahlwilletoolexperts | DE, EN
stahlwille-polska | PL, EN
stahlwille uk | EN
stahlwille-nordic | DA
stahlwille-sau | ES
stahlwille-utensili | IT
stahlwille-b.v. | NL

YouTube
STAHLWILLE1862 | DE, EN

Find out more here
www.stahlwille.com



Staying up-to-date: easy.

Want to know what's new at STAHLWILLE, but don't want to keep checking the website? Our newsletter provides regular updates on new products and promotions, as well as technical information and useful tips.

Simply scan the QR code and fill out the form.
Or use this link: **https://stahlwille.com/en_gb/5f599ab6**

STAHLWILLE WORLDWIDE –
Always where our customers are.

To be a global leader, a global presence is essential. That is why we are represented locally in many markets with our own subsidiaries and have an extensive network of trading partners. No matter where our customers are, we are always close to them.

DE, International
STAHLWILLE Eduard Wille GmbH
Lindenallee 27, 42349 Wuppertal,
Germany
T + 49 202 4791 0
info@stahlwille.de

PL
STAHLWILLE - POLSKA Sp. z o.o.
Strażacka 72, 43-382 Bielsko-Biała,
Polska
T + 48 33 82 80 700
stahlwille@stahlwille.pl

NL
Stahlwille B.V.
Ramgatseweg 13E, 4941 Raamsdonksveer,
Netherlands
T + 31 162 518771
info@stahlwille.nl

FR
STAHLWILLE France Sarl
1-3, Place Giovanni Da Verrazzano,
69009 Lyon
France
T + 33 6 73686423
wacogne@stahlwille.de

DK, FI, NO, SE
Stahlwille Nordic A/S
Baldershøj 11 E-F, 2635 Ishøj
Danmark
T + 45 43 77 77 87
info@stahlwille.dk

IT
STAHLWILLE UTENSILI S.R.L.
Via Liguria, 30, 20068 Peschiera
Borromeo -MI-
Italia
T + 39 02 5537981
info@stahlwille.it

ES
STAHLWILLE S. A.
C/ Sierra de Albarracín, 1, 28830 San
Fernando de Henares (Madrid)
España
T + 34 91 677 03 69
stahlwille@stahlwille.es

CN
STAHLWILLE (Beijing) International
Trade Co. Ltd.
No. 26 Juyuan West Road, Mapo, Shunyi
District, Beijing
China
T + 86 10 69450749
service@stahlwille-china.com

UK, IE
STAHLWILLE Tools Ltd
Unit 2D Albany Park Industrial Estate,
Frimley Road, Camberley, Surrey, GU16 7PL,
United Kingdom
T + 44 (0) 1276 24 080
sales@stahlwille.co.uk

US, CA
STAHLWILLE Tools Inc.
1510 S Sylvania Ave Unit 208, 53177 Sturtevant
United States
T + 1 262 583 4060
info@stahlwille-americas.com


BE
Stahlwille B.V.
Industrielaan 4, 9320 Erembodegem,
Belgium
T + 32 53 841595
info@stahlwille.be

AT, AL, BA, BG, HR, CZ, HU, ME, MK, RO, RS, SK, SI, MT
STAHLWILLE Austria GmbH
Puchgasse 1 (Top 7), 1220 Wien
Austria
T + 43 1 6167616
hubacek@stahlwille.de

Find specialist dealers near you now.

Looking for a STAHLWILLE dealer near you?
https://qr.stahlwille.com/distributors

UP TO DATE WITH STAHLWILLE – everything about events, training courses and current topics.



Training courses & webinars.

Would you like to learn more and expand your know-how in the hand tools and torque technology field? Then take advantage of our training offers or join our free webinars and benefit from our expertise.


qr.stahlwille.com/training_en

Trade fairs & events.

Would you like to visit us at a trade fair to find out more about STAHLWILLE products or to get to know us in person? Then you can find all trade fair and event dates here.

qr.stahlwille.com/events_en





Newsroom.

Stay up-to-date! In our newsroom, you will find updates on new products, services and promotions as well as success stories and interesting case studies.

qr.stahlwille.com/newsroom_en

YOUR FEEDBACK IS OUR TOOL –
Tell us what you think!

We don't just want to offer you high-quality products – we want to create a catalogue that you truly enjoy using.That's why your feedback is so valuable to us! Whether it's suggestions for improvements, corrections, or ideas regarding content, structure, or design – your feedback helps us to respond even more effectively to your needs. Simply use our feedback form – with just a few clicks, you can share your thoughts and help us make things even better. Thank you for your support!



qr.stahlwille.com/feedback_cat_en

Imprint

Upon publication of this catalogue, all previous editions become void. The product range is subject to change without prior notice. No claims can be made based on the the information or illustrations contained in this catalogue. We reserve the right to make changes to technology, design, colour, and specifications at any time. All information regarding scope of delivery, appearance, performance, and dimensions reflects the state of knowledge at the time of printing. The dimensions listed are approximate values and serve as guidelines. Changes, e.g. particularly those aimed at product improvement – may be made at any time. In case of technical work equipment, we comply with the applicable provisions of the Act on Technical Work Equipment.

We accept no liability for typographical or printing errors. This document and all its parts are protected by copyright. All rights reserved, including the rights of reproduction, translation, and electronic processing.

WEEE Reg. No. DE 70431151

STAHLWILLE Eduard Wille GmbH
Lindenallee 27
42349 Wuppertal
Germany
Tel.: +49 202 4791-0
info@stahlwille.de
www.stahlwille.com

STAHLWILLE Eduard Wille GmbH · Lindenallee 27 · 42349 Wuppertal · Germany
Tel.: +49 202 4791-0 · info@stahlwille.de · www.stahlwille.com

© STAHLWILLE Eduard Wille GmbH // 20-11-25 AU // V 2.1 // 91971051